

ETSI TS 138 101-2 v15.9.1 (2020-04)



**5G;
NR;**
User Equipment (UE) radio transmission and reception;
Part 2: Range 2 Standalone
(3GPP TS 38.101-2 version 15.9.1 Release 15)

Redacted Standard Review
https://standards.iteh.afrl.af.mil/standards/sist/77ce8e67-6943-
4c1b-8043-eaa916be4b35/v15.9.1-2020-04



Reference

RTS/TSGR-0438101-2vf91

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88.

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	10
1 Scope	11
2 References	11
3 Definitions, symbols and abbreviations	12
3.1 Definitions.....	12
3.2 Symbols.....	13
3.3 Abbreviations	15
4 General	17
4.1 Relationship between minimum requirements and test requirements	17
4.2 Applicability of minimum requirements	17
4.3 Specification suffix information.....	17
5 Operating bands and channel arrangement.....	18
5.1 General	18
5.2 Operating bands.....	18
5.2A Operating bands for CA	18
5.2A.1 Intra-band CA	18
5.2A.2 Void	19
5.2D Operating bands for UL MIMO	19
5.3 UE Channel bandwidth	20
5.3.1 General.....	20
5.3.2 Maximum transmission bandwidth configuration.....	20
5.3.3 Minimum guardband and transmission bandwidth configuration.....	21
5.3.4 RB alignment	22
5.3A UE channel bandwidth for CA	23
5.3A.1 General.....	23
5.3A.2 Minimum guardband and transmission bandwidth configuration for CA	23
5.3A.3 RB alignment with different numerologies for CA.....	24
5.3A.4 UE channel bandwidth per operating band for CA	24
5.3D Channel bandwidth for UL MIMO.....	25
5.4 Channel arrangement.....	25
5.4.1 Channel spacing	25
5.4.1.1 Channel spacing for adjacent NR carriers.....	25
5.4.2 Channel raster	26
5.4.2.1 NR-ARFCN and channel raster.....	26
5.4.2.2 Channel raster to resource element mapping.....	26
5.4.2.3 Channel raster entries for each operating band	27
5.4.3 Synchronization raster	27
5.4.3.1 Synchronization raster and numbering	27
5.4.3.2 Synchronization raster to synchronization block resource element mapping.....	27
5.4.3.3 Synchronization raster entries for each operating band	28
5.4A Channel arrangement for CA.....	28
5.4A.1 Channel spacing for CA.....	28
5.5 Configurations	29
5.5A Configurations for CA.....	29
5.5A.1 Configurations for intra-band contiguous CA.....	29
5.5A.2 Configurations for intra-band non-contiguous CA	30
5.5D Configurations for UL MIMO	35
6 Transmitter characteristics	36
6.1 General	36

6.2	Transmitter power	36
6.2.1	UE maximum output power.....	36
6.2.1.0	General.....	36
6.2.1.1	UE maximum output power for power class 1	36
6.2.1.2	UE maximum output power for power class 2	37
6.2.1.3	UE maximum output power for power class 3	38
6.2.1.4	UE maximum output power for power class 4.....	39
6.2.2	UE maximum output power reduction.....	40
6.2.2.1	UE maximum output power reduction for power class 1	40
6.2.2.2	UE maximum output power reduction for power class 2.....	41
6.2.2.3	UE maximum output power reduction for power class 3	42
6.2.2.4	UE maximum output power reduction for power class 4.....	42
6.2.3	UE maximum output power with additional requirements	43
6.2.3.1	General.....	43
6.2.3.2	A-MPR for NS_201	43
6.2.3.2.1	A-MPR for NS_201 for power class 1	43
6.2.3.2.2	A-MPR for NS_201 for power class 2	43
6.2.3.2.3	A-MPR for NS_201 for power class 3	44
6.2.3.2.4	A-MPR for NS_201 for power class 4	44
6.2.3.3	A-MPR for NS_202	44
6.2.3.3.1	A-MPR for NS_202 for power class 1	44
6.2.3.3.2	A-MPR for NS_202 for power class 2	44
6.2.3.3.3	A-MPR for NS_202 for power class 3	44
6.2.3.3.4	A-MPR for NS_202 for power class 4	44
6.2.4	Configured transmitted power	44
6.2A	Transmitter power for CA	45
6.2A.1	UE maximum output power for CA.....	45
6.2A.2	UE maximum output power reduction for CA.....	46
6.2A.2.1	General.....	46
6.2A.2.2	Maximum output power reduction for power class 1	46
6.2A.2.3	Maximum output power reduction for power class 2.....	47
6.2A.2.4	Maximum output power reduction for power class 3	47
6.2A.2.5	Maximum output power reduction for power class 4.....	48
6.2A.3	UE maximum output power with additional requirements for CA	48
6.2A.3.1	General.....	48
6.2A.3.2	A-MPR for CA_NS_201	49
6.2A.3.2.1	A-MPR for CA_NS_201 for power class 1	49
6.2A.3.2.2	A-MPR for CA_NS_201 for power class 2	49
6.2A.3.2.3	A-MPR for CA_NS_201 for power class 3	49
6.2A.3.2.4	A-MPR for CA_NS_201 for power class 4	50
6.2A.3.3	A-MPR for CA_NS_202	50
6.2A.3.3.1	A-MPR for CA_NS_202 for power class 1	50
6.2A.3.3.2	A-MPR for CA_NS_202 for power class 2	50
6.2A.3.3.3	A-MPR for CA_NS_202 for power class 3	50
6.2A.3.3.4	A-MPR for CA_NS_202 for power class 4	50
6.2A.4	Configured transmitted power for CA	50
6.2D	Transmitter power for UL MIMO	51
6.2D.1	UE maximum output power for UL MIMO.....	51
6.2D.1.1	UE maximum output power for UL MIMO for power class 1.....	51
6.2D.1.2	UE maximum output power for UL MIMO for power class 2.....	52
6.2D.1.3	UE maximum output power for UL MIMO for power class 3	53
6.2D.1.4	UE maximum output power for UL MIMO for power class 4	53
6.2D.2	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO.....	54
6.2D.2.1	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 1	54
6.2D.2.2	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 2	55
6.2D.2.3	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 3	55
6.2D.2.4	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 4	55
6.2D.3	UE maximum output power reduction with additional requirements for UL MIMO	55

6.2D.3.1	UE maximum output power reduction with additional requirements for UL MIMO for power class 1	55
6.2D.3.2	UE maximum output power reduction with additional requirements for UL MIMO for power class 2	55
6.2D.3.3	UE maximum output power reduction with additional requirements for UL MIMO for power class 3	55
6.2D.3.4	UE maximum output power reduction with additional requirements for UL MIMO for power class 4	56
6.2D.4	Configured transmitted power for UL MIMO	56
6.3	Output power dynamics	56
6.3.1	Minimum output power	56
6.3.1.0	General	56
6.3.1.1	Minimum output power for power class 1	56
6.3.1.2	Minimum output power for power class 2, 3, and 4	56
6.3.2	Transmit OFF power	56
6.3.3	Transmit ON/OFF time mask	57
6.3.3.1	General	57
6.3.3.2	General ON/OFF time mask	57
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries	58
6.3.3.4	PRACH time mask	58
6.3.3.5	Void	59
6.3.3.6	SRS time mask	59
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	60
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	60
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	61
6.3.4	Power control	62
6.3.4.1	General	62
6.3.4.2	Absolute power tolerance	62
6.3.4.3	Relative power tolerance	62
6.3.4.4	Aggregate power tolerance	63
6.3A	Output power dynamics for CA	63
6.3A.1	Minimum output power for CA	63
6.3A.1.0	General	63
6.3A.1.1	Minimum output power for power class 1	64
6.3A.1.2	Minimum output power for power class 2, 3, and 4	64
6.3A.2	Transmit OFF power for CA	64
6.3A.3	Transmit ON/OFF time mask for CA	64
6.3A.4	Power control for CA	65
6.3A.4.1	General	65
6.3D	Output power dynamics for UL MIMO	66
6.3D.1	Minimum output power for UL MIMO	66
6.3D.1.1	Minimum output power for UL MIMO for power class 1	66
6.3D.1.2	Minimum output power for UL MIMO for power class 2, 3 and 4	66
6.3D.2	Transmit OFF power for UL MIMO	66
6.3D.3	Transmit ON/OFF time mask for UL MIMO	66
6.4	Transmit signal quality	66
6.4.1	Frequency Error	66
6.4.2	Transmit modulation quality	66
6.4.2.0	General	66
6.4.2.1	Error vector magnitude	67
6.4.2.2	Carrier leakage	68
6.4.2.2.1	General	68
6.4.2.2.2	Carrier leakage for power class 1	68
6.4.2.2.3	Carrier leakage for power class 2	68
6.4.2.2.4	Carrier leakage for power class 3	68
6.4.2.2.5	Carrier leakage for power class 4	68
6.4.2.3	In-band emissions	69
6.4.2.3.1	General	69
6.4.2.3.2	In-band emissions for power class 1	69
6.4.2.3.3	In-band emissions for power class 2	69
6.4.2.3.4	In-band emissions for power class 3	70

6.4.2.3.5	In-band emissions for power class 4.....	71
6.4.2.4	EVM equalizer spectrum flatness	72
6.4.2.5	EVM spectral flatness for Pi/2 BPSK modulation	73
6.4A	Transmit signal quality for CA.....	74
6.4A.1	Frequency error.....	74
6.4A.2	Transmit modulation quality.....	74
6.4A.2.0	General	74
6.4A.2.1	Error Vector magnitude.....	75
6.4A.2.2	Carrier leakage	75
6.4A.2.2.1	General	75
6.4A.2.2.2	Carrier leakage for power class 1	75
6.4A.2.2.3	Carrier leakage for power class 2	75
6.4A.2.2.4	Carrier leakage for power class 3	75
6.4A.2.2.5	Carrier leakage for power class 4	76
6.4A.2.3	Inband emissions.....	76
6.4A.2.3.1	General	76
6.4A.2.3.2	Inband emissions for power class 1	76
6.4A.2.3.3	Inband emissions for power class 2	77
6.4A.2.3.4	Inband emissions for power class 3	77
6.4A.2.3.5	Inband emissions for power class 4	78
6.4A.2.4	EVM equalizer spectrum flatness	79
6.4D	Transmit signal quality for UL MIMO.....	79
6.4D.0	General.....	79
6.4D.1	Frequency error for UL MIMO.....	79
6.4D.2	Transmit modulation quality for UL MIMO.....	79
6.4D.3	Time alignment error for UL MIMO	80
6.4D.4	Requirements for coherent UL MIMO	80
6.5	Output RF spectrum emissions.....	80
6.5.1	Occupied bandwidth	80
6.5.2	Out of band emissions.....	81
6.5.2.0	General	81
6.5.2.1	Spectrum emission mask	81
6.5.2.2	Void.....	81
6.5.2.3	Adjacent channel leakage ratio	81
6.5.3	Spurious emissions	82
6.5.3.1	Spurious emission band UE co-existence	83
6.5.3.2	Additional spurious emissions	83
6.5.3.2.1	General	83
6.5.3.2.2	Additional spurious emission requirements for NS_201	83
6.5.3.2.3	Additional spurious emission requirements for NS_202	84
6.5A	Output RF spectrum emissions for CA.....	84
6.5A.1	Occupied bandwidth for CA	84
6.5A.2	Out of band emissions.....	84
6.5A.2.1	Spectrum emission mask for CA.....	84
6.5A.2.3	Adjacent channel leakage ratio for CA	85
6.5A.3	Spurious emissions for CA	85
6.5A.3.1	Spurious emission band UE co-existence for CA	85
6.5A.3.2	Additional spurious emissions	86
6.5A.3.2.1	General	86
6.5A.3.2.2	Additional spurious emission requirements for CA_NS_201	86
6.5A.3.2.3	Additional spurious emission requirements for CA_NS_202	86
6.5D	Output RF spectrum emissions for UL MIMO.....	86
6.5D.1	Occupied bandwidth for UL MIMO	86
6.5D.2	Out of band emissions for UL MIMO	87
6.5D.3	Spurious emissions for UL MIMO	87
6.6	Beam correspondence.....	87
6.6.1	General.....	87
6.6.2	(Void).....	87
6.6.3	(Void).....	87
6.6.4	Beam correspondence for power class 3.....	87
6.6.4.1	General.....	87
6.6.4.2	Beam correspondence tolerance for power class 3.....	87

6.6.4.3	Side Conditions	88
6.6.4.3.1	Side Condition for SSB and CSI-RS	88
6.6.5	(Void).....	89
6.6A	Beam correspondence for CA	89
7	Receiver characteristics	90
7.1	General	90
7.2	Diversity characteristics	90
7.3	Reference sensitivity	90
7.3.1	General.....	90
7.3.2	Reference sensitivity power level	90
7.3.2.1	Reference sensitivity power level for power class 1	90
7.3.2.2	Reference sensitivity power level for power class 2	91
7.3.2.3	Reference sensitivity power level for power class 3	91
7.3.2.4	Reference sensitivity power level for power class 4	92
7.3.3	Void	92
7.3.4	EIS spherical coverage.....	92
7.3.4.3	EIS spherical coverage for power class 3	93
7.3A	Reference sensitivity for CA	94
7.3A.1	General.....	94
7.3A.2	Reference sensitivity power level for CA	94
7.3A.2.1	Intra-band contiguous CA	94
7.3D	Reference sensitivity for UL MIMO	95
7.4	Maximum input level	95
7.4A	Maximum input level for CA	95
7.4D	Maximum input level for UL MIMO	96
7.5	Adjacent channel selectivity	96
7.5A	Adjacent channel selectivity for CA.....	98
7.5A.1	Adjacent channel selectivity for Intra-band contiguous CA	98
7.5A.2	Adjacent channel selectivity for Intra-band non-contiguous CA	99
7.5A.3	void	99
7.5D	Adjacent channel selectivity for UL MIMO	99
7.6	Blocking characteristics	99
7.6.1	General.....	99
7.6.2	In-band blocking	100
7.6.3	Void	101
7.6A	Blocking characteristics for CA	101
7.6A.1	General.....	101
7.6A.2	In-band blocking	101
7.6A.2.2	In-band blocking for Intra-band non-contiguous CA	102
7.6A.2.3	void	102
7.6D	Blocking characteristics for UL MIMO	102
7.7	Void.....	102
7.8	Void.....	102
7.9	Spurious emissions	102
7.10	Void.....	102
Annex A (normative):	Measurement channels	103
A.1	General	103
A.2	UL reference measurement channels	103
A.2.1	General	103
A.2.2	Void.....	103
A.2.3	Reference measurement channels for TDD.....	104
A.2.3.1	DFT-s-OFDM Pi/2-BPSK	105
A.2.3.2	DFT-s-OFDM QPSK	107
A.2.3.3	DFT-s-OFDM 16QAM	109
A.2.3.4	DFT-s-OFDM 64QAM	111
A.2.3.5	CP-OFDM QPSK	113
A.2.3.6	CP-OFDM 16QAM	115
A.2.3.7	CP-OFDM 64QAM	117

A.3	DL reference measurement channels	119
A.3.1	General	119
A.3.2	Void.....	121
A.3.3	DL reference measurement channels for TDD.....	121
A.3.3.1	General	121
A.3.3.2	FRC for receiver requirements for QPSK	122
A.3.3.3	FRC for receiver requirements for 16QAM	123
A.3.3.4	FRC for receiver requirements for 64QAM	124
A.4	Void.....	126
A.5	OFDMA Channel Noise Generator (OCNG)	126
A.5.1	OCNG Patterns for FDD.....	126
A.5.2	OCNG Patterns for TDD	126
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs	126
Annex B (informative):	Void	127
Annex C (normative):	Downlink physical channels.....	128
C.1	General	128
C.2	Setup.....	128
C.3	Connection	128
C.3.1	Measurement of Receiver Characteristics	128
Annex D (normative):	Characteristics of the interfering signal	129
D.1	General	129
D.2	Interference signals.....	129
Annex E (normative):	Environmental conditions.....	130
E.1	General	130
E.2	Environmental	130
E.2.1	Temperature	130
E.2.2	Voltage	130
E.2.3	Void.....	131
Annex F (normative):	Transmit modulation.....	132
F.1	Measurement Point.....	132
F.2	Basic Error Vector Magnitude measurement	132
F.3	Basic in-band emissions measurement.....	132
F.4	Modified signal under test.....	133
F.5	Window length	135
F.5.1	Timing offset	135
F.5.2	Window length	135
F.5.3	Window length for normal CP	135
F.5.4	Window length for Extended CP.....	136
F.5.5	Window length for PRACH	136
F.6	Averaged EVM	137
F.7	Spectrum Flatness	138
Annex G (informative):	Void	139
Annex H (informative):	Void	139
Annex I (informative):	Void	139
Annex J (normative):	UE coordinate system	140

J.1	Reference coordinate system.....	140
J.2	Test conditions and angle definitions.....	141
J.3	DUT positioning guidelines	145
Annex K (informative):	Void	147
Annex L (informative):	Change history	148
History		156

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/77ce8e67-6943-4c1b-8043-eaa916be4b33/etsi-ts-138-101-2-v15.9.1-2020-04>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/77ce8e67-6943-4c1b-8043-eaa916be4b33/etsi-ts-138-101-2-v15.9.1-2020-04>

1 Scope

The present document establishes the minimum RF requirements for NR User Equipment (UE) operating on frequency Range 2.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 38.101-1: "NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone"
- [3] 3GPP TS 38.101-3: "NR; User Equipment (UE) radio transmission and reception; Part 3: Range 1 and Range 2 Interworking operation with other radios"
- [4] Void
- [5] 3GPP TS 38.521-2: "NR; User Equipment (UE) conformance specification; Radio transmission and reception; Part 2: Range 2 Standalone"
- [6] Recommendation ITU-R M.1545: "Measurement uncertainty as it applies to test limits for the terrestrial component of International Mobile Telecommunications-2000"
- [7] ITU-R Recommendation SM.329-10, "Unwanted emissions in the spurious domain"
- [8] 47 CFR Part 30, "UPPER MICROWAVE FLEXIBLE USE SERVICE, §30.202 Power limits", FCC.
- [9] 3GPP TS 38.211: "NR; Physical channels and modulation".
- [10] 3GPP TS 38.213: "NR; Physical layer procedures for control".
- [11] 3GPP TS 38.215: "NR; Physical layer measurements".
- [12] 3GPP TS 38.133: "NR; Requirements for support of radio resource management".
- [13] 3GPP TS 38.331: "NR; Radio Resource Control (RRC); Protocol specification".
- [14] 3GPP TS 38.306: "NR; User Equipment (UE) radio access capabilities".
- [15] IEEE Std 149: "IEEE Standard Test Procedures for Antennas", IEEE.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

Aggregated Channel Bandwidth: The RF bandwidth in which a UE transmits and receives multiple contiguously aggregated carriers.

Beam correspondence: the ability of the UE to select a suitable beam for UL transmission based on DL measurements with or without relying on UL beam sweeping.

Carrier aggregation: Aggregation of two or more component carriers in order to support wider transmission bandwidths.

Carrier aggregation band: A set of one or more operating bands across which multiple carriers are aggregated with a specific set of technical requirements.

Carrier aggregation bandwidth class: A class defined by the aggregated transmission bandwidth configuration and maximum number of component carriers supported by a UE.

Carrier aggregation configuration: A combination of CA operating band(s) and CA bandwidth class(es) supported by a UE.

NOTE: Carriers aggregated in each band can be contiguous or non-contiguous.

EIRP(Link=Link angle, Meas=Link angle): measurement of the UE such that the link angle is aligned with the measurement angle. EIRP (indicator to be measured) can be replaced by EIS, Frequency, EVM, carrier Leakage, In-band eission and OBW.

EIRP(Link=TX beam peak direction, Meas=Link angle): measurement of the EIRP of the UE such that the measurement angle is aligned with the beam peak direction within an acceptable measurement error uncertainty. EIRP (indicator to be measured) can be replaced by Frequency, EVM, carrier Leakage, In-band eission and OBW

EIRP(Link=Spherical coverage grid, Meas=Link angle): measurement of the EIRP spherical coverage of the UE such that the EIRP link and measurement angles are aligned with the directions along the spherical coverage grid within an acceptable measurement error uncertainty. Alternatively, the spherical coverage grid can be replaced by the beam peak search grid as the results from the beam peak search can be re-used for spherical coverage.

EIS (equivalent isotropic sensitivity): sensitivity for an isotropic directivity device equivalent to the sensitivity of the discussed device exposed to an incoming wave from a defined AoA

EIS(Link=RX beam peak direction, Meas=Link angle): measurement of the EIS of the UE such that the measurement angle is aligned with the RX beam peak direction within an acceptable measurement error uncertainty.

NOTE 1: The sensitivity is the minimum received power level at which specific requirement is met.

NOTE 2: Isotropic directivity is equal in all directions (i.e. 0 dBi).

Fallback group: Group of carrier aggregation bandwidth classes for which it is mandatory for a UE to be able to fallback to lower order CA bandwidth class configuration. It is not mandatory for a UE to be able to fallback to lower order CA bandwidth class configuration that belong to a different fallback group

Inter-band carrier aggregation: Carrier aggregation of component carriers in different operating bands.

NOTE: Carriers aggregated in each band can be contiguous or non-contiguous.

Intra-band contiguous carrier aggregation: Contiguous carriers aggregated in the same operating band.

Intra-band non-contiguous carrier aggregation: Non-contiguous carriers aggregated in the same operating band.