



SLOVENSKI STANDARD
SIST EN 303 758 V1.1.1:2021

01-september-2021

Radijska oprema TETRA, ki uporablja modulacijo z nekonstantno ovojnico in deluje v kanalih s pasovnimi širinami 25 kHz, 50 kHz, 100 kHz ali 150 kHz - Harmonizirani standard za dostop do radijskega spektra

TETRA radio equipment using non-constant envelope modulation operating in a channel bandwidth of 25 kHz, 50 kHz, 100 kHz or 150 kHz - Harmonised Standard for access to radio spectrum

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 303 758 V1.1.1:2021](https://standards.iteh.ai/catalog/standards/sist/9483cc5b-9e30-4278-954f-86586f2b1c63/sist-en-303-758-v1.1.1-2021)

[https://standards.iteh.ai/catalog/standards/sist/9483cc5b-9e30-4278-954f-](https://standards.iteh.ai/catalog/standards/sist/9483cc5b-9e30-4278-954f-86586f2b1c63/sist-en-303-758-v1.1.1-2021)

[86586f2b1c63/sist-en-303-758-v1.1.1-2021](https://standards.iteh.ai/catalog/standards/sist/9483cc5b-9e30-4278-954f-86586f2b1c63/sist-en-303-758-v1.1.1-2021)

Ta slovenski standard je istoveten z: ETSI EN 303 758 V1.1.1 (2021-07)

ICS:

33.070.10	Prizemni snopovni radio (TETRA)	Terrestrial Trunked Radio (TETRA)
-----------	---------------------------------	-----------------------------------

SIST EN 303 758 V1.1.1:2021	en
------------------------------------	-----------

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 303 758 V1.1.1:2021

<https://standards.iteh.ai/catalog/standards/sist/9483cc5b-9e30-4278-954f-86586f2b1c63/sist-en-303-758-v1-1-1-2021>

ETSI EN 303 758 V1.1.1 (2021-07)



TETRA radio equipment using non-constant envelope modulation operating in a channel bandwidth of 25 kHz, 50 kHz, 100 kHz or 150 kHz; Harmonised Standard for access to radio spectrum

SIST EN 303 758 V1.1.1:2021
<https://standards.iteh.ai/catalog/standards/sist/9483cc5b-9e30-4278-954f-86586f2b1c63/sist-en-303-758-v1-1-1-2021>

Reference

DEN/ERM-TGDMMR-381

Keywords

data, mobile, PMR, radio, repeater, TETRA, voice

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

Contents

Intellectual Property Rights	7
Foreword.....	7
Modal verbs terminology.....	8
1 Scope	9
2 References	9
2.1 Normative references	9
2.2 Informative references.....	10
3 Definition of terms, symbols and abbreviations.....	11
3.1 Terms.....	11
3.2 Symbols.....	12
3.3 Abbreviations	12
4 General	13
4.1 Testing.....	13
4.1.1 Choice of model for testing	13
4.1.1.1 General.....	13
4.1.1.2 Auxiliary test equipment.....	13
4.1.2 Presentation of equipment for testing purposes	14
4.2 Mechanical and electrical design.....	14
4.2.1 Transmitter shut-off facility.....	14
4.3 Measuring continuous mode equipment.....	14
4.4 Measuring discontinuous mode equipment.....	14
4.5 Equipment supporting more than one channel bandwidth.....	14
4.6 Environmental profile.....	15
5 Test conditions, power sources and ambient temperatures.....	15
5.1 Normal and extreme test conditions.....	15
5.2 Test power source.....	15
5.3 Normal test conditions.....	15
5.3.1 Normal temperature and humidity	15
5.3.2 Normal test power source	15
5.3.2.1 Mains voltage.....	15
5.3.2.2 Regulated lead-acid battery power sources used on vehicles.....	16
5.3.2.3 Other power sources.....	16
5.4 Extreme test conditions	16
5.4.1 Extreme temperatures	16
5.4.2 Extreme test source voltages.....	16
5.4.2.1 Mains voltage.....	16
5.4.2.2 Regulated lead-acid battery power sources used on vehicles.....	16
5.4.2.3 Power sources using other types of batteries.....	16
5.4.2.4 Other power sources.....	16
5.5 Procedure for tests at extreme temperatures.....	17
5.5.1 Thermal balance.....	17
5.5.2 Procedure for equipment designed for continuous transmission.....	17
5.5.3 Procedure for equipment designed for intermittent transmission	17
5.5.4 Testing of equipment that does not have an external 50 Ω RF connector (integral antenna equipment).....	17
6 General conditions of measurement	18
6.1 Arrangements for test signals applied to the receiver input.....	18
6.2 Test load (artificial antenna).....	18
6.3 Test signals (wanted and unwanted signals).....	18
6.3.1 General.....	18
6.3.2 Test signal T1 (TETRA wanted signal, phase modulation).....	18
6.3.2.1 Test signal framing.....	18
6.3.2.2 MS testing	18

6.3.2.3	BS testing	19
6.3.3	Test signal T2 (TETRA interferer)	20
6.3.4	Test signal T3 (unmodulated interferer)	20
6.3.5	Test signal T4 (TETRA wanted signal, QAM)	20
6.3.5.1	Test signal structure	20
6.3.5.2	MS testing	20
6.3.5.2.1	Test signal usage	20
6.3.5.2.2	Use of synchronization burst in frame 18 when testing CA MSs	22
6.3.5.2.3	Use of frequency correction burst in frame 18 when testing DA MSs	24
6.3.5.3	BS testing	26
6.4	Transceiver data interface	26
6.5	Duplex equipment	26
6.6	Measurement filter definition	27
6.7	TMO Repeaters	27
7	Technical characteristics of the transmitter	27
7.1	Transmitter output power (conducted)	27
7.1.1	Definitions	27
7.1.2	Method of measurement	28
7.1.3	Limits	28
7.2	Adjacent and alternate channel power	29
7.2.1	Definition	29
7.2.2	Method of measurement	30
7.2.3	Limits	31
7.2.3.1	Limits for TMO Repeaters	31
7.2.3.2	Limits for BS and MS equipment	31
7.2.3.2.1	Limit values for phase modulation	31
7.2.3.2.2	Limit values for QAM	32
7.3	Unwanted emissions in the spurious domain	33
7.3.1	Definition	33
7.3.2	Method of measuring the power level	33
7.3.2.1	Measurement options	33
7.3.2.2	Method of measuring conducted spurious emissions	34
7.3.2.3	Method of measuring radiated spurious emissions	34
7.3.2.4	Method of measuring the effective radiated power	35
7.3.2.5	Method of measuring wideband noise	35
7.3.3	Limits	36
7.3.3.1	Spurious emissions power	36
7.3.3.2	Wideband noise power	37
7.3.3.2.1	Limit values for MS and BS for phase modulation	37
7.3.3.2.2	Limit values for MS and BS for QAM	38
7.3.3.2.3	Limit values for TMO repeater equipment	39
7.4	Intermodulation attenuation	40
7.4.1	Applicability	40
7.4.2	Definition	40
7.4.3	Method of measurement	40
7.4.3.1	Measurement for TMO repeater equipment	40
7.4.3.2	Measurement for BS	41
7.4.4	Limits	41
7.4.4.1	Limits for TMO repeater equipment	41
7.4.4.2	Limits for BS equipment	42
7.5	Adjacent channel transient power measurements	42
7.5.1	Definition	42
7.5.2	Method of Measurement	42
7.5.3	Limits	43
7.6	Frequency error	43
7.6.1	Definition	43
7.6.2	Method of measurement	43
7.6.3	Limits	44
7.7	Out of band gain for TMO repeater equipment	44
7.7.1	Applicability	44
7.7.2	Definition	44

7.7.3	Method of measurement	44
7.7.4	Limits.....	45
7.8	Modulation accuracy	45
7.8.1	Applicability	45
7.8.2	Definition.....	45
7.8.3	Method of measurement	45
7.8.4	Limits.....	46
8	Technical characteristics of the receiver	46
8.1	Applicability.....	46
8.2	Receiver sensitivity	46
8.2.1	General.....	46
8.2.2	Definition.....	46
8.2.3	Method of measurement	47
8.2.4	Limits.....	47
8.2.4.1	Limit values for phase modulation.....	47
8.2.4.2	Limit values for QAM.....	48
8.3	Blocking or desensitization	48
8.3.1	Definition.....	48
8.3.2	Method of measurement	48
8.3.3	Limits.....	49
8.4	Adjacent channel selectivity.....	49
8.4.1	Definition.....	49
8.4.2	Method of measurement	49
8.4.3	Limits.....	50
8.5	Spurious radiations.....	51
8.5.1	Definition.....	51
8.5.2	Methods of measurement.....	51
8.5.2.1	Method of measuring the power level in a specified load.....	51
8.5.2.2	Method of measuring the effective radiated power.....	51
8.5.3	Limits.....	52
8.6	Co-channel rejection.....	53
8.6.1	Definition.....	53
8.6.2	Method of measurement.....	53
8.6.3	Limits.....	54
8.6.3.1	Limit values for phase modulation.....	54
8.6.3.2	Limit values for QAM.....	54
8.7	Intermodulation response rejection	54
8.7.1	Definition.....	54
8.7.2	Method of measurement	55
8.7.3	Limit	55
8.8	Spurious response rejection.....	56
8.8.1	Definition.....	56
8.8.2	Method of measurement	56
8.8.3	Limits.....	56
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	57
Annex B (normative):	Radiated measurement.....	59
B.1	Test sites and general arrangements for measurements involving the use of radiated fields	59
B.1.1	General	59
B.1.2	Anechoic chamber.....	59
B.1.3	Anechoic chamber with a conductive ground plane.....	60
B.1.4	Open Area Test Site (OATS)	61
B.1.5	Test antenna.....	62
B.1.6	Substitution antenna	62
B.1.7	Measuring antenna	63
B.2	Guidance on the use of radiation test sites	63
B.2.1	General	63
B.2.2	Verification of the test site	63

B.2.3	Preparation of the EUT.....	63
B.2.4	Power supplies to the EUT.....	63
B.2.5	Range length.....	63
B.2.6	Site preparation	64
B.3	Coupling of signals.....	65
B.3.1	General	65
B.3.2	Data signals	65
Annex C (normative):	Spectrum analyser specification	66
Annex D (normative):	TETRA receiver testing.....	67
D.1	Test signal T1/T4, content of BSCH, BSCH-Q/T, BNCH/T and BNCH-Q/T.....	67
D.2	Frequencies of spurious response.....	72
Annex E (informative):	Example arrangement for transmitter intermodulation measurement....	74
Annex F (informative):	Maximum measurement uncertainty.....	75
Annex G (informative):	Selection of technical parameters to meet the essential requirements of Directive 2014/53/EU.....	76
Annex H (informative):	Change History	77
History		78

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 303 758 V1.1.1:2021](https://standards.iteh.ai/catalog/standards/sist/9483cc5b-9e30-4278-954f-86586f2b1c63/sist-en-303-758-v1-1-1-2021)

<https://standards.iteh.ai/catalog/standards/sist/9483cc5b-9e30-4278-954f-86586f2b1c63/sist-en-303-758-v1-1-1-2021>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITh STANDARD PREVIEW
(standards.iteh.ai)

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Electromagnetic compatibility and Radio spectrum Matters (ERM).
SIST EN 303 758 V1.1.1:2021
<https://standards.iteh.ai/catalog/standards/sist/303-758-v1-1-1-2021>

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.6] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

National transposition dates	
Date of adoption of this EN:	30 June 2021
Date of latest announcement of this EN (doa):	30 September 2021
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2022
Date of withdrawal of any conflicting National Standard (dow):	31 March 2023

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 303 758 V1.1.1:2021](#)

<https://standards.iteh.ai/catalog/standards/sist/9483cc5b-9e30-4278-954f-86586f2b1c63/sist-en-303-758-v1-1-1-2021>

1 Scope

The present document specifies the technical requirements and methods of measurements for TETRA radio transmitters and receivers used in stations and technical requirements and methods of measurements for TMO repeater in the Private Mobile Radio (PMR) service.

It applies to use in the land mobile service, operating on radio frequencies between 137 MHz and 1 GHz, with channel separations of 25 kHz, 50 kHz, 100 kHz and 150 kHz.

Table 1: Radiocommunications service frequency bands

	Radiocommunications service frequency bands
Transmit	137 MHz to 1 000 MHz
Receive	137 MHz to 1 000 MHz

It applies to equipment for continuous and/or discontinuous transmission of data and/or digital speech.

The equipment (base station and mobile station) comprises a transmitter and associated encoder and modulator and/or a receiver and associated demodulator and decoder.

The types of equipment covered by the present document are as follows:

- base station (equipment fitted with an antenna connector, intended for use in a fixed location);
- mobile station (equipment fitted with an antenna connector, normally used in a vehicle or as a transportable);
- TMO Repeater; and
- those hand portable stations:
 - a) fitted with an antenna connector; or
 - b) without an external antenna connector (integral antenna equipment), but fitted with a permanent internal or a temporary internal 50 Ω Radio Frequency (RF) connector which allows access to the transmitter output and the receiver input.

Hand portable equipment without an external or internal RF connector and without the possibility of having a temporary internal 50 Ω RF connector is not covered by the present document.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.2] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] Recommendation ITU-T O.153 (10-1992): "Basic parameters for the measurement of error performance at bit rates below the primary rate".

- [2] IEEE/ANSI C63.5 (2017): "American National Standard for Electromagnetic Compatibility -- Radiated Emission Measurements in Electromagnetic Interference (EMI) Control -- Calibration and Qualification of Antennas (9 kHz to 40 GHz)".
- [3] ETSI EN 300 392-2 (V3.8.1) (08-2016): "Terrestrial Trunked Radio (TETRA); Voice plus Data (V+D); Part 2: Air Interface (AI)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] CEPT/ERC/REC 74-01 (2019): "Unwanted Emissions in the Spurious domain".
- [i.2] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.

NOTE: Article 3.2 and article 10.8.

- [i.3] ETSI TS 101 789-1 (V1.1.2): "Terrestrial Trunked Radio (TETRA); TMO Repeaters; Part 1: Requirements, test methods and limits".
- [i.4] ETSI EN 300 394-1 (V3.3.1) (04-2015): "Terrestrial Trunked Radio (TETRA); Conformance testing specification; Part 1: Radio".
- [i.5] ETSI EN 303 035-1 (V1.2.1) (12-2001): "Terrestrial Trunked Radio (TETRA); Harmonized EN for TETRA equipment covering essential requirements under article 3.2 of the R&TTE Directive; Part 1: Voice plus Data (V+D)".
- [i.6] Commission Implementing Decision C(2015) 5376 final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.7] ETSI EN 300 793 (V1.1.1) (02-1998): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Land mobile service; Presentation of equipment for type testing".
- [i.8] ETSI TR 102 273 (V1.2.1) (12-2001) (all parts): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties".
- [i.9] ETSI EG 203 336 (V1.2.1) (05-2020): "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

base station: equipment fitted with an antenna connector, for use with an external antenna, and intended for use in a fixed location

bit: binary digit

block: smallest quantity of information that is sent over the radio channel

NOTE: A constant number of useful bits are always sent together with the corresponding redundancy bits.

broadband repeater: repeater which is designed for operation on any combination of carriers (up to a specified maximum number) within the operating band of the repeater

burst or transmission (physical): one or several packets transmitted between power on and power off of a particular transmitter

channelized repeater: repeater which is designed for operation on a specified subset of carriers within the operating band of the repeater

NOTE: The subset of the channels may be determined during the manufacture of the repeater, or may be programmable.

conducted measurements: measurements which are made using direct 50 Ω connection to the equipment under test

data transmission systems: systems which transmit and/or receive data and/or digitized voice

downlink: signal path where base station transmits and mobile or hand portable station receives

hand portable station: equipment either fitted with an antenna connector or integral antenna, or both, normally used on a stand-alone basis, to be carried on a person or held in the hand

NOTE: Test limits specified for MS within the present document apply to mobile stations and handportable stations.

integral antenna: antenna designed to be connected to the equipment without the use of a 50 Ω external connector and considered to be part of the equipment

NOTE: An integral antenna may be fitted internally or externally to the equipment.

mobile station: mobile equipment fitted with an antenna connector, for use with an external antenna, normally used in a vehicle or as a transportable station

NOTE: Test limits specified for MS within the present document apply to mobile stations and handportable stations.

radiated measurements: measurements which involve the absolute measurement of a radiated field

receive band of the equipment: maximum frequency range in accordance with the intended operation of the equipment over which the receiver can be operated without reprogramming or realignment

spurious emissions: unwanted emissions in the spurious domain

testing laboratory: laboratory that performs tests

TMO Repeater: bi-directional Radio Frequency (RF) amplifier which can amplify and transmit a received Mobile Station (MS) signal in the MS transmit band, simultaneously it can amplify and transmit a received Base Station (BS) RF signal in the BS transmit band

transmit band of the equipment: maximum frequency range in accordance with the intended operation of the equipment over which the transmitter can be operated without reprogramming or realignment

Trunked Mode Operation (TMO): mode of operation where a network is used for communication

uplink: signal path where mobile or hand portable station transmits and base station receives

3.2 Symbols

For the purposes of the present document, the following symbols apply:

α	Filter roll-off factor
dB	decibel
dBm	dB relative to 1 mW
dB μ V	dB relative to 1 μ V
f_c	channel centre frequency
f_{lo}	Local Oscillator frequency
f_{rb}	the frequency offset corresponding to the near edge of the receive band, or 5 MHz (10 MHz for frequencies above 520 MHz), whichever is greater
T1, T2, etc.	names of test signals defined in clause 6.3
P_A	average power
V_{min}	minimum extreme test Voltage
V_{max}	maximum extreme test Voltage
T_{min}	minimum extreme test Temperature
T_{max}	maximum extreme test Temperature
λ	wavelength

<https://standards.iteh.ai/>
 (standards.iteh.ai)

3.3 Abbreviations

[SIST EN 303 758 V1.1.1:2021](https://standards.iteh.ai/catalog/standards/sist/9483cc5b-9e30-4278-954f-86586f2b1c63/sist-en-303-758-v1-1-1-2021)

For the purposes of the present document, the following abbreviations apply:

AACH	Access Assignment CHannel
AACH-Q	Access Assignment CHannel, QAM
AC	Alternating Current
ACP	Adjacent Channel Power
AGC	Automatic Gain Control
BCC	Base station Colour Code
BER	Bit Error Rate
BLCH	Base station Linearization CHannel
BNCH/T	Broadcast Network CHannel, Test mode
BS	Base Station
BSCH	Broadcast Synchronization CHannel
BW	BandWidth
CA	Conventional Access
CA MS	Conventional Access Mobile Station
CEPT	European Conference of Postal and Telecommunications administrations
CLCH	Common Linearization CHannel
CW	Continuous Wave
DA	Direct Access
DA MS	Direct Access Mobile Station
dBc	decibels relative to the transmitter power
DC	Direct Current
DMO	Direct Mode Operation
DQPSK	Differential Quadrature Phase Shift Keying
DTX	Discontinuous Transmission
EC	European Community
EFTA	European Free Trade Association
EUT	Equipment Under Test
FCB	Frequency Correction downlink Burst

FER	Frame Erasure Rate
IF	Intermediate Frequency
ITU-T	International Telecommunication Union - Telecommunication standardization sector
MCC	Mobile Country Code
MNC	Mobile Network Code
MS	Mobile Station
OATS	Open Area Test Site
PDU	Protocol Data Unit
PMR	Private Mobile Radio
ppm	parts per million
PQ	Power level of QAM burst
PRBS	Pseudo Random Bit Sequence
QAM	Quadrature Amplitude Modulation
RDC	Radio Downlink Counter
RF	Radio Frequency
rms	root mean square
Rx	Receiver
SCH/F	Signalling CHannel Full
SCH/HD	Signalling CHannel, Half size Downlink
SCH/HU	Signalling CHannel, Half size Uplink
SICH-Q/D	Slot Information CHannel, QAM Downlink
SN-Q	Symbol Number in QAM
STCH	STealing CHannel
TCH/S	Traffic CHannel, Speech
TETRA	TErrestrial Trunked RAdio
TMO	Trunked Mode Operation
Tx	Transmitter
VSWR	Voltage Standing Wave Ratio
$\pi/4$ -DQPSK	$\pi/4$ -shifted Differential Quaternary Phase Shift Keying

STANDARD PREVIEW
(standards.iteh.ai)

4 General

[SIST EN 303 758 V1.1.1:2021](https://standards.iteh.ai/catalog/standards/sist/9483cc5b-9e30-4278-954f-86586f2b1c63/sist-en-303-758-v1-1-1-2021)

<https://standards.iteh.ai/catalog/standards/sist/9483cc5b-9e30-4278-954f-86586f2b1c63/sist-en-303-758-v1-1-1-2021>

4.1 Testing

4.1.1 Choice of model for testing

4.1.1.1 General

One or more samples of the equipment shall be provided, as appropriate for testing. Stand-alone equipment shall be complete with any ancillary equipment needed for testing.

If an equipment has several optional features, considered not to affect the RF parameters, then the tests need only be performed on the equipment configured with the combination of features considered to be the most complex. Where practicable, equipment to be tested shall provide a 50 Ω connector for conducted RF power level measurements.

In the case of integral antenna equipment, if the equipment does not have an internal permanent 50 Ω connector then it is permissible to use a second sample of the equipment with a temporary antenna connector fitted to facilitate testing. Any such modified sample shall not be used for any radiated measurements, except as noted in clause 5.5.4.

The performance of the equipment to be tested shall be representative of the performance of the corresponding production model.

4.1.1.2 Auxiliary test equipment

All necessary test signal sources, setting up instructions and other product information shall be made available with the equipment to be tested.