INTERNATIONAL STANDARD



First edition 2014-05-01

Solid biofuels — Fuel specifications and classes —

Part 7: Graded non-woody briquettes

Biocombustibles solides — Classes et spécifications des **iTeh** STCOMBUSTIBLES PREVIEW Partie 7: Classes de briquettes d'origine agricole (standards.iteh.ai)

<u>ISO 17225-7:2014</u> https://standards.iteh.ai/catalog/standards/sist/12fa79e1-702e-45c8-ae65-8f425a032ef5/iso-17225-7-2014



Reference number ISO 17225-7:2014(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 17225-7:2014</u> https://standards.iteh.ai/catalog/standards/sist/12fa79e1-702e-45c8-ae65-8f425a032ef5/iso-17225-7-2014



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Page

Contents

Foreword		
Introduction		
1	Scope 1	
2	Normative references 1	
3	Terms and definitions 2	
4	Symbols and abbreviated terms 3	
5	Specification of graded non-woody briquettes3	
Bibliography		

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 17225-7:2014</u> https://standards.iteh.ai/catalog/standards/sist/12fa79e1-702e-45c8-ae65-8f425a032ef5/iso-17225-7-2014

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 238, *Solid biofuels*.

ISO 17225 consists of the following parts, under the general title Solid biofuels — Fuel specifications and classes: https://standards.iteh.ai/catalog/standards/sist/12fa79e1-702e-45c8-ae65-8f425a032ef5/iso-17225-7-2014

- Part 1: General requirements
- Part 2: Graded wood pellets
- Part 3: Graded wood briquettes
- Part 4: Graded wood chips
- Part 5: Graded firewood
- Part 6: Graded non-woody pellets
- Part 7: Graded non-woody briquettes

Introduction

The objective of the ISO 17225 series is to provide unambiguous and clear classification principles for solid biofuels; to serve as a tool to enable efficient trading of biofuels; to enable good understanding between seller and buyer as well as a tool for communication with equipment manufacturers. It will also facilitate authority permission procedures and reporting.

This part of ISO 17225 supports the use of graded non-woody pellets for residential, small commercial and public building applications.

The residential, small commercial and public building applications require higher quality fuel for the following reasons:

- Small-scale equipment does not usually have advanced controls and flue gas cleaning
- Appliances is not generally managed by professional heating engineers
- Appliances are often located in residential and populated districts

Non-woody briquettes have high ash, chlorine, nitrogen, sulfur and major element contents, so nonwoody briquettes are recommended to be used in appliances, which are specially designed or adjusted for this kind of briquettes.

NOTE 1 Briquettes produced according to this part of ISO 17225 may be used in stoves, fireplaces, cookers, roomheaters and multifired sauna stoves, which are tested according to European standards EN 13229^[1], EN 12815^[2], EN 12809^[3], EN 13240^[4], EN 15250^[5] and EN 15821^[6], and boilers systems tested according to EN 303–5^[7].

NOTE 2 When using non-woody materials for combustion special attention should be paid to the risk of corrosion in small and medium scale boilers and flue gas systems. Be aware that herbaceous or fruit biomass may influence the fuel ash composition differently depending on growth and soil conditions. The content of chlorine, phosphate and potassium/in the material may form chlorides/and phosphates and other chemical compounds resulting in high hydrochloric emissions and chemically active ash with low melting temperature causing corrosion.

NOTE 3 In general non-woody biomass materials have higher content of ash forming elements and produces ashes with lower melting temperature compared to most woody biomass. This may result in fouling, slagging and corrosion inside boilers. These problems are especially related to materials that contain high content of potassium (K) and silicate (Si) and low content of calcium (Ca).

NOTE 4 For individual contracts ISO 17225-1 can be used.

Although these product standards may be obtained separately, they require a general understanding of the standards based on and supporting ISO 17225-1. It is recommended to obtain and use ISO 17225-1 in conjunction with these standards.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 17225-7:2014</u> https://standards.iteh.ai/catalog/standards/sist/12fa79e1-702e-45c8-ae65-8f425a032ef5/iso-17225-7-2014

Solid biofuels — Fuel specifications and classes —

Part 7: Graded non-woody briquettes

1 Scope

This part of ISO 17225 determines the fuel quality classes and specifications of graded non-woody briquettes. This part of ISO 17225 covers only non-woody briquettes produced from the following raw materials (see ISO 17225-1, Table 1):

2 Herbaceous biomass

NOTE 1 Herbaceous biomass is from plants that have a non-woody stem and which die back at the end of the growing season. It includes grains or seeds crops from food production or processing industry and their byproducts such as cereals.

- **3** Fruit biomass
- 4 Aquatic biomass
- iTeh STANDARD PREVIEW
- 5 Biomass blends and mixtures standards.iteh.ai)

Group 5 Blends and mixtures include blends and mixtures from the main origin-based solid biofuel NOTE 2 groups woody, herbaceous biomass, fruit biomass and aquatic biomass.

Blends are intentionally mixed biofuels, whereas mixtures are unintentionally mixed biofuels. The origin of the blend and mixture is to be described using ISO 17225-1, Table 1.

If solid biofuel blend or mixture contains chemically treated material it shall be stated.

Thermally treated biomass briquettes (e.g. torrefied briquettes) are not included in the scope of this NOTE 3 part of ISO 17225. Torrefaction is a mild pre-treatment of biomass at a temperature between 200 - 300 °C.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO standards describing methods for analysis of fuel properties listed in the Bibliography, will become NOTE normative references when they are published.

ISO 16559, Solid biofuels — Terminology, definitions and descriptions¹

ISO 16948, Solid biofuels — Determination of total content of carbon, hydrogen and nitrogen²)

ISO 16968, Solid biofuels — Determination of minor elements³

ISO 16994, Solid biofuels — Determination of total content of sulfur and chlorine⁴)

- 2) To be published.
- 3) To be published.
- 4) To be published.

¹⁾ To be published.

ISO 17225-1, Solid biofuels — Fuel specifications and classes — Part 1: General requirements

ISO 18122, Solid biofuels — Determination of ash content⁵)

ISO 18134-1, Solid biofuels — Determination of moisture content — Oven dry method — Part 1: Total moisture — Reference method⁶)

ISO 18134-2, Solid biofuels — Determination of moisture content — Oven dry method — Part 2: Total moisture - Simplified method⁷)

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 16559 and the following apply.

3.1

non-woody briquette

densified biofuel made with or without additives in form of cubiform, prismatic or cylindrical unit with diameter of more than 25 mm produced by compressing milled biomass

Note 1 to entry: The raw material for non-woody briquettes can be herbaceous, fruit or aquatic biomass or biomass blends and mixtures.

Note 2 to entry: Briquettes are usually manufactured in a piston press, with the total moisture content on wet basis usually being less than 15 % of the mass.

3.2 additive

iTeh STANDARD PREVIEW

material which has been intentionally introduced into the fuel feed stock to improve quality of fuel (e.g. combustion properties), to reduce emissions or to make production more efficient

Note 1 to entry: Trace amounts of e.g. grease or other lubricants that are introduced into the fuel processing stream as part of normal mill operations are hor considered as additives:e1-702e-45c8-ae65-8f425a032ef5/iso-17225-7-2014

3.3

chemical treatment

any treatment with chemicals other than air, water or heat

EXAMPLE Glue and paint.

Note 1 to entry: Examples of chemical treatment are listed in ISO 17225-1.

3.4

commercial application

facility that utilize solid biofuel burning appliances or equipment that have similar fuel requirements as residential appliances

Note 1 to entry: Commercial applications should not be confused with industrial applications, which can utilize a much wider array of materials and have vastly different fuel requirements.

⁵⁾ To be published.

⁶⁾ To be published.

⁷⁾ To be published.

4 Symbols and abbreviated terms

The symbols and abbreviated terms used in this part of ISO 17225 comply with the SI system of units as far as possible.

d	dry (dry basis)
ar	as received
w-%	weight-percentage
А	Designation for ash content on dry basis, A_d [w-%]
BD	Designation for bulk density as received [kg/m ³]
D	Designation for diameter as received, D [mm]
DU	Designation for mechanical durability as received [w-%]
F	Designation for amount of fines as received [w-%, particles less than 3,15 mm]
L	Designation for length as received, L [mm]
М	Designation for moisture content as received on wet basis, M_{ar} [w-%]
Q	Designation for net calorific value as received, <i>q</i> _{<i>p</i>,net,ar} [MJ/kg or kWh/kg or MWh/t] at constant pressure iTeh STANDARD PREVIEW
NOTE 1	1 MI/kg equals 0.2778 kwh/kg/ kwh/kg equals 1 Mwh/t and 1 MWh/t is 3.6 MI/kg), 1 g/cm ³ equ

NOTE 1 1 MJ/kg equals 0,2778 kwh/kg 1 kwh/kg equals 1 Mwh/t and 1 MWh/t is 3,6 MJ/kg). 1 g/cm³ equals 1 kg/dm³. 1 mg/kg equals 0,000 1 % or 1 ppm.

NOTE 2 Designation symbols are used in combination with a number to specify property levels in Table 1. For designation of chemical properties, chemical symbols like S (sulfur), Cl (chlorine), N (nitrogen) are used and the property class is added at the end of the symbol.

5 Specification of graded non-woody briquettes

The specification of the non-woody briquettes is stated in accordance with <u>Table 1</u> and <u>Figure 1</u>. Sampling and analysis of the properties shall be carried out in accordance with the methods mentioned in the normative references.

Chemical treatment before harvesting of biomass does not need to be stated. Where any operator in the fuel supply chain has reason to suspect serious contamination of land (e.g. coal slag heaps) or if planting has been used specifically for the sequestration of chemicals or biomass is fertilised by sewage sludge (originating from waste water treatment or chemical process), fuel analysis should be carried out to identify chemical impurities such as halogenated organic compounds or heavy metals. In case of raw materials belonging to 2.2.2 and 3.2.2 (chemically treated herbaceous and fruit biomass according to ISO 17225-1, Table 1) the actual origin of the raw material shall be clearly described.