
**Petroleum products — Fuels (class F) —
Specifications of marine fuels**

*Produits pétroliers — Combustibles (classe F) —
Spécifications des combustibles pour la marine*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 8217:2012](https://standards.iteh.ai/catalog/standards/sist/7d951fed-9003-4ea8-a30b-1eb22efd427e/iso-8217-2012)

<https://standards.iteh.ai/catalog/standards/sist/7d951fed-9003-4ea8-a30b-1eb22efd427e/iso-8217-2012>



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 8217:2012

<https://standards.iteh.ai/catalog/standards/sist/7d951fed-9003-4ea8-a30b-1eb22efd427e/iso-8217-2012>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Application	2
4 Sampling	2
5 General requirements	3
6 Specification requirements	3
6.1 Requirements for distillate and residual fuels	3
6.2 Requirements for distillate fuels	3
6.3 Requirements for residual fuels	4
7 Test methods	4
7.1 Density	4
7.2 Sulfur content	4
7.3 Flash point	4
7.4 Total sediment by hot filtration	5
7.5 Total sediment — Aged	5
7.6 Appearance	5
7.7 Vanadium	5
7.8 Sodium	5
7.9 Aluminium plus silicon	5
7.10 Used lubricating oil (ULO)	5
7.11 Hydrogen sulfide	5
8 Precision and interpretation of test results	6
Annex A (informative) Bio-derived products and fatty acid methyl esters	11
Annex B (informative) Deleterious materials	13
Annex C (informative) Sulfur content	14
Annex D (informative) Hydrogen sulfide	15
Annex E (informative) Specific energy	16
Annex F (informative) Ignition characteristics of residual marine fuels	18
Annex G (informative) Flash point	21
Annex H (informative) Acidity	22
Annex I (informative) Sodium and vanadium	23
Annex J (informative) Catalyst fines	25
Annex K (informative) Used lubricating oils	26
Annex L (informative) Precision and interpretation of test results	27
Bibliography	29

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 8217 was prepared by Technical Committee ISO/TC 28, *Petroleum products and lubricants*, Subcommittee SC 4, *Classifications and specifications*.

This fifth edition cancels and replaces the fourth edition (ISO 8217:2010) and incorporates Technical Corrigendum ISO 8217:2010/Cor.1:2011. In addition, a normative reference to IP 570, Procedure A has been added in 7.11 for the purposes of the hydrogen sulfide test method. Corresponding references to IP 570 have been inserted in Tables 1 and 2. In Clause 2, the list of normative references has been updated to refer readers to the most recent edition where no edition date is specified.

STANDARD PREVIEW
(standards.iteh.ai)

[ISO 8217:2012](https://standards.iteh.ai/catalog/standards/sist/7d951fed-9003-4ea8-a30b-1eb22efd427e/iso-8217-2012)

<https://standards.iteh.ai/catalog/standards/sist/7d951fed-9003-4ea8-a30b-1eb22efd427e/iso-8217-2012>

Introduction

0.1 General

This International Standard was prepared in co-operation with ship owners, ship operators, shipping associations, national standards bodies, classification societies, fuel testing services, engine designers, fuel suppliers and the petroleum industry in order to meet the requirements for fuels supplied on a world-wide basis for consumption on board ships. Crude oil supplies, refining methods, ships' machinery, environmental legislation and local conditions vary considerably. These factors have led historically to a large number of categories of residual fuels being available internationally, even though locally or nationally there can be relatively few categories available.

0.2 Classification

The categories of fuel in this International Standard have been classified in accordance with ISO 8216-1^[1].

0.3 International statutory requirements

This International Standard takes into account the SOLAS Convention^[2] in respect of the allowable minimum flash point of fuels.

The Revised MARPOL Annex VI^[3], which controls air pollution from ships, includes a requirement that either the fuel not exceed specified maximum sulfur content or an approved equivalent alternative be used. During the lifetime of this International Standard, regional and/or national bodies can introduce their own local emission requirements, which can impact the allowable sulfur content, for example the EU Sulfur Directive^[4]. It is the users' responsibility to establish the requirement to comply with such statutory requirements and to specify the maximum sulfur content of the fuel to the supplier.

0.4 Changes with respect to ISO 8217:2010

This fifth edition of this International Standard incorporates the following changes with respect to the previous fourth edition:

- on page 5, subclause 7.11 on hydrogen sulfide has been added, including a normative reference to IP 570, Procedure A;
- on page 8, in the row Pour point (upper) of Table 1, for category ISO-F-DMX the previous values “–6” and “0” have been replaced by “—”. (This formed the subject of ISO 8217:2010/Cor.1:2011.)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 8217:2012

<https://standards.iteh.ai/catalog/standards/sist/7d951fed-9003-4ea8-a30b-1eb22efd427e/iso-8217-2012>

Petroleum products — Fuels (class F) — Specifications of marine fuels

WARNING — The handling and use of products specified in this International Standard can be hazardous if suitable precautions are not observed. This International Standard does not purport to address all of the safety and health considerations that can be associated with its use. It is the responsibility of the users of this International Standard to establish appropriate safety and health practices and to determine the applicability of regulatory limitations prior to use.

1 Scope

This International Standard specifies the requirements for petroleum fuels for use in marine diesel engines and boilers, prior to appropriate treatment before use. The specifications for fuels in this International Standard can also be applicable to fuels for stationary diesel engines of the same or similar make and type as those used for marine purposes.

This International Standard specifies four categories of distillate fuel, one of which is for diesel engines for emergency purposes. It also specifies six categories of residual fuel.

NOTE 1 For the purposes of this International Standard, the term “petroleum” is used to include oil from tar sands and from shale.

NOTE 2 Appropriate guidance about fuel treatment systems for diesel engines is published by the International Council on Combustion Engines (CIMAC)^[5].

NOTE 3 Requirements for gas turbine fuels used in marine applications are specified in ISO 4261^[6].

NOTE 4 For the purposes of this International Standard, the terms “mass %” and “volume %” are used to represent the mass and volume fractions respectively.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 91-1:1992, *Petroleum measurement tables — Part 1: Tables based on reference temperatures of 15 °C and 60 °F*

ISO 2719, *Determination of flash point — Pensky-Martens closed cup method*

ISO 3015, *Petroleum products — Determination of cloud point*

ISO 3016, *Petroleum products — Determination of pour point*

ISO 3104, *Petroleum products — Transparent and opaque liquids — Determination of kinematic viscosity and calculation of dynamic viscosity*

ISO 3675, *Crude petroleum and liquid petroleum products — Laboratory determination of density — Hydrometer method*

ISO 3679, *Determination of flash point — Rapid equilibrium closed cup method*

ISO 3733, *Petroleum products and bituminous materials — Determination of water — Distillation method*

ISO 4259, *Petroleum products — Determination and application of precision data in relation to methods of test*

ISO 8217:2012(E)

ISO 4264, *Petroleum products — Calculation of cetane index of middle-distillate fuels by the four-variable equation*

ISO 6245, *Petroleum products — Determination of ash*

ISO 8754, *Petroleum products — Determination of sulfur content — Energy-dispersive X-ray fluorescence spectrometry*

ISO 10307-1, *Petroleum products — Total sediment in residual fuel oils — Part 1: Determination by hot filtration*

ISO 10307-2, *Petroleum products — Total sediment in residual fuel oils — Part 2: Determination using standard procedures for ageing*

ISO 10370, *Petroleum products — Determination of carbon residue — Micro method*

ISO 10478, *Petroleum products — Determination of aluminium and silicon in fuel oils — Inductively coupled plasma emission and atomic absorption spectroscopy methods*

ISO 12156-1, *Diesel fuel — Assessment of lubricity using the high-frequency reciprocating rig (HFRR) — Part 1: Test method*

ISO 12185, *Crude petroleum and petroleum products — Determination of density — Oscillating U-tube method*

ISO 12205, *Petroleum products — Determination of the oxidation stability of middle-distillate fuels*

ISO 12937, *Petroleum products — Determination of water — Coulometric Karl Fischer titration method*

ISO 13739, *Petroleum products — Procedures for transfer of bunkers to vessels*

ISO 14596, *Petroleum products — Determination of sulfur content — Wavelength-dispersive X-ray fluorescence spectrometry*

ISO 14597, *Petroleum products — Determination of vanadium and nickel content — Wavelength-dispersive X-ray fluorescence spectrometry*

EN 14214, *Automotive fuels — Fatty acid methyl esters (FAME) for diesel engines — Requirements and test methods*

IP 470, *Determination of aluminium, silicon, vanadium, nickel, iron, calcium, zinc and sodium in residual fuel oil by ashing, fusion and atomic absorption spectrometry*

IP 500, *Determination of the phosphorus content of residual fuels by ultra-violet spectrometry*

IP 501, *Determination of aluminium, silicon, vanadium, nickel, iron, sodium, calcium, zinc and phosphorus in residual fuel oil by ashing, fusion and inductively coupled plasma emission spectrometry*

IP 570, *Determination of hydrogen sulfide in fuel oils — Rapid liquid phase extraction method*

ASTM D664, *Standard Test Method for Acid Number of Petroleum Products by Potentiometric Titration*

ASTM D6751, *Standard Specification for Biodiesel Fuel Blend Stock (B100) for Middle Distillate Fuels*

3 Application

This International Standard specifies the required properties for fuels at the time and place of custody transfer. Samples for quality verification may be taken in any location agreed between the parties.

4 Sampling

The sampling of petroleum fuels for analysis shall be carried out in accordance with the procedures given in ISO 13739 or an equivalent national standard. Where specific sampling requirements are documented in the referenced test methods, these shall be adhered to.

5 General requirements

5.1 The fuel shall conform to the characteristics and limits given in Table 1 or Table 2, as appropriate, when tested in accordance with the methods specified.

5.2 The fuel shall be a homogeneous blend of hydrocarbons derived from petroleum refining. This shall not preclude the incorporation of additives intended to improve some aspects of the fuel's characteristics and performance. The fuel shall be free from inorganic acids and used lubricating oils.

5.3 Fuels shall be free from any material that renders the fuel unacceptable for use in marine applications.

5.4 The fuel shall be free from bio-derived materials other than “*de minimis*” levels of fatty acid methyl esters (FAMES), where FAMES shall be in accordance with the requirements of EN 14214 or ASTM D6751. In the context of this International Standard, “*de minimis*” means an amount that does not render the fuel unacceptable for use in marine applications. The blending of FAMES shall not be allowed.

NOTE See Annex A.

5.5 The fuel shall not contain any additive at the concentration used in the fuel, or any added substance or chemical waste that

- a) jeopardizes the safety of the ship or adversely affects the performance of the machinery, or
- b) is harmful to personnel, or
- c) contributes overall to additional air pollution.

NOTE See Annex B.

6 Specification requirements

6.1 Requirements for distillate and residual fuels

- a) The hydrogen sulfide, H₂S, concentration shall be as specified in Table 1 or Table 2.

WARNING — H₂S is a highly toxic gas. Exposure to high vapour concentrations is hazardous and in extreme cases can be fatal. It is critical that ship owners, operators and other responsible parties continue to maintain appropriate safety practices designed to protect the crew and others who can be exposed to H₂S; see Annex D.

- b) Acidity shall be as specified in Table 1 or Table 2.

NOTE Acid number limits are included in this International Standard; see Annex H.

6.2 Requirements for distillate fuels

- a) Oxidation stability shall be as specified in Table 1.

NOTE The refinery processes used to manufacture distillate fuels can lead to products that can have limited oxidation stability. In addition, today's non-marine distillate fuels can contain a significant amount (for example, in some areas currently 5 volume % to 7 volume %) of bio-derived products, i.e. FAMES, that can impact on the oxidation stability of the fuel. Furthermore, the transportation of pure distillate fuel and distillate fuel containing bio-derived material (FAME), especially through multi-product pipeline installations, has shown that some FAME is transferred into the pure distillate fuel; see Annex A.

b) The lubricity shall be as specified in Table 1.

NOTE A lubricity requirement has been included in this International Standard and is applicable to clear and bright distillate fuels with a sulfur content below 500 mg/kg (0,050 mass %). The lubricity limit is based on the existing requirements for high-speed automotive and heavy-duty industrial diesel engines.

6.3 Requirements for residual fuels

a) Ignition characteristics, as determined by the Calculated Carbon Aromaticity Index (CCAI), shall be as specified in Table 2.

NOTE 1 CCAI, an indication of ignition performance, has been added in Table 2 in order to avoid fuels with uncharacteristic density-viscosity relationships. For a determination of CCAI, see Annex F.

NOTE 2 For engines and/or applications where the ignition quality is known to be particularly critical, Annex F provides a basis for suppliers and purchasers of residual fuels to agree on tighter ignition quality characteristics.

NOTE 3 For RME 180 and RMK 380, when blending at or close to the maximum density, the CCAI limit can restrict the combination of density and viscosity.

b) The sodium concentration shall be as specified in Table 2.

NOTE A limit for sodium content has been included due to concerns regarding the influences of metals in fuels on ash deposition and high-temperature corrosion. Information on the subject is given in Annex I.

7 Test methods

iTeh STANDARD PREVIEW
(standards.iteh.ai)

7.1 Density

When density is determined in accordance with ISO 3675, the hydrometer readings obtained at ambient temperature for distillate fuels, and at elevated temperatures of between 50 °C and 60 °C for fuels containing residual components, shall be converted to results at 15 °C using ISO 91-1:1992, Table 53B. When density is determined in accordance with ISO 12185, an appropriate correction for the glass expansion coefficient shall be applied to readings obtained by a digital density analyser at any temperature other than 15 °C, before conversion and application of ISO 91-1:1992, Table 53B.

The reference test method shall be ISO 3675.

7.2 Sulfur content

The reference test method shall be ISO 8754.

In the event of a dispute concerning sulfur content, all parties shall agree, prior to testing, upon the same sulfur certified reference material.

NOTE See Annex C.

7.3 Flash point

The flash point for fuels in Table 1 shall be determined in accordance with ISO 2719, Procedure A. If the flash point result of DMX is less than 40 °C, it shall be determined in accordance with ISO 3679.

The flash point of fuels in Table 2 shall be determined in accordance with ISO 2719, Procedure B.

NOTE See Annex G.

7.4 Total sediment by hot filtration

If the appearance of DMB is assessed as not clear and bright (see 7.6), the total sediment shall be determined by the test method ISO 10307-1, typically called total sediment existent.

7.5 Total sediment — Aged

Either of the standard procedures for ageing in ISO 10307-2 can be used: accelerated total sediment (TSA) or potential total sediment test (TSP).

The reference test method shall be the potential total sediment test in accordance with ISO 10307-2.

7.6 Appearance

For distillate fuel, the appearance of a sample shall be assessed by visual inspection in good light, free from glare and shadow, at a temperature between 10 °C and 25 °C.

- DMX, DMA or DMZ shall appear clear and bright. It has been reported that in some countries these grades of fuel are dyed (e.g. black) and not transparent. This affects the compliance with the requirement for clear and bright appearance and, in such circumstances, the water content shall not exceed 200 mg/kg, as determined by the Coulometric Karl Fischer titration method in accordance with ISO 12937.
- If the appearance of DMB affords visual inspection and appears clear and bright, then testing for total sediment by hot filtration and for water is not required.

iTech STANDARD PREVIEW
(standards.iteh.ai)

7.7 Vanadium

The reference test method shall be IP 501.

NOTE See Annex I. <https://standards.iteh.ai/catalog/standards/sist/7d951fed-9003-4ea8-a30b-1eb22efd427e/iso-8217-2012>

7.8 Sodium

The reference test method shall be IP 501.

NOTE See Annex I.

7.9 Aluminium plus silicon

The reference test method shall be IP 501.

NOTE See Annex J.

7.10 Used lubricating oil (ULO)

A fuel shall be free from ULO.

In the context of this International Standard, a fuel shall be considered to contain ULO when combinations of calcium and zinc or calcium and phosphorus are above the specified levels; see Table 2.

The reference test method shall be IP 501.

NOTE See Annex K.

7.11 Hydrogen sulfide

The reference test method shall be IP 570, Procedure A (with Vapor Phase Processor – VPP).

8 Precision and interpretation of test results

The test methods specified in Tables 1 and 2 all contain a statement of precision (repeatability and reproducibility). The determination of reproducibility for CCAI is contained in Annex F.

ISO 4259, which covers the use of precision data in the interpretation of test results, shall be used in cases of dispute. Information about precision and interpretation of test results is also given in Annex L.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 8217:2012](https://standards.iteh.ai/catalog/standards/sist/7d951fed-9003-4ea8-a30b-1eb22efd427e/iso-8217-2012)

<https://standards.iteh.ai/catalog/standards/sist/7d951fed-9003-4ea8-a30b-1eb22efd427e/iso-8217-2012>