

Designation: D6685 - 01(Reapproved 2008)

Standard Guide for the Selection of Test Methods for Fabrics Used for Fabric Formed Concrete (FFC)¹

This standard is issued under the fixed designation D6685; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

- 1.1 This guide lists ASTM standards available for the testing evaluation of fabrics used to form fine aggregate concrete.
- 1.2 This guide identifies the test methods available to manufacturers, engineers, testing organizations and other related parties.
- 1.3 This guide provides a list of test methods that can be used by the reader to determine the properties of fabric used to form fine aggregate concrete.
- 1.4 This guide is not intended to be used in the establishment of performance criteria, but as a guide for product development and purchasing contracts.
- 1.5 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.
- 1.6 This guide offers an organized collection of information or a series of options and does not recommend a specific course of action. This document cannot replace education or experience and should be used in conjunction with professional judgement. Not all aspects of this guide may be applicable in all circumstances. This ASTM standard is not intended to represent or replace the standard of care of which the adequacy of a given professional service must be judged, nor should this document be applied without consideration of a project's many unique aspects. The word "Standard" in the title of this document means only that the document has been approved through the ASTM consensus process.

2. Referenced Documents

2.1 ASTM Standards:²

D4354 Practice for Sampling of Geosynthetics for Testing

D4355 Test Method for Deterioration of Geotextiles by Exposure to Light, Moisture and Heat in a Xenon Arc Type Apparatus

D4439 Terminology for Geosynthetics

D4486 Test Method for Kinematic Viscosity of Volatile and Reactive Liquids

D4491 Test Methods for Water Permeability of Geotextiles by Permittivity

D4533 Test Method for Trapezoid Tearing Strength of Geotextiles

D4595 Test Method for Tensile Properties of Geotextiles by the Wide-Width Strip Method

D4751 Test Method for Determining Apparent Opening Size of a Geotextile

D4759 Practice for Determining the Specification Conformance of Geosynthetics

D4873 Guide for Identification, Storage, and Handling of Geosynthetic Rolls and Samples

D4884 Test Method for Strength of Sewn or Thermally Bonded Seams of Geotextiles

D5261 Test Method for Measuring Mass per Unit Area of Geotextiles

D5321 Test Method for Determining the Coefficient of Soil and Geosynthetic or Geosynthetic and Geosynthetic Friction by the Direct Shear Method

3. Terminology

- 3.1 *Definitions*—For definitions of terms used in this standard, refer to the Terminology for Geosynthetics D4439.
 - 3.2 Definitions of Terms Specific to This Standard:
- 3.2.1 Fabric Formed Concrete (FFC) Revetment— A fine aggregate concrete filled woven mattress used to protect soils

¹ This guide is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.25 on Erosion and Sediment Control Technology.

Current edition approved Jan. 1, 2008. Published February 2008. Originally approved in 2001. Last previous edition approved in 2001 as D6685-01. DOI: 10.1520/D6685-01R08.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.