

ETSI TS 123 003 V16.3.0 (2020-10)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);**

**LTE;
5G;**

**Numbering, addressing and identification
(3GPP TS 23.003 version 16.3.0 Release 16)**



Reference

RTS/TSGC-0423003vg30

Keywords

5G,GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	11
1 Scope	13
1.1 References	14
1.1.1 Normative references.....	14
1.1.2 Informative references	18
1.2 Abbreviations	19
1.3 General comments to references	19
1.4 Conventions on bit ordering	20
2 Identification of mobile subscribers	20
2.1 General	20
2.2 Composition of IMSI.....	20
2.2A Subscription Permanent Identifier (SUPI).....	21
2.2B Subscription Concealed Identifier (SUCI)	21
2.3 Allocation and assignment principles.....	24
2.4 Structure of TMSI	24
2.5 Structure of LMSI	25
2.6 Structure of TLLI	25
2.7 Structure of P-TMSI Signature.....	26
2.8 Globally Unique Temporary UE Identity (GUTI).....	26
2.8.1 Introduction.....	26
2.8.2 Mapping between Temporary and Area Identities for the EUTRAN and the UTRAN/GERAN based systems.....	27
2.8.2.0 Introduction	27
2.8.2.1 Mapping from GUTI to RAI, P-TMSI and P-TMSI signature.....	27
2.8.2.1.1 Introduction	27
2.8.2.1.2 Mapping in the UE	27
2.8.2.1.3 Mapping in the old MME	28
2.8.2.2 Mapping from RAI and P-TMSI to GUTI	28
2.8.2.2.1 Introduction	28
2.8.2.2.2 Mapping in the UE	28
2.8.2.2.3 Mapping in the new MME.....	29
2.9 Structure of the S-Temporary Mobile Subscriber Identity (S-TMSI)	29
2.10 5G Globally Unique Temporary UE Identity (5G-GUTI).....	29
2.10.1 Introduction.....	29
2.10.2 Mapping between Temporary Identities for the 5GS and the E-UTRAN.....	30
2.10.2.0 Introduction.....	30
2.10.2.1 Mapping from 5G-GUTI to GUTI	30
2.10.2.1.1 Introduction	30
2.10.2.1.2 Mapping in the UE	30
2.10.2.1.3 Mapping in the old AMF	31
2.10.2.2 Mapping from GUTI to 5G-GUTI	31
2.10.2.2.1 Introduction	31
2.10.2.2.2 Mapping in the UE	31
2.10.2.2.3 Mapping in the new AMF	32
2.11 Structure of the 5G-S-Temporary Mobile Subscriber Identity (5G-S-TMSI)	32
2.12 Structure of the Truncated 5G-S-Temporary Mobile Subscriber Identity (Truncated 5G-S-TMSI).....	32
3 Numbering plan for mobile stations	32
3.1 General	32
3.2 Numbering plan requirements	33
3.3 Structure of Mobile Subscriber ISDN number (MSISDN)	33
3.4 Mobile Station Roaming Number (MSRN) for PSTN/ISDN routing.....	34

3.5	Structure of Mobile Station International Data Number	34
3.6	Handover Number	34
3.7	Structure of an IP v4 address	35
3.8	Structure of an IP v6 address	35
4	Identification of location areas and base stations	35
4.1	Composition of the Location Area Identification (LAI)	35
4.2	Composition of the Routing Area Identification (RAI)	35
4.3	Base station identification	36
4.3.1	Cell Identity (CI) and Cell Global Identification (CGI)	36
4.3.2	Base Station Identify Code (BSIC)	36
4.4	Regional Subscription Zone Identity (RSZI)	37
4.5	Location Number	38
4.6	Composition of the Service Area Identification (SAI)	38
4.7	Closed Subscriber Group	38
4.8	HNB Name	38
4.9	CSG Type	38
4.10	HNB Unique Identity	39
5	Identification of MSCs, GSNs, location registers and CSSs	39
5.1	Identification for routing purposes	39
5.2	Identification of HLR for HLR restoration application	40
5.3	Identification of the HSS for SMS	40
6	International Mobile Station Equipment Identity, Software Version Number and Permanent Equipment Identifier	40
6.1	General	40
6.2	Composition of IMEI and IMEISV	40
6.2.1	Composition of IMEI	40
6.2.2	Composition of IMEISV	41
6.3	Allocation principles	41
6.4	Permanent Equipment Identifier (PEI)	41
7	Identification of Voice Group Call and Voice Broadcast Call Entities	42
7.1	Group Identities	42
7.2	Group Call Area Identification	42
7.3	Voice Group Call and Voice Broadcast Call References	42
8	SCCP subsystem numbers	43
8.1	Globally standardized subsystem numbers used for GSM/UMTS	43
8.2	National network subsystem numbers used for GSM/UMTS	43
9	Definition of Access Point Name	44
9A	Definition of Data Network Name	44
9.0	General	44
9.1	Structure of APN	44
9.1.1	Format of APN Network Identifier	45
9.1.2	Format of APN Operator Identifier	45
9.2	Definition of the Wild Card APN	46
9.2.1	Coding of the Wild Card APN	46
9.3	Definition of Emergency APN	46
10	Identification of the Cordless Telephony System entities	46
10.1	General description of CTS-MS and CTS-FP Identities	46
10.2	CTS Mobile Subscriber Identities	46
10.2.1	General	46
10.2.2	Composition of the CTSMSI	47
10.2.3	Allocation principles	47
10.2.4	CTSMSI hexadecimal representation	47
10.3	Fixed Part Beacon Identity	47
10.3.1	General	47
10.3.2	Composition of the FPBI	48
10.3.2.1	FPBI general structure	48
10.3.2.2	FPBI class A	48

10.3.2.3	FPBI class B	48
10.3.3	Allocation principles	49
10.4	International Fixed Part Equipment Identity	49
10.4.1	General	49
10.4.2	Composition of the IFPEI	49
10.4.3	Allocation and assignment principles	50
10.5	International Fixed Part Subscription Identity	50
10.5.1	General	50
10.5.2	Composition of the IFPSI	50
10.5.3	Allocation and assignment principles	50
11	Identification of Localised Service Area	51
12	Identification of PLMN, RNC, Service Area, CN domain and Shared Network Area	51
12.1	PLMN Identifier	51
12.2	CN Domain Identifier	51
12.3	CN Identifier	52
12.4	RNC Identifier	52
12.5	Service Area Identifier	52
12.6	Shared Network Area Identifier	52
12.7	Stand-Alone Non-Public Network Identifier	53
12.7.1	General	53
12.7.2	NID of assignment mode 0	53
13	Numbering, addressing and identification within the IP multimedia core network subsystem	54
13.1	Introduction	54
13.2	Home network domain name	54
13.3	Private User Identity	55
13.4	Public User Identity	55
13.4A	Wildcarded Public User Identity	56
13.4B	Temporary Public User Identity	56
13.5	Public Service Identity (PSI)	56
13.5A	Private Service Identity	57
13.6	Anonymous User Identity	57
13.7	Unavailable User Identity	57
13.8	Instance-ID	57
13.9	XCAP Root URI	58
13.9.1	XCAP Root URI on Ut interface	58
13.9.1.1	General	58
13.9.1.2	Format of XCAP Root URI	58
13.10	Default Conference Factory URI for MMTel	59
13.11	Unknown User Identity	59
13.12	Default WWSF URI	59
13.12.1	General	59
13.12.2	Format of the Default WWSF URI	59
13.13	IMEI based identity	60
14	Numbering, addressing and identification for 3GPP System to WLAN Interworking	60
14.1	Introduction	60
14.2	Home network realm	60
14.3	Root NAI	61
14.4	Decorated NAI	61
14.4A	Fast Re-authentication NAI	62
14.5	Temporary identities	62
14.6	Alternative NAI	63
14.7	W-APN	63
14.7.1	Format of W-APN Network Identifier	63
14.7.2	Format of W-APN Operator Identifier	64
14.7.3	Alternative Format of W-APN Operator Identifier	64
14.8	Emergency Realm and Emergency NAI for Emergency Cases	65
15	Identification of Multimedia Broadcast/Multicast Service	65
15.1	Introduction	65
15.2	Structure of TMGI	66

15.3	Structure of MBMS SAI.....	66
15.4	Home Network Realm.....	66
15.5	Addressing and identification for Bootstrapping MBMS Service Announcement.....	67
16	Numbering, addressing and identification within the GAA subsystem	68
16.1	Introduction	68
16.2	BSF address.....	68
17	Numbering, addressing and identification within the Generic Access Network.....	69
17.1	Introduction	69
17.2	Network Access Identifiers	69
17.2.1	Home network realm	69
17.2.2	Full Authentication NAI	69
17.2.3	Fast Re-authentication NAI	70
17.3	Node Identifiers.....	70
17.3.1	Home network domain name	70
17.3.2	Provisioning GANC-SEGW identifier.....	71
17.3.3	Provisioning GANC identifier	71
18	Addressing and Identification for IMS Service Continuity and Single-Radio Voice Call Continuity.....	72
18.1	Introduction	72
18.2	CS Domain Routeing Number (CSRN).....	72
18.3	IP Multimedia Routeing Number (IMRN)	72
18.4	Session Transfer Number (STN).....	72
18.5	Session Transfer Identifier (STI).....	72
18.6	Session Transfer Number for Single Radio Voice Call Continuity (STN-SR).....	72
18.7	Correlation MSISDN.....	72
18.8	Transfer Identifier for CS to PS Single Radio Voice Call Continuity (STI-rSR).....	73
18.9	Additional MSISDN.....	73
19	Numbering, addressing and identification for the Evolved Packet Core (EPC).....	73
19.1	Introduction	73
19.2	Home Network Realm/Domain	73
19.3	3GPP access to non-3GPP access interworking.....	74
19.3.1	Introduction.....	74
19.3.2	Root NAI	74
19.3.3	Decorated NAI.....	75
19.3.4	Fast Re-authentication NAI	76
19.3.5	Pseudonym Identities.....	76
19.3.6	Emergency NAI for Limited Service State	77
19.3.7	Alternative NAI	78
19.3.8	Keyname NAI.....	78
19.3.9	IMSI-based Emergency NAI	78
19.4	Identifiers for Domain Name System procedures	78
19.4.1	Introduction.....	78
19.4.2	Fully Qualified Domain Names (FQDNs)	79
19.4.2.1	General	79
19.4.2.2	Access Point Name FQDN (APN-FQDN).....	79
19.4.2.2.1	Structure	79
19.4.2.2.2	Void.....	80
19.4.2.2.3	Void.....	80
19.4.2.2.4	Void.....	80
19.4.2.3	Tracking Area Identity (TAI).....	80
19.4.2.4	Mobility Management Entity (MME).....	80
19.4.2.5	Routing Area Identity (RAI) - EPC.....	81
19.4.2.6	Serving GPRS Support Node (SGSN) within SGSN pool.....	81
19.4.2.7	Target RNC-ID for U-TRAN.....	81
19.4.2.8	DNS subdomain for operator usage in EPC.....	82
19.4.2.9	ePDG FQDN and Visited Country FQDN for non-emergency bearer services	82
19.4.2.9.1	General	82
19.4.2.9.2	Operator Identifier based ePDG FQDN	82
19.4.2.9.3	Tracking/Location Area Identity based ePDG FQDN.....	83

19.4.2.9.4	Visited Country FQDN.....	84
19.4.2.9.5	Replacement field used in DNS-based Discovery of regulatory requirements.....	84
19.4.2.9A	ePDG FQDN for emergency bearer services	85
19.4.2.9A.1	General	85
19.4.2.9A.2	Operator Identifier based Emergency ePDG FQDN	85
19.4.2.9A.3	Tracking/Location Area Identity based Emergency ePDG FQDN.....	85
19.4.2.9A.4	Visited Country Emergency FQDN.....	86
19.4.2.9A.5	Replacement field used in DNS-based Discovery of regulatory requirements for emergency services	86
19.4.2.9A.6	Country based Emergency Numbers FQDN	86
19.4.2.9A.7	Replacement field used in DNS-based Discovery of Emergency Numbers	87
19.4.2.10	Global eNodeB-ID for eNodeB.....	87
19.4.2.11	Local Home Network identifier	87
19.4.2.12	UCMF	88
19.4.3	Service and Protocol service names for 3GPP.....	88
19.5	Access Network Identity	90
19.6	E-UTRAN Cell Identity (ECI) and E-UTRAN Cell Global Identification (ECGI).....	90
19.6A	NR Cell Identity (NCI) and NR Cell Global Identity (NCGI).....	90
19.7	Identifiers for communications with packet data networks and applications	91
19.7.1	Introduction.....	91
19.7.2	External Identifier	91
19.7.3	External Group Identifier.....	91
19.8	TWAN Operator Name	92
19.9	IMSI-Group Identifier	92
19.10	Presence Reporting Area Identifier (PRA ID).....	93
19.11	Dedicated Core Networks Identifier.....	93
20	Addressing and Identification for IMS Centralized Services.....	93
20.1	Introduction	93
20.2	UE based solution.....	94
20.3	Network based solution.....	94
20.3.1	General.....	94
20.3.2	Home network domain name.....	94
20.3.3	Private User Identity	94
20.3.4	Public User Identity	95
20.3.5	Conference Factory URI.....	95
21	Addressing and Identification for Dual Stack Mobile IPv6 (DSMIPv6)	95
21.1	Introduction	95
21.2	Home Agent – Access Point Name (HA-APN).....	95
21.2.1	General	95
21.2.2	Format of HA-APN Network Identifier.....	96
21.2.3	Format of HA-APN Operator Identifier.....	96
22	Addressing and identification for ANDSF	97
22.1	Introduction	97
22.2	ANDSF Server Name (ANDSF-SN).....	97
22.2.1	General.....	97
22.2.2	Format of ANDSF-SN.....	97
23	Numbering, addressing and identification for the OAM System	97
23.1	Introduction	97
23.2	OAM System Realm/Domain.....	98
23.3	Identifiers for Domain Name System procedures	98
23.3.1	Introduction.....	98
23.3.2	Fully Qualified Domain Names (FQDNs).....	98
23.3.2.1	General	98
23.3.2.2	Relay Node Vendor-Specific OAM System	98
23.3.2.3	Multi-vendor eNodeB Plug-and Play Vendor-Specific OAM System.....	99
23.3.2.3.1	General	99
23.3.2.3.2	Certification Authority server.....	99
23.3.2.3.3	Security Gateway.....	100
23.3.2.3.4	Element Manager.....	100

24	Numbering, addressing and identification for Proximity-based Services (ProSe)	100
24.1	Introduction	100
24.2	ProSe Application ID	100
24.2.1	General	100
24.2.2	Format of ProSe Application ID Name in ProSe Application ID	101
24.2.3	Format of PLMN ID in ProSe Application ID	101
24.2.4	Usage of wild cards in place of PLMN ID in ProSe Application ID	101
24.2.5	Informative examples of ProSe Application ID	102
24.3	ProSe Application Code	102
24.3.1	General	102
24.3.2	Format of PLMN ID in ProSe Application Code	102
24.3.3	Format of temporary identity in ProSe Application Code	103
24.3A	ProSe Application Code Prefix	103
24.3B	ProSe Application Code Suffix	103
24.4	EPC ProSe User ID	104
24.4.1	General	104
24.4.2	Format of EPC ProSe User ID	104
24.5	Home PLMN ProSe Function Address	104
24.6	ProSe Restricted Code	104
24.7	ProSe Restricted Code Prefix	104
24.8	ProSe Restricted Code Suffix	105
24.9	ProSe Query Code	105
24.10	ProSe Response Code	105
24.11	ProSe Discovery UE ID	105
24.11.1	General	105
24.11.2	Format of ProSe Discovery UE ID	105
24.12	ProSe UE ID	105
24.13	ProSe Relay UE ID	106
24.14	User Info ID	106
24.15	Relay Service Code	106
24.16	Discovery Group ID	106
24.17	Service ID	106
25	Identification of Online Charging System	106
25.1	Introduction	106
25.2	Home network domain name	106
26	Numbering, addressing and identification for Mission Critical Services	107
26.1	Introduction	107
26.2	Domain name for MC services confidentiality protection of MC services identities	107
27	Numbering, addressing and identification for V2X	108
27.1	Introduction	108
27.2	V2X Control Function FQDN	108
27.2.1	General	108
27.2.2	Format of V2X Control Function FQDN	108
28	Numbering, addressing and identification for 5G System (5GS)	108
28.1	Introduction	108
28.2	Home Network Domain	109
28.3	Identifiers for Domain Name System procedures	109
28.3.1	Introduction	109
28.3.2	Fully Qualified Domain Names (FQDNs)	109
28.3.2.1	General	109
28.3.2.2	N3IWF FQDN	109
28.3.2.2.1	General	109
28.3.2.2.2	Operator Identifier based N3IWF FQDN	110
28.3.2.2.3	Tracking Area Identity based N3IWF FQDN	110
28.3.2.2.4	Visited Country FQDN for N3IWF	111
28.3.2.2.5	Replacement field used in DNS-based Discovery of regulatory requirements	111
28.3.2.3	PLMN level and Home NF Repository Function (NRF) FQDN	112
28.3.2.3.1	General	112
28.3.2.3.2	Format of NRF FQDN	112

28.3.2.3.3	NRF URI	112
28.3.2.4	Network Slice Selection Function (NSSF) FQDN	112
28.3.2.4.1	General	112
28.3.2.4.2	Format of NSSF FQDN	113
28.3.2.4.3	NSSF URI	113
28.3.2.5	AMF Name	113
28.3.2.6	5GS Tracking Area Identity (TAI) FQDN	114
28.3.2.7	AMF Set FQDN	114
28.3.2.8	AMF Instance FQDN	115
28.3.2.9	SMF Set FQDN	115
28.4	Information for Network Slicing	116
28.4.1	General	116
28.4.2	Format of the S-NSSAI	116
28.5	NF FQDN Format for Inter PLMN Routing	117
28.5.1	General	117
28.5.2	Telescopic FQDN	117
28.6	5GS Tracking Area Identity (TAI)	117
28.7	Network Access Identifier (NAI)	118
28.7.1	Introduction	118
28.7.2	NAI format for SUPI	118
28.7.3	NAI format for SUCI	118
28.7.4	Emergency NAI for Limited Service State	119
28.7.5	Alternative NAI	120
28.7.6	NAI used for 5G registration via trusted non-3GPP access	120
28.7.7	NAI used by N5CW devices via trusted non-3GPP access	120
28.7.8	NAI format for 5G-GUTI	121
28.8	Generic Public Subscription Identifier (GPSI)	121
28.9	Internal-Group Identifier	121
28.10	Presence Reporting Area Identifier (PRA ID)	121
28.11	CAG-Identifier	122
28.12	NF Set Identifier (NF Set ID)	122
28.13	NF Service Set Identifier (NF Service Set ID)	123
28.14	Data Network Access Identifier (DNAI)	124
28.15	Global Cable Identifier (GCI)	124
28.15.1	Introduction	124
28.15.2	NAI format for SUPI containing a GCI	124
28.15.3	User Location Information for RG accessing the 5GC via W-5GCAN (HFC Node ID)	124
28.15.4	GCI	124
28.15.5	NAI format for SUCI containing a GCI	125
28.16	Global Line Identifier (GLI)	125
28.16.1	Introduction	125
28.16.2	NAI format for SUPI containing a GLI	125
28.16.3	User Location Information for RG accessing the 5GC via W-5GBAN	125
28.16.4	GLI	125
28.16.5	NAI format for SUCI containing a GLI	125
28.17	DNS subdomain for operator usage in 5GC	126
29	Numbering, addressing and identification for RACS	126
29.1	Introduction	126
29.2	UE radio capability ID	126
Annex A (informative): Colour Codes		128
A.1	Utilization of the BSIC	128
A.2	Guidance for planning	128
A.3	Example of PLMN Colour Codes (NCCs) for the European region	129
Annex B (normative): IMEI Check Digit computation		130
B.1	Representation of IMEI	130
B.2	Computation of CD for an IMEI	130

B.3	Example of computation	130
Annex C (normative):	Naming convention	132
C.1	Routing Area Identities	132
C.2	GPRS Support Nodes	133
C.3	Target ID	133
Annex D (informative):	Applicability and use of the ".3gppnetwork.org" domain name.....	134
Annex E (normative):	Procedure for sub-domain allocation.....	135
Annex F (informative):	Change history	137
History		145

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/fe970320-3185-47c1-bc09-33f3e420eb62/etsi-ts-123-003-v16.3.0-2020-10>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- shall** indicates a mandatory requirement to do something
- shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- should** indicates a recommendation to do something
- should not** indicates a recommendation not to do something
- may** indicates permission to do something
- need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- can** indicates that something is possible
- cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

might not indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

is (or any other verb in the indicative mood) indicates a statement of fact

is not (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

ITeH STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/fe970320-3185-47c1-bc09-33f3e420eb62/etsi-ts-123-003-v16.3.0-2020-10>