



SLOVENSKI STANDARD

SIST EN 300 286-5 V1.2.4:2005

01-april-2005

8 [[]HJbc`ca fYy`Y`n`]bH[f]fUb]a]gfcf]Hj Ua]fG8 BLÈ`8 cdc`b] bUgfcf]Hj .
a YXi dcfUVb]y`Ug][bU]nUW`Ufl I GkÈ`Dfctc`c`X][]HbY`bUfc b]y`Y`g][bU]nUW`Y
ýH`%fB GG`kÈ`)"XY` .N[fUXVUdfYg_i ýU`bY[U`b]nU]b`bUa Yb]dfYg_i ýUb`U`fHGG` HDL
È`GdYWZ`_UW`UnU`ca fYy`Y`

Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 5: Test Suite Structure and Test Purposes (TSS&TP) specification for the network

[SIST EN 300 286-5 V1.2.4:2005](https://standards.iteh.ai/catalog/standards/sist/40372da2-0df4-4e40-baef-4a12649bf42f/sist-en-300-286-5-v1-2-4-2005)

<https://standards.iteh.ai/catalog/standards/sist/40372da2-0df4-4e40-baef-4a12649bf42f/sist-en-300-286-5-v1-2-4-2005>

Ta slovenski standard je istoveten z: EN 300 286-5 Version 1.2.4

ICS:

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
--------	---	--

SIST EN 300 286-5 V1.2.4:2005 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 286-5 V1.2.4:2005

<https://standards.iteh.ai/catalog/standards/sist/40372da2-0df4-4e40-baef-4a12649bf42f/sist-en-300-286-5-v1-2-4-2005>

EN 300 286-5 V1.2.4 (1998-06)

European Standard (Telecommunications series)

**Integrated Services Digital Network (ISDN);
User-to-User Signalling (UUS) supplementary service;
Digital Subscriber Signalling System No. one (DSS1) protocol;
Part 5: Test Suite Structure and Test Purposes (TSS&TP)
specification for the network**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 286-5 V1.2.4:2005](https://standards.iteh.ai/catalog/standards/sist/40372da2-0df4-4e40-baef-4a12649bf42f/sist-en-300-286-5-v1-2-4-2005)

<https://standards.iteh.ai/catalog/standards/sist/40372da2-0df4-4e40-baef-4a12649bf42f/sist-en-300-286-5-v1-2-4-2005>



Reference

REN/SPS-05145-T-5 (2nd90iqo.PDF)

Keywords

ISDN, DSS1, supplementary service, UUS,
testing, TSS&TP, network

ETSI

Postal address

F-06921, Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C

Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr

<http://www.etsi.fr>

<http://www.etsi.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1998.
All rights reserved.

Contents

Intellectual Property Rights.....	5
Foreword	5
1 Scope.....	6
2 Normative references	6
3 Definitions.....	7
3.1 Definitions related to conformance testing	7
3.2 Definitions related to EN 300 286-1	7
4 Abbreviations	8
5 Test Suite Structure (TSS)	9
6 Test Purposes (TP).....	10
6.1 Introduction.....	10
6.1.1 TP naming convention.....	10
6.1.2 Source of TP definition	10
6.1.3 TP structure.....	10
6.1.4 Test strategy	11
6.1.5 Test of point-to-multipoint configurations	11
6.2 Network TPs for UUS.....	11
6.2.1 Served user.....	11
6.2.1.1 Service 1.....	11
6.2.1.1.1 Activation.....	12
6.2.1.1.1.1 Implicitly requested.....	12
6.2.1.1.1.2 Explicitly requested.....	12
6.2.1.1.2 Invocation	13
6.2.1.1.2.1 During call establishment.....	13
6.2.1.1.2.2 During call clearing.....	13
6.2.1.1.2.2.1 Clearing initiated by the calling user.....	13
6.2.1.1.2.2.2 Clearing initiated by the called user.....	15
6.2.1.2 Service 2	15
6.2.1.2.1 Activation.....	15
6.2.1.2.2 Invocation	16
6.2.1.3 Service 3	17
6.2.1.3.1 Activation.....	18
6.2.1.3.1.1 During call establishment.....	18
6.2.1.3.1.2 During active call state.....	18
6.2.1.3.2 Invocation	19
6.2.1.3.3 Flow control.....	20
6.2.2 Remote user.....	21
6.2.2.1 Service 1	21
6.2.2.1.1 Activation.....	21
6.2.2.1.1.1 Implicitly requested.....	21
6.2.2.1.1.2 Explicitly requested.....	21
6.2.2.1.2 Invocation	32
6.2.2.1.2.1 During call establishment.....	32
6.2.2.1.2.2 During call clearing.....	34
6.2.2.1.2.2.1 Clearing initiated by the calling user.....	34
6.2.2.1.2.2.2 Clearing initiated by the called user.....	35
6.2.2.2 Service 2	38
6.2.2.2.1 Activation.....	38
6.2.2.2.2 Invocation	41
6.2.2.3 Service 3	43
6.2.2.3.1 Activation.....	43
6.2.2.3.1.1 During call establishment.....	43

6.2.2.3.1.2	During active call state.....	48
6.2.2.3.2	Invocation	50
6.2.2.3.3	Flow control.....	51
7	Compliance	53
8	Requirements for a comprehensive testing service.....	53
Annex A (informative):	Changes with respect to the previous ETS 300 286-5	54
History		55

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 300 286-5 V1.2.4:2005

<https://standards.iteh.ai/catalog/standards/sist/40372da2-0df4-4e40-baef-4a12649bf42f/sist-en-300-286-5-v1-2-4-2005>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.fr/ipr> or <http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS).

The present document is part 5 of a multi-part standard covering the Digital Subscriber Signalling System No. one (DSS1) protocol specification for the Integrated Services Digital Network (ISDN) User-to-User (UUS) supplementary service, as described below:

- Part 1: "Protocol specification";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";
- Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";**
- Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

The present version updates the references to the basic call specifications.

National transposition dates	
Date of adoption of this EN:	19 June 1998
Date of latest announcement of this EN (doa):	30 September 1998
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 1999
Date of withdrawal of any conflicting National Standard (dow):	31 March 1999

1 Scope

This fifth part of EN 300 286 specifies the Test Suite Structure and Test Purposes (TSS&TP) for the Network side of the T reference point or coincident S and T reference point (as defined in ITU-T Recommendation I.411 [7]) of implementations conforming to the stage three standard for the User-to-User Signalling (UUS) supplementary service for the pan-European Integrated Services Digital Network (ISDN) by means of the Digital Subscriber Signalling System No. one (DSS1) protocol, EN 300 286-1 [1].

A further part of the present document specifies the Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma based on the present document. Other parts specify the TSS&TP and the ATS and partial PIXIT proforma for the User side of the T reference point or coincident S and T reference point of implementations conforming to EN 300 286-1 [1].

2 Normative references

References may be made to:

- a) specific versions of publications (identified by date of publication, edition number, version number, etc.), in which case, subsequent revisions to the referenced document do not apply; or
- b) all versions up to and including the identified version (identified by "up to and including" before the version identity); or
- c) all versions subsequent to and including the identified version (identified by "onwards" following the version identity); or
- d) publications without mention of a specific version, in which case the latest version applies.

A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- iTeh STANDARD PREVIEW**
(standards.iteh.ai)
- <https://standards.iteh.ai/catalog/standards/sist/en-300-286-5-v1.2.4-2005>
- [1] EN 300 286-1 (V1.2): "Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
 - [2] EN 300 286-2 (V1.2): "Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
 - [3] ISO/IEC 9646-1: "Information Technology - OSI Conformance Testing Methodology and Framework; Part 1: General Concepts".
 - [4] ISO/IEC 9646-2: "Information Technology - OSI Conformance Testing Methodology and Framework; Part 2: Abstract Test Suite specification".
 - [5] ISO/IEC 9646-3: "Information Technology - OSI Conformance Testing Methodology and Framework; Part 3: The Tree and Tabular Combined Notation".
 - [6] EN 300 196-1: "Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
 - [7] ITU-T Recommendation I.411 (1993): "ISDN user-network interfaces - Reference configurations".
 - [8] EN 300 403-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".
 - [9] ITU-T Recommendation I.112: "Vocabulary and terms for ISDNs".
 - [10] CCITT Recommendation E.164: "Numbering plan for the ISDN era".

- [11] ITU-T Recommendation I.210: "Principles of the telecommunication services supported by an ISDN and the means to describe them".
- [12] EN 300 403-3: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 3: Protocol Implementation Conformance Statement (PICS) proforma specification".

3 Definitions

For the purposes of the present document, the following definitions apply.

3.1 Definitions related to conformance testing

abstract test case: Refer to ISO/IEC 9646-1 [3].

Abstract Test Suite (ATS): Refer to ISO/IEC 9646-1 [3].

active test: A test case where the IUT is required to send a particular message, but not in reaction to a received message. This would usually involve the use of PIXIT information to see how this message can be generated and quite often is specified in an ATS using an implicit send event.

Implementation Under Test (IUT): Refer to ISO/IEC 9646-1 [3].

implicit send event: Refer to ISO/IEC 9646-3 [5].

lower tester: Refer to ISO/IEC 9646-1 [3].

passive test: A test case where the IUT is required to respond to a protocol event (e.g. received message) with another protocol event (e.g. send message) which normally does not require any special operator intervention as associated with the implicit send event.

point of control and observation: Refer to ISO/IEC 9646-1 [3].

Protocol Implementation Conformance Statement (PICS): Refer to ISO/IEC 9646-1 [3].

PICS proforma: Refer to ISO/IEC 9646-1 [3].

Protocol Implementation eXtra Information for Testing (PIXIT): Refer to ISO/IEC 9646-1 [3].

PIXIT proforma: Refer to ISO/IEC 9646-1 [3].

system under test: Refer to ISO/IEC 9646-1 [3].

Test Purpose (TP): Refer to ISO/IEC 9646-1 [3].

3.2 Definitions related to EN 300 286-1

call reference: See EN 300 403-1 [8], subclause 4.3.

called user: The user at the destination side of the call.

calling user: The user at the origination side of the call.

component: See EN 300 196-1 [6], subclause 11.2.2.1.

Integrated Services Digital Network (ISDN): See ITU-T Recommendation I.112 [9], definition 308.

ISDN number: A number conforming to the numbering and structure specified in CCITT Recommendation E.164 [10].

invoke component: See EN 300 196-1 [6], subclause 11.2.2.1.

network: The DSS1 protocol entity at the Network side of the user-network interface where a T reference point or coincident S and T reference point applies.

network (S/T): The DSS1 protocol entity at the Network side of the user-network interface where a coincident S and T reference point applies.

network (T): The DSS1 protocol entity at the Network side of the user-network interface where a T reference point applies (Network connected to Private ISDN).

return error component: See EN 300 196-1 [6], subclause 11.2.2.1.

return result component: See EN 300 196-1 [6], subclause 11.2.2.1.

served user: The served user is the user who invokes the UUS supplementary service. The served user is the calling user except for service 3 where the called user, as a network option can invoke the service 3 in the Active call state.

service; telecommunication service: See ITU-T Recommendation I.112 [9], definition 201.

supplementary service: See ITU-T Recommendation I.210 [11], subclause 2.4.

4 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATM	Abstract Test Method
ATS	Abstract Test Suite
CES	Connection Endpoint Suffix
CR	Call Reference
ISDN	Integrated Services Digital Network
IUT	Implementation Under Test
N00	Null call state
N01	Call Initiated call state
N02	Overlap Sending call state
N03	Outgoing Call Proceeding call state
N04	Call Delivered call state
N06	Call Present call state
N07	Call Received call state
N08	Connect Request call state
N09	Incoming Call Proceeding call state
N10	Active call state
N11	Disconnect Request call state
N12	Disconnect Indication call state
N19	Release Request call state
N25	Overlap Receiving call state
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
TP	Test Purpose
TSS	Test Suite Structure
UUS	User-to-User Signalling
UUS1/2/3	UUS service 1/2/3

5 Test Suite Structure (TSS)

Served user	Group
· <u>Service 1</u>	
· activation	
· implicit	(01)
· explicit	(02)
· invocation	
· during call establishment	(03)
· during call clearing	
· initiated by the calling user	(04)
· initiated by the called user	(05)
· <u>Service 2</u>	
· activation	(06)
· invocation	(07)
· <u>Service 3</u>	
· activation	
· during call establishment	(08)
· during active call state	(09)
· invocation	(10)
· flow control	(11)
Remote user	Group
- <u>Service 1</u>	
- activation	
- implicit	(12)
- explicit	(13)
- invocation	
- during call establishment	(14)
- during call clearing	
- initiated by the calling user	(15)
- initiated by the called user	(16)
- <u>Service 2</u>	
- activation	(17)
- invocation	(18)
- <u>Service 3</u>	
- activation	
- during call establishment	(19)
- during active call state	(20)
- invocation	(21)
- flow control	(22)

NOTE: Numbers in brackets represent group numbers and are used in TP identifiers.

Figure 1: Test suite structure

6 Test Purposes (TP)

6.1 Introduction

For each test requirement a TP is defined.

6.1.1 TP naming convention

TPs are numbered, starting at 001, within each group. Groups are organized according to the TSS. Additional references are added to identify the actual test suite and whether it applies to the network or the user (see table 1).

Table 1: TP identifier naming convention scheme

Identifier: <ss>_<iut><group>_<nnn>			
<ss>	=	supplementary service:	e.g. "UUS"
<iut>	=	type of IUT:	U User N Network
<group>	=	group	2 digit field representing group reference according to TSS
<nnn>	=	sequential number	(001-999)

iTeh STANDARD PREVIEW
(standards.iteh.ai)

6.1.2 Source of TP definition

The TPs are based on EN 300 286-1 [1].

[SIST EN 300 286-5 V1.2.4:2005](#)

6.1.3 TP structure

[https://standards.iteh.ai/catalog/standards/sist/40372da2-0df4-4e40-baef-4a12649bf42f/sist-en-300-286-5-v1-2-4-2005](#)

Each TP has been written in a manner which is consistent with all other TPs. The intention of this is to make the TPs more readable and checkable. A particular structure has been used and this is illustrated in table 2. This table should be read in conjunction with any TP, i.e. use a TP as an example to fully understand the table.

Table 2: Structure of a single TP for UUS

TP part	Text	Example
Header	<Identifier> <i>tab</i> <paragraph number in base ETS> <i>tab</i> <type of test> <i>tab</i> <condition> <i>CR</i> .	see table 1 subclause 0.0.0 valid, invalid, inopportune mandatory, optional, conditional
Stimulus	Ensure that the IUT in the <basic call state> <trigger> <i>see below for message structure</i> <i>or</i> <goal>	N10 etc. receiving a XXXX message to request a ...
Reaction	<action> <conditions> <i>if the action is sending</i> <i>see below for message structure</i> <next action>, <i>etc.</i> and remains in the same state <i>or</i> and enters state <state>	sends, saves, does, etc. using en bloc sending, ...
Message structure	<message type> message containing a <i>a)</i> <info element> information element with <i>b)</i> a <field name> encoded as <i>or</i> including <coding of the field> and <i>back to a or b</i> ,	SETUP, FACILITY, CONNECT, ... Bearer capability, Facility, ...
NOTE:	Text in italics will not appear in TPs and text between <> is filled in for each TP and may differ from one TP to the next.	

iTech STANDARD PREVIEW (standards.iteh.ai)

6.1.4 Test strategy

As the base standard EN 300 286-1 [1] contains no explicit requirements for testing, the TPs were generated as a result of an analysis of the base standard and the PICS specification EN 300 286-2 [2]. The criteria applied include the following:

- only the requirements from the point of view of the T or coincident S and T reference point are considered;
- whether or not a test case can be built from the TP is not considered.

6.1.5 Test of point-to-multipoint configurations

In the case of a point-to-multipoint configuration several terminals may be attached to one basic access interface. Each terminal will use a different Connection Endpoint Suffix (CES). To reflect this in the TPs, the CES for which a message is received or sent (e.g. "...on receipt of an ALERTING message for CES1...") is named explicitly where this clarification is needed.

6.2 Network TPs for UUS

All PICS items referred to in this subclause are as specified in EN 300 286-2 [2] unless indicated otherwise by another numbered reference.

6.2.1 Served user

6.2.1.1 Service 1

Selection: Does the IUT support service 1? PICS: MC 2.1.

6.2.1.1.1 Activation

6.2.1.1.1.1 Implicitly requested

UUS_N01_001 **subclause 9.1.1.1.1** **valid** **mandatory**
 Ensure that the IUT, in the call state N00, receiving a valid SETUP message with a User-user information element without user information and the network can accept the request,
 accepts the message (resulting in the inclusion of the same User-user information element in the SETUP message sent to the remote user) and enters the call state N01.

UUS_N01_002 **subclause 9.1.1.1.2** **invalid** **mandatory**
 Ensure that the IUT, in the call state N00, receiving a valid SETUP message with a User-user information element without user information and the network cannot accept the request,
 discards the User-user information element (resulting in the sending of a SETUP message without User-user information element to the remote user) and enters the call state N01.

UUS_N01_003 **subclause 9.1.1.1.2** **invalid** **mandatory**
 Ensure that the IUT, in the call state N00, receiving a valid SETUP message with a User-user information element of less than 3 octets in length,
 discards the User-user information element (resulting in the sending of a SETUP message without User-user information element to the remote user) and enters the call state N01.

6.2.1.1.1.2 Explicitly requested

Selection: Does the IUT support the explicit request of service 1? PICS: MC 2.1.2.

UUS_N02_001 **subclause 9.1.1.2.1** **valid** **mandatory**
 Ensure that the IUT, in the call state N00 receiving a valid SETUP message with a Facility information element including a UserUserService invoke component indicating service 1 preferred,
 accepts the message (resulting in the inclusion of the same Facility information element in the SETUP message sent to the remote user) and enters the call state N01.

UUS_N02_002 **subclause 9.1.1.2.1** **valid** **mandatory**
 Ensure that the IUT, in the call state N00 receiving a valid SETUP message with a Facility information element including a UserUserService invoke component indicating service 1 required,
 accepts the message (resulting in the inclusion of the same Facility information element in the SETUP message sent to the remote user) and enters the call state N01.

UUS_N02_003 **subclause 9.1.1.2.2** **inopportune** **mandatory**
 Ensure that the IUT, in the call state N00 receiving a SETUP message with a Facility information element including a UserUserService invoke component indicating service 1 and an incompatible bearer capability,
 sends a RELEASE COMPLETE message without UserUserService return error component and enters the call state N00.

UUS_N02_004 **subclause 9.1.1.2.2** **inopportune** **mandatory**
 Ensure that the IUT, in the call state N00 receiving a valid SETUP message with a Facility information element including a UserUserService invoke component indicating service 1 preferred and the resources are not available,
 continues with normal call handling and includes a UserUserService return error component with the value "rejectedByNetwork" in a valid SETUP ACKNOWLEDGE, CALL PROCEEDING, PROGRESS, ALERTING or CONNECT message.

UUS_N02_005 **subclause 9.1.1.2.2** **inopportune** **mandatory**
 Ensure that the IUT, in the call state N00 receiving a valid SETUP message with a Facility information element including a UserUserService invoke component indicating service 1 preferred and the service 1 is not subscribed to,
 continues with normal call handling and includes a UserUserService return error component with the value "rejectedByNetwork" in a valid SETUP ACKNOWLEDGE, CALL PROCEEDING, PROGRESS, ALERTING or CONNECT message.

UUS_N02_006 **subclause 9.1.1.2.2** **inopportune** **mandatory**
 Ensure that the IUT, in the call state N00 receiving a valid SETUP message with a Facility information element including a UserUserService invoke component indicating service 1 required and the resources are not available, sends a DISCONNECT or RELEASE COMPLETE message, with cause value #47 "resources unavailable", including a UserUserService return error component with the value "rejectedByNetwork" and enters the call state N12 or N00.

UUS_N02_007 **subclause 9.1.1.2.2** **inopportune** **mandatory**
 Ensure that the IUT, in the call state N00 receiving a valid SETUP message with a Facility information element including a UserUserService invoke component indicating service 1 required and the service 1 is not subscribed to, sends a DISCONNECT or RELEASE COMPLETE message, with cause value #50 "requested facility not subscribed", including a UserUserService return error component with the value "rejectedByNetwork" and enters the call state N12 or N00.

6.2.1.1.2 Invocation

6.2.1.1.2.1 During call establishment

UUS_N03_001 **subclause 9.1.2.1.1** **valid** **mandatory**
 Ensure that the IUT, in the call state N00, receiving a valid SETUP message including a User-user information element with user information,
 accepts the message (resulting in the sending of a SETUP message to the remote user with the same User-user information element) sends a SETUP ACKNOWLEDGE or a CALL PROCEEDING message and enters the call state N02 or N03.

NOTE: This TP corresponds to the invocation of service 1 simultaneously with the activation by the same User-user information element.

UUS_N03_002 **subclause 9.1.2.1.1 (standards.iteh.i)** **valid** **mandatory**
 Ensure that the IUT, in the call state N00, receiving a valid SETUP message including a UserUserService invoke component indicating service 1 and a User-user information element with user information,
 accepts the message (resulting in the sending of a SETUP message to the remote user with the same UserUserService invoke component and User-user information element) sends a SETUP ACKNOWLEDGE or a CALL PROCEEDING message and enters the call state N02 or N03.

UUS_N03_003 **subclause 9.1.2.1.2** **invalid** **mandatory**
 Ensure that the IUT, in the call state N00, receiving a valid SETUP message including a User-user information element with user information with an overall length exceeding 131 octets,
 discards the User-user information element (resulting in the sending of a SETUP message without User-user information element to the remote user) sends a SETUP ACKNOWLEDGE or a CALL PROCEEDING message and optionally sends a STATUS message with cause value #43 "access information discarded".

6.2.1.1.2.2 During call clearing

6.2.1.1.2.2.1 Clearing initiated by the calling user

UUS_N04_001 **subclause 9.1.2.2.1.a** **valid** **mandatory**
 Ensure that the IUT, in the call state N02 and in the service 1 active state, receiving a DISCONNECT message with a User-user information element,
 accepts the message (resulting in the inclusion of a User-user information element in the DISCONNECT message sent to the remote user), sends a RELEASE message and enters the call state N19.

UUS_N04_002 **subclause 9.1.2.2.1.a** **valid** **mandatory**
 Ensure that the IUT, in the call state N03 and in the service 1 active state, receiving a DISCONNECT message with a User-user information element,
 accepts the message (resulting in the inclusion of a User-user information element in the DISCONNECT message sent to the remote user), sends a RELEASE message and enters the call state N19.