



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);**

**LTE;
5G;**

**Support of SMS over IP networks;
Stage 3**

(3GPP TS 24.341 version 16.0.0 Release 16)



ReferenceRTS/TSGC-0124341vg00

Keywords5G,GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	6
1 Scope	7
2 References	7
3 Definitions and abbreviations.....	8
3.1 Definitions	8
3.2 Abbreviations	9
4 Overview of SMS over IP functionality.....	9
4.1 Introduction	9
4.2 SMS over IP	9
4.3 Application utilisation of SMS over IP	10
4.4 SMS over IP and subscription without MSISDN	10
5 SIP related procedures.....	10
5.1 Introduction	10
5.2 Functional entities	10
5.2.1 User Equipment (UE)	10
5.2.1.1 General	10
5.2.1.2 Configuration	10
5.2.1.3 Policy enforcement.....	10
5.2.2 Application Server (AS)	12
5.3 Roles.....	12
5.3.1 SM-over-IP sender.....	12
5.3.1.1 General	12
5.3.1.2 Submitting a short message.....	12
5.3.1.3 Receiving a status report	14
5.3.1.4 SM-over-IP sender procedures for operation without MSISDN	14
5.3.1.4.1 General	14
5.3.1.4.2 Submitting a short message and subscription without MSISDN	14
5.3.1.4.3 Receiving a status report and subscription without MSISDN	14
5.3.2 SM-over-IP receiver	15
5.3.2.1 General	15
5.3.2.2 Registration	15
5.3.2.3 Delivery of a short message	15
5.3.2.4 Sending a delivery report	15
5.3.2.5 Sending a notification about SM-over-IP receiver having memory available.....	16
5.3.2.6 SM-over-IP receiver procedures for operation without MSISDN.....	16
5.3.2.6.1 General	16
5.3.2.6.2 Registration	16
5.3.2.6.3 Delivery of a short message.....	16
5.3.2.6.4 Sending a notification about SM-over-IP receiver having memory available	17
5.3.3 IP-Short-Message-Gateway (IP-SM-GW)	17
5.3.3.1 General	17
5.3.3.2 Indication of SM-over-IP receiver availability status for delivery of short messages.....	18
5.3.3.3 Answering routing information query	18
5.3.3.4 Transport layer interworking.....	19
5.3.3.4.1 Receiving a short message in a SIP MESSAGE request	19
5.3.3.4.2 Delivering a short message in a SIP MESSAGE request	21
5.3.3.4.3 Forwarding a submit report in a SIP MESSAGE request.....	21
5.3.3.4.4 Delivering a status report in a SIP MESSAGE request	21
5.3.3.5 IP-SM-GW procedures for operation without MSISDN.....	22
5.3.3.5.1 General	22

5.3.3.5.2	Receiving a short message in a SIP MESSAGE request from a SM-over-IP sender or SM-over-IP receiver	22
5.3.3.5.3	Delivering a short message in a SIP MESSAGE request to a SM-over-IP receiver.....	24
5.3.3.5.4	Delivering a delivery report in a SIP MESSAGE request	25
5.3.3.5.5	Delivering a submit report in a SIP MESSAGE request	26
5.3.3.5.6	Procedures for receiving a SIP MESSAGE request from an IP-SM-GW	26
5.3.3.6	SIP failure case.....	27
Annex A (normative): Media feature tags defined within the current document		28
A.1	General	28
A.2	Definition of media feature tag g.3gpp.smsip	28
A.3	Definition of media feature tag g.3gpp.smsip-msisdn-less	28
Annex B (informative): Example signalling flows of SMS over IP functionality		29
B.1	Scope of signalling flows	29
B.2	Introduction	29
B.2.1	General	29
B.2.2	Key required to interpret signalling flows.....	29
B.3	Signalling flows demonstrating how IP-SM-GW indicates to HSS the availability of public user identity for delivery of short messages.....	30
B.4	Signalling flows demonstrating how IP-SM-GW indicates to HSS the unavailability of UE for delivery of short messages	33
B.5	Signalling flows demonstrating successful UE originated SM submit procedure over IP.....	35
B.6	Signalling flows demonstrating successful UE terminated SM deliver procedure over IP (including delivery report).....	39
B.7	Signalling flow demonstrating successful procedures for SM over IP in case terminating side is addressed with SIP URI	43
Annex C (normative): XML schemas.....		47
C.1	Short-message-info XML schema	47
C.1.1	General	47
C.1.2	application/vnd.3gpp.sms+xml.....	47
C.1.3	Data semantics.....	47
C.1.4	XML schema	48
C.1.5	IANA registration.....	48
C.1.5.1	Name	48
C.1.5.2	Email	49
C.1.5.3	MIME media type name	49
C.1.5.4	MIME subtype name	49
C.1.5.5	Required parameters.....	49
C.1.5.6	Optional parameters.....	49
C.1.5.7	Encoding considerations.....	49
C.1.5.8	Security considerations.....	49
C.1.5.9	Interoperability considerations	49
C.1.5.10	Published specification.....	49
C.1.5.11	Applications which use this media	49
C.1.5.12	Applications that manipulate MIME typed objects (messaging, download etc.).....	49
C.1.5.13	Additional information	49
C.1.5.14	Intended usage	50
C.1.5.8.15	Other information/general comment.....	50
C.1.5.8.16	Person to contact for further information	50
Annex D (normative): Feature-capability indicators defined within the current document		51
D.1	General	51

D.2	Definition of feature-capability indicator g.3gpp.smsip-msisdn-less.....	51
Annex E (normative):	IP-Connectivity Access Network specific concepts when using EPS to access IM CN subsystem	52
E.1	Scope	52
E.2	EPS aspects when connected to the IM CN subsystem.....	52
E.2.1	Procedures at the UE	52
E.2.1.1	Smart Congestion Mitigation.....	52
E.3	Application usage of SIP	52
E.3.1	Procedures at the UE	52
E.3.1.1	3GPP PS data off	52
E.3.1.1.1	General	52
E.3.1.1.2	Enforcement	53
E.3.2	Procedures at the AS	53
E.3.2.1	3GPP PS data off	53
Annex F (normative):	IP-Connectivity Access Network specific concepts when using GPRS to access IM CN subsystem	55
F.1	Scope	55
F.2	GPRS (Iu mode only) aspects when connected to the IM CN subsystem.....	55
F.2.1	Procedures at the UE	55
F.2.1.1	General.....	55
F.2.1.2	Application specific Congestion control for Data Communication (ACDC) procedure.....	55
F.3	Application usage of SIP	56
F.3.1	Procedures at the UE	56
F.3.1.1	3GPP PS data off	56
F.3.1.1.1	General	56
F.3.1.1.2	Enforcement	56
F.3.2	Procedures at the AS	56
F.3.2.1	3GPP PS data off	56
Annex G (normative):	IP-Connectivity Access Network specific concepts when using 5GS to access IM CN subsystem	57
G.1	Scope	57
G.2	5GS aspects when connected to the IM CN subsystem	57
G.2.1	Procedures at the UE	57
G.2.1.1	Unified Access Control.....	57
G.3	Application usage of SIP	57
G.3.1	Procedures at the UE	57
G.3.1.1	3GPP PS data off	57
G.3.1.1.1	General	57
G.3.1.1.2	Enforcement	58
G.3.2	Procedures at the AS	58
G.3.2.1	3GPP PS data off	58
Annex H (informative):	Change history	59
History		61

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

PREVIEW
iTech STANDARD
(standards.itih.ai)
Full standard:
<https://standards.itih.ai/catalog/standards/sist/fb056cd3-5a77-4283-9ca1-5a7b2701bd8/etsi-ts-124-341-v16.0.0-2020-11>

1 Scope

The present document provides the protocol details for SMS over IP within the IP Multimedia (IM) Core Network (CN) subsystem based on the Session Initiation Protocol (SIP) and SIP Events as defined in 3GPP TS 24.229 [10].

The present document provides the protocol details for SMS over IP within the IP Multimedia (IM) Core Network (CN) subsystem based on the SMS layer as defined in 3GPP TS 24.011 [8].

Where possible the present document specifies the requirements for this protocol by reference to specifications produced by the IETF within the scope of SIP and SIP Events, either directly, or as modified by 3GPP TS 24.229 [10].

The present document is applicable to Application Servers (ASs) and User Equipment (UE) providing SMS over IP functionality.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.002: "Network Architecture".
- [3] 3GPP TS 23.040: "Technical realization of the Short Message Service (SMS)".
- [4] 3GPP TS 23.140: "Multimedia Messaging Service (MMS); Functional description; Stage 2".
- [5] 3GPP TS 23.204: "Support of SMS over generic 3GPP IP access; Stage 2".
- [6] 3GPP TS 23.218: "IP Multimedia (IM) session handling; IM call model; Stage 2".
- [7] 3GPP TS 23.228: "IP Multimedia Subsystem (IMS); Stage 2".
- [8] 3GPP TS 24.011: "Point-to-Point (PP) Short Message Service (SMS) support on mobile radio interface".
- [8A] 3GPP TS 24.167: "3GPP IMS Management Object (MO)".
- [9] 3GPP TS 24.228 Release 5: "Signalling flows for the IP multimedia call control based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3".
- [10] 3GPP TS 24.229: "Internet Protocol (IP) multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3".
- [11] 3GPP TS 29.002: "Mobile Application Part (MAP) specification".
- [12] RFC 3261 (June 2002): "SIP: Session Initiation Protocol".
- [13] RFC 3325 (November 2002): "Private Extensions to the Session Initiation Protocol (SIP) for Asserted Identity within Trusted Networks".
- [14] RFC 3428 (December 2002): "Session Initiation Protocol (SIP) Extension for Instant Messaging".
- [15] RFC 3680 (March 2004): "A Session Initiation Protocol (SIP) Event Package for Registrations".

- [16] RFC 3840 (August 2004): "Indicating User Agent Capabilities in the Session Initiation Protocol (SIP)".
- [17] RFC 3841 (August 2004): "Caller Preferences for the Session Initiation Protocol (SIP)".
- [18] 3GPP TS 31.103: "Characteristics of the IP Multimedia Services Identity Module (ISIM) Application".
- [19] 3GPP TS 31.102: "Characteristics of the Universal Subscriber Identity Module (USIM) Application".
- [20] 3GPP TS 51.011 Release 4: "Specification of the Subscriber Identity Module, Mobile Equipment (SIM - ME) interface".
- [21] 3GPP TS 31.111: "Universal Subscriber Identity Module (USIM) Application Toolkit (USAT)".
- [22] 3GPP TS 23.003: "Numbering, addressing and identification".
- [23] 3GPP TS 29.311: "Service Level Interworking (SLI) for messaging services".
- [24] RFC 6809 (November 2012): "Mechanism to Indicate Support of Features and Capabilities in the Session Initiation Protocol (SIP)".
- [25] RFC 5621 (September 2009): "Message Body Handling in the Session Initiation Protocol (SIP)".
- [26] RFC 4288 (December 2005): "Media Type Specifications and Registration Procedures".
- [27] RFC 6665 (July 2012): "SIP-Specific Event Notification".
- [28] 3GPP TS 22.011: "Service accessibility".
- [29] 3GPP TS 23.221: "Architectural requirements".
- [30] 3GPP TS 24.216: "Communication Continuity Management Object (MO)".
- [31] 3GPP TS 23.122: "Non-Access-Stratum functions related to Mobile Station (MS) in idle mode".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

MSISDN less operation: Operation of SMS over IP for subscriber without MSISDN in the subscription profile as defined in 3GPP TS 23.204 [5] in subclause 6.0a.

SM-over-IP sender: the A party that sends an SM using a SIP MESSAGE request including a vnd.3gpp.sms payload (introduced in 3GPP TS 23.140 [4]).

SM-over-IP receiver: the B party that receives an SM encapsulated in the vnd.3gpp.sms payload of a SIP MESSAGE request.

For the purposes of the present document, the following terms and definitions given in RFC 3261 [12] apply.

Header

Header field

Method

Request

Response

(SIP) transaction

Status-code (see RFC 3261 [12], subclause 7.2)

Tag (see RFC 3261 [12], subclause 19.3)

For the purposes of the present document, the following terms and definitions given in 3GPP TS 23.002 [2], subclauses 4.1.1.1 and 4a.7 apply:

Call Session Control Function (CSCF)
Home Subscriber Server (HSS)

For the purposes of the present document, the following terms and definitions given in 3GPP TS 23.218 [6], subclause 3.1 apply:

Filter criteria
Initial filter criteria

For the purposes of the present document, the following terms and definitions given in 3GPP TS 23.228 [7], subclauses 4.3.3.1, 4.3.6 and 4.6 apply:

Interrogating-CSCF (I-CSCF)
Public Service Identity (PSI)
Proxy-CSCF (P-CSCF)
Serving-CSCF (S-CSCF)

For the purposes of the present document, the following terms and definitions given in 3GPP TS 22.011 [28] apply:

3GPP PS data off
3GPP PS data off exempt service

For the purposes of the present document, the following terms and definitions given in 3GPP TS 24.229 [10] apply:

3GPP PS data off status

For the purposes of the present document, the following terms and definitions given in 3GPP TS 23.122 [31] apply:

Equivalent Home PLMN (EHPLMN)
Home PLMN (HPLMN)
Visited PLMN (VPLMN)

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1], TS 23.040 [3] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

AS	Application Server
IP-SM-GW	IP-Short-Message-Gateway
PS	Packet Switched

4 Overview of SMS over IP functionality

4.1 Introduction

SMS over IP functionality provides the UE with the capability of sending traditional short messages over IMS network. The architecture for SMS is specified in 3GPP TS 23.040 [3] and for SMS over IP functionality in 3GPP TS 23.204 [5].

4.2 SMS over IP

In order to guarantee SMS interoperability the SM-over-IP sender, the SM-over-IP receiver and the IP-SM-GW shall support encapsulation of RPDUs defined in 3GPP TS 24.011 [8], subclause 7.3. The SM-over-IP sender, the SM-over-IP receiver and the IP-SM-GW shall use the MIME type "application/vnd.3gpp.sms" for this purpose.

4.3 Application utilisation of SMS over IP

SMS over generic IP access can be used to support all applications and services that use SMS.

4.4 SMS over IP and subscription without MSISDN

When SMS over IP is to be delivered to a subscriber where the subscription profile does not contain an MSISDN, then there is a need for the IP-SM-GW to become aware of the IMSI during IMS registration for later correlation of short messages. In order to do so the IP-SM-GW derives the IMSI from the private user identity of the user that the UE includes in the REGISTER request at registration or if the private user identity is not available, derives the IMSI from the public user identity.

3GPP TS 23.003 [22] defines the relationship between the private user identity and the IMSI and the relationship between the public user identity and the IMSI.

5 SIP related procedures

5.1 Introduction

5.2 Functional entities

5.2.1 User Equipment (UE)

5.2.1.1 General

To be compliant with short message over IP in this document, a UE shall implement:

- a) the role of an SM-over-IP sender as specified in subclause 5.3.1.1, subclause 5.3.1.2, and subclause 5.3.1.3;
- b) the role of an SM-over-IP receiver as specified in subclause 5.3.2.1, subclause 5.3.2.2, subclause 5.3.2.3, subclause 5.3.2.4, and subclause 5.3.2.5; or
- c) the roles described in item a) and item b).

To be compliant with short message over IP in MSISDN less operation in this document, a UE shall implement:

- a) the role of an SM-over-IP sender as specified in subclause 5.3.1.4.1, subclause 5.3.1.4.2, and subclause 5.3.1.4.3;
- b) the role of an SM-over-IP receiver as specified in subclause 5.3.2.6.1, subclause 5.3.2.6.2, subclause 5.3.2.6.3, and subclause 5.3.2.6.4; or
- c) the roles described in item a) and item b).

NOTE: The capability of sending short messages over IP does not affect current limitations, thus the UE is limited to send at most one UE originated SM and to receive at most one UE terminated SM at a time.

5.2.1.2 Configuration

Parameters such as the PSI of the SC of the SM-over-IP sender can be obtained from the UICC as per 3GPP TS 31.103 [18] and 3GPP TS 31.102 [19] if used or from the SIM as per 3GPP TS 51.011 [20] if used.

5.2.1.3 Policy enforcement

The network operator's preference for selection of the domain to be used for short message service originated by the UE indicates the domain for originating short messages.

The network operator's preference for selection of the domain to be used for short message service originated by the UE can be set to one of the following values:

- a) the SMS service is not to be invoked over the IP networks; and
- b) the SMS service is preferred to be invoked over the IP networks.

The UE shall support the network operator's preference for selection of the domain to be used for short message service originated by the UE.

The UE may support being configured with the network operator's preference for selection of the domain to be used for short message service originated by the UE in the SMS_Over_IP_Networks_Indication of 3GPP TS 24.167 [8A].

Editor's note [CR#0086, IOC_UE_conf]: Handling of any configuration on UICC related to the network operator's preference for selection of the domain to be used for short message service originated by the UE is FFS.

If the network operator's preference for selection of the domain to be used for short message service originated by the UE is set to "the SMS service is not to be invoked over the IP networks", the UE shall not perform the procedures in subclause 5.3.1.

The policy on usage of SMS over IP indicates when the UE is allowed to use SMS over IP.

The policy on usage of SMS over IP can be set to one of the following values:

- a) SMS over IP is used only if voice over PS is available and only on the IP-CAN bearer that is used for the transport of SIP signalling associated with voice over PS;
- b) SMS over IP is used only if voice over PS is available and on any IP-CAN bearer; and
- c) SMS over IP is used irrespective of whether voice over PS is available and on any IP-CAN bearer.

The UE may support the policy on usage of SMS over IP.

If the UE supports the policy on usage of SMS over IP and the network operator's preference for selection of the domain to be used for short message service originated by the UE is set to "the SMS service is preferred to be invoked over the IP networks":

- a) the UE may support being configured with SMSoIP usage policy using one or more of the following methods:
 - 1) the SMSoIP usage policy leaf of the EF_{IMSCofigData} file described in 3GPP TS 31.102 [19];
 - 2) the SMSoIP usage policy leaf of the EF_{IMSCofigData} file described in 3GPP TS 31.103 [18]; and
 - 3) the SMSoIP usage policy leaf of 3GPP TS 24.167 [8A].

If the UE is configured with both the SMSoIP usage policy leaf of 3GPP TS 24.167 [8A] and the SMSoIP usage policy leaf of the EF_{IMSCofigData} file described in 3GPP TS 31.102 [19] or the SMSoIP usage policy leaf of the EF_{IMSCofigData} file described in 3GPP TS 31.103 [18], then the SMSoIP usage policy leaf of the EF_{IMSCofigData} file shall take precedence.

NOTE 1: Precedence for files configured on both the USIM and ISIM is defined in 3GPP TS 31.103 [18].

- b) if the policy on usage of SMS over IP is set to "SMS over IP is used only if voice over PS is available and only on the IP-CAN bearer that is used for the transport of SIP signalling associated with voice over PS":
 - 1) if the domain selection for originating voice calls specified in 3GPP TS 23.221 [29] determines that the UE does not use the IMS to originate voice call then the UE shall not perform the procedures in subclause 5.3.1 and subclause 5.3.2 and determines that SMS over IP is restricted (see 3GPP TS 24.229 [10]); and
 - 2) if:
 - A) the domain selection for originating voice calls specified in 3GPP TS 23.221 [29] determines that the UE uses the IMS to originate voice calls;
 - B) the UE supports multiple registrations as specified in 3GPP TS 24.229 [10];
 - C) the UE registered several registration flows; and

D) at least one of the registration flow was registered via an IP-CAN different than the remaining registration flows;

then the UE shall not perform the procedures in subclause 5.3.1 and subclause 5.3.2 and determines that SMS over IP is restricted (see 3GPP TS 24.229 [10]) over access technology where the audio is restricted or not preferred according to 3GPP TS 24.216 [30]; and

- c) if the policy on usage of SMS over IP is set to "SMS over IP is used only if voice over PS is available and on any IP-CAN bearer" and the domain selection for originating voice calls specified in 3GPP TS 23.221 [29] determines that the UE does not use the IMS to originate voice call then the UE shall not perform the procedures in subclause 5.3.1 and subclause 5.3.2 and determines that SMS over IP is restricted (see 3GPP TS 24.229 [10]).

NOTE 2: If the network operator's preference for selection of the domain to be used for short message service originated by the UE is set to "the SMS service is not to be invoked over the IP networks", the policy on usage of SMS over IP has no effect.

NOTE 3: If the policy on usage of SMS over IP is set to "SMS over IP is used irrespective of whether voice over PS is available and on any IP-CAN bearer", there is no restriction regarding how SMS over IP is used.

5.2.2 Application Server (AS)

To be compliant with short message over IP in this document, an AS shall implement the role of an IP-SM-GW as specified in subclause 5.3.3.1, subclause 5.3.3.2, subclause 5.3.3.3, and subclause 5.3.3.4.

To be compliant with short message over IP in MSISDN less operation in this document, an AS shall implement the role of an IP-SM-GW as specified in subclause 5.3.3.1, subclause 5.3.3.2, subclause 5.3.3.3, and subclause 5.3.3.5.

5.3 Roles

5.3.1 SM-over-IP sender

5.3.1.1 General

In addition to the procedures specified in subclause 5.3.1, the SM-over-IP sender shall support the procedures specified in 3GPP TS 24.229 [10] appropriate to the functional entity in which the SM-over-IP sender is implemented. The SM-over-IP sender shall build and populate RP-DATA message, containing all the information that a mobile station submitting an SM according to 3GPP TS 24.011 [8] would place, for successful delivery. The SM-over-IP sender shall parse and interpret RP-DATA, RP-ACK and RP-ERROR messages, containing all the information that a mobile station receiving an SM according to 3GPP TS 24.011 [8] would see, in a SM submission or status report.

NOTE 1: If the SM-over-IP sender uses SMR entity timers as specified in 3GPP TS 24.011 [8], then TR1M is set to a value greater than timer F (see 3GPP TS 24.229 [10]).

NOTE 2: If the SM-over-IP sender expects to receive a SM submit report will include the "+g.3gpp.smsip" parameter in the Contact header field when sending a REGISTER request.

5.3.1.2 Submitting a short message

When an SM-over-IP sender wants to submit an SM over IP, the SM-over-IP sender shall send a SIP MESSAGE request with the following information:

- a) the Request-URI, which shall contain the PSI of the SC of the SM-over-IP sender;

NOTE 1: The PSI of the SC can be SIP URI or tel URI based on operator policy. The PSI of the SC can be obtained using one of the following methods in the priority order listed below:

- 1) provided by the user;
- 2) if UICC is used, then: