



**SLOVENSKI STANDARD**  
**SIST-TS CEN/TS 17943:2024**

**01-junij-2024**

---

**Karakterizacija odpadkov - Navodilo za določanje elementov in drugih snovi v odpadkih**

Characterization of waste - Guidance on the determination of the content of elements and substances in waste

Charakterisierung von Abfällen - Leitlinien zur Bestimmung des Gehalts von Elementen und Stoffen in Abfällen

Caractérisation des déchets - Guide pour la détermination de la teneur en éléments et substances dans les déchets

**Ta slovenski standard je istoveten z: CEN/TS 17943:2023**

[SIST-TS CEN/TS 17943:2024](https://standards.iteh.com/catalog/standards/sist/67316436-2072-47ba-a78a-6667c4076667/sist-ts-cen-ts-17943-2024)

**ICS:**

13.030.01      Odpadki na splošno      Wastes in general

**SIST-TS CEN/TS 17943:2024**

**en,fr,de**



TECHNICAL SPECIFICATION  
SPÉCIFICATION TECHNIQUE  
TECHNISCHE SPEZIFIKATION

**CEN/TS 17943**

August 2023

ICS 13.030.01

English Version

**Characterization of waste - Guidance on the determination  
of the content of elements and substances in waste**

Caractérisation des déchets - Guide pour la  
détermination de la teneur en éléments et substances  
dans les déchets

Charakterisierung von Abfällen - Leitlinien zur  
Bestimmung des Gehalts von Elementen und Stoffen in  
Abfällen

This Technical Specification (CEN/TS) was approved by CEN on 28 May 2023 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and United Kingdom.

(<https://standards.iteh.ai>)  
**Document Preview**

[SIST-TS CEN/TS 17943:2024](https://standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/b7316436-2c72-47ba-a4ba-0664e487b807/sist-ts-cen-ts-17943-2024>



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels**

<b>Contents</b>	<b>Page</b>
European foreword .....	3
Introduction .....	4
1 Scope.....	5
2 Normative references.....	5
3 Terms and definitions.....	5
4 Principle.....	6
5 Example of analytical methods .....	7
6 Laboratory sample and preparation of test portions.....	7
7 Analysis of liquid wastes .....	8
7.1 General.....	8
7.2 Analysis .....	8
7.3 Expression of the result on liquid waste .....	11
7.4 Mass balance of liquid waste .....	12
8 Analysis of solid waste .....	13
8.1 Analysis .....	13
8.2 Expression of the results on solid waste .....	16
8.3 Mass balance of solid waste .....	17
9 Test report.....	17
Annex A (informative) Organigram of tasks for liquid and solid waste analysis .....	18
Annex B (informative) Example Report Format with two examples .....	20
B.1 Report of mass balance.....	20
B.1.1 Liquids .....	20
B.1.2 Solids .....	21
B.2 Result for each parameter .....	21
B.2.1 Liquids .....	21
B.2.2 Solids .....	23
B.3 Example for a liquid sample mass balance.....	24
B.3.1 Liquid waste mass balance .....	24
B.4 Result for each parameter .....	25
B.4.1 Liquids .....	25
B.4.2 Solid (ash) mass balance .....	27
B.5 Result for each parameter .....	28
B.5.1 Solid (ash).....	28
Annex C (informative) Analytical mass balance .....	32
Bibliography .....	33

## European foreword

This document (CEN/TS 17943:2023) has been prepared by Technical Committee CEN/TC 444 “Environmental characterization of solid matrices”, the secretariat of which is held by NEN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users’ national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.

# iTeh Standards (<https://standards.iteh.ai>) Document Preview

[SIST-TS CEN/TS 17943:2024](https://standards.iteh.ai/catalog/standards/sist/b7316436-2c72-47ba-a4ba-0664e487b807/sist-ts-cen-ts-17943-2024)

<https://standards.iteh.ai/catalog/standards/sist/b7316436-2c72-47ba-a4ba-0664e487b807/sist-ts-cen-ts-17943-2024>

**CEN/TS 17943:2023 (E)****Introduction**

This document is intended to be used for the characterization of waste when information is needed to fulfil the requirements of the Waste Framework Directive 2008/98/EC and the EC Regulation (EU) No 1357/2014, for the classification of waste according to different hazards. This document can also be used for the Classification Labelling and Packaging (CLP) Regulation (EC) No 1272/2008.

This document deals with the determination of elements and substances in waste to assess their hazards if no information is available on their content.

**iTeh Standards**  
**(<https://standards.iteh.ai>)**  
**Document Preview**

[SIST-TS CEN/TS 17943:2024](https://standards.iteh.ai/catalog/standards/sist/b7316436-2c72-47ba-a4ba-0664e487b807/sist-ts-cen-ts-17943-2024)

<https://standards.iteh.ai/catalog/standards/sist/b7316436-2c72-47ba-a4ba-0664e487b807/sist-ts-cen-ts-17943-2024>

## 1 Scope

This document provides guidance to the characterization of waste. It applies to all types of waste, with unknown or partially known composition, by giving examples of EN standards dedicated to waste characterization and analytical methods for parameters not covered by standards. Some requirements concerning the determination of inorganic elements and organic substances content in waste are given to achieve approximately 90 % or the highest possible mass.

In case information on the origin or on the composition of the waste is given by the owner of the waste, it might be sufficient to follow only part of this document to complete missing knowledge about the waste.

## 2 Normative references

There are no normative references in this document.

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

### 3.1

#### **dry matter**

#### **DM**

mass fraction of sample excluding water expressed as mass fraction calculated by determination of dry residue or water content

### 3.2

#### **volatile organic compounds**

#### **VOC**

any organic compound having an initial boiling point less than or equal to 250 °C measured at a standard atmospheric pressure of 101,3 kPa

Note 1 to entry: According to WHO, organic compound whose boiling point is in the range from (50 °C to 100 °C) to (240 °C to 260 °C).

### 3.3

#### **semi-volatile organic compounds**

#### **SVOC**

Organic compound whose boiling point is in the range from (240 °C to 260 °C) to (380 °C to 400 °C), according to WHO

Note 1 to entry: Boiling points of some compounds are difficult or impossible to determine because they decompose before they boil at atmospheric pressure. Vapour pressure is another criterion for classification of compound volatility that can be used for classification of organic chemicals. SVOCs have vapour pressure between  $10^{-2}$  mPa and 10 Pa.

### 3.4

#### **unidentified volatile or semi-volatile compounds**

mass calculated from the unresolved chromatographic areas of the corresponding chromatograms

## CEN/TS 17943:2023 (E)

### 3.5

#### **non-extractable organic compounds**

mass lost by calcination of the dried solid residue remaining after the extraction of semi-volatile substances

Note 1 to entry: Chemical compound that remains un-extractable by a method which do not significantly change the chemical nature of these residues.

### 3.6

#### **internal calibration standards**

compounds added in a known amount to the sample from the beginning of the protocol and enabling analytical coverage throughout the procedure, and that is used to correct for losses during sample preparation and analysis by accounting for all-system matrix effects (recoveries, ionization effect, variability of the detector response of the instrument for example)

### 3.7

#### **external calibration standards**

compounds added in a known amount to a sample which is analysed separately from the unknown sample under identical conditions, and used to facilitate the qualitative identification and/or quantitative determination of the sample components

### 3.8

#### **unresolved chromatographic peak**

portion of a chromatogram where a separation is incomplete, and corresponding to two or more components which may elute together from the chromatographic column

## 4 Principle

This method consists of determining the content of elements and substances above 0,1 % (weight) in content of waste. It applies to laboratory samples of liquid and solid wastes. It is based on standard methods when available, or otherwise on non-standardized methods as briefly described in this document, specifying any extraction procedure and quantitative or semiquantitative analytical method.

All work should be led in compliance with EN 16457. Sampling should be performed in compliance with EN 14899 and with guidance documents CEN/TR 15310-1 to 5. Laboratory samples should be prepared according to EN 15002. All standards to which this document refers to are listed in Table 1.



## 5 Example of analytical methods

**Table 1 — Overview of examples of analytical methods**

Analysis or test	Test method for liquid waste	Test method for solid waste
Sample preparation	EN 15002	EN 15002
Dry matter	EN 15934	EN 15934
Loss on ignition	EN 15935	EN 15935
pH	CEN/TR 16192 EN ISO 10523	CEN/TR 16192 EN ISO 10523
Conductivity	CEN/TR 16192 EN 27888	CEN/TR 16192 EN 27888
Halogens (bromide, chloride, fluoride)	CEN/TR 16192 ISO 10304-1	CEN/TR 16192 ISO 10304-1
Anions (nitrates, orthophosphates, sulfates)	CEN/TR 16192 ISO 10304-1	CEN/TR 16192 ISO 10304-1
Easily liberable cyanides, free cyanides and total cyanides	EN ISO 14403-1 EN ISO 14403-2	ISO 11262 EN ISO 17380
Elements (As, Ba, Cd, Cr, Cu, Hg, Mo, Ni, Pb, Sb, Se, Zn)	EN ISO 11885 EN ISO 17294-2	ISO 22036 EN 16170
Elements (semiquantitative analysis)	EN 15309 (X-Ray fluorescence) EN ISO 11885 EN ISO 17294-2	EN 15309 (X-Ray fluorescence) ISO 22036 or EN 16170
Cr VI	EN ISO 23913 or ISO 11083	EN ISO 15192
BTEX	EN ISO 17943	EN ISO 22155
HAP	ISO 28540	EN 17503
Hydrocarbon content C10-C40 range	EN 14039	EN 14039

## 6 Laboratory sample and preparation of test portions

Given the sheer number of potential analyses and pre-treatments (including any separation of a sample's component liquid and solid phases), it is recommended that the laboratory sample of liquids should be at least 10 l and solids (powders and sludges) should be at least 10 kg.

Analytical test portions taken from the laboratory sample should be prepared according to EN 15002. When samples are composed of several non-miscible phases or fractions, the analyses should be carried out on each phase, and the results aggregated to give a complete result covering the whole sample.

By convention, a waste sample is considered liquid if it flows freely from the orifice of a container within a limited time (Annex B of EN 12457-2:2002).

## CEN/TS 17943:2023 (E)

### 7 Analysis of liquid wastes

#### 7.1 General

The organigram of tasks proposed for the liquid waste analysis is given in Annex A. All the parameters are listed and described below. The standards referred to in this clause are given as examples, but other suitable standards may be used.

#### 7.2 Analysis

When dealing with suspended solids or separated phases in the samples, first separate the fractions using an appropriate method (filtration, centrifugation, decanting), then determine the mass of each fraction and perform the analyses of parameters on the liquid and solid fractions of each phase (EN 15002), provided the concerning fraction contains enough material to perform the test.

Determine the following parameters:

- a) **density:** take at least 10 subsamples of the laboratory sample, using class A laboratory glassware, and individually weigh each subsample, it should be the same mass which is weighed. The deviation between the measurements should not be higher than  $\pm 5\%$  for a series of subsamples. When compared with the mass of same volumes of water, the mean value of these masses gives an adequate evaluation of the density of the liquid sample.
- b) **water content:** following EN 15934, either dry at 105 °C or run a Karl-Fisher titration depending on the waste and the presence of volatile substances. The method used should allow to measure water contents up to 99,9 % of gross weight to identify the presence of substances other than water at 0,1 % of gross weight.
- c) **ignition residue content:** loss on ignition should be performed according to EN 15935 or equivalent method;
- d) **pH and conductivity:** for wastewater and aqueous waste, measure the pH and the electrical conductivity directly in the sample in the field during the sampling if possible or as fast as possible in the laboratory in case of transportation, taking care to minimize exchanges with the ambient air environment.

For paste and non-aqueous liquids (especially with hydrocarbons): the pH and the electrical conductivity should be measured in the leachate obtained according to EN 12457-2, before filtration, taking care to minimize exchanges with the laboratory air environment.

Measure the pH and electrical conductivity according to CEN/TR 16192 which refers to EN ISO 10523 for pH determination and to EN 27888 for electrical conductivity determination.

Record any water-triggered reaction of the waste, as detectable for example by a release of heat or gas.

Record the leaching test performed, in the report.

- e) **determination of halogen content for saline waste (if conductivity > 0,15 S/m):** it is recommended to determine chlorides and preferably all water-soluble halogens, according to CEN/TR 16192, either in the liquid waste (wastewater or aqueous waste) or in a leachate obtained according to EN 12457-2. For example, the ion chromatography method can be used for chloride, bromide, and fluoride according to EN ISO 10304-1. A selective method can also be used for the determination of the fluoride content.

NOTE This result does not interfere with the mass balance as the halogen compounds are integrated via the residue on ignition.

- f) **determination of Total Organic Carbon (TOC):** according to EN 15936. This result does not interfere with the mass balance because carbon compounds are integrated via the organic part like identified compounds or unidentified compounds.
- g) **determination of free or easily liberatable cyanide:** according to EN ISO 14403-1 or to EN ISO 14403-2.
- h) **determination of the elements content (excluding the 10 heavy metals, As and Se), sulphur content, phosphorous content:** perform a total digestion according to EN 13656 and a semiquantitative scanning analysis by ICP-AES (inductively coupled plasma-atomic emission spectrometry), ICP-MS (inductively coupled plasma mass spectrometry) or an analysis by X-ray fluorescence according to EN 15309. Quantitatively determine each individual concentration of the following elements (As, Ba, Cd, Cr, Cu, Hg, Mo, Ni, Pb, Sb, Se, Zn) according to EN ISO 11885 or EN ISO 17294-2, in the solution obtained by acid digestion.
- i) **determination of the hexavalent chromium content if suspected:** it is recommended to determine the hexavalent chromium content according to EN ISO 23913 or ISO 11083;
- j) **determination of the volatile organic compounds content:**

Determine the volatile organic compounds by headspace extraction according to ISO 11423-1 or EN ISO 10301 or after solvent extraction according to ISO 11423-2; the analysis is performed accordingly:

- i) add a solution containing internal calibration standards to the solvent sample blanks. This solution is used to standardize the analyte response factors;
- ii) first, run a semiquantitative analysis with external calibration standards, preferably using three calibration standards (e.g. toluene, trichloroethylene, hexane);
- iii) when possible, and using the results obtained by the semiquantitative analysis, each volatile organic compound detected above the threshold of 0,1 % weight concentration should be quantified by, either:
  - individually quantifying each compound detected with their own calibration standards (external calibration), or;
  - quantifying with three calibration standards (e.g. toluene, trichloroethylene, hexane). The response factors of the detected compounds can be corrected by comparing their TIC (Total Ion Current) with the TIC responses obtained for the internal calibration standards.
- The compound identification rate should be higher than 80 %.

For the best quantification of the identified compounds, it is recommended to use the same chemical compounds as calibration standards. If different calibration standards are used, then it is preferable to create and use a database of response factors with different families of analytes (aliphatic alkanes, aromatics, ketones, alcohols, glycols, chlorinated solvents, etc.). The GC-MS response factors differ widely, according to the chemical nature of the analyte substance. The quantification may be performed by GC-FID (flame ionization detector) as the response factor depends less on the chemical nature of the analyte substance.