
**Intelligent transport systems —
Traffic and travel information (TTI)
via transport protocol experts group,
generation 2 (TPEG2) —**

**Part 4:
UML to XML conversion rules**

iTeh STANDARD PREVIEW

(standards.iteh.ai)
*Systèmes intelligents de transport — Informations sur le trafic et le
tourisme via le groupe expert du protocole de transport, génération 2
(TPEG2) —*

ISO/TS 21219-4:2015

<https://standards.iteh.ai/catalog/standards/sist/64cccd2c-151f-4703-82bc-208947405d76/iso-ts-21219-4-2015>
Partie 4: Règles de conversion d'UML en XML

208947405d76/iso-ts-21219-4-2015



iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/TS 21219-4:2015](https://standards.iteh.ai/catalog/standards/sist/b4cced2e-f3ff-47b3-82bc-208947405d76/iso-ts-21219-4-2015)

<https://standards.iteh.ai/catalog/standards/sist/b4cced2e-f3ff-47b3-82bc-208947405d76/iso-ts-21219-4-2015>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms, definitions and abbreviated terms	1
3.1 Terms and definitions	1
3.2 Abbreviated terms	2
4 Rules for UML to XML format description conversion	2
4.1 Definition of XML format description	2
4.2 The tpegML schema definition	2
4.3 The tpegML xml file definition	3
4.4 XML data type ranges	3
4.5 Abstract data types	4
4.6 TPEG standard tables	4
4.7 Application tables (stereotype <<enumeration>>)	5
4.8 Switching tables	5
4.9 Stereotype <<external>>	6
4.10 Compound data types	8
4.11 Example	14
Annex A (normative) TPEG Data Types schema definition	18
Bibliography	37

<https://standards.iteh.ai/catalog/standards/sist/b4cced2e-f3ff-47b3-82bc-208947405d76/iso-ts-21219-4-2015>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and TISA shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 204 *Intelligent transport systems*, in cooperation with the Traveller Information Services Association (TISA), TPEG Applications Working Group through Category A Liaison status.

ISO/TS 21219 consists of the following parts, under the general title *Intelligent transport systems — Traffic and travel information (TTI) via transport protocol experts group, generation 2 (TPEG2)*:

- *Part 2: UML modelling rules* [Technical Specification]
- *Part 3: UML to binary conversion rules* [Technical Specification]
- *Part 4: UML to XML conversion rules* [Technical Specification]
- *Part 5: Service framework* [Technical Specification]
- *Part 6: Message management container* [Technical Specification]
- *Part 7: Location referencing container* [Technical Specification]
- *Part 18: Traffic flow and prediction application* [Technical Specification]

The following parts are planned:

- *Part 1: Introduction, numbering and versions* [Technical Specification]
- *Part 9: Service and network information* [Technical Specification]
- *Part 10: Conditional access information* [Technical Specification]
- *Part 14: Parking information application* [Technical Specification]
- *Part 15: Traffic event compact application* [Technical Specification]
- *Part 16: Fuel price information application* [Technical Specification]

- *Part 19: Weather information application* [Technical Specification]
- *Part 20: Extended TMC location referencing* [Technical Specification]
- *Part 21: Geographic location referencing* [Technical Specification]
- *Part 22: OpenLR location referencing* [Technical Specification]
- *Part 23: Roads and multi-modal routes application* [Technical Specification]

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO/TS 21219-4:2015](https://standards.iteh.ai/catalog/standards/sist/b4cced2e-f3ff-47b3-82bc-208947405d76/iso-ts-21219-4-2015)

<https://standards.iteh.ai/catalog/standards/sist/b4cced2e-f3ff-47b3-82bc-208947405d76/iso-ts-21219-4-2015>

Introduction

History

TPEG technology was originally proposed by the European Broadcasting Union (EBU) Broadcast Management Committee, who established the B/TPEG project group in the autumn of 1997 with a brief to develop, as soon as possible, a new protocol for broadcasting traffic and travel-related information in the multimedia environment. TPEG technology, its applications and service features were designed to enable travel-related messages to be coded, decoded, filtered and understood by humans (visually and/or audibly in the user's language) and by agent systems. Originally a byte-oriented data stream format, which may be carried on almost any digital bearer with an appropriate adaptation layer, was developed. Hierarchically structured TPEG messages from service providers to end-users were designed to transfer information from the service provider database to an end-user's equipment.

One year later in December 1998, the B/TPEG group produced its first EBU specifications. Two documents were released. Part 2 (TPEG-SSF, which became ISO/TS 18234-2) described the Syntax, Semantics and Framing structure, which was used for all TPEG applications. Meanwhile Part 4 (TPEG-RTM, which became ISO/TS 18234-4) described the first application, for Road Traffic Messages.

Subsequently in March 1999, CEN TC 278/WG 4, in conjunction with ISO/TC 204/WG 10, established a project group comprising members of the former EBU B/TPEG and they continued the work concurrently. Further parts were developed to make the initial set of four parts, enabling the implementation of a consistent service. Part 3 (TPEG-SNI, ISO/TS 18234-3) described the Service and Network Information Application, used by all service implementations to ensure appropriate referencing from one service source to another.

Part 1 (TPEG-INV, ISO/TS 18234-1), completed the series by describing the other parts and their relationship; it also contained the application IDs used within the other parts. Additionally, Part 5, the Public Transport Information Application (TPEG-PTI, ISO/TS 18234-5), was developed. The so-called TPEG-LOC location referencing method, which enabled both map-based TPEG-decoders and non map-based ones to deliver either map-based location referencing or human readable text information, was issued as ISO/TS 18234-6 to be used in association with the other applications parts of the ISO/TS 18234-series to provide location referencing.

The ISO/TS 18234-series has become known as TPEG Generation 1.

TPEG Generation 2

With the inauguration of the Traveller Information Services Association (TISA) in December 2007 derived from former Forums and the CEN/ISO development project group, the TPEG Applications Working Group took over development work for TPEG technology.

It was about this time that the (then) new Unified Modelling Language (UML) was seen as having major advantages for the development of new TPEG Applications in communities who would not necessarily have binary physical format skills required to extend the original TPEG TS work. It was also realized that the XML format for TPEG described within the ISO/TS 24530-series (now superseded) had a greater significance than previously foreseen; especially in the content-generation segment and that keeping two physical formats in synchronism, in different standards series, would be rather difficult.

As a result TISA set about the development of a new TPEG structure that would be UML based – this has subsequently become known as TPEG Generation 2.

TPEG2 is embodied in the ISO/TS 21219-series and it comprises many parts that cover introduction, rules, toolkit and application components. TPEG2 is built around UML modelling and has a core of rules that contain the modelling strategy covered in Parts 2, 3, 4 and the conversion to two current physical formats: binary and XML; others could be added in the future. TISA uses an automated tool to convert from the agreed UML model XMI file directly into an MS Word document file, to minimize drafting errors, that forms the Annex for each physical format.

TPEG2 has a three container conceptual structure: Message Management (Part 6), Application (many Parts) and Location Referencing (Part 7). This structure has flexible capability and can accommodate many differing use cases that have been proposed within the TTI sector and wider for hierarchical message content.

TPEG2 also has many location referencing options as required by the service provider community, any of which may be delivered by vectoring data included in the Location Referencing Container. The following classification provides a helpful grouping of the different TPEG2 parts according to their intended purpose:

Toolkit parts: TPEG2-INV (Part 1), TPEG2-UML (Part 2), TPEG2-UBCR (Part 3), TPEG2-UXCR (Part 4), TPEG2-SFW (Part 5), TPEG2-MMC (Part 6), TPEG2-LRC (Part 7)

Special applications: TPEG2-SNI (Part 9), TPEG2-CAI (Part 10)

Location referencing: TPEG2-ULR (Part 11), TPEG2-ETL (Part 20), TPEG2-GLR (Part 21), TPEG2-OLR (Part 22)

Applications: TPEG2-PKI (Part 14), TPEG2-TEC (Part 15), TPEG2-FPI (Part 16), TPEG2-TFP (Part 18), TPEG2-WEA (Part 19), TPEG2-RMR (Part 23)

TPEG2 has been developed to be broadly (but not totally) backward compatible with TPEG1 to assist in transitions from earlier implementations, while not hindering the TPEG2 innovative approach and being able to support many new features, such as dealing with applications having both long-term, unchanging content and highly dynamic content, such as Parking Information.

This Technical Specification is based on the TISA specification technical/editorial version number: TPEG2-UXCR/2.0/001.

STANDARD PREVIEW
(standards.iteh.ai)

ISO/TS 21219-4:2015

<https://standards.iteh.ai/catalog/standards/sist/b4cced2e-f3ff-47b3-82bc-208947405d76/iso-ts-21219-4-2015>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO/TS 21219-4:2015

<https://standards.iteh.ai/catalog/standards/sist/b4cced2e-f3ff-47b3-82bc-208947405d76/iso-ts-21219-4-2015>

Intelligent transport systems — Traffic and travel information (TTI) via transport protocol experts group, generation 2 (TPEG2) —

Part 4: UML to XML conversion rules

1 Scope

This Technical Specification specifies the rules for converting TPEG application UML models to the tpegML format description. It contains the XML format definition of the abstract data types defined in TISA Specification SP09003. Rules for converting compound data types are also defined.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8601:2004, *Data elements and interchange formats — Information interchange — Representation of dates and times*

ISO/TS 21219-2, *Intelligent transport systems — Traffic and travel information (TTI) via transport protocol experts group, generation 2 (TPEG2) — Part 2: UML modelling rules*

ISO/TS 21219-5, *Intelligent transport systems — Traffic and travel information (TTI) via transport protocol experts group, generation 2 (TPEG2) — Part 5: Service framework (TPEG2-SWF)*

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

The terms and definitions in ISO/TS 21219-2 and the following apply.

3.1.1

Specification Identification

string that uniquely identifies a certain version of a certain TPEG application or toolkit

EXAMPLE The TPEG Traffic Event Compact application, version 2.0 is identified by the Specification Identification string “TEC_2_0”.

3.1.2

Specification Name

string that verbosely describes a certain TPEG application or toolkit

EXAMPLE The TPEG Traffic Event Compact application, “TrafficEventCompact”.

3.1.3

application namespace prefix

string of the lower case application/toolkit abbreviation as defined in the UML tagged value “ApplicationAbbreviation”

3.2 Abbreviated terms

The abbreviated terms in ISO/TS 21219-2 and the following apply.

XML	eXtensible Markup Language
XSD	XML Schema Definition
UML	Unified Modelling Language
app	a placeholder for an application namespace prefix to create examples in this Technical Specification. It is replaced by the lowercase application abbreviation of the relevant TPEG application.

4 Rules for UML to XML format description conversion

NOTE In the course of ISO processing, XML-compliant quotation marks are replaced with non-compliant quotation marks. When taking over material from these sections, be advised to substitute any double quote to the XML-compliant equivalent quotation mark (Unicode U +0022).

4.1 Definition of XML format description

The xml format description of TPEG applications is included in application and toolkit specifications as a normative annex. This annex shall be named according to the following scheme:

[Specification Identification], tpegML representation

The annex shall have two subclauses: Introduction and Application data type definition. The content of these subclauses is subject to the specifications in this clause.

The introduction shall use a similar formulation as in the following:

This chapter defines the tpegML format representation of the *[specification or toolkit name]* message components, datastructures and its attributes. For further descriptions of these objects see the related clauses [reference to clauses] in this Technical Specification.

The application data type definition shall follow the rules that are specified in [4.10](#).

4.2 The tpegML schema definition

The xml format of TPEG applications will be described according to „XML Schema Definition“.

Each tpegML schema shall contain at least the following definitions:

- Default namespace shall be set to the tpegML schema itself;
- Target namespace shall be set to the tpegML schema itself;
- The XSD elements shall be qualified;
- The *elementFormDefault* should be set to “qualified”;
- The *attributesFormDefault* should be set to “qualified”;
- The prefix and namespace of service framework tpegML schema shall be declared and imported (see TISA Specification SP10007).

The path to the tpegML schema shall have following syntax:

“http://www.tisa.org/TPEG/[SpecificationIdentification]”

with

[Specification Identification] = [upper case Application or Toolkit abbreviation]_[Major version number]_[Minor version number]

The *schemaLocation* of all imported schemas must be changed to local path for the validating process.

Accordingly, the resulting start tag of tpegML schema shall be:

```
<xs:schema xmlns="http://www.tisa.org/TPEG/[Specification Identification]"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  targetNamespace="http://www.tisa.org/TPEG/[Specification Identification]"
  xmlns:sfw="http://www.tisa.org/TPEG/ServiceFramework_0_0"
  elementFormDefault="qualified"
  attributeFormDefault="qualified">
  <xs:import namespace="http://www.tisa.org/TPEG/ServiceFramework_0_0"
    schemaLocation="http://www.tisa.org/TPEG/ServiceFramework_0_0.xsd" />
  ...
</xs:schema>
```

4.3 The tpegML xml file definition

For the xml file defined by the tpegML schema definition in 4.2, the following shall apply:

- No default name space shall be used. All elements and attributes shall have namespace prefixes. This enhances readability and prevents attribute naming problems with imported xsds.
- The name space of the applications and toolkits should be defined by using the application namespace prefix.
- The document encoding shall be "UTF-8".

Accordingly, the xml document will look similar to this example ("app" and "APP" used as placeholders):

```
<?xml version="1.0" encoding="UTF-8" ?>
<app:applicationRootElement xmlns:app="http://www.tisa.org/TPEG/APP_0_0"
  xmlns:mmc="http://www.tisa.org/TPEG/MMC_0_0"
  xmlns:tdt="http://www.tisa.org/TPEG/TPEGDataTypes0_0"
  xmlns:sfw="http://www.tisa.org/TPEG/ServiceFramework_0_0"
  ...
</app:applicationRootElement>
```

The xml files defined by this Technical Specification can hold one application message only (UML class tagged as "ApplicationRoot"). To encode several TPEG application messages, an xml framing has to be applied, for example as defined in TISA Specification SP10007.

4.4 XML data type ranges

XML data type	Range
xs:byte	-128 .. 127
xs:short	-32768 .. 32767
xs:int	-2147483648 .. 2147483647
xs:integer	-infinite .. infinite
xs:unsignedByte	0 .. 255
xs:unsignedShort	0 .. 65535
xs:unsignedInt	0 .. 4294967295
xs:float	$m * 2^e$, where $-2^{24} < m \leq 2^{24}$ and $-149 < e \leq 104$

4.5 Abstract data types

The UML attributes of abstract data types shall be converted to the XSD local elements using the “TPEG Data Types” schema [see [Annex A](#)]. The “TPEG Data Type” schema contains the XSD definition for all TPEG abstract data types. To use “TPEG Data Types” schema, the <xs:schema/> tag shall contain the definition for the namespace [http://www.tisa.org/TPEG/TPEGDataTypes_\[MajorVersion\]_\[MinorVersion\]](http://www.tisa.org/TPEG/TPEGDataTypes_[MajorVersion]_[MinorVersion]), where the version numbers are the release versions of the specification as released by TISA. Additionally, the schema shall be imported by adding the <xs:import/> element (see XSD example). The definition of the “schemaLocation” attribute within the <xs:import /> element can differ from the defined namespace URI but it must contain the valid URI where the “TPEG Data Type” schema is to be found.

To achieve a common appearance of all tpegML schemas it is recommended to use “tdt” prefix for the “TPEG Data Types” namespace.

When using an UML attribute of abstract data type, the tpegML schema shall contain the following definition:

```
<xs:element name="UMLAttributeName" type="tdt:AbstractDataType"/>
```

where *UMLAttributeName* is the name of the attribute as defined in UML, *tdt* is the prefix of the “TPEG Data Types” namespace and *AbstractDataType* is one of the abstract data types defined in TISA Specification SP09003.

The syntax of abstract data types in tpegML format is described in [Annex A](#).

XSD example:

```
<xs:schema xmlns="http://www.tisa.org/TPEG/[Specification Identification]"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  targetNamespace="http://www.tisa.org/TPEG/[Specification Identification]"
  xmlns:tdt="http://www.tisa.org/TPEG/TPEGDataTypes_0_0"
  elementFormDefault="qualified"
  attributeFormDefault="qualified">
  <xs:import namespace="http://www.tisa.org/TPEG/TPEGDataTypes_0_0"
    schemaLocation="http://www.tisa.org/TPEG/TPEGDataTypes_0_0.xsd"/>
  <xs:complexType name="class1">
    <xs:sequence>
      <xs:element name="attr1" type="tdt:FixedPercentage"/>
      <xs:element name="attr2" type="tdt:Boolean"/>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```

XML example:

```
<?xml version="1.0"?>
<app:class1 xmlns:app="http://www.tisa.org/TPEG/[Specification Identification]">
  <app:attr1>3</app:attr1>
  <app:attr2>true</app:attr2>
</app:class1>
```

4.6 TPEG standard tables

The UML attributes of the TPEG standard table type shall be converted similar to abstract data types. The “TPEG Data Types” schema contains definition for all TPEG standard tables.

The syntax of abstract data types is described in [Annex A](#).

XSD example:

```
<xs:schema xmlns="http://www.tisa.org/TPEG/[Specification Identification]"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  targetNamespace="http://www.tisa.org/TPEG/[Specification Identification]"
  xmlns:tdt="http://www.tisa.org/TPEG/TPEGDataTypes_0_0"
  elementFormDefault="qualified"
  attributeFormDefault="qualified">
  <xs:complexType name="class1">
    <xs:sequence>
      <xs:element name="attr1" type="tdt:typ001_LanguageCode"/>
    </xs:sequence>
  </xs:complexType>
</xs:schema>
```

```

    <xs:element name="attr2" type="tdt:typ002_SpecialDay"/>
  </xs:sequence>
</xs:complexType>
</xs:schema>

```

XML example:

```

<?xml version="1.0"?>
<app:class1 xmlns:app="http://www.tisa.org/TPEG/[Specification Identification]"
  xmlns:tdt="http://www.tisa.org/TPEG/TPEGDataTypes_0_0">
  <app:attr1 tdt:table="typ001_LanguageCode" tdt:code="33" />
  <app:attr2 tdt:table="typ002_SpecialDay" tdt:code="2" />
</app:class1>

```

4.7 Application tables (stereotype <<enumeration>>)

The UML class with stereotype <<enumeration>> shall be converted to the XSD with the same syntax as TPEG standard tables. The colon in the class name shall be replaced by an underscore “_”. The value of the attribute “table” shall always contain this class name as fixed value.

To use a UML attribute of the application table type, the XSD shall contain the following complex type.

XSD example:

```

<xs:complexType name="xxxxyy_applicationTableName">
  <xs:attribute name="table" type="xs:string" fixed="xxxxyy_applicationTableName"
  use="required"/>
  <xs:attribute name="code" use="required">
    <xs:simpleType>
      <xs:restriction base="xs:unsignedByte">
        <!-- here the restrictions can be defined -->
      </xs:restriction>
    </xs:simpleType>
  </xs:attribute>
</xs:complexType>

```

where *applicationTableName* is the name of the application table, *xxxxyy* is the application table prefix [1], and *code* is an integer value up to 255

Accordingly the UML attribute of this type shall be:

```

<xs:element name="UMLAttributeName" type="xxxxyy_applicationTableName">

```

4.8 Switching tables

Each child table of a switching table group shall be converted to the XSD according to rule 4.7. The abstract parent class of a switching table group will be defined as standard application table with following conditions:

- The “table” attribute shall be defined as enumeration of all child table names;
- The “code” attribute shall not have any restrictions and shall always be set to “xs:unsignedByte” type.

The XSD example of the abstract blank class for a switching table group:

```

<xs:complexType name="SubTableType">
  <xs:attribute name="table" use="required">
    <xs:simpleType>
      <xs:restriction base="xs:string">
        <xs:enumeration value="xyz101_SubTableType1"/>
        <xs:enumeration value="xyz102_SubTableType2"/>
        ...
        <xs:enumeration value="xyz10N_SubTableTypeN"/>
      </xs:restriction>
    </xs:simpleType>
  </xs:attribute>
  <xs:attribute name="code" type="xs:unsignedByte" use="required"/>
</xs:complexType>

```

The XSD example for usage of a switching table type linked to a main table: