

DRAFT INTERNATIONAL STANDARD

ISO/DIS 24155

ISO/TC 113/SC 5

Secretariat: ANSI

Voting begins on:
2014-11-05

Voting terminates on:
2015-02-05

Hydrometry — Hydrometric data transmission systems — Specification of system requirements

Hydrométrie — Systèmes de transmission des données hydrométriques — Spécification des exigences des systèmes

ICS: 17.120.20

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/cea33161-9d56-4cb8-863a-3fb57738a503/iso-24155-2016>

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENT AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.



Reference number
ISO/DIS 24155:2014(E)

© ISO 2014

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/cea33161-9d56-4cb8-863a-3fb57738a503/iso-24155-2016>

Copyright notice

This ISO document is a Draft International Standard and is copyright-protected by ISO. Except as permitted under the applicable laws of the user's country, neither this ISO draft nor any extract from it may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission being secured.

Requests for permission to reproduce should be addressed to either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Reproduction may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Definitions	1
4 Basic requirements	1
4.1 General.....	1
4.2 Objectives of use.....	1
4.3 Functional requirements.....	1
4.4 Geographical structures.....	2
4.5 Time structures.....	2
4.6 Installation conditions.....	2
4.7 Considerations for designing.....	3
5 Functional requirements of system	4
5.1 General.....	4
5.2 Remote telemetry stations.....	4
5.3 Telemetry system.....	5
5.4 Receiving centre.....	6
5.5 System monitoring.....	7
5.6 Power supply.....	8
6 Operational requirement	8
6.1 General.....	8
6.2 Operation and maintenance manual.....	8
6.3 Maintenance.....	9
Annex A (informative) Configuration of hydrometric data transmission systems	10
Annex B (informative) Functional block diagram of hydrometric data transmission systems	12
Annex C (informative) Locations of remote telemetry stations	14
Annex D (informative) Interfaces of hydrometric sensors at remote telemetry stations	16
Annex E (informative) Data collection sequence	17
Annex F (informative) Communication links for data transmission	24
Annex G (normative) Design of VHF/UHF radio link	28
Annex H (informative) Network architecture	30
Annex I (informative) Data repeating methods at a relay station	35
Annex J (informative) General power supply for remote telemetry stations	36

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/DIS 24155 was prepared by Technical Committee ISO/TC 113, *Hydrometry*, Subcommittee SC 5, *Instruments, equipment and data management*.

PREVIEW
iTeh STANDARD
(standards.itih.ai)
Full standard:
<https://standards.itih.ai/catalog/standards/sist/cea3316c-9d56-4cb8-863a-3fb57738a503/iso-24155-2016>

Introduction

Hydrometric data transmission systems provide data for the day-to-day management of water resources and for warning and forecasting of floods, droughts and conditions affecting water quality and public health. The systems transmit data measured at remote telemetry stations to a receiving centre for further processing.

This standard defines and standardizes the required specifications of hydrometric data transmission systems. It does not describe the specifications of the equipment and units constituting hydrometric data transmission systems, but does describe the functional performance that the hydrometric data transmission systems should provide.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/cea33161-9d56-4cb8-863a-3fb57738a503/iso-24155-2016>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/cea33161-9d56-4cb8-863a-3fb57738a503/iso-24155-2016>

Hydrometry — Hydrometric data transmission systems — Specification of system requirements

1 Scope

This international standard ISO 24155 specifies the technical requirements that should be considered in designing and operating hydrometric data transmission systems and also the necessary functions of those systems.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 772, *Hydrometry — Vocabulary and symbols*

ISO 1000, *SI units and recommendations for the use of their multiples and of certain other units*

ISO/IEC 2382-1, *Information technology — Vocabulary — Part 1: Fundamental terms*

3 Definitions

For the purposes of this document, the terms and definitions given in ISO 772 and ISO/IEC 2382-1 apply.

4 Basic requirements

4.1 General

This clause specifies the general requirements for designing a hydrometric data transmission system (HDTS).

An HDTS shall be designed to meet the basic requirements, defined hereinafter, taking into consideration functionality, geographical structures, time structures, installation conditions, reliability, safety, maintainability and economy. The final system specifications should be determined through the process of repetitive discussions among technological specialists in hydrological and telecommunications fields.

The conceptual configuration of an HDTS is shown in [Annex A](#).

4.2 Objectives of use

An HDTS shall be designed with a full understanding of the necessity and importance of hydrometric services for appropriate water management in river basins, such as needed for early warning of high flood levels, or low flows in ecologically sensitive rivers, in which this system is to be used.

4.3 Functional requirements

The functional requirements for an HDTS are classified into the following:

- a) **Mandatory requirements:** the minimum requirements that an HDTS designer shall comply with in designing the system. The mandatory requirements include legal requirements, for example, for the site where the system will be installed, and applicable specifications of various standards.

- b) **Optional requirements:** the functions and methods of implementing them that an HDTS designer can select. The optional requirements include the requirements, such as the data collection sequence and selection of communication links as specified in [Clause 5.3.4](#).

An HDTS should be designed to fully achieve the mandatory functional requirements, and to meet the optional requirements in full consideration of the user's requirements and operational purposes of the system so as to demonstrate the required system functionality.

4.4 Geographical structures

The following geographical structures shall be determined as a fundamental element of HDTS:

- a) location(s) of the remote telemetry station(s);
- b) location(s) of the receiving centre(s); and
- c) location(s) of the relay station(s), if necessary.

A remote telemetry station is located at a selected hydrometric-observation point. Therefore, remote telemetry stations are distributed over a geographically wide area, including a river basin. Remote telemetry stations cannot always be located at optimum hydrological sites, and may be relocated to alternate sites because of geographical problems and difficulties in data transmission.

A receiving centre consists of equipment and receives data from remote telemetry stations for data processing and display; it is located at a site where data and/or information are needed. Therefore, the receiving centre will usually be located within the facility of a user organization. In large river basins, receiving centres may be distributed at user organizations near a hydrometric-observation point.

According to the necessity of the communication medium, a relay station shall be provided in the system.

These geographical structures should be considered not only at the time of designing but also for the future plans.

4.5 Time structures

Usually, an HDTS is used on a real-time basis. An HDTS has two time domains: the first domain is the time used in the natural world; the other is the time series in system operation.

The basic property of time in system operation is the time when the hydrometric observation is made at a gauging point; the gauging intervals and the delay times that are required in data presentation.

Usually, sensors at remote telemetry stations continuously measure hydrological phenomena, but the data monitored at the receiving centre are sampled in a time series. Therefore, these time characteristics and their allowable error range should be determined for the purposes of operation. Details are shown in [Annex E](#).

4.6 Installation conditions

The environmental conditions of the remote telemetry stations may be more severe than those of telecommunication equipment installed indoors. Therefore, the following conditions should be considered:

- a) temperature range and rate of change;
- b) relative humidity range with no condensation;
- c) wind velocity;
- d) lightning protection;
- e) seismic resistance;

- f) damage due to sea wind, dust, and/or corrosive gases;
- g) available power supply conditions;
- h) equipment damage and access during flooding.

The environmental conditions of the telecommunications and information processing system equipment to be installed at a receiving centre should also be considered for items a), b), d), e), and g) above. Details are shown in [Annex C](#).

4.7 Considerations for designing

4.7.1 Reliability

An HDTS is basically designed for continuous operation for its original purpose of use, particularly in the case of heavy rains and floods. Designers shall consider the reliability of equipment and the entire system. For the important functions of the system, alternative means or a redundancy of the system should be provided.

For example, duplicate communication links can be installed to connect important remote telemetry stations in a gauging area to a receiving centre. A hot-standby system can also be used for the equipment having important functions. The hydrological data measured by important remote telemetry stations also can be input to site recorder and the storage term(s) and period should meet the user's requirements.

4.7.2 Safety

An HDTS shall be designed as a safe (fail-safe) system that can always secure safe system operation in the case of a malfunction of equipment, faulty operation by a user, or a system failure due to any external factor. The fail-safe should prevent such problems from spreading over the entire system.

If the malfunction or failure in part of the system or faulty operation by a user is non-critical, the principal functions of the system should continuously operate because of the importance of hydrometric observation.

4.7.3 Data permanence

The permanence of hydrometric data should be ensured, since these are stored and used for water resources management over a long period.

The permanence of the data shall be ensured even if peripheral unit(s) is replaced. In addition, interface specifications shall be defined for the data transmission system, format and transfer timing between the sensors to be installed in the pre-stage of an HDTS and the information processing system to be installed in the post-stage of an HDTS. Data received at the receiving centre should be saved on reliable storage media.

4.7.4 Maintainability

The HDTS equipment shall be designed to have a composition that is easy to maintain and repair.

The HDTS equipment should be designed so that it is easy to check and replace parts, and so that inspections and adjustments can be conducted (easily or) conveniently.

Software shall be designed with future maintainability taken into consideration, i.e. for future modifications and/or future improvements. Documentation shall be provided in order to easily carry out necessary procedures for the cases when modifications are required.

The HDTS should also include the capability of performing end to end line testing. This will ensure that what is transmitted by the remote telemetry station is displayed at the receiving centre.

4.7.5 Operability

Each piece of the equipment shall be designed to allow for simple operation and to prevent unauthorized access, illegal operation, and unintentional shutoff of the power. An HDTS should be designed to enable the receiving centre to monitor the operational status of the entire system, identify problems and control necessary operations.

4.7.6 Economy

An HDTS should be designed to have a good cost performance in terms of required functions and reliability. The economy of the system should be evaluated considering the entire life cycle cost including the initial cost and operational cost. An HDTS should allow for future updating or expansion.

5 Functional requirements of system

5.1 General

The functional block diagram of an HDTS is shown in [Annex B](#). The hydrometric data measured at remote telemetry stations are encoded into a format suitable for transmission at the remote telemetry stations. Communications are made between the remote telemetry stations and the receiving centre according to a prescribed collection sequence, transmitting the encoded data from the remote telemetry stations to the receiving centre. The receiving centre decodes the received data and performs data verification and processing to disseminate it to users as hydrometric information. An information processing system may be provided in the stage following this system.

5.2 Remote telemetry stations

5.2.1 General

The principal function of a remote telemetry station is to measure hydrometric data using sensors. This is a process for collecting data to be input to the system and for monitoring hydrological phenomena that change with time.

5.2.2 Locations

The locations of remote telemetry stations shall be determined in considering features of communication link(s) to be introduced as well as hydrological points of view. The possibility of using the sites, the availability of existing communication links and radio links, the radio propagation conditions (if radio links are chosen), the lead-in conditions from power sources, and the access roads should also be considered as important factors for determining the locations. The items that should be investigated in selecting the sites of remote telemetry stations from the viewpoint of data transmissions are shown in [Annex C](#).

5.2.3 Data measurements

The measuring conditions for data to be acquired shall be specified based on operational purposes.

The items to be specified are:

- a) data type and number of measuring points,
- b) range of measurement, effective digits,
- c) measurement accuracy and resolution,
- d) timing of measurement,
- e) input interface (typical interfaces are shown in [Annex D](#)),

- f) threshold values for detecting alarms, and
- g) other necessary items.

Specifications of sensors and converters are outside the scope of this standard. However, the SI Units (International System of Units) specified in ISO 1000 shall be used for measurement.

5.2.4 Data processing

In general, the results of data measurements should be transmitted as momentary data without being processed. However, such input data may be processed for conversion into a form that can be transmitted at the interfaces with the sensors. For some data and under certain measuring conditions, it may be effective to calculate the moving average or maximum and minimum values of the data measured at successive time points at remote telemetry stations and transmit the calculated results. Abnormal data should be marked or highlighted for further inspection.

In recording and displaying the data measured at remote telemetry stations, the following items should be considered and decided:

- a) storage of multiple data for batch transmission;
- b) protection against data loss due to system troubles;
- c) provision of displaying raw data, etc. for easy maintenance on site.

The sampling intervals of a data logger should be determined by the balance among its operation purposes of the logging, the recordable time depending on the recording capacity and intervals of the logger, the intervals of log collecting and its cost, and the risk of loss of data through natural causes or vandalism, etc.

5.3 Telemetry system

5.3.1 General

The telemetry system is the core of this HDTS, and its principal function is to transmit the data measured by sensors at remote telemetry stations to the data processing system at the receiving centre.

5.3.2 Amount and intervals of data transmission

The total amount of data and intervals of data transmission shall be provided for each data transmission link. The necessary capacity (speed) of a communication link is determined by adding the allowable transmission delay time to these parameters and also depends on the selected data communication channel.

5.3.3 Data collection sequence

The data collection sequence that is the fundamental function of the telemetry system shall be determined. There are various data collection and transmission sequences, such as continuous data transmission with time, data transmission in certain intervals, and data transmission when the data reaches certain threshold values.

The method in which the receiving centre polls the remote telemetry stations one after another and receives the data measured at each polling time may cause time differences in measurement as restricted by the polling order. On the other hand, the method in which remote telemetry stations measure data at regular times, temporarily store the data and transmit the data to the receiving centre asynchronously with the measurements can minimize the delay time in measurements.

The typical methods are shown in [Annex E](#).

5.3.4 Communication links

There are various types of communication links and communication methods such as wired lines, radio links, public telecommunication lines, mobile telephone network, Internet and satellite communication links. The type of communication link and communication method shall be decided by taking into consideration the communication environment and conditions of use including the amount of information to be transmitted, transmission speed, reliability of transmission, operating environment, feasibility and economy, and allowable delay time.

The communication links available for data transmission and their technical outlines are shown in [Annex F](#). Communication links should be decided through comprehensive evaluation of the following items:

- a) types and functions of communication lines that are provided by telecommunication company in the area where HDTS is to be installed;
- b) possibility (including technical and legal restrictions) of constructing dedicated communication lines for the telemetry system other than those provided by telecommunication company;
- c) required transmission speed calculated from the amount of data that the telemetry system transmits (amount of data transmissions), sampling intervals, and allowable delay time;
- d) required reliability and economy of communication links. Reliability should be considered in event of disasters and floods, and economy should be considered for the initial cost and life cycle cost.

Usually, exclusive radio communication links are used. In such cases, the frequencies and output powers are provided by international standards and national laws. Radio communications are usually available over distances of several tens of kilometres. Relay stations may be needed for longer distances and/or rugged terrain. Since the quality of radio communication depends on the peripheral conditions, propagation tests should be made after designing the communication links. A general process of designing simplex radio links is shown in [Annex G](#).

5.3.5 Network architecture

Networks for interconnecting remote telemetry stations and receiving centres may be configured as various architectures depending on the locations of the remote telemetry stations and the receiving centres, the types of communication links to be used, presence of relay stations, etc. Appropriate network architecture shall be determined with a full understanding of the advantages and disadvantages of various architectures, such as economy, reliability, and adaptability. Some network architectures for the telemetry system are shown in [Annex H](#). Data repeating methods at a relay station are shown in [Annex I](#).

5.4 Receiving centre

5.4.1 General

The principal functions of the receiving centre are data collection through telemetry, data verification and processing, and dissemination of the results to users. Data processing may be conducted by providing a separate information processing system. In such a case, the details are outside the scope of standard.

5.4.2 Data verification

Data shall be verified to ensure the quality of collected data.

The data verification can be classified into two processes.

- The first is to detect errors in data transmission. This can be performed using parity bit, Cyclic Redundancy Check (CRC) error detection codes or other methods. These methods may be included in the communication control procedure.