
**Road vehicles— FlexRay
communications system —**

**Part 4:
Electrical physical layer specification**

Véhicules routiers — Système de communications FlexRay —

Partie 4: Spécification de la couche d'application électrique

<https://standards.iteh.ai>
Document Preview

[ISO 17458-4:2013](https://standards.iteh.ai/catalog/standards/iso/a89a209f-5fc9-4ca4-95ed-409b8c2f791e/iso-17458-4-2013)

<https://standards.iteh.ai/catalog/standards/iso/a89a209f-5fc9-4ca4-95ed-409b8c2f791e/iso-17458-4-2013>



iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ISO 17458-4:2013](https://standards.iteh.ai/catalog/standards/iso/a89a209f-5fc9-4ca4-95ed-409b8c2f791e/iso-17458-4-2013)

<https://standards.iteh.ai/catalog/standards/iso/a89a209f-5fc9-4ca4-95ed-409b8c2f791e/iso-17458-4-2013>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction.....	vi
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	1
3.1 Terms and definitions	1
3.2 Abbreviated terms	10
3.3 Symbols.....	12
4 Document reference according to OSI model	13
5 Conventions	14
5.1 General	14
5.2 Notational and parameter prefix conventions.....	14
5.3 Important preliminary notes	15
6 Communication channel basics	16
6.1 Objective.....	16
6.2 Propagation delay	16
6.3 Frame TSS length change	18
6.4 Symbol length change	18
6.5 FES1 length change	19
6.6 Collisions.....	19
6.7 Stochastic jitter.....	20
6.8 Wakeup patterns.....	20
7 Principle of FlexRay networking.....	22
7.1 Objective.....	22
7.2 Interconnection of nodes.....	22
7.3 Electrical signalling.....	23
8 Network components	24
8.1 Objective.....	24
8.2 Cables	24
8.3 Connectors.....	25
8.4 Cable termination	25
8.5 Termination concept	27
8.6 Common mode chokes	27
8.7 DC bus load.....	27
9 Network topology	28
9.1 Objective.....	28
9.2 Point-to-point connection.....	29
9.3 Passive star.....	29
9.4 Linear passive bus	30
9.5 Active star network	31
9.6 Cascaded active stars.....	32
9.7 Hybrid topologies	32
9.8 Dual channel topologies	33
10 Asymmetric delay budget.....	33
10.1 Objective.....	33
10.2 Basic topology for asymmetric delay budget.....	34
10.3 Definition of Test Planes.....	34

10.4	Requirements to the asymmetric delay budget.....	36
10.5	Definition of maximum asymmetric delay portions	36
10.6	Other networks.....	43
11	Signal integrity	43
11.1	Objective.....	43
11.2	Mask test at TP1 / TP11	44
12	Electrical bus driver	49
12.1	Overview	49
12.2	Operation modes	50
12.3	Operation mode transitions.....	51
12.4	Bus driver – communication controller interface.....	53
12.5	Bus driver – bus guardian interface (optional).....	57
12.6	Bus driver – host interface	57
12.7	Bus driver – power supply interface.....	61
12.8	Bus driver - level shift interface (optional).....	63
12.9	Bus driver - bus interface	63
12.10	Bus driver – wakeup interface (optional)	77
12.11	Remote wakeup event detector (optional)	78
12.12	Bus driver behaviour under fault conditions	80
12.13	Bus driver functional classes.....	85
12.14	Bus driver signal summary.....	87
13	Active Star	88
13.1	Overview	88
13.2	Hardware overview	88
13.3	Signal timing	90
13.4	Active star device operation modes	98
13.5	Autonomous power moding flag (APM flag).....	100
13.6	Branch operating states.....	101
13.7	Branch transmitter and receiver circuit	104
13.8	Active star - communication controller interface (optional)	105
13.9	Active star – bus guardian interface (optional)	115
13.10	Active star – host interface (optional)	115
13.11	Active star – power supply interface	115
13.12	Active star – level shift interface (optional)	118
13.13	Active star – bus interface	118
13.14	Active star – wake interface (optional).....	119
13.15	Active star functional classes	119
13.16	Active star behaviour under fault conditions	120
13.17	Active star signal summary	122
14	Interface definitions.....	123
14.1	Overview	123
14.2	Communication controller – bus driver interface	123
14.3	Host	126
15	General features for FlexRay physical layer parts	127
15.1	Objective.....	127
15.2	Voltage limits for digital output signals	127
15.3	Input voltage thresholds for digital signals	127
15.4	ESD protection on chip level (HBM)	128
15.5	ESD protection on chip level (IEC61000-4-2)	128
15.6	ESD protection on ECU level.....	128
15.7	Operating temperature	128
15.8	Serial peripheral interface (SPI)	129
Annex A (informative)	Application notes	131

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17458-4 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 3, *Electrical and electronic equipment*.

ISO 17458 consists of the following parts, under the general title *Road vehicles — FlexRay communications system*:

- Part 1: *General information and use case definition*
- Part 2: *Data link layer specification*
- Part 3: *Data link layer conformance test specification*
- Part 4: *Electrical physical layer specification*
- Part 5: *Electrical physical layer conformance test specification*

Introduction

The FlexRay communications system is an automotive focused high speed network and was developed with several main objectives which were defined beyond the capabilities of established standardized bus systems like CAN and some other proprietary bus systems. Some of the basic characteristics of the FlexRay protocol are synchronous and asynchronous frame transfer, guaranteed frame latency and jitter during synchronous transfer, prioritization of frames during asynchronous transfer, single or multi-master clock synchronization, time synchronization across multiple networks, error detection and signalling, and scalable fault tolerance.

The FlexRay communications system is defined for advanced automotive control applications. It serves as a communication infrastructure for future generation high-speed control applications in vehicles by providing:

- A message exchange service that provides deterministic cycle based message transport;
- Synchronization service that provides a common time base to all nodes;
- Start-up service that provides an autonomous start-up procedure;
- Error management service that provides error handling and error signalling;
- Wakeup service that addresses the power management needs.

Since start of development the automotive industry world-wide supported the specification development. The FlexRay communications system has been successfully implemented in production vehicles today.

The ISO 17458 series specifies the use cases, the communication protocol and physical layer requirements of an in-vehicle communication network called "FlexRay communications system".

This part of ISO 17458 has been established in order to define the electrical physical layer of the FlexRay data link. <https://standards.iteh.ai/catalog/standards/iso/a89a209f-5fe9-4ca4-95ed-409b8c2f791e/iso-17458-4-2013>

To achieve this, it is based on the Open Systems Interconnection (OSI) Basic Reference Model specified in ISO/IEC 7498-1 and ISO/IEC 10731, which structures communication systems into seven layers. When mapped on this model, the protocol and physical layer requirements specified by ISO 17458 are broken into:

- Diagnostic services (layer 7), specified in ISO 14229-1 [7], ISO 14229-4 [9];
- Presentation layer (layer 6), vehicle manufacturer specific;
- Session layer services (layer 5), specified in ISO 14229-2 [8];
- Transport layer services (layer 4), specified in ISO 10681-2 [1];
- Network layer services (layer 3), specified in ISO 10681-2 [1];
- Data link layer (layer 2), specified in ISO 17458-2, ISO 17458-3;
- Physical layer (layer 1), specified in ISO 17458-4, ISO 17458-5;

in accordance with Table 1.

Table 1 — FlexRay communications system specifications applicable to the OSI layers

Applicability	OSI 7 layers	FlexRay communications system	Vehicle manufacturer enhanced diagnostics
Seven layer according to ISO 7498-1 and ISO/IEC 10731	Application (layer 7)	vehicle manufacturer specific	ISO 14229-1, ISO 14229-4
	Presentation (layer 6)	vehicle manufacturer specific	vehicle manufacturer specific
	Session (layer 5)	vehicle manufacturer specific	ISO 14229-2
	Transport (layer 4)	vehicle manufacturer specific	ISO 10681-2
	Network (layer 3)	vehicle manufacturer specific	
	Data link (layer 2)	ISO 17458-2, ISO 17458-3	
	Physical (layer 1)	ISO 17458-4, ISO 17458-5	

Table 1 shows ISO 17458 Parts 2 – 5 being the common standards for the OSI layers 1 and 2 for the FlexRay communications system and the vehicle manufacturer enhanced diagnostics.

The FlexRay communications system column shows vehicle manufacturer specific definitions for OSI layers 3 – 7.

The vehicle manufacturer enhanced diagnostics column shows application layer services covered by ISO 14229-4 which have been defined in compliance with diagnostic services established in ISO 14229-1, but are not limited to use only with them. ISO 14229-4 is also compatible with most diagnostic services defined in national standards or vehicle manufacturer's specifications. The presentation layer is defined vehicle manufacturer specific. The session layer services are covered by ISO 14229-2. The transport protocol and network layer services are specified in ISO 10681.

(<https://standards.iteh.ai>)
Document Preview

<https://standards.iteh.ai>
ISO 17458-4:2013

<https://standards.iteh.ai/catalog/standards/iso/a89a209f-5fe9-4ca4-95ed-409b8c2f791e/iso-17458-4-2013>

Road vehicles — FlexRay communications system — Part 4: Electrical physical layer specification

1 Scope

This part of ISO 17458 specifies the electrical physical layer for FlexRay communications systems.

The electrical physical layer for FlexRay is designed for time-triggered networks with data-rates up to 10 Mbit/s to connect automotive electronic control units (ECUs). The medium that is used is dual wires. Signalling on the bus is accomplished by asserting a differential voltage between those wires. Topology variations range from point-to-point connections via linear passive busses and passive stars up to active star topologies.

This part of ISO 17458 includes the definition of electrical characteristics of the transmission itself and also documentation of basic functionality for bus driver (BD) and active star (AS) devices.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 17458-1, *Road vehicles — FlexRay communications system — Part 1: General information and use case definition*

<https://standards.iteh.ai/catalog/standards/iso/a89a209f-5fe9-4ca4-95ed-409b8c2f791e/iso-17458-4-2013>

ISO 17458-2, *Road vehicles — FlexRay communications system — Part 2: Data link layer specification*

3 Terms, definitions, symbols and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 17458-1, ISO 17458-2 and the following apply.

3.1.1

alternating current busload

AC busload

equivalent circuit of a passive star from transmitting view of the bus driver

3.1.2

active elements

components which work with power supply and amplifiers

3.1.3

active star network

AS network

all *point-to-point* connections plugged to an AS

3.1.4

activity

See "bus state"

NOTE activity distinguishes two states: *Data_0* and *Data_1*.

3.1.5

Activity

signal to the Central_Logic when this *communication path* is not *idle*(see also *NoActivity*)

3.1.6

asymmetric delay budget

maximum bit-deformation in the time domain

NOTE It is derived from the specified synchronization and sampling procedure and the properties of their implementation. When transmitting a FlexRay data stream the receiving CC must be able to detect the data without any error. If the *asymmetric delay* of the data stream is higher than the *asymmetric delay budget*, the decoder samples faulty bit values.

3.1.7

asymmetric delay

bit-deformation in the time domain when passing a data stream e.g. via a *BD*

EXAMPLE

A data stream is applied to the BD's input TxD: ...00100

The single 1 at the centre shall have a length of 100 ns

The *BD* passes the data stream to its output *BP* and *BM*.

The single 1 may be shortened or lengthened a little bit to e.g. 102 ns

In this case the *asymmetric delay* has to be determined to 2 ns.

3.1.8

bus driver – bus driver interface

BD-BD-interface

consideration of all involved effects of the timing of each *BD/AS*

NOTE The timing is specified based on measurement set-ups easy to be used. When connecting two *BDs/ASs* (via e.g. a *passive star*) the resulting delays are not equal to twice the specified values.

3.1.9

bus guardian enable

BGE

input pin of the *BD* that allows deactivating the bus output stage of the *BD*

3.1.10

bias voltage

voltage source with high output impedance

3.1.11

bus minus

BM

bidirectional pin of the *BD/AS* to allow the *BD/AS* the access to the bus.

3.1.12

bus plus

BP

bidirectional pin of the *BD/AS* to allow the *BD/AS* the access to the bus.

3.1.13

branch

component within *active star topologies*

NOTE A *branch* can be built of a *point-to-point* connection, a *linear bus* or a *passive star*.

3.1.14

byte start sequence

BSS

pre-defined sequence of two bits (logical: 10) which is sent in front of each byte

3.1.15

bus guardian

BG

component which allows the node only to transmit during the pre-defined timing slots

3.1.16

bus state

status of the bus FlexRay communication

NOTE Several different states are visible due to the operating modes of the FlexRay system.

EXAMPLE

idle: there is no communication on the bus. Approximately 0 V differential voltage is measurable.

activity: there is an on-going communication on the bus. Approximately ± 600 mV up to $\pm 1\,000$ mV differential voltage is measurable, etc.

3.1.17

cascade

topology character

NOTE If a topology uses more than 1 AS the wording "cascaded ASs" is used.

3.1.18

common mode

mode in which two test points are handled simultaneously against ground

EXAMPLE

<https://standards.iteh.ai/catalog/standards/iso/a89a209f-5fe9-4ca4-95ed-409b8c2f791e/iso-17458-4-2013>

common mode input impedance of the *BD*'s bus pins *BP* and *BM* to ground.

common mode voltage on the bus: $\frac{1}{2} (u_{BP} + u_{BM})$

3.1.19

communication path

branches CC interface and Intra Star Interface

3.1.20

connection network

components like CMC, termination resistors, ESD protection circuits, lines on the *PCB*, connectors, etc

NOTE When implementing a FlexRay system each *BD/AS* has to be plugged to a FlexRay *cable* via these components.

3.1.21

Data_0

bus-state "*activity*" where a logical 0 is transmitted

3.1.22

Data_1

bus-state "*activity*" where a logical 1 is transmitted.

3.1.23

differential mode

mode in which two test points are handled against each other

EXAMPLE

differential mode input impedance of the BD's bus pins BP and BM to ground.

differential mode voltage on the bus: ($u_{BP} - u_{BM}$).

differential mode impedance of the FlexRay cable

3.1.24

dummy load

summary of loads that can be applied to components which are specified by easy-to-use measurement set-ups

EXAMPLE

dummy load at BP and BM: 40 Ω || 100 pF.

dummy load at RxD: 15 pF

3.1.25

eye-diagram

diagram that is visible when overlying edge synchronized measured bus signals

NOTE The shape of the eye allows specifying the bus-signals.

3.1.26

frame end sequence

FES

bit sequence that consists of two bits (01) and is sent at the end of each FlexRay data frame

NOTE The asymmetric delay budget is based on the end of a data frame: in the worst case up to 10 consecutive identical bits can be seen.

$BSS + 1 \text{ byte} + FES = 10 \text{ 00000000 01}$

3.1.27

functional class

grouping of various features that are implemented together

NOTE The *BD/AS* offers various technical features. To keep the resulting products testable and to offer them a good chance on the market it is required to implement various features only together.

3.1.28

generic bus driver

simulation model which is derived from the specification directly

NOTE The knowledge about real implementations is taken into consideration. The generic *BD* supports a receiver stage, a transmitter stage and optionally the *AS* routing behaviour.

3.1.29

idle

see "*bus state*".

Idle distinguishes 3 bus biasing states:

idle while all nodes are neither un-powered nor in a low power mode, thus all nodes are biasing the bus.

idle while all nodes are either un-powered or in a low power, thus none of the nodes is biasing the bus.

idle while some nodes are biasing the bus and others not.

3.1.30

leg

passive network that is involved in the calculation of *timing budget*

NOTE A topology is interpreted as a single path from a transmitter to a receiver that contains several passive networks. Each of these passive networks is named *leg*.

3.1.31

linear passive bus

FlexRay bus that consists of 2 terminated FlexRay nodes with one *cable* between

NOTE Additionally some un-terminated FlexRay nodes are plugged to the cable by *splices* and short *stubs*.

3.1.32

monolithic

see: *active star*.

NOTE This term is used to characterize various implementations on an AS. If the AS is *monolithic* implemented all specified components are included in a single device.

3.1.33

NoActivity

signal to the Central_Logic when this communication path is *idle* is detected (see also *Activity*)

3.1.34

non-monolithic

character of various implementations on an AS

NOTE This term is used to characterize various implementations on an AS. If the AS is *non-monolithic* implemented all specified components are not included in a single device, two devices are used at least. See "*active star*".

3.1.35

NotReceiveActive

communication path signals *NotReceiveActive* to the Central_Logic when a state is entered at that the *communication path* is idle or is actively transmitting data

3.1.36

parasitic capacity

capacity that appears although it is not technically necessary

EXAMPLE

pins of a device housing generate a capacity

3.1.37

parasitic resistance

resistance that appears although it is not technically necessary

3.1.38

passive net

all possible implementation of AS *branches*

NOTE *This summarizes:* point-to-point connections, linear busses and passive stars. They do not include *BD/ASs*.

3.1.39

passive star network

network consisting of passive stars

3.1.40

physical layer

component that includes all components between *TP0* and *TP5*

3.1.41

ReceiveActive

communication path signals *ReceiveActive* to the *Central_Logic* when a state is entered at that the incoming data stream is forwarded to other *communication paths*

3.1.42

receiver

device or entity that receives an information transfer originated by a transmitter

NOTE A term that is used in various ways based on the context.

EXAMPLE

BD's input stage from the bus.
FlexRay *communication element* receiving node

3.1.43

receive enable not

RxEN

output pin at the *BD* to show the state of the bus

NOTE Two states are distinguished: *idle* or *activity*

3.1.44

serial peripheral interface

SPI

synchronously working hardware interface to exchange data among circuits mounted on a *PCB*

3.1.45

signal integrity

SI

procedures or requirements to *differential* bus signals to guarantee the faultless transmission of FlexRay *communication elements*

3.1.46

signal integrity voting

SI voting

procedure to determine *Sq* based on measured *bus* signals

3.1.47

specific line delay

propagation of a FlexRay signal per meter of a transmission line in ns/m

3.1.48

splice

any implementation of a connection-point where 3 or more transmission lines are plugged together

NOTE A *splice* may contain passive components to damp radiation

EXAMPLE

A *splice* in a linear bus allows to connect a stub to a FlexRay node.

3.1.49

signal quality

Sq

parameter to describe whether the required *signal integrity* of FlexRay signals on the bus is met

NOTE Pass or fail are the possible results.