



SLOVENSKI STANDARD
kSIST FprEN 13203-5:2015
01-junij-2015

**Plinske gospodinjske kurilne naprave za pripravo tople sanitarne vode - 5. del:
Ocenjevanje porabe energije plinskih aparatov, kombiniranih z električno toplotno
črpalko**

Gas-fired domestic appliances producing hot water - Part 5: Assessment of energy
consumption of gas fired appliances combined with electrical heat pump

Gasbeheizte Geräte für die sanitäre Warmwasserbereitung für den Hausgebrauch - Teil
5: Bewertung des Energieverbrauchs von Gasgeräten mit elektrischer Wärmepumpe

Appareils domestiques produisant de l'eau chaude sanitaire utilisant les combustibles
gazeux - Partie 5 : Evaluation de la consommation énergétique des appareils à gaz
combinés à une pompe à chaleur électrique

Ta slovenski standard je istoveten z: FprEN 13203-5

ICS:

91.140.65 Oprema za ogrevanje vode Water heating equipment

kSIST FprEN 13203-5:2015

en,fr,de

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

FINAL DRAFT
FprEN 13203-5

April 2015

ICS 91.140.65

English Version

Gas-fired domestic appliances producing hot water - Part 5: Assessment of energy consumption of gas fired appliances combined with electrical heat pump

Appareils domestiques produisant de l'eau chaude sanitaire
utilisant les combustibles gazeux - Partie 5 : Evaluation de
la consommation énergétique des appareils à gaz
combinés à une pompe à chaleur électrique

This draft European Standard is submitted to CEN members for unique acceptance procedure. It has been drawn up by the Technical Committee CEN/TC 109.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents	Page
Foreword.....	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 General test conditions	7
4.1 Reference conditions	7
4.2 Specific heat source conditions.....	7
4.3 Measurement uncertainties	8
4.4 Test conditions	9
4.4.1 General.....	9
4.4.2 Test room.....	9
4.4.3 Water supply	10
4.4.4 Steady-state.....	10
4.4.5 Initial adjustment of the appliance.....	10
4.4.6 Electrical supply	11
5 Determination of the energy consumption of the appliance.....	11
5.1 General.....	11
5.2 Tapping cycles	11
5.3 Measurement of the energy recovered by the useful water	20
5.4 Calculation of gas energy	20
5.4.1 Calculation of daily gas energy consumption	20
5.4.2 Calculation of total gas energy consumption.....	21
5.5 Calculation of electrical energy.....	22
5.5.1 Calculation of daily electrical energy consumption.....	22
5.5.2 Calculation of total electrical energy consumption	22
5.6 Corrections to apply for fans and liquid pumps.....	23
5.6.1 Power absorbed by the fans of connected heat pumps	23
5.6.2 Power absorbed by liquid pumps	24
6 Determination of the wasted water	25
7 Eco design Related Products Data	25
7.1 Water heating energy efficiency.....	25
7.2 Annual fuel consumption (AFC).....	26
7.3 Annual electricity consumption (AEC)	27
Annex A (informative) Test conditions.....	28
Annex B (informative) Test rig and measurement devices	32
B.1 General.....	32
B.2 Pressure measurement	33
B.3 Temperature measurement.....	33
Annex C (informative) Packages covered by the present document.....	37
Annex D (informative) Additional performance data	42
D.1 Heating time	42
D.2 Standby power input	43
D.3 Coefficient of primary energy performance or primary energy yield (PER).....	43

D.4	Total consumption of primary energy.....	44
Annex ZA (informative)	Relationship between this European Standard and the requirements of Commission Regulation (EC) n° 814/2013	45
Annex ZB (informative)	Relationship between this European Standard and the requirements of Commission Regulation n° 812/2013.....	46
Annex ZC (informative)	Relationship between this European Standard and the requirements of Commission Regulation (EU) n° 813/2013	47
Annex ZD (informative)	Relationship between this European Standard and the requirements of Commission Delegated Regulation (EU) n° 811/2013.....	48
Bibliography.....		49

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 13203-5:2019

<https://standards.iteh.ai/catalog/standards/sist/355d6071-f62f-41dd-903e-e2a9004a1ed0/sist-en-13203-5-2019>

FprEN 13203-5:2015 (E)**Foreword**

This document (FprEN 13203-5:2015) has been prepared by Technical Committee CEN/TC 109 “Central heating boilers using gaseous fuels”, the secretariat of which is held by NEN.

This document is currently submitted to the Unique Acceptance Procedure.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative Annex ZA, B, C or D, which are integral parts of this document.

The safety operation of the boiler is not covered by this standard. Safety should be proved by means of the essential safety requirements of the Gas Appliances Directive 2009/142/EC. This way be achieved by compliance with the appropriate existing harmonized standards.

NOTE Useful standards are EN 26, EN 89, EN 15502–1, EN 15502–2-1 and EN 15502–2-2.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 13203-5:2019

<https://standards.iteh.ai/catalog/standards/sist/355d6071-f62f-41dd-903e-e2a9004a1ed0/sist-en-13203-5-2019>

1 Scope

This European Standard is applicable to gas-fired appliances producing domestic hot water. It applies to both instantaneous and storage gas-fired appliances combined with electrical heat pump.

It applies to a package marketed as single unit or fully specified by a manufacturer that have:

- a gas heat input not exceeding 70 kW;
- a hot water storage capacity not exceeding 500 l.

Standard EN 13203-1 sets out in qualitative and quantitative terms the performance in delivery of domestic hot water for a selected variety of uses. It also gives a system for presenting the information to the user. This Part 5 sets out a method for assessing the energy performance of gas fired appliances combined with heat pump with electrically driven compressor according to EN 16147.

This European standard does not apply for gas boilers with recovery systems using combustion products as heat source for the electrical heat pump.

When the electrical heat pump does not work for domestic hot water production in the summer period, the present standard is not applicable for energy performances assessing, EN 13203-2 should be used.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13203-1, *Gas-fired domestic appliances producing hot water - Appliances not exceeding 70 kW heat input and 300 l water storage capacity - Part 1: Assessment of performance of hot water deliveries*

<https://standards.iteh.ai/catalog/standards/sist/355d6071-f62f-41dd-903e->

EN 13203-2, *Gas-fired domestic appliances producing hot water - Appliances not exceeding 70 kW heat input and 300 l water storage capacity - Part 2: Assessment of energy consumption*

EN 14511-3:2013, *Air conditioners, liquid chilling packages and heat pumps with electrically driven compressors for space heating and cooling - Part 3: Test methods*

EN 16147, *Heat pumps with electrically driven compressors – Testing and requirements for marking for domestic hot water units*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

control cycle

time cycle for keeping components and/or the tank (if any) of the domestic hot water circuit at predetermined temperature level, consists of an «ON» duration time during which the heating of the domestic hot water (by gas energy and/or auxiliary energy) is operating, and an «OFF» duration time during which no heating occurs

3.2

domestic water test temperature

temperature of the delivered water at which the tests are conducted

FprEN 13203-5:2015 (E)

- 3.3
nominal domestic hot water heat input**
 Q_{nw}
value of the heat input as stated by the technical instructions for the production of domestic hot water
- Note 1 to entry: Q_{nw} is expressed in kilowatt (kW)
- 3.4
off mode**
state of an appliance, selected by the user, in which domestic hot water can not be provided
- 3.5
stand-by mode**
operating state in which the appliance can provide domestic hot water at any time
- Note 1 to entry: In the case of an appliance with a control cycle for keeping components and/or the tank (if any) of the domestic hot water circuit at predetermined temperature level, no tapping is made
- 3.6
summer mode**
conditions during which the appliance supplies energy only for the production of domestic hot water
- 3.7
storage tank**
reservoir for domestic hot water
- 3.8
useful water**
quantity of water delivered at the tap for which the temperature increase is in accordance with the requirement fixed for each individual delivery of the tapping cycles
- 3.9
wasted water**
quantity of water delivered at the tap for which the temperature increase is not in accordance with the requirement fixed for each individual delivery of the tapping cycles
- 3.10
winter mode**
conditions during which the appliance supplies energy for the production of domestic hot water and/or space heating
- 3.11
indoor ambient air**
heat source for a heat pump which absorbs heat by a heat exchanger in direct contact with the air inside a building without any dedicated duct
- 3.12
brine**
heat transfer medium which has a freezing point depressed relative to water

3.13**gas-fired appliance combined with electrical heat pump**

appliance which is either placed on the market or specified as a complete package to deliver safely and effectively domestic hot water or domestic hot water and heating, comprising as relevant:

- electrical heat pump;
- gas-fired appliance;
- ducts if appropriate;
- thermal store

3.14**useful water flow rate**

flow rate of water delivered at the tap for which the temperature increase is in accordance with the requirement fixed for each individual delivery of the tapping cycles

3.15**useful water temperature**

water temperature, expressed in degrees Celsius, delivered at the tap

3.16**appliance flow rate**

flow rate delivered by the appliance before the mixing device, if applicable

3.17**appliance water temperature**

(T_a)

water temperature, expressed in degrees Celsius, delivered by the appliance before the mixing device

4 General test conditions**4.1 Reference conditions**

Unless otherwise stated, the general test conditions shall be as follows:

- cold water temperature: 10°C
 - maximum average variation over the test period: ± 2 K
- cold water pressure: $(2 \pm 0,1)$ bar
- ambient air temperature: 20°C
 - maximum average variation over the test period ± 1 K
 - maximum variation during the tests ± 2 K
- electrical supply voltage: (230 ± 2) V (single phase).

4.2 Specific heat source conditions

The tests shall be carried out at the test conditions specified in Table 1 as appropriate.

Table 1 - Test conditions for particular types of systems

Type of heat source	Heat source temperature (°C)	Range of ambient temperature for heat pump (°C)	Ambient temperature of storage tank (°C)
Outside air (heat pump indoor) with air duct	7 ± 0,2 (6 ± 0,3)	20 ± 3	20 ± 3
Outside air (heat pump outdoor)	7 ± 0,2 (6 ± 0,3)	7 ± 3 ^a	20 ± 3
Exhaust air	20 ± 0,2 (12 ± 0,3)	20 ± 3 ^a	20 ± 3 ^a
Water (inlet)	10 ± 0,15	20 ± 3	20 ± 3
Brine (inlet)	0 ± 0,15	20 ± 3	20 ± 3
Direct evaporation	4 ± 0,5	20 ± 3	20 ± 3
^a In this case the ambient temperature of the heat pump is the same as the temperature of the heat source (the difference with EN 16147 is justified because of the possible installation of the appliance into a living room).			
NOTE 1 All heat source temperatures are inlet temperatures in °C.			
NOTE 2 All air temperatures in (brackets) are wet bulb temperatures in °C.			
NOTE 3 Permissible external pressure difference and associated internal pressure difference at the outdoor heat exchanger as stated in the installation and/or operation manual in Pascal (Pa) for appliances with duct connection.			

4.3 Measurement uncertainties

Except where otherwise stated in the clauses describing the tests, the uncertainties of measurements carried out shall be not greater than the maximum uncertainties indicated below.

<https://standards.iteh.ai/catalog/standards/sist/355d6071-f62f-41dd-903e->

The standard deviations shall be evaluated taking account of the various sources of uncertainty: contribution from the instrument, repeatability, calibration, ambient conditions:

- water rate: ± 1 %;
- gas rate: ± 1 %;
- time: ± 0,2 s;
- temperatures:
 - ambient air: ± 1 K;
 - air as heat source dry bulb temperature: ± 0,2 °C;
 - air as heat source wet bulb temperature: ± 0,3 °C;
 - water/brine as heat source: ± 0,15 K
 - water: ± 0,5 K;
 - gas: ± 0,5 K;
- mass: ± 0,5 %;

- gas pressure: ± 1 %;
- gas calorific value: ± 1 %;
- gas density: $\pm 0,5$ %;
- electrical energy: ± 2 %.

The stated measurement uncertainties relate to individual measurements. For measurements that combine a number of individual measurements, smaller uncertainties on the individual measurements may be necessary to ensure a total uncertainty within ± 2 % under the steady-state conditions.

These uncertainties correspond to two standard deviations (2σ).

4.4 Test conditions

4.4.1 General

Except where otherwise stated, the appliance is tested under the following conditions.

The tests are carried out only in summer mode.

The test conditions are given in Table 1.

If liquid heat transfer media other than water are used, the specific heat capacity and density of such heat transfer media shall be determined and taken into consideration in the evaluation.

When the electric heat pump combined with a gas-fired appliance does not operate in heat pump mode for domestic hot water production according to data in Table 1, the test shall be performed according to EN 13203-2 instead.

For all tests defined by this standard, the same adjustment of the appliance shall be maintained.

4.4.2 Test room

The package shall be installed in a well-ventilated, draught-free room (air speed less than 0,5 m/s).

The package shall be protected from direct solar radiation and radiation from heat generators.

If the package incorporates an air source outdoor heat exchanger a further test room is needed. The size of this test room shall be designed to avoid any resistance to air flow at the air inlet and air outlet orifices of the test object. The air flow through this room shall not cause any short circuit between the two orifices, and therefore the velocity of air flow at these two locations shall not exceed 1,5 m/s when the test object is switched off. The air velocity in the room shall also not be greater than the mean velocity through the unit inlet.

Unless otherwise stated in the technical documentation, the air inlet and air outlet orifices shall not be less than 1m from the surfaces of the test room; this also applies to any measuring ducts.

The setting of the external static pressure difference on the air side for heat pumps with duct connection is described by 4.4.1.4 of EN 14511-3:2013.

For heat pumps separated from the tank, the liquid flow rate has to be set on the liquid outlet side of the heat pump to the nominal flow rate specified in the technical documentation.

The package shall be installed and connected for the test as specified in the installation instructions.

Temperature and pressure measuring points shall be situated in order to obtain significant mean values.

FprEN 13203-5:2015 (E)

Set points for internal control equipment of the unit such as thermostats, pressure switches or mixing valves shall be set to the values stated in the technical documentation.

Air and entrained gases shall be removed from all water and other heat transfer liquid systems

In the case of package incorporating a single split heat pump, the following installation conditions shall be complied with for the tests:

- a) each refrigerant pipe shall be installed in accordance with the installation instructions;
- b) the connecting pipes shall be installed so that the difference in elevation does not exceed 1 m. The length of each connecting pipe shall be between 5 m and 7,5 m;
- c) thermal insulation shall be applied to the pipes in accordance with the installation instructions;
- d) unless constrained by the design at least half of the interconnecting pipes shall be exposed to the outdoor conditions with the rest of the pipes exposed to the indoor conditions.

For indirect systems each water pipe shall be installed in accordance with the installation instructions to the maximum stated length or 5 m whichever is shorter. Thermal insulation shall be applied to the pipes in accordance with the installation instructions.

4.4.3 Water supply

For the tests:

- the domestic water pressure is the static inlet pressure under dynamic conditions measured as close as possible to the appliance;
- the inlet and outlet temperatures of the domestic water shall be measured in the centre of the flow and as close as possible to the appliance.

The inlet temperatures shall be measured immediately upstream of the water inlet connection. Except where otherwise stated, the outlet temperatures shall be measured immediately downstream of the outlet connection or, in the case of an appliance with spout delivery, by means of an immersed temperature measuring device, e.g. a u-tube fitted at the outlet of a tube of the same length as the minimum length of the spout normally supplied together with the appliance.

The hot water temperature shall be measured with a rapid response thermometer.

“Rapid response thermometer” means a measuring instrument with a response time such that 90 % of the final temperature rise, from 15 °C to 100 °C, is obtained within about 1 s, when the sensor is plunged into still water.

4.4.4 Steady-state

Steady-state operating conditions shall be regarded as established when the appliance operates for sufficient time to reach thermal stabilization. The steady-state is reached when the water temperature at the outlet does not vary by more than $\pm 0,5$ K.

NOTE This condition can be reached with a gas which is different from the specified test gas, provided that the appliance is supplied with the specified test gas for at least 5 min before the requirements are verified.

4.4.5 Initial adjustment of the appliance

The appliance shall be installed in accordance with the installation instructions.

The heat input shall be adjusted to within $\pm 2\%$ of the nominal domestic hot water heat input under the conditions prevailing at the time of the test.

The delivered water temperature at the appliance outlet shall be as follows (see Figures A.1 and A.2):

- a) appliances with an adjustable temperature: the tests are carried out at a temperature not greater than $65\text{ }^{\circ}\text{C}$, with a minimum temperature increase equal to or greater than 45 K above water inlet temperature;
- b) appliances with a fixed temperature: the tests are carried out at the temperature specified by the manufacturer, with a minimum temperature increase equal to or greater than 45 K .

The same conditions of initial adjustment stated in the appliance documentation shall be used for all the tests.

These conditions shall be included in the test report.

4.4.6 Electrical supply

The appliance shall be supplied with the nominal voltage or a voltage included within the range of nominal voltages stated in the installation instructions.

5 Determination of the energy consumption of the appliance

5.1 General

This clause defines the test methods to be employed in determining the energy consumption of appliances.

5.2 Tapping cycles

All patterns define a 24 h measurement cycle and within that cycle the starting times and the total energy content (in kWh equivalent of hot water tapped) of each draw-off are defined.

Furthermore, the draw-off can be characterized in two ways, either "basin" type draw-off versus "continuous flow" draw-off.

The aim of the "basin" type is to arrive at an average temperature of the tub, so all supplied energy can be considered useful from the very beginning of the draw-off (minimum useful temperature increase is 0 K). The average temperature rising (ΔT desired) to be achieved during tapping, shall be for floor cleaning and bath 30 K and for the dish washes 45 K .

The aim of the "continuous flow" type is to use only the water with a minimum temperature. For the shower, household cleaning and large draw-offs a temperature rise of 30 K shall be reached before counting the useful energy. For the small draw-offs a temperature rise of 15 K shall be reached.

NOTE 1 The temperature rises (in K) stated above are equivalent to the temperatures (in $^{\circ}\text{C}$) given by the load profiles tables in Regulations n $^{\circ}$ 811/2013, n $^{\circ}$ 812/2013, n $^{\circ}$ 813/2013 and n $^{\circ}$ 814/2013 based on $10\text{ }^{\circ}\text{C}$ inlet water temperature.

The tapping flow rates used to perform the different types of tapping of each of the seven tapping cycles defined by Tables 2 to 8.

When these tapping rates result in a tapping period of less than 15 s the flow rate should be decreased such that the tapping period is $(16 \pm 1)\text{ s}$.

In the tapping cycles, the requirements for flow and temperatures are based on the delivery on the taps in a mix of hot and cold water. Under the conditions of the initial adjustment, the appliance itself produces hot water with a minimum temperature rise of 45 K .

FprEN 13203-5:2015 (E)

To fulfil the requirements stated in Tables 2 to 8 mixing hot water from the appliance with cold water of 10°C at the tap is allowed either by using a mixing device (see Figure B.5) or by recalculating the minimum appliance flow rate (see 3.16) according to the following formula:

$$D_{\min} = D_{\text{useful}(\Delta T)} \cdot \frac{\Delta T_{\text{useful}}}{\Delta T_d} \tag{1}$$

Where:

- D_{\min} is the minimum test rig setting for the appliance flow rate of each individual tapping at temperature rise corresponding to ΔT_d , in l/min;
- $D_{\text{useful}(\Delta T)}$ is the useful water flow rate according to Tables 2 to 8, in l/min;
- ΔT_d is the appliance delivered water temperature rise with a minimum of 45 K, in K;
- ΔT_{useful} is the higher value between the temperature rise to be achieved and the minimum temperature rise for counting the useful energy according to Tables 2 to 8, in K.

The tests shall be performed by using the useful flow rates defined by Tables 2 to 8. If the appliance cannot deliver these flow rates, for instance due to the flow restrictor, it shall be checked that the requirements are fulfilled by checking that D_{\min} is delivered.

If by design the appliance is fitted with a flow restrictor, the tests shall be carried out with this flow restrictor.

Table 2 – Load profile S

Tapping n°	Start (h.min)	Energy (kWh)	Type of draw off	Useful water flow rate at the tap (l/min)	ΔT to be achieved during tapping ^a (K)	Minimum ΔT for counting useful energy (K)
1	07.00	0,105	Small	3		15
2	07.30	0,105	Small	3		15
3	08.30	0,105	Small	3		15
4	09.30	0,105	Small	3		15
5	11.30	0,105	Small	3		15
6	11.45	0,105	Small	3		15
7	12.45	0,315	Dish washing n°1	4	45	0
8	18.00	0,105	Small	3		15
9	18.15	0,105	Household cleaning	3		30
10	20.30	0,420	Dish washing n°2	4	45	0
11	21.30	0,525	Large	5		35
Q_{ref}		2,100				

^a On continuous basis.

Equivalent hot water litres at 60°C

36

Table 3 – Load profile M

Tapping n°	Start (h.min)	Energy (kWh)	Type of draw off	Useful water flow rate at the tap (l/min)	ΔT to be achieved during tapping ^a (K)	Minimum ΔT for counting useful energy (K)
1	07.00	0,105	Small	3		15
2	07.05	1,400	Shower n°1	6		30
3	07.30	0,105	Small	3		15
4	08.01	0,105	Small	3		15
5	08.15	0,105	Small	3		15
6	08.30	0,105	Small	3		15
7	08.45	0,105	Small	3		15
8	09.00	0,105	Small	3		15
9	09.30	0,105	Small	3		15
10	10.30	0,105	Floor cleaning	3	30	0
11	11.30	0,105	Small	3		15
12	11.45	0,105	Small	3		15
13	12.45	0,315	Dish washing n°1	4	45	0
14	14.30	0,105	Small	3		15
15	15.30	0,105	Small	3		15
16	16.30	0,105	Small	3		15
17	18.00	0,105	Small	3		15
18	18.15	0,105	Household cleaning	3		30
19	18.30	0,105	Household cleaning	3		30
20	19.00	0,105	Small	3		15
21	20.30	0,735	Dish washing n°3	4	45	0
22	21.15	0,105	Small	3		15
23	21.30	1,400	Shower n°1	6		30
Q_{ref}		5,845				

^a On continuous basis.

Equivalent hot water litres at 60°C

100,2