
**Tools for moulding — Ejector sleeves
with cylindrical head — Basic series
for general purposes**

*Outils de moulage — Éjecteurs tubulaires à tête cylindrique —
Série de base pour usages généraux*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 8405:2013](https://standards.iteh.ai/catalog/standards/sist/70b6df16-8333-4943-bded-22c18661b085/iso-8405-2013)

[https://standards.iteh.ai/catalog/standards/sist/70b6df16-8333-4943-bded-
22c18661b085/iso-8405-2013](https://standards.iteh.ai/catalog/standards/sist/70b6df16-8333-4943-bded-22c18661b085/iso-8405-2013)



iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 8405:2013](https://standards.iteh.ai/catalog/standards/sist/70b6df16-8333-4943-bded-22c18661b085/iso-8405-2013)

<https://standards.iteh.ai/catalog/standards/sist/70b6df16-8333-4943-bded-22c18661b085/iso-8405-2013>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: http://www.iso.org/iso/home/standards_development/resources-for-technical-work/foreword.htm (standards.iteh.ai)

The committee responsible for this document is ISO/TC 29, *Small tools*, Subcommittee SC 8, *Tools for pressing and moulding*. [ISO 8405:2013](https://standards.iteh.ai/catalog/standards/sist/70b6df16-8333-4943-bded-23186e3b0175/iso-8405-2013)

This third edition cancels and replaces the second edition (ISO 8405:1998), which has been technically revised.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 8405:2013](#)

<https://standards.iteh.ai/catalog/standards/sist/70b6df16-8333-4943-bded-22c18661b085/iso-8405-2013>

Tools for moulding — Ejector sleeves with cylindrical head — Basic series for general purposes

1 Scope

This International Standard specifies the dimensions and tolerances, in millimetres, of ejector sleeves with cylindrical head which are used in compression and injection moulds and in die casting dies.

It also gives material guidelines and hardness requirements, and specifies the designation of ejector sleeves with cylindrical head.


2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6751:2011, *Tools for moulding — Ejector pins with cylindrical head*

3 Dimensions

The dimensions of ejector sleeves with cylindrical head shall be in accordance with the indications of [Figure 1](#) and [Table 1](#).



Key

- a Ra 0,8 for hot worked steel. Ra 0,4 for alloyed cold worked steel.
- b $t = 0,012 \text{ mm } (L_1 \times 10^{-1})$.

Figure 1 — Ejector sleeves

Table 1 — Ejector sleeves

Dimensions in millimetres

D_1^a H5	D_2 g6	D_3	D_4 0 -0,2	L_1 +1 0	L +1 0									H^b 0 -0,05	R +0,2 0
					75	100	125	150	175	200	225	250	275		
2	4	2,5 +0,2 -0,1	8	35	X	X	X							3	0,3
2,5	5	3 +0,2 -0,1	10		X	X	X								
3				3,5 +0,2 -0,1		X	X	X	X						
4	8	4,5 +0,2 -0,1	14	45	X	X	X	X	X	X			5	0,5	
5					5,5 +0,3 -0,1	X	X	X	X	X	X				
6	10	6,5 +0,3 -0,1	16			X	X	X	X	X	X				
8	12	8,5 +0,3 -0,1	20			X	X	X	X	X	X	X			
10	14	10,5 +0,3 -0,1	22			X	X	X	X	X	X	X	7	0,8	
12	16	12,5 +0,3 -0,1					X	X	X	X	X	X			X

iTeh STANDARD PREVIEW (standards.itech.ai)

ISO 8405:2013

https://standards.itech.ai/catalog/standards/sist/70b6df16-8333-4943-bded-22c18661b085/iso-8405-2013

^a For repair, the following diameters are recommended: 2,2; 2,7; 3,2; 4,2; 5,2; 6,2; 8,2; 10,2; 12,5 (for $D_1 = 12,5$, $D_3 = 13$).

^b For shaft diameters, D_2 , larger than those given in Table 1, up to 32 mm, the ratio of head height and diameter shall be the same as for ejector pins given in ISO 6751.

4 Material and hardness

Ejector sleeves with cylindrical head shall be made of hot worked steel or alloyed cold worked steel. The hardness of the shaft and head, respectively, are given in Table 2.

Table 2 — Material and hardness

Material	Hardness ^a	
	Shaft	Head
Hot worked steel	min. 1 400 MPa core strength min. 950 HV 0,3	(45 ± 5) HRC hot-forged
Alloyed cold worked steel	(60 ± 2) HRC	

^a The point at which hardness is measured is left to the manufacturer's discretion.

5 Designation

Ejector sleeves with cylindrical head according to this International Standard shall be designated by the following:

- a) “Ejector sleeve with cylindrical head”;
- b) a reference to this International Standard (i.e. ISO 8405:2013);
- c) the diameter, D_1 , in millimetres;
- d) the length, L , in millimetres;
- e) the material.

EXAMPLE An ejector sleeve with cylindrical head with diameter $D_1 = 2$ mm, length $L = 75$ mm, and made of hot worked steel is designated as follows:

Ejector sleeve with cylindrical head ISO 8405 - 2 - 75 - Hot worked steel

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 8405:2013](https://standards.iteh.ai/catalog/standards/sist/70b6df16-8333-4943-bded-22c18661b085/iso-8405-2013)

<https://standards.iteh.ai/catalog/standards/sist/70b6df16-8333-4943-bded-22c18661b085/iso-8405-2013>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 8405:2013](https://standards.iteh.ai/catalog/standards/sist/70b6df16-8333-4943-bded-22c18661b085/iso-8405-2013)

<https://standards.iteh.ai/catalog/standards/sist/70b6df16-8333-4943-bded-22c18661b085/iso-8405-2013>