



**Universal Mobile Telecommunications System (UMTS);
LTE;
5G;
Characteristics of the Universal Subscriber
Identity Module (USIM) application
(3GPP TS 31.102 version 15.10.0 Release 15)**



ReferenceRTS/TSGC-0631102vfa0

Keywords

5G,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	12
Introduction	13
1 Scope	14
2 References	14
3 Definitions, symbols, abbreviations and coding conventions	18
3.1 Definitions	18
3.2 Symbols.....	19
3.3 Abbreviations	19
3.4 Coding Conventions.....	21
4 Contents of the Files.....	21
4.1 Contents of the EFs at the MF level	21
4.2 Contents of files at the USIM ADF (Application DF) level.....	22
4.2.1 EF _{LI} (Language Indication).....	22
4.2.2 EF _{IMSI} (IMSI)	23
4.2.3 EF _{Keys} (Ciphering and Integrity Keys)	24
4.2.4 EF _{KeysPS} (Ciphering and Integrity Keys for Packet Switched domain)	24
4.2.5 EF _{PLMNwAcT} (User controlled PLMN selector with Access Technology)	25
4.2.6 EF _{HPLMN} (Higher Priority PLMN search period)	26
4.2.7 EF _{ACMmax} (ACM maximum value).....	27
4.2.8 EF _{UST} (USIM Service Table)	29
4.2.9 EF _{ACM} (Accumulated Call Meter).....	32
4.2.10 EF _{GID1} (Group Identifier Level 1)	33
4.2.11 EF _{GID2} (Group Identifier Level 2)	33
4.2.12 EF _{SPN} (Service Provider Name)	34
4.2.13 EF _{PUCT} (Price per Unit and Currency Table).....	35
4.2.14 EF _{CBMI} (Cell Broadcast Message identifier selection)	36
4.2.15 EF _{ACC} (Access Control Class).....	36
4.2.16 EF _{FPLMN} (Forbidden PLMNs)	37
4.2.17 EF _{LOCI} (Location Information).....	37
4.2.18 EF _{AD} (Administrative Data).....	38
4.2.19 Void	40
4.2.20 EF _{CBMID} (Cell Broadcast Message Identifier for Data Download).....	40
4.2.21 EF _{ECC} (Emergency Call Codes)	41
4.2.22 EF _{CBMIR} (Cell Broadcast Message Identifier Range selection)	42
4.2.23 EF _{PSLOCI} (Packet Switched location information)	43
4.2.24 EF _{FDN} (Fixed Dialling Numbers)	44
4.2.25 EF _{SMS} (Short messages)	44
4.2.26 EF _{MSISDN} (MSISDN)	46
4.2.27 EF _{SMSP} (Short message service parameters).....	46
4.2.28 EF _{SMSS} (SMS status)	48
4.2.29 EF _{SDN} (Service Dialling Numbers).....	48
4.2.30 EF _{EXT2} (Extension2).....	49
4.2.31 EF _{EXT3} (Extension3).....	49
4.2.32 EF _{SMSR} (Short message status reports).....	50
4.2.33 EF _{ICI} (Incoming Call Information).....	50
4.2.34 EF _{OCI} (Outgoing Call Information).....	54
4.2.35 EF _{ICT} (Incoming Call Timer)	55
4.2.36 EF _{OCT} (Outgoing Call Timer)	55
4.2.37 EF _{EXT5} (Extension5).....	56
4.2.38 EF _{CCP2} (Capability Configuration Parameters 2)	56

4.2.39	EF _{eMLPP} (enhanced Multi Level Precedence and Pre-emption).....	57
4.2.40	EF _{AaeM} (Automatic Answer for eMLPP Service).....	58
4.2.41	Void	59
4.2.42	EF _{Hiddenkey} (Key for hidden phone book entries)	59
4.2.43	Void	59
4.2.44	EF _{BDN} (Barred Dialling Numbers)	59
4.2.45	EF _{EXT4} (Extension4).....	60
4.2.46	EF _{CMi} (Comparison Method Information)	60
4.2.47	EF _{EST} (Enabled Services Table).....	61
4.2.48	EF _{ACL} (Access Point Name Control List)	62
4.2.49	EF _{DCK} (Depersonalisation Control Keys)	62
4.2.50	EF _{CNL} (Co-operative Network List).....	63
4.2.51	EF _{START-HFN} (Initialisation values for Hyperframe number).....	64
4.2.52	EF _{THRESHOLD} (Maximum value of START).....	65
4.2.53	EF _{OPLMNwACT} (Operator controlled PLMN selector with Access Technology)	65
4.2.54	EF _{HPLMNwACT} (HPLMN selector with Access Technology)	66
4.2.55	EF _{ARR} (Access Rule Reference).....	67
4.2.56	Void	68
4.2.57	EF _{NETPAR} (Network Parameters)	68
4.2.58	EF _{PNN} (PLMN Network Name)	70
4.2.59	EF _{OPL} (Operator PLMN List).....	71
4.2.60	EF _{MBDN} (Mailbox Dialling Numbers)	72
4.2.61	EF _{EXT6} (Extension6).....	73
4.2.62	EF _{MBI} (Mailbox Identifier).....	73
4.2.63	EF _{MWIS} (Message Waiting Indication Status)	74
4.2.64	EF _{CFIS} (Call Forwarding Indication Status)	76
4.2.65	EF _{EXT7} (Extension7).....	77
4.2.66	EF _{SPDI} (Service Provider Display Information)	77
4.2.67	EF _{MMSN} (MMS Notification)	78
4.2.68	EF _{EXT8} (Extension 8)	80
4.2.69	EF _{MMSICP} (MMS Issuer Connectivity Parameters)	80
4.2.70	EF _{MMSUP} (MMS User Preferences)	83
4.2.71	EF _{MMSUCP} (MMS User Connectivity Parameters)	84
4.2.72	EF _{NIA} (Network's Indication of Alerting).....	84
4.2.73	EF _{VGCS} (Voice Group Call Service).....	85
4.2.74	EF _{VGCS} (Voice Group Call Service Status).....	87
4.2.75	EF _{VBS} (Voice Broadcast Service).....	88
4.2.76	EF _{VBS} (Voice Broadcast Service Status).....	89
4.2.77	EF _{VGSCA} (Voice Group Call Service Ciphering Algorithm)	90
4.2.78	EF _{VBSA} (Voice Broadcast Service Ciphering Algorithm).....	91
4.2.79	EF _{GBABP} (GBA Bootstrapping parameters).....	91
4.2.80	EF _{MSK} (MBMS Service Keys List)	92
4.2.81	EF _{MUK} (MBMS User Key).....	93
4.2.82	Void	95
4.2.83	EF _{GBANL} (GBA NAF List).....	95
4.2.84	EF _{EHPLMN} (Equivalent HPLMN)	96
4.2.85	EF _{EHPLMNPi} (Equivalent HPLMN Presentation Indication)	96
4.2.86	EF _{LRPLMNSI} (Last RPLMN Selection Indication).....	97
4.2.87	EF _{NAFKCA} (NAF Key Centre Address)	97
4.2.88	EF _{SPNI} (Service Provider Name Icon)	98
4.2.89	EF _{PNNI} (PLMN Network Name Icon)	99
4.2.90	EF _{NCP-IP} (Network Connectivity Parameters for USIM IP connections).....	99
4.2.91	EF _{EPSLOCI} (EPS location information)	102
4.2.92	EF _{EPSNSC} (EPS NAS Security Context).....	104
4.2.93	EF _{UFC} (USAT Facility Control).....	106
4.2.94	EF _{NASCONFIG} (Non Access Stratum Configuration)	107
4.2.95	EF _{UICCIARI} (UICC IARI).....	112
4.2.96	EF _{PWS} (Public Warning System).....	113
4.2.97	EF _{FDNURI} (Fixed Dialling Numbers URI).....	113
4.2.98	EF _{BDNURI} (Barred Dialling Numbers URI).....	114
4.2.99	EF _{SDNURI} (Service Dialling Numbers URI).....	115

4.2.100	EF _{IWL} (IMEI(SV) White Lists)	116
4.2.101	EF _{IPS} (IMEI(SV) Pairing Status).....	117
4.2.102	EF _{IPD} (IMEI(SV) of Pairing Device)	117
4.2.103	EF _{ePDGId} (Home ePDG Identifier).....	119
4.2.104	EF _{ePDGSelection} (ePDG Selection Information).....	120
4.2.104a	EF _{ePDGIdEm} (Emergency ePDG Identifier)	121
4.2.105	EF _{ePDGSelectionEm} (ePDG Selection Information for Emergency Services).....	122
4.2.106	EF _{FromPreferred} (From Preferred)	122
4.2.107	EF _{IMSCConfigData} (IMS Configuration Data)	123
4.2.108	EF _{TVCONFIG} (TV Configuration)	123
4.2.109	EF _{3GPPPSDATAOFF} (3GPP PS Data Off)	125
4.2.110	EF _{3GPPPSDATAOFFServiceList} (3GPP PS Data Off Service List).....	126
4.2.111	EF _{XCAPConfigData} (XCAP Configuration Data).....	127
4.2.112	EF _{EARFCNList} (EARFCN list for MTC/NB-IOT UEs).....	127
4.3	DFs at the USIM ADF (Application DF) Level	128
4.4	Contents of DFs at the USIM ADF (Application DF) level	129
4.4.1	Contents of files at the DF SoLSA level	129
4.4.1.1	EF _{SAI} (SoLSA Access Indicator).....	129
4.4.1.2	EF _{SLL} (SoLSA LSA List).....	130
4.4.1.3	LSA Descriptor files	132
4.4.2	Contents of files at the DF PHONEBOOK level	133
4.4.2.1	EF _{PBR} (Phone Book Reference file)	134
4.4.2.2	EF _{IAP} (Index Administration Phone book).....	136
4.4.2.3	EF _{ADN} (Abbreviated dialling numbers)	136
4.4.2.4	EF _{EXT1} (Extension1)	139
4.4.2.5	EF _{PBC} (Phone Book Control).....	141
4.4.2.6	EF _{GRP} (Grouping file).....	142
4.4.2.7	EF _{AAS} (Additional number Alpha String).....	142
4.4.2.8	EF _{GAS} (Grouping information Alpha String).....	143
4.4.2.9	EF _{ANR} (Additional Number).....	143
4.4.2.10	EF _{SNE} (Second Name Entry).....	145
4.4.2.11	EF _{CCP1} (Capability Configuration Parameters 1).....	146
4.4.2.12	Phone Book Synchronisation	146
4.4.2.12.1	EF _{UID} (Unique Identifier).....	146
4.4.2.12.2	EF _{PSC} (Phone book Synchronisation Counter).....	147
4.4.2.12.3	EF _{CC} (Change Counter)	148
4.4.2.12.4	EF _{PUID} (Previous Unique Identifier)	149
4.4.2.13	EF _{EMAIL} (e-mail address).....	149
4.4.2.14	Phonebook restrictions	150
4.4.2.15	EF _{PURI} (Phonebook URIs)	150
4.4.3	Contents of files at the DF GSM-ACCESS level (Files required for GSM Access).....	151
4.4.3.1	EF _{Kc} (GSM Ciphering key Kc)	152
4.4.3.2	EF _{KcGPRS} (GPRS Ciphering key KcGPRS).....	152
4.4.3.3	Void.....	153
4.4.3.4	EF _{CPBCCCH} (CPBCCCH Information)	153
4.4.3.5	EF _{InvScan} (Investigation Scan)	154
4.4.4	Contents of files at the MexE level	155
4.4.4.1	EF _{MexE-ST} (MexE Service table)	155
4.4.4.2	EF _{ORPK} (Operator Root Public Key)	155
4.4.4.3	EF _{ARPK} (Administrator Root Public Key).....	157
4.4.4.4	EF _{TPRPK} (Third Party Root Public Key).....	158
4.4.4.5	EF _{TKCDF} (Trusted Key/Certificates Data Files).....	159
4.4.5	Contents of files at the DF WLAN level.....	159
4.4.5.1	EF _{Pseudo} (Pseudonym)	159
4.4.5.2	EF _{UPLMNWLAN} (User controlled PLMN selector for I-WLAN Access)	160
4.4.5.3	EF _{OPLMNWLAN} (Operator controlled PLMN selector for I-WLAN Access)	161
4.4.5.4	EF _{UWSIDL} (User controlled WLAN Specific Identifier List).....	161
4.4.5.5	EF _{OWSIDL} (Operator controlled WLAN Specific IdentifierList)	162
4.4.5.6	EF _{WRI} (WLAN Reauthentication Identity).....	162
4.4.5.7	EF _{HWSIDL} (Home I-WLAN Specific Identifier List).....	163
4.4.5.8	EF _{WEHPLMNPI} (I-WLAN Equivalent HPLMN Presentation Indication).....	164
4.4.5.9	EF _{WHPI} (I-WLAN HPLMN Priority Indication).....	164

4.4.5.10	EF _{WLRPLMN} (I-WLAN Last Registered PLMN).....	165
4.4.5.11	EF _{HPLMNDAI} (HPLMN Direct Access Indicator)	165
4.4.6	Contents of files at the DF HNB level	166
4.4.6.1	Introduction.....	166
4.4.6.2	EF _{ACSGL} (Allowed CSG Lists).....	166
4.4.6.3	EF _{CSGT} (CSG Type).....	169
4.4.6.4	EF _{HNB} (Home NodeB Name)	170
4.4.6.5	EF _{OCSGL} (Operator CSG Lists)	171
4.4.6.6	EF _{OCSGT} (Operator CSG Type).....	173
4.4.6.7	EF _{OHNB} (Operator Home NodeB Name).....	174
4.4.7	Void	174
4.4.8	Contents of files at the DF ProSe level	174
4.4.8.1	Introduction.....	174
4.4.8.2	EF _{PROSE_MON} (ProSe Monitoring Parameters).....	174
4.4.8.3	EF _{PROSE_ANN} (ProSe Announcing Parameters).....	175
4.4.8.4	EF _{PROSEFUNC} (HPLMN ProSe Function).....	177
4.4.8.5	EF _{PROSE_RADIO_COM} (ProSe Direct Communication Radio Parameters)	177
4.4.8.6	EF _{PROSE_RADIO_MON} (ProSe Direct Discovery Monitoring Radio Parameters).....	179
4.4.8.7	EF _{PROSE_RADIO_ANN} (ProSe Direct Discovery Announcing Radio Parameters)	181
4.4.8.8	EF _{PROSE_POLICY} (ProSe Policy Parameters)	182
4.4.8.9	EF _{PROSE_PLMN} (ProSe PLMN Parameters).....	184
4.4.8.10	EF _{PROSE_GC} (ProSe Group Counter)	185
4.4.8.11	EF _{PST} (ProSe Service Table)	187
4.4.8.12	EF _{PROSE_UIRC} (ProSe UsageInformationReportingConfiguration).....	187
4.4.8.12	EF _{PROSE_GM_DISCOVERY} (ProSe Group Member Discovery Parameters).....	191
4.4.8.13	EF _{PROSE_RELAY} (ProSe Relay Parameters).....	192
4.4.8.14	EF _{PROSE_RELAY_DISCOVERY} (ProSe Relay Discovery Parameters).....	193
4.4.9	Contents of files at the DF ACDC level	196
4.4.9.1	Introduction.....	196
4.4.9.2	EF _{ACDC_LIST} (ACDC List)	196
4.4.9.3	EF _{ACDC_OS_CONFIG} (ACDC OS configuration).....	197
4.4.10	Contents of files at the DF TV level	198
4.4.10.1	Introduction.....	198
4.4.10.2	EF _{TVUSD} (TV User Service Description)	198
4.4.11	Contents of files at the DF _{5GS} level.....	199
4.4.11.1	Introduction.....	199
4.4.11.2	EF _{5GS3GPPLOC} (5GS 3GPP location information).....	199
4.4.11.3	EF _{5GSN3GPPLOC} (5GS non-3GPP location information).....	201
4.4.11.4	EF _{5GS3GPPNSC} (5GS 3GPP Access NAS Security Context)	201
4.4.11.5	EF _{5GSN3GPPNSC} (5GS non-3GPP Access NAS Security Context)	204
4.4.11.6	EF _{5GAUTHKEYS} (5G authentication keys).....	205
4.4.11.7	EF _{UAC_AIC} (UAC Access Identities Configuration)	206
4.4.11.8	EF _{SUCI_Calc_Info} (Subscription Concealed Identifier Calculation Information EF)	207
4.4.11.9	EF _{OPL5G} (5GS Operator PLMN List).....	208
4.4.11.10	EF _{NSI} (Network Specific Identifier).....	209
4.4.11.11	EF _{Routing_Indicator} (Routing Indicator EF).....	209
4.5	Contents of Efs at the TELECOM level.....	210
4.5.1	EF _{ADN} (Abbreviated dialling numbers).....	210
4.5.2	EF _{EXT1} (Extension1).....	210
4.5.3	EF _{ECCP} (Extended Capability Configuration Parameter).....	210
4.5.4	EF _{SUME} (SetUpMenu Elements).....	210
4.5.5	EF _{FARR} (Access Rule Reference).....	211
4.5.6	EF _{ICE_DN} (In Case of Emergency – Dialling Number)	211
4.5.7	EF _{ICE_FF} (In Case of Emergency – Free Format).....	211
4.5.8	EF _{RM} (Remote Management Actions).....	212
4.5.9	EF _{PSISMSC} (Public Service Identity of the SM-SC).....	213
4.6	Contents of DFs at the TELECOM level.....	213
4.6.0	List of DFs at the TELECOM level.....	213
4.6.1	Contents of files at the DF _{GRAPHICS} level.....	213
4.6.1.1	EF _{IMG} (Image)	213
4.6.1.2	EF _{IIDF} (Image Instance Data Files).....	215

4.6.1.3	EF _{ICE_graphics} (In Case of Emergency – Graphics).....	215
4.6.1.4	Void.....	216
4.6.1.5	Void.....	216
4.6.2	Contents of files at the DF _{PHONEBOOK} under the DF _{TELECOM}	216
4.6.3	Contents of files at the DF _{MULTIMEDIA} level.....	216
4.6.3.1	EF _{MML} (Multimedia Messages List).....	216
4.6.3.2	EF _{MMDf} (Multimedia Messages Data File).....	219
4.6.4	Contents of files at the DF _{MCS} level	220
4.6.4.1	EF _{MST} (MCS Service Table).....	220
4.6.4.2	EF _{MCS_CONFIG} (MCS configuration data).....	220
4.6.4.3	Void.....	221
4.6.4.4	Void.....	221
4.6.4.5	Void.....	222
4.6.5	Contents of files at the DF _{V2X} level	222
4.6.5.1	V2X configuration data related files	222
4.6.5.2	EF _{VST} (V2X Service Table).....	222
4.6.5.3	EF _{V2X_CONFIG} (V2X configuration data).....	222
4.7	Files of USIM.....	224
5	Application protocol.....	231
5.1	USIM management procedures	231
5.1.1	Initialisation	231
5.1.1.1	USIM application selection.....	231
5.1.1.2	USIM initialisation.....	231
5.1.1.3	GSM related initialisation procedures.....	232
5.1.2	Session termination.....	233
5.1.2.1	3G session termination	233
5.1.2.1.1	GSM termination procedures.....	233
5.1.2.2	3G session reset.....	233
5.1.3	USIM application closure	233
5.1.4	Emergency call codes	233
5.1.5	Language indication.....	234
5.1.6	Administrative information request	234
5.1.7	USIM service table request.....	234
5.1.8	Void	234
5.1.9	UICC presence detection	234
5.1.10	UICC interface in PSM.....	234
5.1.11	UICC interface during eDRX	235
5.1.12	UICC interface during MICO.....	235
5.2	USIM security related procedures	236
5.2.1	Authentication algorithms computation.....	236
5.2.2	IMSI request	236
5.2.3	Access control information request	236
5.2.4	Higher Priority PLMN search period request	236
5.2.5	Location information	236
5.2.6	Cipher and Integrity key	236
5.2.7	Forbidden PLMN.....	236
5.2.8	Void	236
5.2.9	User Identity Request.....	236
5.2.10	GSM Cipher key.....	236
5.2.11	GPRS Cipher key.....	237
5.2.12	Initialisation value for Hyperframe number.....	237
5.2.13	Maximum value of START	237
5.2.14	HPLMN selector with Access Technology request	237
5.2.15	Packet Switched Location information	237
5.2.16	Cipher and Integrity key for Packet Switched domain	237
5.2.17	LSA information.....	237
5.2.18	Voice Group Call Services	237
5.2.19	Voice Broadcast Services	237
5.2.20	Generic Bootstrapping architecture (Bootstrap)	238
5.2.21	Generic Bootstrapping architecture (NAF Derivation).....	238
5.2.22	MSK MIKEY Message Reception.....	238

5.2.23	MTK MIKEY Message Reception	238
5.2.24	Void	238
5.2.25	EHPLMN request	238
5.2.26	Last RPLMN Selection Indication request	238
5.2.29	Non Access Stratum Configuration	239
5.2.30	PWS Configuration.....	239
5.2.33	NSI request	239
5.3	Subscription related procedures	239
5.3.1	Phone book procedures	239
5.3.1.1	Initialisation	239
5.3.1.2	Creation/Deletion of information	239
5.3.1.3	Hidden phone book entries.....	240
5.3.2	Dialling numbers	240
5.3.3	Short messages.....	242
5.3.4	Advice of charge.....	242
5.3.5	Capability configuration parameters	242
5.3.6	User controlled PLMN selector with Access Technology	243
5.3.7	Cell broadcast message identifier	243
5.3.8	Group identifier level 1	243
5.3.9	Group identifier level 2	243
5.3.10	Service provider name	243
5.3.11	Enhanced multi level precedence and pre-emption service	243
5.3.12	Cell broadcast message identifier ranges	243
5.3.13	Short message status report.....	243
5.3.14	APN Control List	244
5.3.15	Depersonalisation Control Keys	244
5.3.16	Co-operative Network List	244
5.3.17	CPBCCCH information.....	245
5.3.18	Investigation Scan.....	245
5.3.19	Enabled Services Table Request.....	245
5.3.20	Operator controlled PLMN selector with Access Technology	245
5.3.21	HPLMN selector with Access Technology.....	245
5.3.22	Automatic Answer on eMLPP service.....	245
5.3.23	Network Parameter information	245
5.3.24	PLMN network name.....	245
5.3.25	Operator PLMN List.....	245
5.3.26	Message Waiting Indication	246
5.3.27	Call Forwarding Indication Status	246
5.3.28	Service Provider Display Information	246
5.3.29	MMS Notifications	246
5.3.30	MMS Issuer Connectivity Parameters	247
5.3.31	MMS User Preferences	247
5.3.32	MMS User Connectivity Parameters	247
5.3.33	Network's indication of alerting.....	247
5.3.34	Multimedia Messages Storage	247
5.3.35	Equivalent HPLMN Presentation Indication request.....	247
5.3.36	NAF Key Centre Address request.....	248
5.3.37	Service provider name Icon	248
5.3.38	PLMN network name Icon	248
5.3.39	ICE Information request	248
5.3.40	eCall Related Procedures	248
5.3.40.1	eCall Only support	248
5.3.40.2	eCall and Normal call support.....	249
5.3.40.3	Change of eCall mode.....	249
5.3.41	SM-over-IP	249
5.3.42	UICC access to IMS	249
5.3.43	TV Configuration.....	250
5.3.44	3GPP PS Data Off related procedures	250
5.3.45	3GPP PS Data Off service list related procedures	250
5.3.46	EARFCN list for MTC/NB-IOT UEs	250
5.3.47	SUCI Calculation information procedure	250
5.3.48	SUCI Calculation by the USIM procedure	250

5.3.49	Control plane-based Steering of Roaming related procedures	251
5.3.50	5GS Operator PLMN List.....	251
5.3.51	Routing Indicator procedure for ME.....	251
5.4	USAT related procedures	251
5.4.1	Data Download via SMS-PP.....	251
5.4.2	Image Request	251
5.4.3	Data Download via SMS-CB.....	251
5.4.4	Call Control by USIM.....	251
5.4.5	MO-SMS control by USIM	251
5.4.6	Data Download via USSD and USSD application mode.....	252
5.4.7	Additional TERMINAL PROFILE after UICC activation	252
5.4.8	Terminal Applications	252
5.4.9	Call control on EPS PDN connection by USIM	252
5.4.10	Communication Control for IMS by USIM	252
5.4.11	USAT Facility Control.....	252
5.4.12	Extended Terminal Applications	252
5.4.13	USAT application pairing procedure	252
5.4.14	Call control on PDU Session by USIM	253
5.5	MexE related procedures.....	253
5.5.1	MexE ST.....	253
5.5.2	Operator root public key	253
5.5.3	Administrator root public key	253
5.5.4	Third Party root public key(s).....	253
5.5.5	Trusted Key/Certificates Data Files.....	254
5.6	WLAN related procedures.....	254
5.6.1	WLAN Selection related Procedures	254
5.6.2	WLAN PLMN Selection related procedures	254
5.6.3	WLAN access authentication related procedures	254
5.6.4	WLAN access re-authentication related procedures	254
5.7	Network Connectivity Parameters for UICC IP connections related procedures	254
5.8	H(e)NB related procedures.....	255
5.8.1	CSG Access Control procedures.....	255
5.8.2	CSG Type related procedures	255
5.8.3	HNB name display related procedures.....	255
5.9	ProSe related procedures.....	256
5.9.1	ProSe Direct Discovery Provisioning parameters.....	256
5.9.2	HPLMN ProSe Function address	256
5.9.3	ProSe direct communication related Procedures.....	256
5.9.4	ProSe direct discovery related Procedures.....	256
5.9.5	ProSe direct communication related Procedures.....	256
5.9.6	ProSe direct communication related Procedures.....	257
5.9.7	ProSe Group Counter related Procedures	257
5.9.8	ProSe Usage Information Reporting Configuration related Procedures	257
5.9.9	ProSe Group Member Discovery related Procedures	257
5.9.10	ProSe Relay related Procedures	257
5.10	ePDG Selection related procedures	257
5.10.1	Home ePDG Identifier	257
5.10.2	ePDG Selection Information.....	258
5.10.3	ePDG configuration information configured but empty	258
5.11	ACDC related procedures	258
5.11.1	ACDC Configuration.....	258
5.12	MCS related procedures	258
5.12.1	MCS configuration	258
5.12.2	Void	258
5.12.3	Void	258
5.12.4	Void	258
5.13	ePDG Selection for Emergency Services related procedures	258
5.13.1	Emergency ePDG Identifier.....	258
5.13.2	ePDG Selection Information for Emergency Services.....	259
5.13.3	ePDG configuration information for Emergency Services configured but empty	259
5.13.4	From Preferred related procedures.....	259
5.13.5	IMS Configuration Data related procedures	259

5.13.6	XCAP Configuration Data related procedures.....	259
5.14	V2X related procedures.....	259
5.14.1	V2X configuration	259
5.15	UAC Access Identities related procedures	260
5.15.1	UAC Access Identities Configuration.....	260
6	Security features.....	260
6.1	Authentication and key agreement procedure	260
6.2	Cryptographic Functions	260
6.3	GSM Conversion Functions	261
6.4	User verification and file access conditions	261
7	USIM Commands.....	261
7.1	AUTHENTICATE	261
7.1.1	Command description	261
7.1.1.1	3G security context	262
7.1.1.2	GSM security context.....	263
7.1.1.3	VGCS/VBS security context.....	263
7.1.1.4	GBA security context (Bootstrapping Mode)	263
7.1.1.5	GBA security context (NAF Derivation Mode)	264
7.1.1.6	MBMS security context (MSK Update Mode)	265
7.1.1.7	Void.....	266
7.1.1.8	MBMS security context (MTK Generation Mode).....	266
7.1.1.9	MBMS security context (MSK Deletion Mode).....	267
7.1.1.10	MBMS security context (MUK Deletion Mode).....	267
7.1.1.11	Local Key Establishment security context (Key Derivation mode).....	268
7.1.1.12	Local Key Establishment security context (Key Availability Check mode).....	268
7.1.2	Command parameters and data	269
7.1.2.1	GSM/3G security context.....	270
7.1.2.2	VGCS/VBS security context.....	271
7.1.2.3	GBA security context (Bootstrapping Mode)	272
7.1.2.4	GBA security context (NAF Derivation Mode).....	272
7.1.2.5	MBMS security context (All Modes).....	273
7.1.2.6	Local Key Establishment security context (All Modes).....	274
7.1.2.6.1	Local Key Establishment security context (Key Derivation mode).....	274
7.1.2.6.2	Local Key Establishment security context (Key Availability Check mode)	276
7.2	Void.....	277
7.3	Status Conditions Returned by the USIM	277
7.3.1	Security management.....	277
7.3.2	Status Words of the Commands.....	278
7.4	Optional commands.....	279
7.5	GET IDENTITY	279
7.5.1	Command description	279
7.5.1.1	SUCI context.....	279
7.5.2	Command parameters and data	280
7.5.2.1	SUCI context.....	281
8	Void.....	282
Annex A (informative):	EF changes via Data Download or USAT applications	283
Annex B (normative):	Image Coding Schemes.....	288
B.1	Basic Image Coding Scheme.....	288
B.2	Colour Image Coding Scheme	289
B.3	Colour Image Coding Scheme with Transparency.....	290
Annex C (informative):	Structure of the Network parameters TLV objects.....	291
Annex D (informative):	Tags defined in 31.102	292
Annex E (informative):	Suggested contents of the EFs at pre-personalization	298

Annex F (informative):	Examples of coding of LSA Descriptor files for SoLSA	303
Annex G (informative):	Phonebook Example	304
Annex H (normative):	List of SFI Values.....	308
H.1	List of SFI Values at the USIM ADF Level.....	308
H.2	List of SFI Values at the DF GSM-ACCESS Level.....	308
H.3	List of SFI Values at the DF WLAN Level.....	309
H.4	List of SFI Values at the DF HNB Level	309
H.5	List of SFI Values at the DF ProSe Level	309
H.6	List of SFI Values at the DF ACDC Level.....	309
H.7	List of SFI Values at the DF MCS Level	310
H.8	List of SFI Values at the DF V2X Level.....	310
H.9	List of SFI Values at the DF 5GS Level	310
Annex I (informative):	USIM Application Session Activation/Termination	311
Annex J (informative):	Example of MMS coding.....	312
J.1	Coding example for MMS User Preferences.....	312
J.2	Coding Example for MMS Issuer/User Connectivity Parameters.....	312
Annex K (informative):	Examples of VService_Id coding	314
Annex L (normative):	USIM-INI and USIM-RN for Relay Nodes	315
L.1	Introduction	315
L.2	Application selection procedure.....	315
L.3	Secure channel operation.....	316
L.4	Support of commands.....	316
L.5	Storage of certificates.....	316
L.6	Relay Node files support	316
L.6.1	USIM-INI Files.....	316
L.6.1.1	EF _{CERT} (UICC Certificate).....	316
L.6.2	USIM-RN Files.....	317
L.6.2.1	eF _{RNid} (Relay Node identifier).....	317
L.6.2.2	EF _{SCCmax} (maximum value of Secure Channel Counter).....	318
Annex M (normative):	USIM application dedicated for IOPS	319
M.1	Introduction	319
M.2	Features of the USIM dedicated for IOPS.....	319
M.3	Selection mechanisms.....	319
Annex N (informative):	Change history	320
History		327

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- shall** indicates a mandatory requirement to do something
- shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- should** indicates a recommendation to do something
- should not** indicates a recommendation not to do something
- may** indicates permission to do something
- need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- can** indicates that something is possible
- cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document