

**SLOVENSKI STANDARD  
SIST EN ISO 21268-3:2020****01-januar-2020****Nadomešča:****SIST-TS CEN ISO/TS 21268-3:2010**

---

**Kakovost tal - Postopki izluževanja za nadaljnje kemijsko in ekotoksikološko preskušanje tal in tlem podobnih materialov - 3. del: Preskus v koloni s tokom navzgor (ISO 21268-3:2019)**

Soil quality - Leaching procedures for subsequent chemical and ecotoxicological testing of soil and soil-like materials - Part 3: Up-flow percolation test (ISO 21268-3:2019)

Bodenbeschaffenheit - Elutionsverfahren für die anschließende chemische und ökotoxikologische Untersuchung von Boden und von Bodenmaterialien - Teil 3: Perkolationsstest im Aufwärtsstrom (ISO 21268-3:2019)

<https://standards.iteh.ai/catalog/standards/sist/b2ecc0bb-d925-4e6c-bfaf-12099-2020>  
Qualité du sol - Modes opératoires de lixiviation en vue d'essais chimiques et écotoxicologiques ultérieurs des sols et matériaux du sol - Partie 3: Essai de percolation à écoulement ascendant (ISO 21268-3:2019)

**Ta slovenski standard je istoveten z: EN ISO 21268-3:2019****ICS:**

13.080.05      Preiskava tal na splošno      Examination of soils in general

**SIST EN ISO 21268-3:2020****en,fr,de**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN ISO 21268-3:2020](#)

<https://standards.iteh.ai/catalog/standards/sist/b2ecc0bb-d925-4e6c-bfaf-fc58eb00fcd8/sist-en-iso-21268-3-2020>

EUROPEAN STANDARD

**EN ISO 21268-3**

NORME EUROPÉENNE

EUROPÄISCHE NORM

October 2019

ICS 13.080.05

Supersedes CEN ISO/TS 21268-3:2009

English Version

## Soil quality - Leaching procedures for subsequent chemical and ecotoxicological testing of soil and soil-like materials - Part 3: Up-flow percolation test (ISO 21268-3:2019)

Qualité du sol - Modes opératoires de lixiviation en vue d'essais chimiques et écotoxicologiques ultérieurs des sols et matériaux du sol - Partie 3: Essai de percolation à écoulement ascendant (ISO 21268-3:2019)

Bodenbeschaffenheit - Elutionsverfahren für die anschließende chemische und ökotoxikologische Untersuchung von Boden und von Bodenmaterialien - Teil 3: Perkolationsstest im Aufwärtsstrom (ISO 21268-3:2019)

This European Standard was approved by CEN on 1 September 2019.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

(standards.iteh.ai)

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

<https://standards.iteh.ai/catalog/standards/sist/b2ecc0bb-d925-4e6c-bf1f-866111111111>

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels**

Contents	Page
European foreword.....	3

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN ISO 21268-3:2020](https://standards.iteh.ai/catalog/standards/sist/b2ecc0bb-d925-4e6c-bfaf-fc58eb00fd8/sist-en-iso-21268-3-2020)  
<https://standards.iteh.ai/catalog/standards/sist/b2ecc0bb-d925-4e6c-bfaf-fc58eb00fd8/sist-en-iso-21268-3-2020>

## European foreword

This document (EN ISO 21268-3:2019) has been prepared by Technical Committee ISO/TC 190 "Soil quality" in collaboration with Technical Committee CEN/TC 444 "Test methods for environmental characterization of solid matrices" the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2020, and conflicting national standards shall be withdrawn at the latest by April 2020.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes CEN ISO/TS 21268-3:2009.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

**iTeh STANDARD PREVIEW**  
**Endorsement notice**  
**(standards.iteh.ai)**

The text of ISO 21268-3:2019 has been approved by CEN as EN ISO 21268-3:2019 without any modification.

[SIST EN ISO 21268-3:2020  
https://standards.iteh.ai/catalog/standards/sist/b2ecc0bb-d925-4e6c-bfaf-fc58eb00fcd8/sist-en-iso-21268-3-2020](https://standards.iteh.ai/catalog/standards/sist/b2ecc0bb-d925-4e6c-bfaf-fc58eb00fcd8/sist-en-iso-21268-3-2020)

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN ISO 21268-3:2020](#)

<https://standards.iteh.ai/catalog/standards/sist/b2ecc0bb-d925-4e6c-bfaf-fc58eb00fcd8/sist-en-iso-21268-3-2020>

INTERNATIONAL  
STANDARD

ISO  
21268-3

First edition  
2019-09

---

---

**Soil quality — Leaching procedures  
for subsequent chemical and  
ecotoxicological testing of soil and  
soil-like materials —**

Part 3:  
**Up-flow percolation test**

iTeh STANDARD PREVIEW

(standards.iteh.ai)  
*Qualité du sol — Modes opératoires de lixiviation en vue d'essais  
chimiques et écotoxicologiques ultérieurs des sols et matériaux du  
sol —*

SIST EN ISO 21268-3:2020

<https://standards.iteh.ai/catalog/standards/sist/b2ccc000-d925-4600-b1af-fc58eb00fd8/sist-en-iso-21268-3-2020>

Partie 3: Essai de percolation à écoulement ascendant



Reference number  
ISO 21268-3:2019(E)

© ISO 2019

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN ISO 21268-3:2020](https://standards.iteh.ai/catalog/standards/sist/b2ecc0bb-d925-4e6c-bfaf-fc58eb00fd8/sist-en-iso-21268-3-2020)

<https://standards.iteh.ai/catalog/standards/sist/b2ecc0bb-d925-4e6c-bfaf-fc58eb00fd8/sist-en-iso-21268-3-2020>



### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Fax: +41 22 749 09 47  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland



# Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>2</b>
<b>3 Terms and definitions</b> .....	<b>2</b>
<b>4 Principle</b> .....	<b>3</b>
<b>5 Reagents and materials</b> .....	<b>4</b>
<b>6 Apparatus</b> .....	<b>4</b>
<b>7 Sample pre-treatment</b> .....	<b>6</b>
7.1 Preparation of laboratory sample and specification of particle size.....	6
7.2 Preparation of the test sample.....	7
7.3 Test portion.....	7
7.4 Determination of dry matter content.....	7
<b>8 Procedure</b> .....	<b>8</b>
8.1 Temperature.....	8
8.2 Preparation of the eluent.....	8
8.3 Preparation of the column.....	8
8.4 Packing of the column.....	8
8.5 Start of the test.....	9
8.6 Sample Collection and Liquid/Solid separation step.....	10
8.7 Collection of additional eluate fractions.....	11
8.8 Further preparation of the eluates for analysis.....	12
8.9 Blank test.....	12
<b>9 Calculation</b> .....	<b>12</b>
<b>10 Test report</b> .....	<b>13</b>
<b>11 Analytical determination</b> .....	<b>13</b>
11.1 General.....	13
11.2 Blank test information.....	13
<b>12 Performance characteristics</b> .....	<b>14</b>
12.1 General.....	14
12.2 Validation trials performed in Japan.....	15
12.2.1 Round robin tests performed in accordance with ISO/TS 21268-3:2007.....	15
12.2.2 Robustness testing and validation results considering equilibration period and flow rate.....	15
12.3 Validation results obtained in Germany (DIN 19528 <sup>[5]</sup> ).....	16
12.3.1 General.....	16
12.3.2 Results for validation trial 1.....	17
12.3.3 Results for validation trial 2.....	20
<b>Annex A (informative) Suggestions for packing the column, water saturation and establishment of equilibrium conditions</b> .....	<b>25</b>
<b>Annex B (informative) Justification of the choices made in developing the test procedure</b> .....	<b>27</b>
<b>Annex C (informative) Calculation of centrifugation duration depending on centrifugation speed and rotor dimensions</b> .....	<b>31</b>
<b>Annex D (informative) Additional information on robustness testing and validation results based on waste materials</b> .....	<b>33</b>
<b>Bibliography</b> .....	<b>34</b>

## ISO 21268-3:2019(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 190, *Soil quality*, Subcommittee SC 7, *Impact assessment*.

This first edition of ISO 21268-3:2019 cancels and replaces (ISO/TS 21268-3:2007), which has been technically revised. The main changes compared to the previous edition are as follows:

- the maximum grain size has been changed to <2 mm as usual for soil;
- demineralized water has been added as possible leachant;
- the column diameter has been changed from "5 cm or 10 cm" to "5 cm to 10 cm";
- flow rate of 30 cm/d has been added as option based on robustness testing;
- [7.1](#) and [7.2](#) has been exchanged to read [7.1](#) "Particle size" and [7.2](#) "Sample preparation";
- [11.1](#) "General", [11.2](#) "Validation trials performed in Japan" and [12.3](#) "Validation results obtained in Germany (DIN 19528)" have been added;
- [B.2](#) "Particle size distribution" has been deleted;
- a new informative [Annex C](#) "Calculation of centrifugation duration depending on centrifugation speed and rotor dimensions" has been added;
- references in [Clause 2](#) and Bibliography has been updated.

A list of all parts in the ISO 21268 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).

## Introduction

In various countries, tests have been developed to characterize and assess the substances which can be released from materials. The release of soluble substances upon contact with water is regarded as a main mechanism of release, which results in a potential risk to the environment during the use or disposal of materials. The intent of these tests is to identify the leaching properties of materials. The complexity of the leaching process makes simplifications necessary<sup>[1]</sup>.

Not all of the relevant aspects of leaching behaviour can be addressed in one standard (see description of influencing factors in [Annex A](#)).

Tests to characterise the behaviour of materials can generally be divided into three categories addressed in ISO 18772<sup>[2]</sup> and EN 12920<sup>[3]</sup>. The relationships between these tests are summarized below.

- a) “Basic characterization” tests are used to obtain information on the short- and long-term leaching behaviour and characteristic properties of materials. Liquid/solid (L/S) ratios, leachant composition, factors controlling leachability, such as pH, redox potential, complexing capacity, role of dissolved organic carbon (DOC), ageing of material and physical parameters, are addressed in these tests.
- b) “Compliance” tests are used to determine whether the material complies with a specific behaviour or with specific reference values. The tests focus on key variables and leaching behaviour previously identified by basic characterisation tests.
- c) “On-site verification” tests are used as a rapid check to confirm that the material is the same as that which has been subjected to the compliance test(s). On-site verification tests are not necessarily leaching tests.

The test procedure described in this method belongs to category a): basic characterization tests.

This document was originally elaborated on the basis of CEN/TS 14405:2004<sup>[4]</sup>. Especially, modifications considering requirements on subsequent ecotoxicological testing and analysis of organic substances have been included. Validation results have been adopted from DIN 19528<sup>[5]</sup> and from Japanese validation studies<sup>[15,16]</sup>.

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST EN ISO 21268-3:2020](https://standards.iteh.ai/catalog/standards/sist/b2ecc0bb-d925-4e6c-bfaf-fc58eb00fd8/sist-en-iso-21268-3-2020)

<https://standards.iteh.ai/catalog/standards/sist/b2ecc0bb-d925-4e6c-bfaf-fc58eb00fd8/sist-en-iso-21268-3-2020>

# Soil quality — Leaching procedures for subsequent chemical and ecotoxicological testing of soil and soil-like materials —

## Part 3: Up-flow percolation test

### 1 Scope

This document specifies a test, which is aimed at determining the leaching behaviour of inorganic and organic substances from a soil and soil-like materials. The method is a once-through up-flow percolation test under standardized conditions of flow rate. The material is leached under dynamic hydraulic conditions. The document has been developed to measure the release of inorganic and organic substances from soil and soil-like material as well as to produce eluates for subsequent ecotoxicological testing. For ecotoxicological testing, see ISO 15799<sup>[6]</sup> and ISO 17616<sup>[7]</sup>. The test results enable the distinction between different release patterns, for instance wash-out and release under the influence of interaction with the matrix, when approaching local equilibrium between material and leachant.

This test method produces eluates, which can subsequently be characterized by physical, chemical and ecotoxicological methods in accordance with existing standard methods. The results of eluate analysis are presented as a function of the liquid/solid (L/S) ratio. The test is not suitable for substances that are volatile under ambient conditions.

NOTE 1 Volatile organic substances include the low-molecular-weight substances in mixtures such as mineral oil.

NOTE 2 It is not always possible to optimize test conditions simultaneously for inorganic and organic substances and optimum test conditions can also vary between different groups of organic substances. Test requirements for organic substances are generally more stringent than those for inorganic substances. The test conditions suitable for measuring the release of organic substances will generally also be applicable to inorganic substances.

NOTE 3 Within the category of organic substances, a significant difference in behaviour exists between the more polar, relatively water-soluble compounds and apolar, hydrophobic organic substances (HOCs). In the latter case, mechanisms of release (e.g. particle-bound or dissolved organic carbon-bound) can be more crucial as well as sorption losses of soluble HOCs on different materials with which they come in contact (e.g. bottles, filters). The test and the results should be used for leaching of organic substances only with thorough consideration of the specific properties of the substances in question and the associated potential problems.

NOTE 4 For ecotoxicological testing, eluates representing the release of both inorganic and organic substances are needed. In this document, ecotoxicological testing is also meant to include genotoxicological testing.

NOTE 5 The test is generally not suitable for soils with hydraulic conductivities below  $10^{-8}$  m/s (see also [Annex B](#)). It can be difficult to maintain the designated flow rate already in the range of saturated hydraulic conductivity between  $10^{-7}$  m/s and  $10^{-8}$  m/s.

The application of this test method alone is not sufficient for the determination of the leaching behaviour of a material under specified conditions different to those from the test procedure, since this generally requires the application of several test methods, behavioural modelling and model validation. This document does not address issues related to health and safety. It only determines the leaching properties as outlined in [Clause 4](#).