
**Cycles — Lighting and retro-
reflective devices —**

**Part 3:
Installation and use of lighting and
retro-reflective devices**

iTeh STANDARD PREVIEW
Cycles — Éclairages et dispositifs rétro réfléchissant —
(standards.iteh.ai)
Partie 3: Installation et usage des éclairages et des dispositifs
rétro réfléchissant

ISO 6742-3:2015

[https://standards.iteh.ai/catalog/standards/sist/4e1051bf-87e6-43ff-8044-
ce4a1f934534/iso-6742-3-2015](https://standards.iteh.ai/catalog/standards/sist/4e1051bf-87e6-43ff-8044-ce4a1f934534/iso-6742-3-2015)



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 6742-3:2015

<https://standards.iteh.ai/catalog/standards/sist/4e1051bf-87e6-43ff-8044-ce4a1f934534/iso-6742-3-2015>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 General	1
4.1 Tolerances.....	1
4.2 Conditions.....	1
4.3 Order of tests.....	2
5 Requirements	2
5.1 Lighting devices.....	2
5.1.1 Installation requirements.....	2
5.1.2 Fixation requirements.....	2
5.1.3 Control requirements.....	2
5.2 Retro-reflective devices.....	2
6 Test method	2
6.1 Lighting devices.....	2
6.1.1 Test method for installation.....	2
6.1.2 Test method for fixation.....	3
6.2 Retro-reflective devices.....	5
7 Manufacturer's instructions	5
7.1 Lighting devices.....	5
7.1.1 Mounting instructions.....	5
7.1.2 Instructions for use.....	5
7.2 Retro-reflective devices.....	6
Bibliography	7

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: [Foreword — Supplementary information](#).

The committee responsible for this document is ISO/TC 149, *Cycles*, SC 1, *Cycles and sub-assemblies*.

ISO 6742 consists of the following parts, under the general title *Cycles — Lighting and retro-reflective devices*:

- *Part 1: Lighting and light signalling devices*
- *Part 2: Retro reflective devices*
- *Part 3: Installation and use of lighting and retro-reflective devices*
- *Part 4: Lighting systems powered by the cycle's movement*
- *Part 5: Lighting systems not powered by the cycle's movement*

Introduction

This International Standard has been developed in response to demand throughout the world, and the aim has been to ensure that bicycles manufactured in compliance with it will be as safe as is practically possible. The tests have been designed to ensure the strength and durability of individual parts as well as of the bicycle as a whole, demanding high quality throughout and consideration of safety aspects from the design stage onwards.

The test method with PSD (6.1.2.2) reflects today's state of the art and should be preferred to the sine sweep vibration test (6.1.2.3).

Users of the standard are invited to provide their feedback to ISO/TC 149/SC 1.

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 6742-3:2015

<https://standards.iteh.ai/catalog/standards/sist/4e1051bf-87e6-43ff-8044-ce4a1f934534/iso-6742-3-2015>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 6742-3:2015

<https://standards.iteh.ai/catalog/standards/sist/4e1051bf-87e6-43ff-8044-ce4a1f934534/iso-6742-3-2015>

Cycles — Lighting and retro-reflective devices —

Part 3:

Installation and use of lighting and retro-reflective devices

1 Scope

This part of ISO 6742 is applicable to lighting and retro-reflective devices used on cycles intended to be used on public roads and, especially, bicycles complying with ISO 4210 and ISO 8098.

This part of ISO 6742 specifies the safety requirements and test methods of lighting and retro-reflective devices for fastening devices, control, (guidelines for maintenance), instructions for mounting and use.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6742-1:2015, *Cycles — Lighting and retro-reflective devices — Part 1: Lighting and light signalling devices*

IEC 60068-2-6, *Environmental testing — Part 2-6: Tests — Test Fc: Vibration (sinusoidal)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 6742-1 and the following apply.

3.1

control

any part of a device directly or indirectly actuated by the cyclist which changes the state or functioning of the lighting devices

4 General

4.1 Tolerances

The tolerances given in [Table 1](#) apply unless others specifications are indicated in the text.

Table 1 — General tolerances

Angles	$\pm 0,1^\circ$
Masses	$\pm 1\%$
Time	- 0 s / +5 s
Temperature	$\pm 5^\circ\text{C}$

4.2 Conditions

Unless otherwise specified, all tests shall be performed at an ambient temperature of $(23 \pm 5)^\circ\text{C}$ and at a humidity of $(50 \pm 20)\% \text{RH}$.

4.3 Order of tests

Each test shall be conducted on a new test sample, but if only one sample is available, it is allowed to carry out all of the tests on the same sample in the order that they appear in this part of ISO 6742.

All components shall be in the fully-finished condition.

5 Requirements

5.1 Lighting devices

5.1.1 Installation requirements

After tested by the method described in [6.1.1](#):

- the lighting device can be mounted according to manufacturer's instructions;
- the fastening device shall not mask/obscure the light beam.

NOTE All structural components should be assembled in accordance with the national regulation in the country, where the bicycle is marketed and the manufacturer's instruction that is containing information on.

5.1.2 Fixation requirements

After tested by the method described in [6.1.2](#):

- there shall be no fracture or visible cracks in any part of the lighting device and fixation device;
- the lighting device shall be functional;
- there shall be not any bolt failure or loosening;
- there shall be no movement between the lighting device and the fixture.

5.1.3 Control requirements

In case of combination of functions in one product, each function shall be identified on the control device. Control device shall be positioned in order to be easily manipulated by the cyclist. The functions shall be described in the instructions of use.

NOTE It is recommended to use the standardised symbols from ISO 7000:2012.

5.2 Retro-reflective devices

When tested by the following method, the optical axis of the reflector (excluding pedal reflectors or spoke mounted reflectors) shall not deflect more than 15 ° during test, and shall not exhibit a permanent displacement greater than 5 ° after the test.

6 Test method

6.1 Lighting devices

6.1.1 Test method for installation

All structural components shall be assembled in accordance with the manufacturer's instruction as described in [7.1.1](#).

In case of adjustments are possible, they shall be made in the way to obtain the most onerous situation that can occur in practice (i.e. position of the device which generates the greatest torque on the attachment point).

6.1.2 Test method for fixation

6.1.2.1 General

If the equipment is tested without cycle, it has to be assembled on a fixture that is representative of the part of the bicycle to which the lighting system is designed to fit, using the fastening devices supplied by the manufacturer.

The test method shall be performed using one of the methods described in [6.1.2.2](#) or shall be performed using method described in [6.1.2.3](#).

6.1.2.2 Method A

6.1.2.2.1 Equipment

The vibration of the test machine shall be performed randomly according to a normal distribution of the instant values. The vibrations shall be defined by their Power spectral density (PSD) and their frequency from 3 Hz to 200 Hz or from 6 Hz to 200 Hz.

6.1.2.2.2 Test method

After mounting the device on the fixture in which it is designed to be fitted to a cycle, as described in [6.1.2.1](#). Fasten the assembly to a vibration test machine in a position similar to its normal operating position. Vibrate the lighting device by the Power spectral density (PSD) for 10 h on the vertical direction "z" under the conditions PSD1 or PSD2 of [Figure 1](#) and [Table 2](#).

The excitation of vibrations is performed by using a measured acceleration. The measured acceleration shall be placed near the fixation point of the lighting device.