



**SLOVENSKI STANDARD**  
**SIST ISO 6164:2021**

**01-julij-2021**

**Nadomešča:**  
**SIST ISO 6164:1995**

---

**Fluidna tehnika - Hidravlika - Enodelni 4-vijačni kvadratni prirobnični spoji za tlake 42 MPa, DN 25 do 80**

Hydraulic fluid power -- Four-screw, one-piece square flange connections for use at pressures of 42 MPa, DN 25 to 80

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

Transmissions hydrauliques -- Brides de raccordement carrées monobloc à quatre vis pour des pressions d'utilisation de 42 MPa, DN 25 à 80

<https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae4f-b11a51836235/sist-iso-6164-2021>

**Ta slovenski standard je istoveten z: ISO 6164:2018**

---

**ICS:**

23.100.40 Cevna napeljava in sklopke Piping and couplings

**SIST ISO 6164:2021**

**en,fr,de**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ISO 6164:2021](#)

<https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae44-b11a51836235/sist-iso-6164-2021>

INTERNATIONAL  
STANDARD

ISO  
6164

Second edition  
2018-06

---

---

**Hydraulic fluid power — Four-screw,  
one-piece square flange connections  
for use at pressures of 42 MPa, DN 25  
to 80**

*Transmissions hydrauliques — Brides de raccordement carrées  
monobloc à quatre vis pour des pressions d'utilisation de 42 MPa,  
DN 25 à 80*

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[SIST ISO 6164:2021](https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae44-b11a51836235/sist-iso-6164-2021)

[https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae44-  
b11a51836235/sist-iso-6164-2021](https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae44-b11a51836235/sist-iso-6164-2021)



Reference number  
ISO 6164:2018(E)

© ISO 2018

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 6164:2021

<https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae44-b11a51836235/sist-iso-6164-2021>



### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Fax: +41 22 749 09 47  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

<b>Contents</b>	<b>Page</b>
<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>2</b>
<b>4 Material</b> .....	<b>2</b>
<b>5 Selection criteria</b> .....	<b>3</b>
<b>6 Tolerances</b> .....	<b>3</b>
<b>7 Corrosion protection</b> .....	<b>3</b>
<b>8 Pressure/temperature requirements</b> .....	<b>4</b>
<b>9 Marking</b> .....	<b>4</b>
<b>10 Designation of flange connections and their parts</b> .....	<b>4</b>
<b>Annex A (informative) Assembly procedures and screw torque levels for flange connections conforming to this document</b> .....	<b>11</b>
<b>Annex B (informative) O-ring designation codes and dimensions</b> .....	<b>13</b>
<b>Bibliography</b> .....	<b>14</b>

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

[SIST ISO 6164:2021](https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae44-b11a51836235/sist-iso-6164-2021)

<https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae44-b11a51836235/sist-iso-6164-2021>

## ISO 6164:2018(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html). (standards.iteh.ai)

This document was prepared by Technical Committee ISO/TC 131, *Fluid power systems*, Subcommittee SC 4, *Connectors and similar products and components*.

This second edition cancels and replaces the first edition (ISO 6164:1994), which has been technically revised.

The following are the main changes made since the previous edition:

- The 25 MPa flange series have been removed from the document due to same envelope dimensions versus the 40 MPa series.
- The sizes DN 10 to DN 19 have been removed from the document. These sizes are typically covered by tube fittings rather than flanges.
- The working pressure was increased from 40 MPa to 42 MPa to be in line with common hose working pressures.
- The design factor from 2,5 was increased to 4 including verification testing.

## Introduction

In hydraulic fluid power systems, power is transmitted and controlled through a liquid under pressure within an enclosed circuit. Components are interconnected through their ports and associated fluid conductor connector ends.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST ISO 6164:2021](https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae44-b11a51836235/sist-iso-6164-2021)

<https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae44-b11a51836235/sist-iso-6164-2021>

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST ISO 6164:2021

<https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae4-b11a51836235/sist-iso-6164-2021>



# Hydraulic fluid power — Four-screw, one-piece square flange connections for use at pressures of 42 MPa, DN 25 to 80

## 1 Scope

This document gives general and dimensional specifications for flanged heads, flange clamps, ports and mounting surfaces applicable to four-screw, one-piece square flange clamp type tube connectors and hose fittings for use at a pressure of 42 MPa [420 bar<sup>1)</sup>]. It also specifies the dimensions of the seals to be used, as well as the grooves that house the seals.

These connections are intended for application in hydraulic systems on industrial and commercial products where it is desired to avoid the use of threaded connectors.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 48, *Rubber, vulcanized or thermoplastic — Determination of hardness (hardness between 10 IRHD and 100 IRHD)*

ISO 261, *ISO general purpose metric screw threads — General plan*

ISO 724, *ISO general-purpose metric screw threads — Basic dimensions*

ISO 898-1, *Mechanical properties of fasteners made of carbon steel and alloy steel — Part 1: Bolts, screws and studs with specified property classes — Coarse thread and fine pitch thread*

ISO 1302, *Geometrical Product Specifications (GPS) — Indication of surface texture in technical product documentation*

ISO 2768-1, *General tolerances — Part 1: Tolerances for linear and angular dimensions without individual tolerance indications*

ISO 3601-1, *Fluid power systems — O-rings — Part 1: Inside diameters, cross-sections, tolerances and designation codes*

ISO 3601-3, *Fluid power systems — O-rings — Part 3: Quality acceptance criteria*

ISO 4017, *Fasteners — Hexagon head screws — Product grades A and B*

ISO 4762, *Hexagon socket head cap screws*

ISO 5598, *Fluid power systems and components — Vocabulary*

ISO 7089, *Plain washers — Normal series — Product grade A*

ISO 9227, *Corrosion tests in artificial atmospheres — Salt spray tests*

ISO 10763, *Hydraulic fluid power — Plain-end, seamless and welded precision steel tubes — Dimensions and nominal working pressures*

1) 1 bar = 0,1 MPa = 10<sup>5</sup> Pa; 1 Pa = 1 N/m<sup>2</sup>.

## ISO 6164:2018(E)

ISO 19879, *Metallic tube connections for fluid power and general use — Test methods for hydraulic fluid power connections*

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5598 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

### 4 Material

**WARNING** — Users of this document shall ensure that suitable material is chosen for the port to maintain the required working pressure, if carbon steel is not used. Also, the tube material and wall thickness depend on the selected working pressure and tube diameter. Tube dimensions shall be calculated in accordance with ISO 10763.

**4.1 Flange clamps**, (see [Figure 2](#)) which shall be of ferrous material with the following properties in the finished condition:

- minimum yield strength: 330 MPa;
- minimum elongation at fracture: 5 %.

IteH STANDARD PREVIEW  
(standards.iteh.ai)

**4.2 Flanged heads**, which shall be of ferrous material with the following properties in the finished condition:

[SIST ISO 6164:2021](https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae44-b11a51836235/sist-iso-6164-2021)

- minimum yield strength: 330 MPa; <https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae44-b11a51836235/sist-iso-6164-2021>
- minimum elongation at fracture: 10 %.

**4.3 Screws**. Unless otherwise specified, one of the following screw options shall be used:

- a) hexagon head screws conforming to ISO 4017 of property class 10.9 (minimum) in accordance with ISO 898-1;

or

- b) socket head screws conforming to ISO 4762 of property class 10.9 (minimum) in accordance with ISO 898-1.

**4.4 O-rings**. Unless otherwise specified, the O-rings shall be made of NBR (nitrile) with a hardness of  $(90 \pm 5)$  IRHD, measured in accordance with ISO 48, for use at the pressure and temperature requirements given in [Clause 8](#) and for testing. The O-rings specified in [Table B.1](#) shall conform to the dimensions given in ISO 3601-1 for the relevant size code. They shall also conform to tolerance class A in ISO 3601-1 and shall meet or exceed the O-ring quality acceptance criteria for grade N of ISO 3601-3. If the flange connection will be used at temperatures higher than specified in [Clause 8](#), O-rings made of materials that meet the higher temperature requirements shall be used.

**NOTE** Connectors conforming to this document contain elastomeric seals. Unless otherwise specified, connectors are made and delivered with elastomeric seals for use within the specified working temperature range with petroleum base hydraulic fluids. The use of these connectors and elastomeric seals with other hydraulic fluids might result in a reduced working temperature range or might render the connectors unsuitable for the application. Manufacturers can supply, upon request, connectors with elastomeric seals for use with hydraulic fluids other than petroleum base hydraulic fluids which will meet the specified working temperature range of the connectors.

## 5 Selection criteria

The following specifications supplement the dimensional data contained in [Tables 1](#) to [4](#) with respect to all unspecified details:

- a) The nominal matching flange size clamp shall be selected for the matching port size from [Figures 3](#) and [Table 3](#).
- b) The flanged head size, shown in [Figure 4](#) and [Table 4](#), shall be selected in accordance with the size selected for the flange clamps and ports.
- c) O-rings shall be selected conforming to the dimensions given in ISO 3601-1 and corresponding to the size code in [Annex B, Table B.1](#).
- d) Metric screws shall be selected corresponding to the sizes and lengths indicated in [Table 1](#).
- e) Screw type shall be designated according to [4.3](#) as well as thread size and length of screws.
- f) Designate square flange connector sizes by the nominal flange size that corresponds to the maximum diameter of the bore through the flanged head.

## 6 Tolerances

**6.1** Unless otherwise specified, tolerances shall be in accordance with ISO 2768-m (medium).

**6.2** Dimensions and tolerances given in the tables apply to the finished parts, plated or otherwise processed, as specified by agreement between purchaser and manufacturer.

## 7 Corrosion protection

SIST ISO 6164:2021

<https://standards.iteh.ai/catalog/standards/sist/08a6dca2-1f81-4a6d-ae4-b11a51836235/sist-iso-6164-2021>

**7.1** The external surface of all carbon steel flange clamps and all carbon steel flanged heads, except weld-on flanged heads, shall be protected with an appropriate coating to pass a minimum 72 h salt spray test in accordance with ISO 9227, unless otherwise agreed upon by the supplier and purchaser. Weld-on flanged heads shall be protected from corrosion by an oil film, phosphate coating or by other means that do not negatively affect weldability. This protection shall meet or exceed a 16 h neutral salt spray test in accordance with ISO 9227, unless otherwise agreed upon by the supplier and purchaser.

**7.2** Screws shall be protected from corrosion by an oil film, phosphate coating, or other means that do not encourage hydrogen embrittlement, to meet or exceed the requirements of a 16 h neutral salt spray test in accordance with ISO 9227.

**7.3** Appearance of red rust during the above salt spray tests shall be considered failure, except for in the following locations:

- all internal passages;
- edges;
- areas where the parts are suspended or affixed in the test chamber and condensate can accumulate.

**7.4** Parts conforming to this document shall not be cadmium plated. Hexavalent chromate coatings are not preferred for commercial and industrial usage for environmental reasons. Changes in plating can affect assembly torques and require requalification.

**7.5** Internal fluid passages shall be protected from corrosion during storage and shipping.