

SIST ISO 6707-1:2015

SLOVENSKI STANDARD SIST ISO 6707-1:2015

01-januar-2015

Stavbe in gradbeni inženirski objekti - Slovar - 1. del: Splošni izrazi

Buildings and civil engineering works -- Vocabulary -- Part 1: General terms

Bâtiments et ouvrages de génie civil -- Vocabulaire -- Partie 1: Termes généraux

Ta slovenski standard je istoveten z: ISO 6707-1:2014

		<u>5707-1:2015</u> ards/sist/aa202dd5-e13b-408c-b50d-	
ICS:		-iso-6707-1-2015	
01.040.91	Gradbeni materiali in gradnja (Slovarji)	Construction materials and building (Vocabularies)	
01.040.93	Nizke gradnje (Slovarji)	Civil engineering (Vocabularies)	
91.010.01	Gradbeništvo na splošno	Construction industry in general	
93.010	Nizke gradnje na splošno	Civil engineering in general	

en



iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 6707-1:2015</u> https://standards.iteh.ai/catalog/standards/sist/aa202dd5-e13b-408c-b50daf6d8aa3a82f/sist-iso-6707-1-2015

SIST ISO 6707-1:2015

INTERNATIONAL STANDARD

ISO 6707-1

Fourth edition 2014-03-15

Buildings and civil engineering works — Vocabulary —

Part 1: General terms

Bâtiments et ouvrages de génie civil — Vocabulaire —

iTeh STPartie Diernes généraux VIEW (standards.iteh.ai)

SIST ISO 6707-1:2015 https://standards.iteh.ai/catalog/standards/sist/aa202dd5-e13b-408c-b50daf6d8aa3a82f/sist-iso-6707-1-2015



Reference number ISO 6707-1:2014(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 6707-1:2015</u> https://standards.iteh.ai/catalog/standards/sist/aa202dd5-e13b-408c-b50daf6d8aa3a82f/sist-iso-6707-1-2015



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Contents

Page

Foreword		iv
Introd	luction	v
1	Scope	1
2	Vocabulary structure	1
3	Types of buildings and civil engineering works3.1Base terms3.2Civil engineering works3.3Civil engineering works — Transport3.4Buildings	
4	Spaces 4.1 Base terms 4.2 Spaces associated with particular parts of the building 4.3 Functional spaces 4.4 Spaces associated with circulation and movement	
5	Parts of buildings and civil engineering works5.1Structural parts5.2Dividing and enclosing parts5.3Openings and associated closing parts5.4Services fitments and equipment5.5Other parts	20 28 35 39 45
6	Materials (standards.iteh.ai) 6.1 Base terms 6.2 Earth and stone SIST ISO 6707~1:2015 6.3 Wood and timber.iteh ai/catalog/standards/sist/aa202dd5~e13b~408c~b50d~ 6.4 Functional materials/6d8aa3a82f/sist-iso-6707~1.2015	53 55 55
7	Operations, documentation, and equipment 7.1 Operations 7.2 Documentation 7.3 Equipment	64 70 71
8	Persons involved in projects and users	
9	Characteristics and performance9.1Base terms.9.2Size and dimensions.9.3Functional properties.9.4Testing properties.	
10	Environment and physical planning	
	Annex A (informative) Synonyms and alternative spellings used in Great Britain/United Kingdom (GB)	
Annex B (informative) Alphabetical index of US synonyms		
Biblio	Bibliography	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 59, Buildings and civil engineering works, Subcommittee SC 2, Terminology and harmonization of languages.

This fourth edition cancels and replaces the third edition (ISO 6707-1:2004)) which has been technically revised.

ISO 6707 consists of the following parts, under the general title *Buildings and civil engineering works* — *Vocabulary*:

- Part 1: General terms
- Part 2: Contract terms

Introduction

With the growth in the number of international construction projects and the development of the international market in construction products, there is an increasing need for agreement on a common language in the domain.

This part of ISO 6707 is a first step towards a complete set of general terms for use by the construction industry. It will be updated as further terms and definitions are agreed upon.

This International Standard includes terms and concepts that are commonly used in documentation governing construction work as well as terms used to specify products and works. It is important to note that when used in legislation, some general construction terms have a narrower interpretation and hence, the definition given in this International Standard will not apply.

The adoption of this International Standard by the various national construction industries will improve communication in the design, execution, and maintenance of construction works within those industries. Its use in other standards will aid harmonization and provide a basis for specialist terminology.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 6707-1:2015</u> https://standards.iteh.ai/catalog/standards/sist/aa202dd5-e13b-408c-b50daf6d8aa3a82f/sist-iso-6707-1-2015



iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 6707-1:2015 https://standards.iteh.ai/catalog/standards/sist/aa202dd5-e13b-408c-b50daf6d8aa3a82f/sist-iso-6707-1-2015

Buildings and civil engineering works — Vocabulary —

Part 1: General terms

1 Scope

This part of ISO 6707 contains the terms and definitions of general concepts to establish a vocabulary applicable to buildings and civil engineering works.

It comprises

- a) fundamental concepts, which can be the starting point for other, more specific, definitions, and
- b) more specific concepts, used in several areas of construction and frequently used in standards, regulations, and contracts.

2 Vocabulary structure

The terms are arranged within categories to allow ready comparison of related concepts.

Where a given preferred term **designates more than one conc**ept, each concept has been treated in a separate entry and a note to entry included to acknowledge the homonymy created and a reference included to the other term entry. <u>SIST ISO 6707-1:2015</u>

Where a preferred or admitted term is specific to a particular English-speaking country, e.g. the United States of America, etc., this has been given in boldface type following the international preferred term and annotated by the respective country code. Where no preferred terms are listed indicating usage in a specific geographical location, this signifies that the international preferred term is the accepted term in the English-speaking countries. A term following the preferred term not given in boldface type is an admitted (non-preferred) synonym. Country codes are also assigned to these terms.

In most countries, synonyms and alternative spellings exist for the preferred terms used in this part of ISO 6707, and a list of synonyms and alternative spellings is given in <u>Annex A</u>. To facilitate a ready comparison with US synonyms and alternative spellings, these are given in <u>Annex B</u>.

3 Types of buildings and civil engineering works

3.1 Base terms

3.1.1 construction works US: **construction** everything that is constructed or results from construction operations

Note 1 to entry: In the US, there are homographs for the term "construction". See <u>5.5.6</u> and <u>7.1.1</u>.

3.1.2 civil engineering works US: civil engineering project

construction works (3.1.1) comprising a structure (3.1.4), such as a dam (3.2.22), bridge (3.3.19), road (3.3.1), railway (3.3.3), runway, utilities, pipeline (3.2.30), or sewerage system (5.4.40), or the result of operations such as dredging, *earthwork* (7.1.6), geotechnical processes, but excluding a *building* (3.1.3)and its associated site (3.1.6) works

Note 1 to entry: Associated siteworks are included in US civil engineering projects.

3.1.3

building

construction works (3.1.1) that has the provision of shelter for its occupants or contents as one of its main purposes, usually partially or totally enclosed and designed to stand permanently in one place

Note 1 to entry: In English, there is a homograph for the term "building". See 7.1.4.

3.1.4

structure

construction works (3.1.1) having a *structure* (5.1.2)

Note 1 to entry: In English, there is a homograph for the term "structure". See <u>5.1.2</u>.

3.1.5

external works

US: sitework construction works (3.1.1) or landscape work on land (10.1) associated with, and adjacent to, civil engineering works (3.1.2) or a building (3.1.8) andards.iteh.ai)

3.1.6

SIST ISO 6707-1:2015

site area of land (10.1) or waten where construction work (7.111) on other development is undertaken af6d8aa3a82f/sist-iso-6707-1-2015

3.2 **Civil engineering works**

3.2.1

earthworks result of change of existing terrain

3.2.2

excavation

result of digging, lifting, and removing earth, *fill* (6.4.9), or other *material* (6.1.1) from the *ground* (6.2.1)

3.2.3

embankment

section of *earthworks* (3.2.1), often formed by *cut* (3.2.5) or *fill* (6.4.9), where the *finished ground level* (9.2.34) is above or below original ground level (9.2.33) and whose length (9.2.18) usually greatly exceeds its width (9.2.16)

3.2.4 bund US: berm low embankment (3.2.3)

3.2.5 cut

material (6.1.1) excavated in bulk

Note 1 to entry: In English, there is a homograph for the term "cut". See <u>3.2.6</u>.

3.2.6

cut

void that results from bulk *excavation* (3.2.2) of *material* (6.1.1)

Note 1 to entry: In English, there is a homograph for the term "cut". See <u>3.2.5</u>.

3.2.7

cut and fill

earthwork (7.1.6) technique for lessening or increasing a variation in *ground level* (9.2.33) by using *material* (6.1.1) excavated from higher ground (6.2.1) to raise the level (9.2.32) of lower ground or the reverse

3.2.8

adit

nearly level tunnel (3.3.18) driven to underground workings

3.2.9

made ground

US: fill

ground (6.2.1) that has been formed by using material (6.1.1) to fill in a depression or to raise the level (9.2.32) of a site (3.1.6)

Note 1 to entry: In the US, there is a homograph for the term "fill". See <u>6.4.9</u>.

3.2.10

US: retaining earthworks bund wall

wall (5.2.46) that forms an enclosure around a storage tank and is used to retain the contents in the event of tank failure

3.2.11

SIST ISO 6707-1:2015 https://standards.iteh.ai/catalog/standards/sist/aa202dd5-e13b-408c-b50ddumpling af6d8aa3a82f/sist-iso-6707-1-2015 US: mound

large mass of ground (6.2.1) intended to be excavated but temporarily left as a support during construction work (7.1.1)

3.2.12

trench

horizontal or slightly inclined long, narrow open *excavation* (3.2.2), usually with vertical sides

3.2.13

shaft

vertical or steeply inclined *excavation* (3.2.2), usually of limited cross-section in relation to its *depth* (<u>9.2.15</u>)

3.2.14

borrow pit

area within which *earthwork* (7.1.6) takes place in order to produce *material* (6.1.1) for *earthworks* (3.2.1)

3.2.15

borehole

hole, usually vertical, bored to determine ground (6.2.1) conditions, for extraction of water, other liquids, or gases, or *measurement* (7.1.25) of groundwater *level* (9.2.32)

3.2.16

retaining wall

wall (5.2.46) that provides lateral support to the ground (6.2.1) or that resists pressure from a mass of other *material* (6.1.1)

3.2.17

diaphragm wall

wall (5.2.46) made of concrete (6.4.15) constructed in a trench (3.2.12) temporarily supported by *bentonite* (3.2.18) suspension

Note 1 to entry: In English, there is a homograph for the term "diaphragm wall". See 5.1.63.

Note 2 to entry: In the US, there are homographs for the term "diaphragm wall". See 5.1.61 and 5.1.63.

3.2.18

bentonite

clay, formed by the decomposition of volcanic ash, that swells as it absorbs water

3.2.19

water tower

civil engineering works (3.1.2) that comprises a large water tank raised above ground level (9.2.33)

3.2.20

silo

structure (3.1.4) for the storage of a large volume of loose material

3.2.21

breakwater

long structure (3.1.4) in a body of water designed to protect a basin (3.3.64) or the shore from waves

3.2.22

dam

iTeh STANDARD PREVIEW

barrier (5.2.9) constructed to retain water in order to raise its level (9.2.32), form a reservoir (3.2.36), or (stanuarus.itell.al) reduce or prevent flooding

3.2.23

SIST ISO 6707-1:2015 flood bank https://standards.iteh.ai/catalog/standards/sist/aa202dd5-e13b-408c-b50dembankment (3.2.3) built up to retain or control the level (9.2.32) of flood water

3.2.24

cofferdam

structure (3.1.4), usually temporary, that is built to support the surrounding ground (6.2.1) or to exclude water or *soil* (6.2.2) sufficiently to permit work within it to proceed safely without excessive pumping

3.2.25

swale

slightly inclined, often heavily vegetated or paved with gravel, stone (6.2.4), or concrete (6.4.15) and at times swampy, depression, constructed to contain water and other liquids

Note 1 to entry: In the US, there is a homograph for the term "swale". See <u>10.8</u>.

3.2.26

irrigation

artificial distribution of water to *land* (10.1), usually for growing crops

3.2.27

weir

structure (3.1.4) over which water can flow, used to control the upstream water level (9.2.32) in a watercourse (10.8) or other channel (5.4.16), and/or to measure the flow (9.3.41)

3.2.28

penstock

US: lock gate

gate, usually rectangular, that moves vertically between guides

3.2.29

spillway

passage for the discharge of excess water from a reservoir (3.2.36) or channel (5.4.16)

3.2.30

pipeline

long continuous line of *pipes* (5.4.17), including ancillary equipment, used for transporting liquids or gases

3.2.31

aqueduct

conduit (5.4.14) for conveying water over long distances, and including the supporting *structure* (5.1.2)

3.2.32

water supply adit

tunnel (3.3.18) driven from the ground to provide access to or drainage from underground workings

3.2.33

culvert

transverse drain (5.4.38) or waterway structure (3.1.4) under a road (3.3.1), railway (3.3.3), or canal (3.3.61), or through an *embankment* (3.2.3), in the form of a large *pipe* (5.4.17) or enclosed *channel* (<u>5.4.16</u>)

3.2.34

headworks

intake and associated works at the upstream end of a water engineering (7.1.11) scheme

3.2.35 rising main

(standards.iteh.ai)

water main or pressurized section of a *drain* (5.4.38) or *sewer* (5.4.41) through which liquid is pumped to a higher *level* (9.2.32) <u>SISTISC 0707-1.2010</u> https://standards.iteh.ai/catalog/standards/sist/aa202dd5-e13b-408c-b50d-

af6d8aa3a82f/sist-iso-6707-1-2015

3.2.36 reservoir

pond, lake, or basin (3.3.64), either naturally occurring or man-made, for storage, regulation, and control of water and other liquids or gases

3.3 Civil engineering works — Transport

3.3.1 road

way mainly for vehicles

3.3.2

exit

designated point of departure from a road (3.3.1)

Note 1 to entry: In English, there is a homograph for the term "exit". See 4.4.17.

3.3.3 railway US: railroad

national or regional transport system for guided passage of wheeled vehicles on rails

3.3.4 tramway US: streetcar

local transport system for guided passage of wheeled vehicles on rails

SIST ISO 6707-1:2015

ISO 6707-1:2014(E)

3.3.5

aerial ropeway

US: **cableway** US: lift

local transport system for guided passage of cabins or containers carried on *cables* (6.4.54) on intermediate supports

3.3.6

underground railway

US: subway

railway (3.3.3) that operates mainly below ground level (9.2.33)

3.3.7

mass transit railway

railway (3.3.3) for the rapid movement of high passenger load densities in urban areas

3.3.8

monorail

railway (3.3.3) that has a single running rail with beam (5.1.11) support

3.3.9

track

assembly (5.5.5) of rails, *fastenings* (5.5.72), and support, for passage of vehicles

3.3.10

sleeper US: tie

iTeh STANDARD PREVIEW

member providing vertical and lateral support to rails of a railway (3.3.3) or tramway (3.3.4)

Note 1 to entry: In the US, there is a homograph for the term "tie". See <u>5.1.22</u>.

3.3.11

https://standards.iteh.ai/catalog/standards/sist/aa202dd5-e13b-408c-b50daf6d8aa3a82f/sist-iso-6707-1-2015

airfield af6d8aa3a82f/sist-iso-6707-1-2015 defined area including any *buildings* (3.1.3), *installations* (5.4.3), and equipment, for the arrival, departure, and movement of aircraft

3.3.12

airport

area containing an *airfield* (3.3.11) and facilities for handling passengers and cargo

3.3.13

noise barrier

structure (3.1.4) provided to deflect and absorb noise

Note 1 to entry: In the US, there is a homograph for the term "noise barrier". See <u>3.3.14</u>.

3.3.14 noise bund US: **noise barrier** US: sound barrier *noise barrier* (3.3.13) in the form of an *embankment* (3.2.3)

Note 1 to entry: In the US, there is a homograph for the term "noise barrier". See <u>3.3.13</u>.

3.3.15 subgrade

upper part of the *soil* (6.2.2), natural or constructed, that supports the *loads* (9.3.19) transmitted by the overlying *structure* (5.1.2) of a *road* (3.3.1), runway, or similar hard surface

3.3.16 road formation US: grade

surface of *subgrade* (3.3.15) in its final shape after completion of *earthwork* (7.1.6)

Note 1 to entry: In the US, there is a homograph for the term "grade". See <u>9.2.33</u>.

3.3.17

pavement

road (3.3.1), runway, or similar construction (5.5.6) above the subgrade (3.3.15)

3.3.18

tunnel

horizontal or sloping underground enclosed way of some *length* (9.2.18)

3.3.19

bridge

civil engineering works (3.1.2) that affords passage to pedestrians, animals, vehicles, and *services* (5.4.1) above obstacles or between two points at a *height* (9.2.20) above *ground* (6.2.1)

Note 1 to entry: In the US, there is a homograph for the term "bridge". See <u>7.3.10</u>.

3.3.20

arch bridge

bridge (3.3.19) that has one or more *arches* (5.1.7) as its main *structure* (5.1.2)

iTeh STANDARD PREVIEW

3.3.21 bow string bridge

bridge (3.3.19) that has an arch (5.1.7) and its the (5.1.22) as the main structure (5.1.2)

3.3.22

SIST ISO 6707-1:2015

cantilever bridge https://standards.iteh.ai/catalog/standards/sist/aa202dd5-e13b-408c-b50dbridge (3.3.19), the main structural members (5.1.3) of which are cantilevers (5.1.17)

3.3.23

cable stayed bridge

bridge (3.3.19), the main *structural members* (5.1.3) of which are the *beams* (5.1.11) for the *deck* (5.1.35) supported by a tower and one or more inclined *cables* (6.4.54) connected to the top or the shaft of the tower

3.3.24

suspension bridge

bridge (3.3.19), the main *structural members* (5.1.3) of which are catenary *cables* (6.4.54) from which the *deck* (5.1.35) is suspended

3.3.25

floating bridge *bridge* (3.3.19) supported by water

3.3.26

movable bridge

bridge (3.3.19) over a waterway, the *deck* (5.1.35) of which can be moved

3.3.27

bascule bridge

movable bridge (3.3.26), the *deck* (5.1.35) of which is counterbalanced and hinged on a horizontal axis

3.3.28 vertical lift bridge

US: drawbridge

movable bridge (3.3.26), the deck (5.1.35) of which can be raised vertically