

SLOVENSKI STANDARD
oSIST prEN 15611:2018
01-oktober-2018

Železniške naprave - Zavore - Ventili za kontrolo tlaka

Railway applications - Braking - Relay valves

Bahnanwendungen - Bremse - Relaisventile

Applications ferroviaires - Freinage - Relais pneumatiques

Ta slovenski standard je istoveten z: prEN 15611

<https://standards.iteh.ai/catalog/standards/sist/44f10272-308d-4a9f-b2de-fba24a8ea64e/sist-en-15611-2020>

ICS:

23.060.99	Drugi ventili	Other valves
45.040	Materiali in deli za železniško tehniko	Materials and components for railway engineering

oSIST prEN 15611:2018

en,fr,de

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

DRAFT
prEN 15611

August 2018

ICS 45.040

Will supersede EN 15611:2008+A1:2010

English Version

Railway applications - Braking - Relay valves

Applications ferroviaires - Freinage - Relais
pneumatiques

Bahnanwendungen - Bremse - Relaisventile

This draft European Standard is submitted to CEN members for enquiry. It has been drawn up by the Technical Committee CEN/TC 256.

If this draft becomes a European Standard, CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

This draft European Standard was established by CEN in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

<https://standards.cen.eu/catalog/standards/sist/44f10272-308d-4a9f-b2de-fba24a8ea64e/sist-15611-2018>

Warning : This document is not a European Standard. It is distributed for review and comments. It is subject to change without notice and shall not be referred to as a European Standard.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

Page

European foreword.....	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Symbols and abbreviations	10
5 Design and manufacture.....	10
5.1 General.....	10
5.2 Functional requirements.....	11
5.2.1 General.....	11
5.2.2 Minimum output pressure.....	11
5.2.3 Accuracy of the output pressure and changeover.....	12
5.2.4 Control signal characteristics (types B1, B2, C1, C2, C1D, C2D, E)	13
5.2.5 Enabling of a change of relay valve ratio during brake application of a relay valve of type B1	14
5.2.6 Prevention of a change of relay valve ratio during brake application of a relay valve of type B2 and a variable load relay valve, types C1, C2, C1D, C2D, E.....	14
5.2.7 Kinked characteristic of a variable load relay valve (type E)	14
5.2.8 Interaction of a relay valve and a distributor valve	14
5.2.9 Hysteresis.....	16
5.2.10 Sensitivity	16
5.2.11 Flow	16
5.2.12 Tightness.....	16
5.2.13 Change of relay valve ratio	16
5.3 Shock and vibration	17
5.4 Environmental conditions	17
5.4.1 General.....	17
5.4.2 Temperature.....	17
5.4.3 Other environmental conditions.....	17
5.5 Compressed air quality	19
5.6 Service life.....	19
5.7 Fire behaviour.....	19
5.8 External appearance	20
5.9 Design requirements regarding pressure stress.....	20
5.10 Interface	20
5.10.1 General.....	20
5.10.2 Mechanical.....	20
5.10.3 Pneumatic.....	20
6 Materials.....	20
7 Type tests	20
7.1 General.....	20
7.2 Type test of an individual relay valve.....	21
7.2.1 Test bench for individual relay valves	21
7.2.2 Sampling for type tests.....	23
7.2.3 Test temperature and air quality	23

7.2.4	Procedure for type tests.....	23
8	In-service assessment.....	46
9	Designation	47
10	Identification and marking	47
Annex A	(informative) In-service assessment.....	48
A.1	General	48
A.2	Test set-up and sampling.....	48
A.3	Procedure	48
A.4	Pass/fail criteria	48
Annex ZA	(informative) Relationship between this European Standard and the essential requirements of Directive 2008/57/EC aimed to be covered.....	49
Bibliography	51

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 15611:2020

<https://standards.iteh.ai/catalog/standards/sist/44f10272-308d-4a9f-b2de-fba24a8ea64e/sist-en-15611-2020>

prEN 15611:2018 (E)**European foreword**

This document (prEN 15611:2018) has been prepared by Technical Committee CEN/TC 256 “Railway applications”, the secretariat of which is held by DIN.

This document is currently submitted to the CEN Enquiry.

This document will supersede EN 15611:2008+A1:2010.

This document has been prepared under a standardization request given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive 2008/57/EC.

For relationship with EU Directive 2008/57/EC, see informative Annex ZA, which is an integral part of this document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 15611:2020

<https://standards.iteh.ai/catalog/standards/sist/44f10272-308d-4a9f-b2de-fba24a8ea64e/sist-en-15611-2020>

1 Scope

This document is applicable to relay valves designated to control the brake cylinder pressure of compressed air brakes fitted to railway vehicles, in association with an air brake distributor valve or other control device. It covers one stage relay valves and relay valves adjusting the brake cylinder pressure in response to a change in vehicle speed or load that is either continuously variable or in two or more stages, i.e. empty – loaded.

Relay valves operating with other pressures, in particular the brake pipe pressure, are not included.

This document specifies the requirements for the design, manufacture and testing of relay valves.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 14478, *Railway applications – Braking - Generic vocabulary*

EN 15355, *Railway applications – Braking - Distributor valves and distributor-isolating devices*

EN 15625, *Railway applications – Braking - Automatic variable load sensing devices*

EN 45545-1, *Railway applications - Fire protection on railway vehicles – Part 1: General*

EN 45545-2, *Railway applications - Fire protection on railway vehicles – Part 2: Requirements for fire behaviour of materials and components*

EN 50125-1, *Railway applications - Environmental conditions for equipment – Part 1: Rolling stock and on-board equipment*

EN 60721-3-5:1997, *Classification of environmental conditions – Part 3: Classification of groups of environmental parameters and their severities – Section 5: Ground vehicle installations (IEC 60721-3-5:1997)*

EN 61373:2010, *Railway applications - Rolling stock equipment - Shock and vibration tests (IEC 61373:2010)*

EN ISO 228-1, *Pipe threads where pressure-tight joints are not made on the threads – Part 1: Dimensions, tolerances and designation (ISO 228-1:2000)*

ISO 8573-1:2010, *Compressed air – Part 1: Contaminants and purity classes*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 14478, EN 15355 and the following apply.


ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

relay valve

device, the main function of which is to control a pneumatic output pressure as a function of the variation of one or more input pressures (see Figure 1)



Key

- 1 first input pressure
- 2 second input pressure
- 3 third input pressure
- 4 control signal – continuous load sensing pressure (*Lcp*), or control signal – empty/load signal pressure (*Lsp*), or mechanical input (lever) or electrical input
- 5 auxiliary reservoir pressure, supply pressure (AR)
- 6 output pressure
- 7 relay valve

Figure 1 — Relay valve, pressures and signals

3.2

input pressure

control pressure received by the relay valve

Note 1 to entry: Pressure generally considered as being the output pressure from a distributor or a brake control unit; sometimes referred to as pilot pressure or dummy brake cylinder pressure.

3.3

output pressure

pressure output from the relay valve, generally considered as being the brake cylinder pressure

Note 1 to entry: This pressure can also be used as the input pressure to another relay valve. The output pressure can obtain one or more fixed levels or it can be changed continuously between a minimum and a maximum or vice versa.

3.4

relay valve ratio

ratio of the output pressure value to input pressure value

3.5**control signal**

signal used to change the relay valve ratio:

- received from the continuous load sensing device (L_{cp}),
- received from empty-loaded changeover device (L_{sp}),
- generated by the position of mechanical changeover,
- generated by other means, e.g. speed dependent

3.6**relay valve type A**

relay valve with one fixed relay valve ratio, where the ratio can be less (step-down), equal or greater (step-up) than 1

3.7**relay valve type B1**

relay valve with two or more fixed relay valve ratios that can change during a brake application, where the ratio can be less (step-down), equal or greater (step-up) than 1

Note 1 to entry: Typically two stages “empty/load” relay valve, giving an empty (tare) or a loaded output pressure proportional to input pressure dependant on the load signal input and used on vehicles operated in empty or fully loaded condition. Alternatively the ratio can be changed in function of speed.

3.8**relay valve type B2**

relay valve with two or more fixed relay valve ratios that cannot change during a brake application, where the ratio can be less (step-down), equal or greater (step-up) than 1

Note 1 to entry: Typically two stage “empty/load” relay valve, giving an empty (tare) or a loaded output pressure proportional to input pressure dependant on the load signal input. Blocking the relay valve ratio during brake application is typically used to avoid frequent changeovers taking place on vehicles operated near the changeover weight.

3.9**relay valve type C1**

one stage relay valve with a continuously changeable relay valve ratio, where a load signal is used to change the ratio

3.10**relay valve type C2**

relay valve with a continuously changeable relay valve ratio, where a load signal is used to change the ratio and with a multi-stage feature added

Note 1 to entry: Typically a load signal is used to change the relay valve ratio and a control signal (automatic or manual) is used to change the stage(s). The typical result is that at the same load and input pressure, in the lower stage (e.g. P-mode, passenger train) results a lower output pressure and in a higher stage (e.g. R-mode, rapid passenger train) this results in a higher output pressure.

prEN 15611:2018 (E)**3.11****function D for a relay valve**

overlay function to relay valve type A, C1, C2 with two or more input pressures

Note 1 to entry: In this case the type of the relay valve is resp. AD, C1D and C2D.

3.12**relay valve type E**

variable load relay valve with a special, non-linear characteristic, which automatically comes into operation when the vehicle has more than a certain load

Note 1 to entry: The E type may be a combination of a C1 or C2 type and an additional functional block, or may be a specific generic design. This function reduces (in comparison with a linear characteristic) the output pressure for low input pressures to a certain level to limit the heat impact to the wheels during continuous braking.

3.13**sensitivity**

change of input pressure causing a variation of output pressure, when the change of input pressure is in the same direction, with no overshoot or reversal

3.14**initial sensitivity**


change of input pressure, starting at 0 bar which causes the output pressure to start increasing (see Figure 2)

3.15**sensitivity at reversal**

change of input pressure causing a variation of output pressure, when the input pressure is changing from increasing to decreasing (see Figure 2)

3.16**hysteresis**

difference in output pressure with the same input pressure, first rising to a value and then, having been taken past that value, subsequently falls to the same value (see Figure 2)

**Key**

- 1 initial sensitivity
- 2 hysteresis
- 3 sensitivity at reversal

NOTE The figure is simplified for illustrative purposes, e.g. the real pressure development is not shown.

Figure 2 — Hysteresis and sensitivity

3.17**normal litre**

unit of amount of a gas equal to the amount of 1 l at a pressure of 1 atmosphere and at a standard temperature, at 20 °C

<https://standards.iteh.ai/catalog/standards/sist/44f10272-308d-4a9f-b2de-fba24a8ea64e/sist-15611-2018>

Note 1 to entry: Air flow is often stated in normal litres per minute (Nl/min).

3.18**matched pair**

combination of a distributor valve and one or more relay valves to achieve specific tolerances of brake cylinder pressure and timings

Note 1 to entry: The combination is usually kept together throughout the lifetime of the components.

4 Symbols and abbreviations

Table 1 — Symbols and abbreviations

Symbol	Designation	Unit
B_{cp}	brake cylinder pressure	bar
L_{cp}	control signal – continuous load sensing pressure	bar
L_{sp}	control signal – empty/load signal pressure	bar
p	pressure	bar
p_i	input pressure	bar
p_o	output pressure	bar
t	time	s
AR	auxiliary reservoir pressure, supply pressure	bar

5 Design and manufacture

5.1 General

A relay valve shall enable a distributor valve or a brake control unit to be used without any vehicle specific modification to the distributor or the brake control unit, related to the brake cylinder volume. This includes the independence of the brake application and release times, the inshot feature and the output pressure development for any output (brake cylinder and piping) volume.

The use of a relay valve shall not alter any of the characteristics of the distributor and/or a brake control unit that are not specified in this standard.

The use of a relay valve shall enable the brake cylinder pressure to be maintained between prescribed limits. These limits may be defined by different brake modes or speed-dependent requirements or where there is a requirement to maintain a nominal constant brake performance irrespective of load.

Table 2 below provides a description of relay valve types described in this standard with the relevant clause references.

Table 2 — Relay valve types

Basic type	Design variants	Optional additional function	Type (EN15611-2010)	Type (new)
one fixed ratio of output/input pressures	adaptable by diameters of pistons or adjustable by screw	no	A	A
		multi input for "select high"		AD
more than one fixed ratio of output/ input pressures ^a	adaptable by diameters of pistons or adjustable by screw	ratio can change during brake application	B1	B1
		ratio cannot change during brake application	B2	B2
variable load relay valve		no	C	C1
		with a multi stage feature added	C1	C2
		two input pressures for "select high"	D	C1D
		two input pressures for "select high" with a multi stage feature added	D	C2D
variable load relay valve with kinked characteristics ^b		special nonlinear characteristic (kink valve)	E	E
<p>^a A multi stage relay valve with only two stages giving output pressures corresponding to empty or laden vehicle can be named empty/load relay valve.</p> <p>^b The Etype may be a combination of a C1 or C2 type and additional functional block, or may be a specific generic design.</p>				

5.2 Functional requirements


5.2.1 General

The requirements shall be tested as given by Table 5.

5.2.2 Minimum output pressure

The specific minimum output pressure of a relay valve as response to a first brake step with an input pressure of $(0,75 \pm 0,02)$ bar shall have a fixed value, defined by its documentation.

Figure 3 gives an example of the output pressure of a relay valve for different conditions of vehicle load.

**Key**

- 1 empty condition
- 2 loaded condition
- 3 input pressure ($0,75 \pm 0,02$) bar
- 4 minimum output pressure loaded
- 5 minimum output pressure empty

NOTE The kinked characteristics is an option.

Figure 3 — Example of the output pressure p_o of a relay valve (brake cylinder pressure) in relation to the input pressure p_i for different conditions of vehicle load

5.2.3 Accuracy of the output pressure and changeover

5.2.3.1 General (all types)

The output pressure of the relay valve shall be within the following tolerances, related to the minimum (empty)/maximum (loaded) figures, given by the type plate and the installation drawing of the relay valve:

- $\pm 0,10$ bar for nominal output pressures $\leq 3,8$ bar at an input pressure of ($3,8 \pm 0,02$) bar (ratios ≤ 1);
- $\pm 0,15$ bar for nominal output pressures $> 3,8$ bar at an input pressure of ($3,8 \pm 0,02$) bar (ratios > 1).

A relay valve may change from a ratio < 1 in empty to > 1 in loaded status.

5.2.3.2 Accuracy of the changeover of a multi-stage relay valve (types B1 and B2)

The relay valve shall be designed to changeover from the empty (low), to intermediate (if applicable), and to the loaded (high) condition and reverse, as defined in 5.2.4, at specified values of the control signal such as load signal pressure or load sensing pressure (L_{sp}/L_{cp}) or with a mechanical changeover. The accuracy of the changeover shall be tested in accordance with 7.2.4.4 (types B1 and B2).

5.2.3.3 Accuracy of the changeover of a variable load relay valve with a multi-stage function overlaid to the variable load brake function (types C2 and C2D)

It shall be possible at any input pressure and any load control pressure (L_{cp}) to change from a lower to a higher level of the output pressure or vice versa.

The ratio of the output to the input pressures between the higher value of the output pressure to the lower value shall be constant between initial and full service and within a tolerance of $\pm 10\%$ for every load condition; this condition is related to a nominal input pressure of 3,8 bar and shall be initiated by a pneumatic or electric control signal.

5.2.3.4 Accuracy of the output pressure of a relay valve designed for two or more input pressures (types AD, C1D and C2D)

The output pressure of the relay valve shall correspond to the highest of the input pressures. The tolerance of the maximum output pressure values shall be $\pm 0,1$ bar, if the nominal value is $\leq 3,8$ bar and $\pm 0,15$ bar, if the nominal value is $> 3,8$ bar. In the case where two or more input pressures are acting simultaneously, the output pressure tolerance shall be $\pm 0,20$ bar, if the nominal value is $\leq 3,8$ bar and $\pm 0,30$ bar, if the nominal value is $> 3,8$ bar.

5.2.3.5 Accuracy of the output pressure in relation to the load control pressure (types C1, C2, C1D, C2D)

For relay valves C1, C2 the differences of the output pressure, when load control pressure (L_{cp}) has been increased or decreased, shall not exceed 0,20 bar if the ratio is ≤ 1 and 0,30 bar if the ratio is > 1 .

For a relay valve type C1D, C2D, the differences when load control pressure (L_{cp}) has been increased or decreased shall not exceed 0,25 bar if the ratio is ≤ 1 and 0,3 bar if the ratio is > 1 .

For relay valves C1, C2, C1D, C2D in case that the quotient $\Delta B_{cp}/\Delta L_{cp}$ is greater than 1, the differences when load control pressure (L_{cp}) has been increased or decreased shall not exceed 0,3 bar if the quotient is ≤ 1 and 0,4 bar if the ratio is > 1 .

5.2.4 Control signal characteristics (types B1, B2, C1, C2, C1D, C2D, E)

The design of the relay valve shall allow interaction with at least one of the following load signal types:

- a) manual empty-load signal, where this signal is provided by a lever, either mounted directly on the relay valve, or remotely operated on the vehicle to manually change from the low to the high output pressure, or vice versa;
- b) pneumatic empty/load signal, where the relay valve shall be designed to operate on receipt of the relevant signal pressure dependent on the brake system design, as follows:
 - 1) Where the control pressure L_{sp}/L_{cp} is $\leq 0,5$ bar this indicates a load that is less than the switching point and shall cause the relay valve to output its lower ratio. If L_{sp}/L_{cp} pressure is $\geq 3,0$ bar this indicates a load greater than the switching point and shall cause the relay valve to output its higher ratio. Other switching points may be defined by the design documentation.
 - 2) Where the changeover device is supplied from the B_{cp} , the load signal can either be 0 bar and shall cause relay valve to output its lower output ratio or equivalent to the brake cylinder pressure and shall cause relay valve to output its higher ratio.

NOTE The signal pressure is typically supplied as a load control signal pressure (L_{sp}) from a manually operated pneumatic device, e.g. a changeover cock, or an automatic empty-load changeover device. Alternatively it is supplied as a continuous load sensing pressure (L_{cp}).

- c) variable load signal, i.e. where the load sensing pressure (L_{cp}) comes from an automatic continuously variable load sensing device (weighing valve) giving continuous load information, see EN 15625;
- d) speed dependent or other control signal, where the pressure settings shall be defined by the design documentation.