INTERNATIONAL STANDARD

ISO/IEC 14443-3

> Second edition 2011-04-15 **AMENDMENT 6** 2014-06-01

Identification cards — Contactless integrated circuit cards — Proximity cards —

Part 3: **Initialization and anticollision**

iTeh STAMENDMENT6: Bit rates of 3fc/4, fc, (st3fc/2 and 2fc from PCD to PICC

Cartes d'identification — Cartes à circuit(s) intégré(s) sans contact — La Cartes de proximité — Cartes de proximité — La Cartes de la Cartes

17ca8502Partie 3cInitialisation et anticollision

AMENDEMENT 6: Débits binaires de 3fc/4, fc, 3fc/2 et 2fc de PCD à PICC



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 14443-3:2011/Amd 6:2014 https://standards.iteh.ai/catalog/standards/sist/c5042708-26fd-461e-b41b-17ca85028abe/iso-iec-14443-3-2011-amd-6-2014



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC | TC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 6 to ISO/IEC 14443-3:2011 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Cards and personal identification*.

iTeh STANDARD PREVIEW (standards.iteh.ai)

iTeh STANDARD PREVIEW (standards.iteh.ai)

Identification cards — Contactless integrated circuit cards — Proximity cards —

Part 3:

Initialization and anticollision

AMENDMENT 6: Bit rates of 3fc/4, fc, 3fc/2 and 2fc from PCD to PICC

Page 5, 6.1 (amended by ISO/IEC 14443-3:2011/Amd.2:2012)

Add the following after Table 1:

"For bit rates of 3fc/4, fc, 3fc/2 and 2fc see E.1."

Page 7, 6.2.1.1 (amended by ISO/IEC 14443-3:2011/Amd.2:2012)

Add the following after second paragraph:

"For bit rates of 3fc/4, Jc, 3fc/2 and 2fc see E.2.1.P.D PREVIEW

Page 9, 6.2.1.1 (amended by ISO/IEC 14443-3:2011/Amd.2:2012)

Complete the enumeration of bit rates in Table 2 by adding bit rates of 3fc/4, fc, 3fc/2 and 2fc in last row.

Page 11, 6.2.3.2.2 https://standards.iteh.ai/catalog/standards/sist/c5042708-26fd-461e-b41b-17ca85028abe/iso-iec-14443-3-2011-amd-6-2014

Add the following subclause and sentence after 6.2.3.2.2:

"6.2.3.2.3 PCD standard frame for bit rates of 3fc/4, fc, 3fc/2 and 2fc

See E.2.2.1."

Page 23, 7.1.1

Add the following below Figure 13:

"For bit rates of 3fc/4, fc, 3fc/2 and 2fc see E.2.2.3."

Page 24, 7.1.3

Add the following paragraph below Figure 14:

"For bit rates of 3fc/4, fc, 3fc/2 and 2fc see E.2.2.2."

Page 26, 7.1.4

Add the following paragraph before 7.1.5:

"For bit rates of 3fc/4, fc, 3fc/2 and 2fc see E.2.2.2."

Page 27, 7.1.5

Add the following paragraph at the end of the subclause:

"For bit rates of 3fc/4, fc, 3fc/2 and 2fc see E.2.2.2."

ISO/IEC 14443-3:2011/Amd.6:2014(E)

Page 28, 7.1.7

Add the following paragraph at the end of the subclause:

"For bit rates of 3fc/4, fc, 3fc/2 and 2fc see E.2.1.2.2."

After Annex D of ISO/IEC 14443-3:2011/Amd.2:2012

Add the following **Annex E**:

"

iTeh STANDARD PREVIEW (standards.iteh.ai)

Annex E

(normative)

Bit rates of 3fc/4, fc, 3fc/2 and 2fc from PCD to PICC

E.1 etu

The value of the etu for each bit rate is defined in Table E.1.

Table E.1 — etu

	Bit rates	etu	
	3fc/4 (~ 10,17 Mbit/s)	4/fc (~ 0,29 μs)	
	<i>fc</i> (~ 13,56 Mbit/s)	4/fc (~ 0,29 μs)	
	3fc/2 (∼ 20,34 Mbit/s)	2/fc (~ 0,15 μs)	
iT	eh ST /2fc\DARI (~ 27,12 Mbit/s)	PRF2/fgFW (~ 0,15 μs)	
,	(standards.iteh.ai)		

E.2 Frame format and timing EC 14443-3:2011/Amd 6:2014

The frame format and timing requirements are defined in 6.2 for Type A and in 7.1 for Type B.

E.2.1 Frame delay time

The frame delay time is defined as the time between two frames transmitted in opposite directions.

E.2.1.1 Frame timing PCD to PICC

This is the time between the end of the last phase modulation transmitted by the PCD and the first modulation edge transmitted by the PICC.

E.2.1.1.1 Frame delay time PCD to PICC for Type A

The FDT shall be at least 1116/fc.

E.2.1.1.2 Timing before PICC SOF for Type B

The timing before PICC SOF as specified in 7.1.6 (amended by ISO/IEC 14443-3:2011/Amd.2:2012) shall be used.

E.2.1.2 Frame timing PICC to PCD

E.2.1.2.1 Frame delay time PICC to PCD for Type A

This is the time between the last modulation transmitted by the PICC and the beginning of the first phase modulation transmitted by the PCD.

The Frame delay time PICC to PCD for Type A shall be at least 1172/fc.

E.2.1.2.2 Timing before PCD start of communication for Type B

This is the time between the end of the last character transmitted by the PICC and the beginning of the first phase modulation transmitted by the PCD.

The timing before PCD start of communication for Type B shall comply with the requirements defined in 7.1.7.

E.2.2 Frame format

E.2.2.1 Frame format for PICC Type A

The standard frame format as defined in ISO/IEC 14443-3:2011/Amd.2:2012, 6.2.3.2.1 shall be used.

Start and end of communication are specified in ISO/IEC 14443-2:2010/Amd.5.

E.2.2.2 Frame format for PICC Type B

The frame format as specified in 7.1.3 shall be used whereas the frame shall be delimited by start and end of communication as specified in ISO/IEC 14443-2:2010/Amd.5.

E.2.2.3 Character transmission format for PICC Type B

The character transmission format as specified in 7.1.1 shall be used whereas the start and stop bits shall be omitted and no character separation shall be applied. PREVIEW

(standards.iteh.ai)

iTeh STANDARD PREVIEW (standards.iteh.ai)