INTERNATIONAL STANDARD

First edition 2012-12-15

Cork — Cork stoppers for still wine — Sampling plan for the quality control of cork stoppers

Liège — Bouchons de liège pour vins tranquilles — Plan d'échantillonnage pour le contrôle qualité des bouchons de liège

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 17727:2012</u> https://standards.iteh.ai/catalog/standards/sist/19042833-279f-47c5-8fcb-156f7d706e5e/iso-17727-2012



Reference number ISO 17727:2012(E)

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 17727:2012</u> https://standards.iteh.ai/catalog/standards/sist/19042833-279f-47c5-8fcb-156f7d706e5e/iso-17727-2012



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Page

Contents

Forew	vord	i	V		
1	Scope		L		
2	Terms	s and definitions	L		
3	Initial sampling of the batch1				
4	Sampling implementation				
5	Samp 5.1	ling of stoppers for each test	2		
	5.2 5.3	Normal distribution parameters Random distribution parameters	2 3		
Biblio		7	4		

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 17727:2012</u> https://standards.iteh.ai/catalog/standards/sist/19042833-279f-47c5-8fcb-156f7d706e5e/iso-17727-2012

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17727 was prepared by Technical Committee ISO/TC 87, Cork.

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 17727:2012</u> https://standards.iteh.ai/catalog/standards/sist/19042833-279f-47c5-8fcb-156f7d706e5e/iso-17727-2012

Cork — Cork stoppers for still wine — Sampling plan for the quality control of cork stoppers

1 Scope

This International Standard describes the quality control sampling plans for the receipt and shipping of ready-to-use, cylindrical stoppers (flush with cork mouth finish) in semi-worked or finished cork used for still wines.

These plans do not apply to controls made during production.

This sampling plan applies to the following parameters, for which a standardized analysis method is available. These are the parameters which are applicable to:

- physical tests: dimensions, mass, and apparent density for agglomerate cork stoppers, moisture content, dimensional recovery after compression, extraction force, liquid tightness, and dust content [see ISO 9727 (all parts)];
- chemical tests: analysis of oxidizing residues (see ISO 21128);
- microbiological tests: enumeration of colony-forming units of yeasts, moulds, and bacteria capable
 of growth in an alcoholic medium (see ISO 10718);
- sensory analysis (see ISO 22
- the analysis of releasable 2, 4, 6-trichloroanisole (TCA) (see ISO 20752).

Type tests and validation tests are not included in this International Standard (for example global migration).

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

2.1

outer packaging

cardboard box that contains bags of stoppers

2.2

packaging

plastic bag that contains the stoppers

3 Initial sampling of the batch

The definition of a batch will vary according to the supplier, who will define this concept such that a group of stoppers is as homogeneous as possible for the characteristics evaluated.

An initial sample of *n* stoppers will be taken from a batch of *N* stoppers.

The quantity *n* of stoppers to be sampled will be the optimum amount of stoppers necessary to perform the controls: stoppers used in non-destructive tests can be reused. Controls shall be carried out in a logical order, according to this optimization criterion.

ISO 17727:2012(E)

Take a sufficient quantity so as not to have to repeat the sampling in the event that the test shall be repeated.

- a) For stoppers packaged in bags that are repackaged in cardboard boxes:
 - number of boxes constituting a batch = K;
 - sample size (for analysis) = n stoppers;
 - number of boxes to be opened: $k = \sqrt{K}$;
 - the sampling shall be taken from *k* boxes with *n/k* stoppers per box;
 - take stoppers from a single pack of each box opened.
- b) For stoppers directly packaged in large bags:
 - number of bags constituting a batch = K;
 - sample size (for analysis) = n stoppers;
 - number of bags to be opened: $k = \sqrt{K}$;
 - the sampling shall be taken from k bags with n/k stoppers per bag.

4 Sampling implementation

For microbiological analysis (see ISO 10718), the sampling shall take place under specific hygiene conditions. The list of characteristics that follow a normal random distribution includes the "Checking visual appearance compliance and anomaly count" test. This visual check shall be done first, in order to eliminate stoppers with defects.

ISO 17727:2012 https://standards.iteh.ai/catalog/standards/sist/19042833-279f-47c5-8fcb-5 Sampling of stoppers for each test/d706e5e/iso-17727-2012

5.1 General

The different parameters to be tested for the stoppers shall be treated by differentiating those following a normal distribution and those following a random distribution.

5.2 Normal distribution parameters

This affects the following parameters:

- dimensions;
- density (for agglomerate cork stoppers);
- moisture content;
- dimensional recovery;
- extraction force;
- liquid tightness;
- dust content;
- peroxide residues;
- microbiological analysis.

Number	Parameter	Sample size
	Dimensions	32
	Apparent density (agglomerate)	20
	Moisture	20
	Dimensional recovery	5
1 to 500 000	Extraction force	5
	Liquid tightness	6
	Dust	1 x 4
	Peroxide residues	1 x 4
	Microbiological analysis	1 x 8

Table 1 — Sampling plan

5.3 Random distribution parameters

This affects the following parameters:

- TCA;
- organoleptic analysis.

Number (sta	ndar Parameter ai)	Sample size				
1 40 25 000	Organoleptic analysis	32				
1 to 35 000	ISO IReleasable TCA	1 x 20				
35 001 to 150 000 ¹⁵⁶	talog/standards/sist/19042833-2/91 Organoleptic-analysis	50				
55 001 10 150 000	Releasable TCA	2 x 20				
150 001 to 500 000	Organoleptic analysis	64				
150 001 10 500 000	Releasable TCA	3 x 20				

iTeh STATable 2 Sampling plan IEW

Bibliography

- [1] ISO 2859-1, Sampling procedures for inspection by attributes Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection
- [2] ISO 9727-1, Cylindrical cork stoppers Physical tests Part 1: Determination of dimensions
- [3] ISO 9727-2, Cylindrical cork stoppers Physical tests Part 2: Determination of mass and apparent density for agglomerated cork stoppers
- [4] ISO 9727-3, Cylindrical cork stoppers Physical tests Part 3: Determination of humidity content
- [5] ISO 9727-4, Cylindrical cork stoppers Physical tests Part 4: Determination of dimensional recovery after compression
- [6] ISO 9727-5, Cylindrical cork stoppers Physical tests Part 5: Determination of extraction force
- [7] ISO 9727-6, Cylindrical cork stoppers Physical tests Part 6: Determination of liquid tightness
- [8] ISO 9727-7, Cylindrical cork stoppers Physical tests Part 7: Determination of dust content
- [9] ISO 10718, Cork stoppers Enumeration of colony-forming units of yeasts, moulds and bacteria capable of growth in an alcoholic medium
- [10] ISO 20752, Cork stoppers Determination of releasable 2, 4, 6-trichloroanisol (TCA)
- [11] ISO 21128, Cork stoppers Determination of oxidizing residues Iodometric titration method
- [12] ISO 22308, Cork stoppers Sensory analysis

https://standards.iteh.ai/catalog/standards/sist/19042833-279f-47c5-8fcb-156f7d706e5e/iso-17727-2012

iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>ISO 17727:2012</u> https://standards.iteh.ai/catalog/standards/sist/19042833-279f-47c5-8fcb-156f7d706e5e/iso-17727-2012