
**Road vehicles — Flat attachment fixing
nuts for commercial vehicles — Test
methods**

*Véhicules routiers — Écrous de fixation des roues à attache plate pour
véhicules utilitaires — Méthodes d'essai*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 10597:2012](https://standards.iteh.ai/catalog/standards/sist/430711df-eaec-40a1-8391-9c62bf3a3fdb/iso-10597-2012)

[https://standards.iteh.ai/catalog/standards/sist/430711df-eaec-40a1-8391-
9c62bf3a3fdb/iso-10597-2012](https://standards.iteh.ai/catalog/standards/sist/430711df-eaec-40a1-8391-9c62bf3a3fdb/iso-10597-2012)



iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 10597:2012

<https://standards.iteh.ai/catalog/standards/sist/430711df-eaec-40a1-8391-9c62bf3a3fdb/iso-10597-2012>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Test method for nut body	1
3.1 Proof load test procedure	1
3.2 Rejection criteria	3
4 Nut assembly test methods	4
4.1 Torque/tension — Clamping force	4
4.2 Torque/tension — Retorque	5
Bibliography	6

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 10597:2012](https://standards.iteh.ai/catalog/standards/sist/430711df-eaec-40a1-8391-9c62bf3a3fdb/iso-10597-2012)

<https://standards.iteh.ai/catalog/standards/sist/430711df-eaec-40a1-8391-9c62bf3a3fdb/iso-10597-2012>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 10597 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 19, *Wheels*.

This third edition cancels and replaces the second edition (ISO 10597:2004), of which this constitutes a minor revision.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 10597:2012](https://standards.iteh.ai/catalog/standards/sist/430711df-eacc-40a1-8391-9c62bf3a3fdb/iso-10597-2012)

<https://standards.iteh.ai/catalog/standards/sist/430711df-eacc-40a1-8391-9c62bf3a3fdb/iso-10597-2012>

Introduction

This International Standard was developed to provide test methods for evaluating flat attachment fixing nuts for use as wheel fasteners. The test methods are based on the needs of the wheel in order to function properly. These fasteners were first standardized dimensionally in ISO 7575 and this International Standard extends this standardization.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 10597:2012](https://standards.iteh.ai/catalog/standards/sist/430711df-eaec-40a1-8391-9c62bf3a3fdb/iso-10597-2012)

<https://standards.iteh.ai/catalog/standards/sist/430711df-eaec-40a1-8391-9c62bf3a3fdb/iso-10597-2012>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 10597:2012

<https://standards.iteh.ai/catalog/standards/sist/430711df-caec-40a1-8391-9c62bf3a3fdb/iso-10597-2012>

Road vehicles — Flat attachment fixing nuts for commercial vehicles — Test methods

1 Scope

This International Standard specifies test methods and performance requirements for ensuring proper wheel or rim assembly on road vehicles by means of hexagonal nuts with a flat seating captive washer used with 18 mm, 20 mm and 22 mm studs. It is applicable to commercial vehicles as defined in ISO 3833 and to those nuts as specified in ISO 7575. It is not applicable to fasteners for less common or special applications.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6157-2, *Fasteners — Surface discontinuities — Part 2: Nuts*

3 Test method for nut body

3.1 Proof load test procedure

Use only fully processed nut assemblies with required corrosion protection which are production parts intended for the vehicle.

Measure the initial height of the nut, H , before beginning the proof load/compression test.


Load the nut on a threaded fixture or bolt as shown in Figure 1 or 2. The complete nut assembly shall be loaded axially through the threads three times to a load of $0,6 \times$ proof load (F).

Measure the final height of the nut, H .

After three loadings, apply a fourth loading of $1 \times F$. The values for proof load F calculated for nuts in property class 10 shall be according to Table 1. Hold the load for 15 s.

The nut shall resist the load without failure by stripping or rupture and shall be removable by hand after the load is released. If the threads on the bolt or test fixture are damaged during the test, the test should be discarded. The test fixture or test bolt (suggested class 10.9 or higher) used shall be threaded to a tolerance class that is representative of the parts to be used in production.

It could be necessary to use a manual wrench to start the nut in motion. Such wrenching is permissible, provided that it is restricted to one half-turn and that the nut is then removable by hand.



$$D = d_{+0,40}^{+0,25}$$

where


D is the diameter of the clearance hole, in millimetres;

d is the nominal diameter of the thread, in millimetres;

Key

- 1 bolt or threaded fixture
- 2 nut assembly
- 3 fixed plate

Figure 1 — Two-piece flange nut proof/tension test arrangement



iTeh STANDARD PREVIEW
(standards.iteh.ai)

$$D = d^{+0,40}_{+0,25}$$

where

ISO 10597:2012

D is the diameter of the clearance hole, in millimetres;

d is the nominal diameter of the thread, in millimetres.

Key

- 1 bolt or threaded fixture
- 2 nut assembly
- 3 fixed plate

Figure 2 — Two-piece flange nut proof/compression test arrangement

Table 1 — Proof loads

Thread	Proof load values
	F kN
M18 × 1,5	235
M20 × 1,5	295
M22 × 1,5	360

3.2 Rejection criteria

The criteria for rejection due to cracks or other surface discontinuities shall be according to ISO 6157-2.

The permanent deformation in nut height H after unloading shall not exceed 0,13 mm.