

SLOVENSKI STANDARD SIST EN 13523-1:2017

01-maj-2017

Nadomešča: SIST EN 13523-1:2010

Prevlečene kovine, ki se navijajo - Preskusne metode - 1. del: Debelina premaza

Coil coated metals - Test methods - Part 1: Film thickness

Bandbeschichtete Metalle - Prüfverfahren - Teil 1: Schichtdicke

Tôles prélaquées - Méthodes d'essai - Partie 1 : Epaisseur du revêtement (standards.iteh.ai)

Ta slovenski standard je istoveten <u>ZSTEN EN 313523</u>-1:2017 https://standards.iteh.ai/catalog/standards/sist/22f07f53-3fe0-4e70-8e1d-

7ea9aa156931/sist on 13523 1 2017

ICS:

17.040.20Lastnosti površin25.220.60Organske prevleke

Properties of surfaces Organic coatings

SIST EN 13523-1:2017

en,fr,de



iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 13523-1:2017 https://standards.iteh.ai/catalog/standards/sist/22f07f53-3fe0-4e70-8e1d-7ea9aa15693f/sist-en-13523-1-2017

SIST EN 13523-1:2017

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 13523-1

February 2017

ICS 17.040.20; 25.220.60

Supersedes EN 13523-1:2009

English Version

Coil coated metals - Test methods - Part 1: Film thickness

Tôles prélaquées - Méthodes d'essai - Partie 1 : Épaisseur du revêtement Bandbeschichtete Metalle - Prüfverfahren - Teil 1: Schichtdicke

This European Standard was approved by CEN on 18 December 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

> SIST EN 13523-1:2017 https://standards.iteh.ai/catalog/standards/sist/22f07f53-3fe0-4e70-8e1d-7ea9aa15693f/sist-en-13523-1-2017



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

SIST EN 13523-1:2017

EN 13523-1:2017 (E)

Contents

European foreword		
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Principle	5
4.1	Method A: Measurement on a magnetic substrate - magnetic induction	5
4.2	Method B: Measurement on a non-magnetic substrate – eddy current	6
4.3	Method C: Measurement on all substrates – micrometer method	6
4.4	Method D: Measurement on all substrates – optical method	6
5	Apparatus and materials	6
6	Sampling	6
7	Test panels	6
8	Procedure	6
8.1	Calibration	6
8.1.1	General. II EN STANDARD PREVIEW	6
8.1.2	Calibration standards	7
8.2	Scale rating.	7
8.3	Measurement	7
8.3.1	Ambient conditions	7
8.3.2	Number of measurements	7
8.3.3	Method A: Magnetic induction	7
8.3.4	Method B: Eddy current	8
8.3.5	Method C: Micrometer method	8
8.3.6	Method D: Optical method	8
9	Expression of results	9
10	Accuracy	9
11	Test report	9
Bibliography 10		

European foreword

This document (EN 13523-1:2017) has been prepared by Technical Committee CEN/TC 139 "Paints and varnishes", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 2017, and conflicting national standards shall be withdrawn at the latest by August 2017.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 13523-1:2009.

The main changes are:

- a reference to EN 13523-0 concerning conditioning of the test panels was added; a)
- b) the principle clause for methods A and B have been stated more precisely;
- c) the number of measurements has been added to methods C and D;
- d) the text has been editorially revised and the normative references have been updated.
- The EN 13523 series, *Coil coated metals Test methods*, consists of the following parts:
- SIST EN 13523-1:2017 - Part 0: General introduction s.iteh.ai/catalog/standards/sist/22f07f53-3fe0-4e70-8e1d-7ea9aa15693f/sist-en-13523-1-2017
- Part 1: Film thickness
- Part 2: Gloss
- Part 3: Colour difference Instrumental comparison
- Part 4: Pencil hardness
- Part 5: Resistance to rapid deformation (impact test)
- Part 6: Adhesion after indentation (cupping test)
- Part 7: Resistance to cracking on bending (T-bend test)
- Part 8: Resistance to salt spray (fog)
- Part 9: Resistance to water immersion
- Part 10: Resistance to fluorescent UV radiation and water condensation
- *Part 11: Resistance to solvents (rubbing test)*
- Part 12: Resistance to scratching
- Part 13: Resistance to accelerated ageing by the use of heat

EN 13523-1:2017 (E)

- Part 14: Chalking (Helmen method)
- Part 15: Metamerism
- Part 16: Resistance to abrasion
- Part 17: Adhesion of strippable films
- Part 18: Resistance to staining
- Part 19: Panel design and method of atmospheric exposure testing
- Part 20: Foam adhesion
- Part 21: Evaluation of outdoor exposed panels
- Part 22: Colour difference Visual comparison
- Part 23: Resistance to humid atmospheres containing sulfur dioxide
- Part 24: Resistance to blocking and pressure marking
- Part 25: Resistance to humidity
- Part 26: Resistance to condensation of water
- (standards.iteh.ai)
- Part 27: Resistance to humid poultice (Cataplasm test)
- Part 29: Resistance to environmental soiling (Dirt pick-up and striping)
 Huns/Standards ten aveilage/standards/strip/2210/155-5120-4e70-8e1d-

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

This part of the EN 13523 series specifies the procedures for determining the dry-film thickness of an organic coating on a metallic substrate (coil coating).

Four appropriate methods are given in this European Standard:

- a) magnetic induction;
- b) eddy current;
- c) micrometer;
- d) optical.

The methods are applicable only to products with smooth and flat substrates but the coating itself may be textured. In that case, for methods a) and b) the average of a series of readings will represent an average of the thickness of the organic coating, while method c) will give the maximum thickness and method d) can provide the minimum, maximum and average thickness.

Non-destructive continuous-web methods on measurement of dry-film thickness (see EN ISO 2808) are not dealt with.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13523-0:2014. Coil coated metals - Test methods-Part 0: General introduction https://standards.iteh.ai/catalog/standards/sist/22f07f53-3fe0-4e70-8e1d-

EN 23270, Paints and varnishes and their raw materials - Temperatures and humidities for conditioning and testing (ISO 3270)

EN ISO 3611, Geometrical product specifications (GPS) - Dimensional measuring equipment: Micrometers for external measurements - Design and metrological characteristics (ISO 3611)

Terms and definitions 3

For the purposes of this document, the terms and definitions given in EN 13523-0 and the following apply.

3.1

film thickness

distance between the surface of the film and the surface of the substrate

[SOURCE: EN ISO 2808:2007, 3.3]

Principle 4

4.1 Method A: Measurement on a magnetic substrate - magnetic induction

The film thickness on a magnetic substrate is determined by means of an electromagnetic probe placed on the coating and developing an electromagnetic field. The variation of this field is a function of the distance between the probe and the substrate. This signal is measured and converted to the film thickness reading.

4.2 Method B: Measurement on a non-magnetic substrate – eddy current

The film thickness on a non-magnetic conductive substrate is determined by means of an electromagnetic probe placed on the coating and generating eddy currents in the substrate. The magnitude of the eddy currents is a function of the distance between the probe and the substrate. This measuring signal is derived from the impedance change in the probe and converted to the film thickness reading.

4.3 Method C: Measurement on all substrates - micrometer method

The film thickness is determined by measuring the coated sample and then removing the organic coating and re-measuring the sample minus the coating or by measuring a film of organic coating that has been removed from the sample.

4.4 Method D: Measurement on all substrates - optical method

The film thickness is determined by microscopical measurement of a section cut through the film. The defined cut may be made in the coating using a special blade (symmetrical cut), a special paint borer (conical bore) or a milling tool (sloping cut).

5 Apparatus and materials

5.1 Instruments for measuring film thickness, using the principles described in Clause 4.

5.2 Solvent, suitable for removing organic coatings, for example methyl ethyl ketone (2-butanone).

5.3 Suitable abrasive and/or blunt knife or other means of removing softened organic coatings that do not damage the substrate.

5.4 Cutting tool, for Method Dstandards.iteh.ai/catalog/standards/sist/22f07f53-3fe0-4e70-8e1d-7ea9aa15693f/sist-en-13523-1-2017

5.4.1 Blade, for making a symmetrical cut in the coating.

5.4.2 Paint borer, for making a conical bore in the coating.

5.4.3 Milling tool, for making a sloping cut in the coating.

6 Sampling

Shall be according to EN 13523-0.

7 Test panels

Shall be according to EN 13523-0.

8 Procedure

8.1 Calibration

8.1.1 General

For the measurement, the instructions of the manufacturer of the instrument shall be taken into account, in particular regarding the calibration and/or setting up procedure.

Before use, calibrate each instrument in accordance with the manufacturer's instructions using calibration standards. For instruments that cannot be calibrated, determine the deviation from the nominal value by comparison with calibration standards and take this into consideration for all measurements.

During use, check the calibration of the instrument as specified by the instrument's manufacturer.

8.1.2 Calibration standards

Calibration standards of known and uniform thickness are available either as foils or shims, or as coated standards with assigned values traceable to nationally recognized standards.

Calibration foils are generally made of plastics materials. They are subject to indentation and shall, therefore, be replaced frequently.

For methods A and B the surface and magnetic properties and the thickness of the metallic substrate of the coated calibration standards shall be similar to those of the test specimen.

For methods C and D the substrate of the test specimen and of the calibration standards shall be the same, provided the critical thickness (see Note) is not exceeded.

NOTE For each instrument, there is a critical thickness of metallic substrate above which instruments will not be affected by an increase in thickness.

8.2 Scale rating

For methods A and B, and if necessary, select the scale with a maximum above the estimated thickness of the coating and adjust the instrument to the thickness of a known non-metallic standard measured on the reference plate. The readings at several positions shall not vary by more than ± 5 %. The thickness of the standard shall be greater than half the measuring scale used.

8.3 Measurement

SIST EN 13523-1:2017 https://standards.iteh.ai/catalog/standards/sist/22f07f53-3fe0-4e70-8e1d-7ea9aa15693f/sist-en-13523-1-2017 8.3.1 Ambient conditions

Measure the film thickness at ambient temperature. For more accurate measurements, as required for instance in case of dispute, the temperature shall be (23 ± 2) °C and the relative humidity (50 ± 5) %, in accordance with EN 23270. Conditioning is carried out in accordance with EN 13523-0:2014, Clause 6.

8.3.2 Number of measurements

For methods A and B, take at least five measurements on smooth surfaces, and at least 10 measurements on textured coatings.

For methods C and D, it is recommended that a minimum number of five measurements is taken.

8.3.3 Method A: Magnetic induction

The samples shall be measured on a non-metallic and non-conductive table.

Place the probe perpendicular to and in contact with the coated panel and read the film thickness on the standard scale.

In the case of metallic coated steel (e.g. galvanized steel), the electromagnetic probe cannot measure simultaneously the metallic and the organic coating. Therefore, determine first the total thickness of the metallic coating and organic coating and, after having removed the organic coating, measure the thickness of the metallic coating on the same place. The difference gives the thickness of the organic coating.