

Designation: B793 - 08

Standard Specification for Zinc Casting Alloy Ingot for Sheet Metal Forming Dies and Plastic Injection Molds¹

This standard is issued under the fixed designation B793; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope*

- 1.1 This specification covers commercial zinc alloys in ingot form for remelting for the manufacture of dies and molds from the alloys as shown in Table 1.
- 1.2 This specification presents requirements for zinc alloys suitable for the production of sand cast or plaster cast forming dies for sheet metal stamping operations and plastic injection molding. Alloy A is intended for use in the fabrication of dies for sheet metal stamping under drop hammer and hydraulic pressure. Alloy B is a special purpose alloy of closely controlled composition and is primarily used in the manufacture of plastic injection molds.
- 1.3 This specification covers two zinc alloys which are specified and designated as follows:

UNS	ASTM	Traditional
Z35543	Alloy A	Kirksite A
Z35542	Alloy B	Kirksite B

1.4 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to become familiar with all hazards including those identified in the appropriate Material Safety Data Sheet (MSDS) for this product/material as provided by the manufacturer, to establish appropriate safety and health practices, and determine the applicability of regulatory limitations prior to use.

2. Referenced Documents

2.1 The following documents of the issue in effect on date of order acceptance form a part of this specification to the extent referenced herein:

2.2 ASTM Standards:²

B897 Specification for the Configuration of Zinc and Zinc Alloy Jumbo and Block Ingot

TABLE 1 Chemical and North American Color Code
Requirements^{A,B}

Tiequire in enter			
	Composition, %		
	UNS Z35543 Alloy A Kirksite A	UNS Z35542 Alloy B Kirksite B	
Color Code ^C	Green/Red	Green/Black	
Element			
Aluminum Cadmium Copper Iron Lead Magnesium Tin	3.5–4.5 0.005 max 2.5–3.5 0.100 max 0.007 max 0.02–0.10 0.005 max	3.9–4.3 0.003 max 2.5–2.9 0.075 max 0.003 max 0.02–0.05 0.001 max	
Zinc	Remainder	Remainder	

^A The following applies to all specified limits in this table: For purposes of determining conformance with this specification, the observed value or calculated value obtained from analysis shall be rounded off "to the nearest unit" in the last right hand place of figures used in expressing the specified limit, in accordance with the rounding method of Practice E29.

B899 Terminology Relating to Non-ferrous Metals and 5 Alloys 6 and 6 by 8 and

B908 Practice for the Use of Color Codes for Zinc Casting Alloy Ingot

B949 Specification for General Requirements for Zinc and Zinc Alloy Products

E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

E47 Test Methods for Chemical Analysis of Zinc Die-Casting Alloys ³

E88 Practice for Sampling Nonferrous Metals and Alloys in Cast Form for Determination of Chemical Composition

E527 Practice for Numbering Metals and Alloys in the Unified Numbering System (UNS)

E536 Test Methods for Chemical Analysis of Zinc and Zinc Alloys

3. Terminology

3.1 Terms shall be defined in accordance with Terminology B899.

¹ This specification is under the jurisdiction of ASTM Committee B02 on Nonferrous Metals and Alloys and is the direct responsibility of Subcommittee B02.04 on Zinc and Cadmium.

Current edition approved March 1, 2008. Published April 2008. Originally approved in 1988. Last previous edition approved in 2003 as B793-03. DOI: 10.1520/B0793-08.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

^B UNS designations were established in accordance with Practice E527.

^C Refer to Practice B908. (Note: Colors indicated are for North American applications.)

³ Withdrawn