# INTERNATIONAL STANDARD

ISO/IEC 24779-4

First edition 2017-01

Information technology — Crossjurisdictional and societal aspects of implementation of biometric technologies — Pictograms, icons and symbols for use with biometric systems —

iTeh STANDARD PREVIEW
Part 4:
(stringerprint applications

Technologies de l'information — Aspects sociétaux et transhttps://standards.iteh.ajoridictionnels de la mise en oeuvre des technologies biométriques pictogrammes, icônes et symboles pour utilisation avec les systèmes biométriques —

Partie 4: Applications des empreintes digitales



# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 24779-4:2017 https://standards.iteh.ai/catalog/standards/sist/38832203-45be-42b8-babd-54e3eeef49b0/iso-iec-24779-4-2017



#### COPYRIGHT PROTECTED DOCUMENT

#### © ISO/IEC 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Contents Foreword			
1	Scop	e	
2	•	native references	
3		ns and definitions	
4			
	1 <b>naiv</b> 4.1	vidual symbols, icons and pictograms  General	
	4.2	General symbol indicating fingerprint application	
	4.3	Finger/hand placement	
	4.4	Finger/hand quality feedback	
		4.4.1 Press (more or less)	
		4.4.2 Raise/lower angle	7
5	Finger/hand positioning		
	5.1	General	
	5.2	Overlay visual guidance for finger/hand orientation	
	5.3	Necessary finger/hand movement	
		5.3.1 Lateral movements 5.3.2 Forward/backward movements	
	5.4		
	5.4	Rotation 7. 1. STANDARD PREVIEW 5.4.1 General	17
		5.4.2 Rotate clockwise	17
		5.4.2 Rotate clockwise charges it characters. 5.4.3 Rotate Counter-Clockwise	18
	5.5	Change angle 5.5.1 General ISO/IEC 24779-4:2017 5.5.2 Angle Raise in General angles is 138832203-45be-42b8-babd- 5.5.3 Lower/decrease finger angles 4779-4-2017	20
		5.5.1 General 180/IFC 24 / /9-4:201 /	20
		5.5.2 Raise/increase finger angles 5.5.2 4.5.54e3eee49h0/iso-jeg-24779-4-2017	20
	5.6	5.5.3 Lower/decrease finger angles.	22
	5.6 5.7	Rolling finger(s) Testing of hand-positioning visual guidance	23
Ann		formative) <b>Usability testing approach</b>	
	ex B (in	formative) Usability study of corrective visual guidance — Lateral, forward/	
		ward and rotating movements	
Annex C (informative) Stepwise illustrations of the animation of Figure 30			34
Rihl	ingranh	NV	37

#### **Foreword**

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC ITC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see <a href="www.iso.org/directives">www.iso.org/directives</a>).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see <a href="https://www.iso.org/patents">www.iso.org/patents</a>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: <a href="https://www.iso.org/iso/foreword.html">www.iso.org/iso/foreword.html</a>.

The committee responsible for this document is ISO/IEC JTC1, *Information technology*, Subcommittee SC 37, *Biometrics*.

https://standards.iteh.ai/catalog/standards/sist/38832203-45be-42b8-babd-

A list of all parts in the ISO/IEC 24779 series can be found on the ISO website.

#### Introduction

A major public application of biometric recognition today is likely to be passports, but in the near future, it is probable that biometric recognition will be used in other public devices. These devices will be located in a variety of environments including unsupervised, a device supervised by an attendant or only partly supervised — for example, an attendant supervising a number of devices or devices observed via CCTV and an audio link. Language-independent pictograms, icons and symbols that indicate the biometric modality and illustrate actions and behaviour required will be particularly important for occasional users. In general, it is desirable for there to be more than one mode of presentation (e.g. visual and audible or tactile). Only visual presentation is addressed in ISO/IEC 24779.

It is recommended that pictograms, icons and symbols are used in the enrolment process, so that the subject becomes familiar with their meaning.

A standard family of pictograms, icons and symbols is required since in the absence of widely used standard pictograms, icons and symbols, manufacturers will adopt their own proprietary printed pictograms, icons and symbols for display on screens. This is likely to lead to confusion for public users of self-service devices.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 24779-4:2017 https://standards.iteh.ai/catalog/standards/sist/38832203-45be-42b8-babd-54e3eeef49b0/iso-iec-24779-4-2017

## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC 24779-4:2017 https://standards.iteh.ai/catalog/standards/sist/38832203-45be-42b8-babd-54e3eeef49b0/iso-iec-24779-4-2017

# Information technology — Cross-jurisdictional and societal aspects of implementation of biometric technologies — Pictograms, icons and symbols for use with biometric systems —

#### Part 4:

## Fingerprint applications

#### 1 Scope

This document contains a set of symbols, icons and pictograms to help the general public understand the concepts and procedures for using electronic systems that collect and/or process fingerprints. This set of symbols, icons and pictograms is designed to be used to

- identify the type of biometric device,
- provide static instructions related to a fingerprint device,
- display dynamic real-time information related to the fingerprint device, and
- indicate the status of the fingerprint device. s.iteh.ai)

To provide this functionality, the set of symbols, icons and pictograms includes both directional symbols, icons and pictograms and real-time action or feedback symbols, icons and pictograms. The fingerprint device symbols, icons and pictograms can be categorized as

- finger/hand general biometric,
  - kind of finger, four fingers or hand device,
- finger/hand placement,
  - biometric position and impression which needs to be presented next,
  - hand orientation (switched hands),
- finger/hand quality feedback,
  - press (more or less),
  - raise/lower angle,
- finger/hand positioning,
  - hand/finger orientation,
  - necessary finger/hand movement (forward, backward, lateral),
  - rotation,
  - change angle, and
  - rolling finger(s).

Although the symbols, icons and pictograms are presented individually, it is intended that the symbols, icons and pictograms be combined to fully illustrate the fingerprinting interaction.

#### ISO/IEC 24779-4:2017(E)

Alternative illustrations might be used; for example, in a customs or immigration environment, procedures constructed from the individual symbols, icons and pictograms could additionally be presented as

- a series of posters while waiting to use the biometric system,
- a series of transitional frames in a biometric booth,
- an animated video or series of transitional frames while waiting to use the biometric system, and
- instructional leaflets to read while waiting to use the biometric system.

This multi-part International standard focuses on communication with the data capture subject. Operators could use this International standard, but they might need additional symbols and information.

#### 2 Normative references

There are no normative references in this document.

#### 3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <a href="http://www.electropedia.org/">http://www.electropedia.org/</a>
- ISO Online browsing platform: available at <a href="http://www.iso.org/obp\_ISO/IEC 24779-4:2017">http://www.iso.org/obp\_ISO/IEC 24779-4:2017</a>

nttps://standards.iteh.ai/catalog/standards/sist/38832203-45be-42b8-babd-

4 Individual symbols, icons and pictograms<sub>c-24779-4-2017</sub>

#### 4.1 General

The symbols and icons for aiding the fingerprint presentations are shown in the following figures.

The symbols, icons and pictograms included in this clause have undergone usability testing  $^{1)}$ . The symbols, icons and pictograms were tested with representative users using two different methods. The first round of testing used interviews. Using this approach, the interviewers described the context in which the symbols, icons and pictograms were to be used and asked each participant to identify the meaning of each symbol, icon or pictogram. This testing was followed by operational testing or task-based testing where participants were asked to take actions and interact with fingerprint devices based on the symbols, icons or pictograms. A more detailed description of the testing procedures and results are presented in Annex A.

#### 4.2 General symbol indicating fingerprint application

The following symbol should be used to indicate that a fingerprint application is in place.

<sup>1)</sup> Research conducted by the National Institute of Standards and Technology (NIST).



Figure 1 — Fingerprint application [IEC 60417-6338]

On biometric systems, this symbol is used to indicate that the system is dedicated to fingerprint applications.

There should also be an indication of the finger(s) to be used. VIEW

4.3 Finger/hand placement (standards.iteh.ai)

The platen and fingers are visualized at equal value or identical line width to better convey pressing and touching, and too prevent hove ingerhals are included to reinforce hand orientation and prevent "hovering" over the platen. In the full procedure, these symbols, icons and pictograms should be accompanied by a consistent profile image (see Figures 7, 8 and 9) to reinforce pressing and not hovering.

Symbols, icons and pictograms visualizing other fingers than those shown above can be drawn equivalently.




Figure 2 — Finger/hand placement, index finger of right hand [IEC 60417-6339-1]

On biometric systems, this symbol is used to indicate that the system requests the index finger of the right hand to be placed on the platen.

A mirrored graphical symbol may be used to indicate that the system requests the index finger of the left hand to be placed on the platen.

NOTE 1 The meaning of this graphical symbol depends on its orientation.



Figure 3 — Finger/hand placement four fingers of right hand [IEC 60417-6339-2]

On biometric systems, this symbol is used to indicate that the system requests the four fingers of the right hand to be placed on the platen.

54e3eeef49b0/iso-iec-24779-4-2017

A mirrored graphical symbol may be used to indicate that the system requests the four fingers of the left hand to be placed on the platen.

NOTE 2 The meaning of this graphical symbol depends on its orientation.





Figure 4 — Finger/hand placement, thumb of right hand [IEC 60417-6339-3]

On biometric systems, this symbol is used to indicate that the system requests the thumb of the right hand to be placed on the platen.

A mirrored graphical symbol may be used to indicate that the system requests the thumb of the left hand to be placed on the platen.

NOTE 3 The meaning of this graphical symbol depends on its orientation.



## iTeh STANDARD PREVIEW (standards.iteh.ai)

Figure 5 — Finger/hand placement, thumbs of left and right hands [IEC 60417-6340-1]

https://standards.iteh.ai/catalog/standards/sist/38832203-45be-42b8-babd-On biometric systems, this symbol is used to indicate that the system requests the thumbs of the left and right hands to be placed together on the platen.




Figure 6 — Finger/hand placement, index fingers of left and right hands [IEC 60417-6340-2]

On biometric systems, this symbol is used to indicate that the system requests the index fingers of the left and right hands to be placed together on the platen.

#### 4.4 Finger/hand quality feedback

#### 4.4.1 Press (more or less)

To reinforce pressing and not hovering, each main fingerprinting symbol should be accompanied by a consistent "press" image. In the complete procedure, this has been visualized as a profile of a generalized finger or thumb, either at a downward angle, or side angle (to reflect the general orientation of the device). For a dynamic "Press more/less" indicator on the device itself, a simple + or – sign can suffice, as the device can provide more context about what is "more" or "less" required.




Figure 7 — Press IEC 60417-63411 https://standards.iten.ai/catalog/standards/sist/38832203-45be-42b8-babd-54e3eeef49b0/iso-iec-24779-4-2017

On biometric systems, this symbol is used to indicate that the system requests the finger should be placed on the platen.




Figure 8 — Increase pressure [IEC 60417-6342-1]

On biometric systems, this symbol is used to indicate that the system requests the finger/hand should be placed on the platen with increased pressure.




Figure 9 — Decrease pressure [IEC 60417-6342-2]

On biometric systems, this symbol is used to indicate that the system requests the finger/hand should be placed on the platen with decreased pressure.

### NDARD PREVIEW

#### Raise/lower angle 4.4.2

The following symbols should be used in order to indicate that the subject needs to raise or to lower the angle of the finger(s). ISO/IEC 24779-4:2017

https://standards.iteh.ai/catalog/standards/sist/38832203-45be-42b8-babd-54e3eeef49b0/iso-iec-24779-4-2017




Figure 10 — Raise angle [IEC 60417-6344-1]

On biometric systems, this symbol is used to indicate that the subject needs to raise the angle of the finger(s).