



SLOVENSKI STANDARD
kSIST ISO/FDIS 12647-5:2014
01-oktober-2014

Grafična tehnologija - Vodenje procesa izdelave rastriranih barvnih izvlečkov, preskusnih in proizvodnih odtisov - 5. del: Sitotisk

Graphic technology - Process control for the manufacture of half-tone colour separations, proof and production prints - Part 5: Screen printing

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Technologie graphique - Contrôle du processus de confection de sélections couleurs tramées, d'épreuves et de tirages - Partie 5: Sérigraphie

https://standards.iteh.ai/catalog/standards/sist/87556d9b-7a04-4431-998f-910d16b1e558/sist_iso_12647_5_2014

Ta slovenski standard je istoveten z: ISO/FDIS 12647-5

ICS:

37.100.01	Grafična tehnologija na splošno	Graphic technology in general
-----------	---------------------------------	-------------------------------

kSIST ISO/FDIS 12647-5:2014	en
------------------------------------	-----------

FINAL
DRAFT

INTERNATIONAL
STANDARD

ISO/FDIS
12647-5

ISO/TC 130

Secretariat: SAC

Voting begins on:
2014-08-25

Voting terminates on:
2014-10-25

Graphic technology — Process control for the manufacture of half-tone colour separations, proof and production prints —

Part 5: Screen printing

Technologie graphique — Contrôle du processus de confection de sélections couleurs tramées, d'épreuves et de tirages —

Partie 5: Sérigraphie

SIST ISO 12647-5:2015

<https://standards.iteh.ai/catalog/standards/sist/87556d9b-7a04-4431-998f-910d46b1e558/sist-iso-12647-5-2015>

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.



Reference number
ISO/FDIS 12647-5:2014(E)

© ISO 2014

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 12647-5:2015

<https://standards.iteh.ai/catalog/standards/sist/87556d9b-7a04-4431-998f-910d46b1e558/sist-iso-12647-5-2015>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Requirements	2
4.1 Data requirements for screen printing systems.....	2
4.2 Printing forme requirements.....	2
4.3 Print production requirements.....	3
5 Test method and reporting: Control strip	5
Annex A (informative) Process control strip example	6
Annex B (normative) Correction of colourimetric data for variation in substrate colour	7
Annex C (normative) Solid patch aims for various gamut options	8
Bibliography	9

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST ISO 12647-5:2015

<https://standards.iteh.ai/catalog/standards/sist/87556d9b-7a04-4431-998f-910d46b1e558/sist-iso-12647-5-2015>

ISO/FDIS 12647-5:2014(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 130, *Graphic technology*.

ISO 12647 consists of the following parts, under the general title *Graphic technology — Process control for the manufacture of half-tone colour separations, proof and production prints*:

- *Part 1: Parameters and measurement methods*
- *Part 2: Offset lithographic processes*
- *Part 3: Coldset offset lithography on newsprint*
- *Part 4: Publication gravure printing*
- *Part 5: Screen printing*
- *Part 6: Flexographic printing*
- *Part 7: Proofing processes working directly from digital data*
- *Part 8: Validation print processes working directly from digital data*

Introduction

Historically, this International Standard established the process control parameters and their aim values and tolerances for the most important professional printing processes of the graphic arts industry. The initial concept was that the groundwork for the series was laid down in ISO 12647-1. This part of the ISO 12647 series differs from that concept because screen printing has changed significantly since this International Standard was initially conceived.

This edition of this part of ISO 12647 differs from the earlier edition by not defining specific printing condition aims but instead requiring that a specific reference printing condition (characterization data set) be specified. This part of ISO 12647 requires that the colour of the printed product match a characterization data set or a printing condition agreed upon by the provider and the receiver and specifies minimum requirements and tolerances to be communicated and produced. Where specific physical parameters can impact the final result (screen angles, resolution, screen mesh, etc.), specifications and tolerances are provided for these parameters.

Because material produced by screen printing varies widely in both size and nominal viewing distance, a viewing distance metric is introduced as part of all screening and resolution requirements.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST ISO 12647-5:2015](https://standards.iteh.ai/catalog/standards/sist/87556d9b-7a04-4431-998f-910d46b1e558/sist-iso-12647-5-2015)

<https://standards.iteh.ai/catalog/standards/sist/87556d9b-7a04-4431-998f-910d46b1e558/sist-iso-12647-5-2015>

Graphic technology — Process control for the manufacture of half-tone colour separations, proof and production prints —

Part 5: Screen printing

1 Scope

This part of ISO 12647 specifies the requirements for the screen printing of four-colour process-colour material used for display, signage, and graphics using flat bed or cylinder printing equipment. Both the size and resolution of the finished product are unrestricted. The process stages included are

- data preparation and delivery,
- proof production,
- printing forme preparation, and
- production printing.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12639:2004, *Graphic technology — Prepress digital data exchange — Tag image file format for image technology (TIFF/IT)*

ISO 12647-1:2004, *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints — Part 1: Parameters and measurement methods*

ISO 12647-2:2004, *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints — Part 2: Parameters and measurement methods*

ISO 12647-7:2007, *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints — Part 7: Proofing processes working directly from digital data*

ISO 12647-8:2012, *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints — Part 8: Validation print processes working directly from digital data*

ISO 13655:2009, *Graphic technology — Spectral measurement and colorimetric computation for graphic arts images*

ISO 15930-1:2001, *Graphic technology — Prepress digital data exchange — Use of PDF — Part 1: Complete exchange using CMYK data (PDF/X-1 and PDF/X-1a)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12647-1 apply.

ISO/FDIS 12647-5:2014(E)

4 Requirements

4.1 Data requirements for screen printing systems

4.1.1 Data delivery

Screen print systems shall accept digital data delivered as PDF/X data files as defined in ISO 15930 or TIFF/IT files as defined in ISO 12639.

The intended printing condition shall be either

- 1) a published Characterized Reference Printing Condition (CRPC) as listed in the ICC registry at www.color.org, or
- 2) a custom data set where none of the available reference colour characterization data sets are considered appropriate for the intended printing because of the inks, paper, or other factors.

Where the characterization data to be used have a substrate colour (CIELAB values) that does not match the substrate to be used, the data should be adjusted using the tristimulus correction method defined in [Annex C](#).

Prior agreement as to the characterization data and substrate adjustment to be used shall be obtained between all parties involved before copy preparation work is started.

Characterization data sets are the only method recognized by this part of ISO 12647 for the proper identification of the printing condition to be used. Film and/or directly exposed screens shall be generated from digital data and legacy film should be assumed to have been prepared to some agreed upon reference characterization.

4.1.2 Data resolution

Input data should be provided at a data spacing of twice the screen ruling to be used as determined by the scaling criteria, e.g.: 140 cm⁻¹ pixels for a 70 cm⁻¹ screen ruling.

4.2 Printing forme requirements

4.2.1 Resolution

Printed material produced by screen printing varies widely in both size and nominal viewing distance. For screen printing the reference acceptable image quality criteria shall be based on a 70 cm⁻¹ screen ruling viewed at a distance of 42 cm (175 lpi at 16,5 inches). This relationship of distance and screen ruling defines when rosettes are no longer visible to a viewer with 20/20 vision (dot fusion).

This relationship should be scaled for other viewing distances or other screen rulings. For the same viewing quality at different distances, maintain the relationship of resolution to distance.

NOTE For a convenient approximation, divide either the desired distance in meters or the desired resolution in dots per centimetre into 30 to compute the other for that specific pair. This is sometimes referred to as the rule of 30.

The target resolution shall be based on an agreement between the printer and their customer. It should be in accordance with the following three criteria:

- 1) a minimum screen ruling with dots large enough to reproduce a tonal range from 1 % to 98 % using the mesh as configured, the imaging technique, the emulsion and the ink;
- 2) a minimum printed dot size that is not less than 1,5x the width of the thread diameter of the mesh;
- 3) a maximum screen ruling as recommended by the “rule of 30” for the intended viewing condition.