This document is not an ASTM standard and is intended only to provide the user of an ASTM standard an indication of what changes have been made to the previous version. Because it may not be technically possible to adequately depict all changes accurately, ASTM recommends that users consult prior editions as appropriate. In all cases only the current version of the standard as published by ASTM is to be considered the official document.



Designation: F2122-05 Designation: F 2122 - 08

An American National Standard

## Standard Practice for Treestand Safety Devices<sup>1</sup>

This standard is issued under the fixed designation F 2122; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 This practice provides guidance for providing user safety devices on treestands.

1.2The values stated are in inch-pound units and are to be regarded as the standard.

1.2 The values stated in inch-pound units are to be regarded as standard. No other units of measurement are included in this standard.

1.3 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

## 2. Referenced Documents

2.1 ASTM Standards: <sup>2</sup>

F 2121 Practice for Treestand Labels

F 2123 Practice for Treestand Instructions

F 2337 Test Method for Treestand Fall Arrest System

## 3. Terminology

3.1 The terminology and definitions in the referenced documents are applicable to this practice.

3.2 Definitions:

3.2.1 *backbar*—the adjustable, n—adjustable component of a climbing treestand or handclimber that engages the tree to provide support. The backbar may be rigid or flexible.

3.2.2 *climbing stick*—a device, *n*—device to assist climbing a tree primarily to a fixed position treestand. A structure that is secured to the tree and allows the user to support his weight and climb to the desired height on the tree.

3.2.3 *climbing treestand*. <u>n</u>—atreestand that provides both the means to ascend the tree, and allow the user to remain at a desired elevation.  $\Delta STM E2122_{-}08$ 

3.2.4 *fall arrest system*—a system, *n*—system that is assembled for the purpose of arresting an accidental fall of its user. A FAS consists of a full body harness, lanyard, anchorage means, and connecting.

3.2.5 *full body harness, n*—acomponent with a design of straps that is fastened about the person in a manner so as to contain the torso and distribute the fall arrest forces over at least the upper thighs, pelvis, chest, and shoulders, with means for attaching it to other components or subsystems.

3.2.6 *handclimber, or climbing aid*—a device, <u>n</u>—device to assist climbing with a climbing treestand. A structure that allows the user to support his weight when lifting a climbing treestand with his legs.

3.2.7 integral seat, <u>n</u>—atreestand seat which is attached to the base (where the user stands) platform.

3.2.8 *ladder treestand*, <u>n</u>—atreestand that is secured to the tree at the elevation where the platform is located. (The ladder treestand may be secured to the tree at other locations and has steps that are used to reach the platform or hunting position.)

3.2.9 *non-climbing, fixed position or hang-on treestand, n*—atreestand that is secured to the tree at the elevation where it is used. (The user usually ascends the tree by some means and then lifts the treestand to the desired position and secures it for use.)

3.2.10 *platform*—the horizontal, *n*—horizontal structural area of a treestand on which the user stands and/or places his feet.

3.2.11 tripod or tower stand—a tripod or tower stand is constructed to be self-supporting and is not required to be secured to a tree. suspension relief device, *n*—device to allow relief of a person's weight on the lower extremities if suspended in a harness. The device is to help maintain circulation in the legs and help prevent suspension trauma (blood pooling).

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States.

<sup>&</sup>lt;sup>1</sup> This practice is under the jurisdiction of ASTM Committee F08 on Sports Equipment and Facilities and is the direct responsibility of Subcommittee F08.16 on Archery Products.

Current edition approved Oet:<u>April</u> 1, 2005:2008. Published October 2005:<u>April 2008.</u> Originally approved in 2001. Last previous edition approved in 20012005 as F 2122 - 015.

<sup>&</sup>lt;sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.