



SLOVENSKI STANDARD SIST EN 521:2019

01-junij-2019

Nadomešča:
SIST EN 521:2006

Specifikacije za plinske aparate na utekočinjeni naftni plin - Prenosni aparati, ki delujejo s tlakom uparjenega plina

Specifications for dedicated liquefied petroleum gas appliances - Portable vapour pressure liquefied petroleum gas appliances

Festlegungen für Flüssiggasgeräte Tragbare, mit Dampfdruck betriebene Flüssiggasgeräte

(standards.iteh.ai)

Spécifications pour les appareils fonctionnant exclusivement aux gaz de pétrole liquéfiés - Appareils portatifs alimentés à la pression de vapeur des gaz de pétrole liquéfiés

Ta slovenski standard je istoveten z: EN 521:2019

ICS:

27.060.20 Plinski gorilniki Gas fuel burners

SIST EN 521:2019 en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 521:2019](#)

<https://standards.iteh.ai/catalog/standards/sist/a2318112-dec6-4b5f-8c65-29582b6114d4/sist-en-521-2019>

EUROPEAN STANDARD

EN 521

NORME EUROPÉENNE

EUROPÄISCHE NORM

April 2019

ICS 27.060.20

Supersedes EN 521:2006

English Version

Specifications for dedicated liquefied petroleum gas appliances - Portable vapour pressure liquefied petroleum gas appliances

Spécifications pour les appareils fonctionnant
exclusivement aux gaz de pétrole liquéfiés - Appareils
portatifs alimentés à la pression de vapeur des gaz de
pétrole liquéfiés

Festlegungen für Flüssiggasgeräte - Tragbare, mit
Dampfdruck betriebene Flüssiggasgeräte

This European Standard was approved by CEN on 15 February 2019.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword.....	5
1 Scope	6
2 Normative references	7
3 Terms and definitions	7
4 Classification	11
4.1 Classification of gases.....	11
4.2 Categories of appliances.....	12
5 Safety requirements	12
5.1 General.....	12
5.2 Adjustment of the burner.....	12
5.3 Materials.....	12
5.4 Assembly, cleaning and maintenance.....	12
5.4.1 Assembly.....	12
5.4.2 Cleaning, maintenance.....	13
5.5 Strength and stability.....	13
5.5.1 Strength.....	13
5.5.2 Stability.....	13
5.6 Soundness of the gas circuit assembly.....	14
5.7 Connections.....	14
5.7.1 General.....	14
5.7.2 Appliances intended to be directly fitted to the gas cartridge or gas cylinder.....	14
5.8 Transport, fixing and mobility devices.....	16
5.9 Taps.....	16
5.9.1 General.....	16
5.9.2 Needle valves.....	16
5.10 Control handles.....	17
5.10.1 Construction.....	17
5.10.2 Marking.....	17
5.11 Injectors.....	18
5.12 Ignition devices.....	18
5.13 Flame supervision devices.....	18
5.14 Burners and radiant elements.....	19
5.15 Grids.....	19
5.15.1 General.....	19
5.15.2 Grid with a rigid useful area.....	19
5.16 Turnspit.....	19
5.17 Fireguards for heating appliances.....	20
5.18 Locations and compartments for gas cartridge or gas cylinder.....	20
5.18.1 Compartments for gas cylinder.....	20
5.18.2 Compartment for gas cartridge.....	21
5.19 Heat input.....	21
5.20 Resistance to overheating.....	21
5.21 Temperature of various parts of the appliance.....	21
5.21.1 Floor standing or table standing appliances.....	21
5.21.2 Appliances designed to be held during use.....	22

5.22	Temperature of panels (floors, walls or ceilings).....	22
5.22.1	Floor and table standing appliances.....	22
5.22.2	Appliances intended for suspension	22
5.23	Ignition, crosslighting and flame stability.....	22
5.24	Resistance to draught.....	23
5.25	Resistance to liquid spillage	23
5.26	Combustion	23
5.27	Accumulation of un-burnt gas.....	23
5.28	Safety at high temperature.....	23
5.29	Sooting - condensation.....	23
5.30	Rational use of energy.....	23
5.30.1	Efficiency of stove burners.....	23
5.31	Durability of markings.....	24
5.32	Strength and endurance requirements	24
6	Test methods.....	24
6.1	General	24
6.1.1	Test gases.....	24
6.1.2	Test conditions	25
6.1.3	Test gases and pressures	25
6.1.4	Test vessel.....	26
6.2	Adjustment of the burner	26
6.3	Materials	26
6.4	Assembly, cleaning and maintenance	26
6.5	Strength and stability.....	26
6.5.1	Strength.....	26
6.5.2	Stability	27
6.6	Soundness of the gas circuit assembly.....	28
6.6.1	Soundness of the appliance.....	28
6.6.2	Soundness of flexible tube connections.....	29
6.6.3	Soundness of burner assemblies	29
6.7	Connections	29
6.7.1	General	29
6.7.2	Appliances directly connected to gas cartridge or gas cylinder.....	29
6.8	Transport, fixing and mobility devices.....	30
6.9	Taps	30
6.10	Control handles	30
6.11	Injectors	31
6.12	Ignition devices	31
6.13	Flame supervision devices.....	31
6.13.1	General	31
6.13.2	Ignition delay time	31
6.13.3	Extinction delay time.....	31
6.14	Burners and radiant elements.....	31
6.15	Grids	31
6.16	Turnspit.....	31
6.17	Fireguards for heating appliances.....	32
6.17.1	Strength of fireguards	32
6.17.2	Dimensions	32
6.18	Locations and compartments for gas cartridge or gas cylinder	32
6.19	Verification of heat inputs.....	32
6.19.1	Test	32
6.19.2	Calculation of heat inputs.....	33

6.20	Resistance to overheating.....	33
6.21	Temperatures of the various parts of the appliance	34
6.21.1	Test installation	34
6.21.2	Test method	34
6.22	Temperature of panels (floor, wall or ceiling)	35
6.22.1	Floor standing appliances	35
6.22.2	Fixed appliances	35
6.23	Ignition, crosslighting and flame stability	35
6.23.1	Test conditions.....	35
6.23.2	Test on individual burners, others being extinguished	36
6.23.3	Test on individual burners, others being lit.....	36
6.24	Resistance to draught.....	37
6.25	Resistance to liquid spillage.....	37
6.26	Combustion	38
6.26.1	General conditions.....	38
6.26.2	Stove burners.....	38
6.26.3	Analysis of the products of combustion	38
6.27	Accumulation of un-burnt gases	39
6.28	Safety at high temperature	39
6.29	Sooting - condensation	39
6.30	Rational use of energy	40
6.30.1	Uncovered stove burners	40
6.30.2	Covered burners.....	41
6.31	Durability of the marking.....	41
6.32	Strength and endurance test.....	42
7	Markings.....	42
7.1	Appliance marking	42
7.2	Packaging marking.....	43
8	Instructions for use, maintenance and assembly	43
8.1	General.....	43
8.2	Instruction contents.....	43
Annex A (normative)	Characteristics of test vessels (see 6.5.2.3).....	58
Annex B (normative)	Tests on needle valves (see 6.9).....	60
B.1	Resistance to temperature	60
B.2	Endurance.....	60
Annex C (informative)	Examples of authorized solutions.....	61
Bibliography	68

European foreword

This document (EN 521:2019) has been prepared by Technical Committee CEN/TC 181 “Appliances and leisure vehicle installations using liquefied petroleum gas and appliances using natural gas for outdoor use”, the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2019, and conflicting national standards shall be withdrawn at the latest by October 2019.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 521:2006.

The main changes from the 2006 version are linked to the fact that the flat gas stoves have been removed from the scope of this new version.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom. (standards.iteh.ai)

[SIST EN 521:2019](https://standards.iteh.ai/catalog/standards/sist/a2318112-dec6-4b5f-8c65-29582b6114d4/sist-en-521-2019)

<https://standards.iteh.ai/catalog/standards/sist/a2318112-dec6-4b5f-8c65-29582b6114d4/sist-en-521-2019>

EN 521:2019 (E)**1 Scope**

This document specifies the construction and performance characteristics related to safety and the rational use of energy of portable appliances burning liquefied petroleum gases at the vapour pressure within the gas cartridge or gas cylinder, excepting those where the gas cartridge is inserted horizontally in the chassis.

NOTE These appliances are referred to in the body of the text as “appliances”.

This document applies to various types of portable appliances burning liquefied petroleum gases at vapour pressure and designed to be used with cartridges as complying with EN 417 or gas cylinders.

This document covers appliances for outdoor or in well ventilated areas uses only.

For example the following types of appliances are covered:

a) cooking appliances (stoves, grills, barbecues...);

This document does not cover barbecues that can be used indoors;

b) lighting appliances;

c) heating appliances;

This document only applies to appliances with a maximum heat input of up to 3 kW (H_S) for outdoor use only;

d) blowtorches;

This document only applies to blowtorches without a flexible hose;

e) laboratory burners.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
[SIST EN 521:2019
https://standards.iteh.ai/catalog/standards/sist/a2318112-dec6-4b5f-8c65-29582b6114d4/sist-en-521-2019](https://standards.iteh.ai/catalog/standards/sist/a2318112-dec6-4b5f-8c65-29582b6114d4/sist-en-521-2019)

The requirements apply to these appliances or their functional sections whether or not the latter are independent or incorporated into an assembly.

Appliances covered by this document are not connected to a flue for the discharge of products of combustion and are not connected to the mains electricity supply.

This document covers neither appliances supplied with LPG in the liquid phase nor appliance with fixed integral container which may or may not be refilled by the user

It does not apply to lighters as defined in EN ISO 9994.

It does not apply to gas appliances operating with a valve cartridge which is horizontally integrated into the chassis of the appliance also called “flat portable gas stove”.

Requirements for rational use of energy have been included for stove burners.

However, such requirements have not been included for the other types of appliances because:

- for grills and barbecues, this is a type of cooking which is achieved by various means such as radiant elements; in addition this type of cooking varies according to the type of food and region where the appliance is used;
- for lighting appliances, the consumption is insignificant because these appliances have a very low rate and are used only for a few hours in a year;
- for heating appliances, all the heat produced is discharged into the environment;

- for tools such as blowtorches which are not professional tools in regular use, the gas consumption depends very much on the way it is used.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 30-1-1:— ¹⁾, *Domestic cooking appliances burning gas fuel — Part 1-1: Safety — General*

EN 125:2010+A1:2015, *Flame supervision devices for gas burning appliances — Thermoelectric flame supervision devices*

EN 437:2018, *Test gases — Test pressures — Appliance categories*

EN 549:1994, *Rubber materials for seals and diaphragms for gas appliances and gas equipment*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

stove

cooking appliance incorporating one or several burners and a pan support(s) designed in such a way that it(they) can support the vessels containing the food

3.2

flat portable gas stove

flat stove operating with a gas cartridge horizontally placed in the chassis for which the length or width is bigger than its height

Note 1 to entry: Figure 2 gives an example of a flat portable gas stove

3.3

vapour pressure appliance

appliance for which the pressure at the gas inlet is equal to the pressure in the gas cartridge or gas cylinder

Note 1 to entry: If the appliance is fixed directly to the gas cylinder by a rigid connection, the appliance inlet is the part of the connection that takes the gas from the cylinder. A pressure reducing device may be incorporated in the gas circuit, between the gas inlet and the injector.

Note 2 to entry: If the appliance is connected to the gas cylinder by a flexible hose, the pressure in the flexible hose once it is connected to the gas cylinder is equal to the pressure in the gas cylinder. A pressure reducing device may be incorporated in the gas circuit downstream of the flexible hose

¹⁾ Under preparation. Stage at the time of publication: prEN 30-1-1:2017

EN 521:2019 (E)**3.4****gas cylinder**

refillable or non-refillable container fitted with a valve filled with gas or a gas mixture

3.5**gas cartridge**

non-refillable container with a maximum capacity of 1 000 ml filled with gas or a gas mixture

Note 1 to entry: It may be fitted with a valve. If it is not fitted with a valve, the release of gas is carried out following perforation of the cartridge by means of a device incorporated in the appliance

3.6**cooking device**

device supplied with the appliance designed to hold or receive the food to be cooked

Note 1 to entry: Grid, turnspit, baking tray etc.

3.7**useful part of a cooking device**

part of the device in contact with food during cooking

3.8**grid**

cooking device designed to hold the food to be cooked

Note 1 to entry: Its useful component(s) can be rigid or flexible

3.9**grid with flexible useful components**

cooking device made up of two jointed components enabling tight gripping of the food to be cooked

Note 1 to entry: Each component consists of a rigid frame on which metallic wires are fixed and form a flexible mesh inside the frame distorting around the food

3.10**barbecue**

appliance designed principally to roast and/or grill food

Note 1 to entry: Cooking is carried out by radiant heat and, possibly, by convection and conduction

3.11**griddle**

part of a stove consisting of a plate placed above a burner, that allows the cooking of food by direct contact with the surface of the plate which is brought to a high temperature

3.12**stabilizer**

part of the appliance designed to increase mechanical stability

3.13**pan support**

support placed above an open stove burner and designed to support the pan to be heated

3.14**turnspit**

cooking device enabling the rotation of the food to be roasted

Note 1 to entry: The rotation can be manual or using a mechanical or electrical motor (battery)

3.15**glass panel**

glass surface or part of a glass surface allowing the inside of an enclosure to be seen

3.16**fittings**

safety devices, controlling devices or regulating devices and sub-assemblies thereof, designed to be incorporated into an appliance or to be assembled to constitute an appliance

Note 1 to entry: for example valves, flame supervision devices

Note 2 to entry: cartridge is not considered as fittings

3.17**flame supervision device**

device which, due to the presence of a flame on the sensing element, keeps open the gas flow to the burner and any pilot and which cuts off the gas supply to the burner and possibly a pilot in the event of extinction of the supervised flame

3.18**ignition delay time**

time between the ignition of the supervised flame and the moment when the effect of this flame is sufficient to keep the closing device open

3.19**extinction delay time**

time between the extinction of the supervised flame and the closure of the gas supply to the burner and possibly a pilot

3.20**tap**

controlling device, part of the appliance, designed to isolate a burner from the internal gas pipework and possibly to adjust its rate during use

3.21**control handle**

component designed to be operated manually so as to operate a control of the appliance

Note 1 to entry: e.g. a tap, thermostat etc.

3.22**gripping area**

outside part of the appliance designed to be handled during use

EN 521:2019 (E)**3.23****burner**

component that allows the gas to burn

Note 1 to entry: two types of burners are distinguished

— ignition burner: small burner whose flame is designed to light a main burner. It is referred to as “pilot” in this European Standard;

— main burner: burner designed to fulfil a thermal function of the appliance. It is referred to as “burner” in this European Standard

3.24**injector**

component part that admits the gas into a burner

Note 1 to entry: An injector is said to be calibrated when the section of the outlet orifice is fixed

3.25**ignition device**

device to ignite one or more burners directly or indirectly

3.26**primary air adjuster**

device allowing the modification of the primary air rate

Note 1 to entry: The action consisting in operating this device is termed “primary air adjustment”

3.27**means of sealing**

static or dynamic device designed to ensure leak tightness

[SIST EN 521:2019](https://standards.iteh.ai/catalog/standards/sist/a2318112-dec6-4b5f-8c65-29582b6114d4/sist-en-521-2019)

<https://standards.iteh.ai/catalog/standards/sist/a2318112-dec6-4b5f-8c65-29582b6114d4/sist-en-521-2019>

Note 1 to entry: for example: flat-faced joints, O-ring or conical joints, diaphragms, grease, pastes, putties etc.

3.28**detachable**

possible to dismantle without using a tool

3.29**removable**

removal only possible with a tool

3.30**soft solder**

solder for which the lowest temperature of the melting range, after application, is less than 450 °C

3.31**flame stability**

flames are stable at the burner ports when the phenomena of flame lift or light back do not occur

3.32**flame lift**

phenomenon characterized by the partial or total movement of the base of the flame away from the burner port

3.33**light back**

phenomenon characterized by the return of the flame inside the body of the burner

3.34**calorific value**

quantity of heat produced by the complete combustion, at a constant pressure equal to 1 013,25 mbar, of a unit volume or mass of gas, the constituents of the combustible mixture being taken at reference conditions and the products of combustion being brought back to the same conditions

Note 1 to entry: A distinction is made between:

- the gross calorific value H_s : the water produced by combustion is assumed to be condensed;
- the net calorific value H_i : the water produced by combustion is assumed to be in the vapour state

Note 2 to entry: The calorific value is expressed:

- either in megajoules per cubic metre (MJ/m³) of dry gas under the reference conditions;
- or in megajoules per kilogram (MJ/kg) of dry gas.

[SOURCE: EN 437:2018]

3.35**gas supply pressure**

difference between the static pressure measured at the gas inlet connection of the appliance and the atmospheric pressure. It is expressed in bar

4 Classification**4.1 Classification of gases**

Gases likely to be used are classified in three groups according to their pressures:

a) butane:

Mixture of hydrocarbons containing mainly butanes and butenes having a maximum pressure of 8 bar gauge at 50 °C;

b) butane-propane mixture:

Mixture of hydrocarbons containing mainly butanes, butenes, propane and propene having a pressure between 8 bar gauge and 12 bar gauge at 50 °C;

c) propane:

Mixture of hydrocarbons containing mainly propane and propene having a pressure above 12 bar gauge at 50 °C.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 521:2019](https://standards.iteh.ai/catalog/standards/sist/a2318112-dec6-4b5f-8c65-29582b6114d4/sist-en-521-2019)

<https://standards.iteh.ai/catalog/standards/sist/a2318112-dec6-4b5f-8c65-29582b6114d4/sist-en-521-2019>

EN 521:2019 (E)**4.2 Categories of appliances**

Appliances are classified in three categories according to the gases likely to be used:

- category direct pressure - butane;
- category direct pressure - butane-propane mixture;
- category direct pressure - propane.

5 Safety requirements**5.1 General**

The test methods and the means of verification are indicated in Clause 6.

The design shall make it impossible to incorrectly fit or refit any user-removable or replaceable part(s) or component(s) that can have an adverse effect on combustion or cause CO emissions to exceed limits in Clause 5.26.

5.2 Adjustment of the burner

For appliances of types a), b) and c) of the scope of this European Standard, not any adjustment of the burner shall be possible.

5.3 Materials

Non-metallic materials used as radiant elements in appliances (for example volcanic rocks, refractory blocks) shall be of a quality suitable to their use.

The quality and thickness of materials used in the construction of appliances shall be such that the constructional and performance characteristics are not altered in use. In particular all the parts of the appliance shall withstand mechanical, chemical and thermal actions to which they may be submitted during use. In normal conditions of operation, of cleaning or of adjustment, they shall not be liable to any alterations which might impair their safety.

Sheet-metal parts, not made of corrosion-resistant material, shall be effectively protected against corrosion. This requirement does not apply to grilles supporting lava rocks nor to cooking devices.

Seals and joining compounds shall have characteristics suited to their use.

Rubber based materials shall comply with EN 549:1994 class A2 minimum, and LPG resistant.

Hoses being part of the appliance shall be LPG resistant.

Copper tubing shall be used upstream of the injector only if its temperature does not exceed 100 °C when the test described in 6.21 is carried out.

Asbestos or asbestos based materials shall not be used.

5.4 Assembly, cleaning and maintenance**5.4.1 Assembly**

The entire appliance gas circuit, including the injector and flexible hoses if any, shall be factory assembled. If clamps are used, they shall be of the machine formed type. Removable clamps are not permitted.

Parts, whose assembly is carried out by the user, shall be able to be assembled correctly by following the instructions given in the instructions.

It shall not be possible to dismantle parts which are adjusted at the factory, which are not intended to be dismantled by the user and whose dismantling would affect safety, without using tools. If dismantling is possible using an open ended spanner or a screwdriver, direct access to such nuts and screw heads shall not be possible, unless they are sealed.

If a pressure reducing device is integrated in the gas circuit, it shall not be removable nor replaceable by the user.

NOTE This device can provide the functions of adjustment, opening and closing of the gas flow.

Connections shall allow the flexible hose to move freely without risk of coming into contact with a part of the appliance whose temperature rise exceeds 70 K during the test defined in 6.21 when fitted in accordance with the instructions.

5.4.2 Cleaning, maintenance

All parts of the appliance requiring frequent cleaning by the user shall be easily accessible. It shall be possible to put these parts back correctly.

There shall be no sharp corners and edges on the accessible parts of an appliance which could give rise to injury, for example during cleaning.

5.5 Strength and stability

5.5.1 Strength

5.5.1.1 General

The construction of an appliance shall be such that, during normal conditions of use:

- any displacement of parts;
- any distortion;
- any deterioration

likely to impair safe operation will not occur.

5.5.1.2 Stove pan supports

The application of a mass as described in 6.5.1.2 on the pan support shall not cause any breakage or permanent distortion of the pan support exceeding 1 mm.

5.5.1.3 Glass components

The accessible edges of glass components shall not be sharp. They shall withstand the various stresses to which they are subjected during the tests described in this European Standard without damage. In particular they shall withstand the tests described in 6.5.1.3.1 (when they are a part of the appliance) and in 6.5.1.3.2.

5.5.2 Stability

If the appliance is fitted with a foldable support, it shall be possible to lock this in the position of use (for example: stop, locking device).

If the radiant device of a barbecue or a grill can have several positions, a stop shall be provided for each of them.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 521:2019](#)

<https://standards.iteh.ai/catalog/standards/sist/a2318112-dec6-4b5f-8c65-29582b6114d4/sist-en-521-2019>