



SLOVENSKI STANDARD

SIST EN 300 175-1 V1.4.2:2003

01-december-2003

8][]HJbY]nVc`ýUbYVfYnj fj] bYHfY_ca i b]_UWYfB97HLÈG_i db]j a Ygb]_`f7 ÆÈ
%rXY. `DfY[`YX

Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1:
Overview

iTeh STANDARD PREVIEW (standards.iteh.ai)

Ta slovenski standard je istoveten z: **EN 300 175-1 Version 1.4.2**

<https://standards.iteh.ai/catalog/standards/sist/7957ca2a-e269-465c-ab05-58be1999d3f3/sist-en-300-175-1-v1-4-2-2003>

ICS:

33.070.30 Öä ää} ^/ä à[|zä ^ Digital Enhanced Cordless
à/ ^: ç|çã } ^/ä | ^ \ [{ ~ } ä ää Telecommunications (DECT)
ÖÖÖVD

SIST EN 300 175-1 V1.4.2:2003

en

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

SIST EN 300 175-1 V1.4.2:2003

<https://standards.iteh.ai/catalog/standards/sist/7957ca2a-e2b9-465c-ab05-58be1999d3f3/sist-en-300-175-1-v1-4-2-2003>

EN 300 175-1 V1.4.2 (1999-06)

European Standard (Telecommunications series)

Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 175-1 V1.4.2:2003](https://standards.iteh.ai/catalog/standards/sist/7957ca2a-e2b9-465c-ab05-58be1999d3f3/sist-en-300-175-1-v1-4-2-2003)

<https://standards.iteh.ai/catalog/standards/sist/7957ca2a-e2b9-465c-ab05-58be1999d3f3/sist-en-300-175-1-v1-4-2-2003>



Reference

REN/DECT-000129-1 (1mc90jdc.PDF)

Keywords

DECT, radio

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C

Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr

Individual copies of this ETSI deliverable
can be downloaded from

<http://www.etsi.org>

If you find errors in the present document, send your
comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999.
All rights reserved.

Contents

| | |
|---|----|
| Intellectual Property Rights | 4 |
| Foreword | 4 |
| 1 Scope | 5 |
| 2 References | 5 |
| 3 Definitions and abbreviations | 6 |
| 3.1 Definitions | 6 |
| 3.2 Abbreviations | 13 |
| 4 Structure | 16 |
| 4.1 Part 1: Overview | 16 |
| 4.2 Part 2: Physical Layer (PHL) | 16 |
| 4.3 Part 3: Medium Access Control (MAC) layer | 16 |
| 4.4 Part 4: Data Link Control (DLC) layer | 16 |
| 4.5 Part 5: Network (NWK) layer | 16 |
| 4.6 Part 6: Identities and addressing | 16 |
| 4.7 Part 7: Security features | 17 |
| 4.8 Part 8: Speech coding and transmission | 17 |
| 5 The objectives of the CI standard | 17 |
| 6 General description of the system | 18 |
| 7 Description of the protocol architecture | 19 |
| 7.1 General | 19 |
| 7.2 The DECT layered structure | 19 |
| 7.3 Physical Layer (PHL) | 19 |
| 7.4 MAC layer | 20 |
| 7.5 DLC layer | 20 |
| 7.6 Network (NWK) layer | 20 |
| 7.7 Lower Layer Management Entity (LLME) | 20 |
| 7.8 Interworking Units (IWU) | 21 |
| 8 Proprietary escapes within the CI | 21 |
| 8.1 Primary escape routes | 21 |
| 8.2 Secondary escape routes | 22 |
| 9 Levels of conformance | 22 |
| History | 23 |

STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 175-1 V1.4.2:2003

[https://standards.iteh.ai/catalog/standards/sist/7957ca2a-e2b9-465c-ab05-](https://standards.iteh.ai/catalog/standards/sist/7957ca2a-e2b9-465c-ab05-58be1999d3f3/sist-en-300-175-1-v1-4-2-2003)

[58be1999d3f3/sist-en-300-175-1-v1-4-2-2003](https://standards.iteh.ai/catalog/standards/sist/7957ca2a-e2b9-465c-ab05-58be1999d3f3/sist-en-300-175-1-v1-4-2-2003)

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Project Digital Enhanced Cordless Telecommunications (DECT).

The present document is part 1 of a multi-part EN covering the Common Interface (CI) for the Digital Enhanced Cordless Telecommunications (DECT), as identified below:

Part 1: "Overview";

Part 2: "Physical Layer (PHL)";

Part 3: "Medium Access Control (MAC) layer";

Part 4: "Data Link Control (DLC) layer";

Part 5: "Network (NWK) layer";

Part 6: "Identities and addressing";

Part 7: "Security features";

Part 8: "Speech coding and transmission".

TECHNICAL STANDARD PREVIEW
(standards.iteh.ai)
<https://standards.iteh.ai/catalog/standards/sist/7957ca2a-e2b9-465c-ab05-58be1999d3f3/sist-en-300-175-1-v1-4-2-2003>
 SIST EN 300 175-1 V1.4.2:2003

The following aspects of the present document are subject to controlled distribution:

- a) DECT identities, as defined in EN 300 175-6 [5];
- b) DECT cryptographic algorithms.

The cryptographic algorithms specify the details of the DECT standard authentication algorithm and the DECT standard cipher.

These aspects are distributed on an individual basis. Further information and details of the current distribution procedures can be obtained from the ETSI Secretariat at the address on the second page of the present document.

Further details of the DECT system may be found in ETR 015 [9], ETR 043 [11] and ETR 056 [12].

| National transposition dates | |
|--|------------------|
| Date of adoption of this EN: | 28 May 1999 |
| Date of latest announcement of this EN (doa): | 31 August 1999 |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 29 February 2000 |
| Date of withdrawal of any conflicting National Standard (dow): | 29 February 2000 |

1 Scope

The present document gives an introduction and overview of the complete Digital Enhanced Cordless Telecommunications (DECT) Common Interface (CI).

This part of the DECT CI contains an abstract of the other parts of the DECT standard together with a general description of:

- the objectives of the present document;
- the DECT CI;
- the protocol architecture of DECT.

The present document also provides an extensive vocabulary, in particular it contains the common definitions of all the technical terms used in different parts of the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- <https://standards.iteh.ai/catalog/standards/sist/7957ca2a-e2b9-465c-ab05-58ba1999d3f3/sist-en-300-175-1-v1-4-2-2003>
- [1] EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical Layer (PHL)".
 - [2] EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
 - [3] EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".
 - [4] EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
 - [5] EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".
 - [6] EN 300 175-7: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features".
 - [7] EN 300 175-8: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech coding and transmission".
 - [8] EN 300 176: "Digital Enhanced Cordless Telecommunications (DECT); Approval test specification; (Part 1: Radio; Part 2: Speech)".
 - [9] ETR 015: "Digital Enhanced Cordless Telecommunications (DECT); Reference document".
 - [10] ETR 042: "Digital Enhanced Cordless Telecommunications (DECT); A Guide to DECT features that influence the traffic capacity and the maintenance of high radio link transmission quality, including the results of simulations".

- [11] ETR 043: "Digital Enhanced Cordless Telecommunications (DECT); Common interface; Services and facilities requirements specification".
- [12] ETR 056: "Digital Enhanced Cordless Telecommunications (DECT); System description document".
- [13] EN 300 403-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".
- [14] CEPT Recommendation T/SGT SF2 (89) 6/0: "Draft Recommendation T/SF Services and Facilities of Digital European Cordless Telecommunications".
- [15] CCIR Report 662 (1978): "Definition of spectrum use and efficiency".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

antenna diversity: diversity implies that the Radio Fixed Part (RFP) for each bearer independently can select different antenna properties such as gain, polarization, coverage patterns, and other features that may effect the practical coverage. A typical example is space diversity, provided by two vertically polarized antennas separated by 10 - 20 cm.

attach: process whereby a Portable Part (PP) within the coverage area of a Fixed Part (FP) to which it has access rights, notifies the FP that it is operative. The reverse process is detach, which reports the PP as inoperative.

NOTE 1: An operative PP is assumed to be ready to receive calls.

authentication (of a subscriber): process whereby a DECT subscriber is positively verified to be a legitimate user of a particular FP.

NOTE 2: Authentication is generally performed at call set-up, but may also be done at any other time (e.g. during a call).

bearer: see Medium Access Control (MAC) bearer or bearer service.

bearer handover: internal handover process provided by the MAC layer, whereby one MAC connection can modify its underlying bearers while maintaining the service provided to the Data Link Control (DLC) layer.

NOTE 3: Bearer handover is slot based.

bearer service: type of telecommunication service that provides a defined capability for the transmission of signals between user-network interfaces.

NOTE 4: The DECT user-network interface corresponds to the top of the DECT network layer (layer 3).

broadcast: simplex point-to-multipoint mode of transmission.

NOTE 5: The transmitter may disregard the presence or absence of receivers.

C-plane: control plane of the DECT protocol stacks, which contains all of the internal DECT protocol control, but may also include some external user information.

NOTE 6: The C-plane stack always contains protocol entities up to and including the network layer.

call: all of the Network (NWK) layer processes involved in one NWK layer peer-to-peer association.

NOTE 7: Call may sometimes be used to refer to processes of all layers, since lower layer processes are implicitly required.

cell: domain served by a single antenna(e) system (including a leaky feeder) of one FP.

NOTE 8: A cell may include more than one source of radiated Radio Frequency (RF) energy (i.e. more than one radio end point).

Central Control Fixed Part (CCFP): physical grouping that contains the central elements of a FP. A FP contains a maximum of one CCFP.

NOTE 9: A CCFP controls one or more RFPs.

centrex: implementation of a private telecommunication network exchange that is not located on the premises of the private network operator. It may be co-located with, or physically a part of a public exchange.

channel: see physical channel.

cluster: logical grouping of one or more cells between which bearer handover is possible. A Cluster Control Function (CCF) controls one cluster.

NOTE 10: Internal handover to a cell which is not part of the same cluster can only be done by connection handover.

connection: see "MAC connection".

connection handover: internal handover process provided by the DLC layer, whereby one set of DLC entities (C-plane and U-plane) can re-route data from one MAC connection to a second new MAC connection, while maintaining the service provided to the NWK layer.

NOTE 11: Connection handover is DLC frame based.

Connectionless mode (C/L): transmission mode that transfers one packet (one self contained unit) of data from one source point to one (or more) destination points in a single phase.

NOTE 12: Connectionless transmissions require the peer-to-peer associations to be prearranged, and the transmission is unacknowledged at that layer.

Connection Oriented mode (C/O): transmission mode that transfers data from one source point to one or more destination points using a protocol based on three phases: "Set-up", "Data transfer" and "Release".

NOTE 13: C/O mode requires no prearranged associations between peer entities (unlike C/L mode).

Cordless Radio Fixed Part (CRFP): Wireless Relay Station (WRS) that provides independent bearer control to a PT and FT for relayed connections.

coverage area: area over which reliable communication can be established and maintained.

DECT Network (DNW): network that uses the DECT air interface to interconnect a local network to one or more portable applications. The logical boundaries of the DECT network are defined to be at the top of the DECT NWK layer.

NOTE 14: A DNW is a logical grouping that contains one or more Fixed radio Terminations (FTs) plus their associated Portable radio Termination (PT). The boundaries of the DECT network are not physical boundaries.

DLC broadcast: simplex "connectionless" mode of transmission from the DLC broadcast entity of one FT to the DLC broadcast entities in one or more PT.

NOTE 15: The transmitter may disregard the presence or absence of receivers.

DLC data link (DLC link): association between two DLC layer entities. This can either be one C-plane association or one U-plane association.

NOTE 16: This is not the same as a MAC connection.

DLC frame: format used to structure all messages that are exchanged between DLC layer peer entities.

NOTE 17: Different DLC frames are used in the C-plane and the U-plane, and there is more than one format of DLC frame in each plane.

double duplex bearer: use of two duplex bearers (see duplex bearer) which refer to the same MAC connection, sharing their simplex bearers (see simplex bearer) for the information flow.

double-simplex bearer: use of two simplex bearers operating in the same direction on two physical channels. These pairs of channels always use the same RF carrier and always use evenly spaced slots (i.e. separated by 0,5 Time Division Multiple Access (TDMA) frame).

A double-simplex bearer only exists as part of a multibearer MAC connection.

down-link: transmission in the direction FT to PT.

duplex bearer: use of two simplex bearers operating in opposite directions on two physical channels. These pairs of channels always use the same RF carrier and always use evenly spaced slots (i.e. separated by 0,5 TDMA frame).

End System (ES): logical grouping that contains application processes and supports telecommunication services.

NOTE 18: From the OSI point of view, end systems are considered as sources and sinks of information.

external handover: process of switching a call in progress from one FP to another FP.

field: continuous region of data (i.e. adjacent bits) that jointly convey information. Typically, a message will contain several fields. If data is not continuous then it is defined as two (or more) fields.

Fixed Part (DECT Fixed Part) (FP): physical grouping that contains all of the elements in the DECT network between the local network and the DECT air interface.

NOTE 19: A DECT FP contains the logical elements of at least one FT, plus additional implementation specific elements.

Fixed radio Termination (FT): logical group of functions that contains all of the DECT processes and procedures on the fixed side of the DECT air interface. (standards.iteh.ai)

NOTE 20: A FT only includes elements that are defined in EN 300 175 parts 1 to 8. This includes radio transmission elements (layer 1) together with a selection of layer 2 and layer 3 elements.

flow control: mechanism that is used to regulate the flow of data between two peer entities.

fragment: one of the Service Data Units (SDUs) that is produced by the process of fragmentation.

NOTE 21: This is not the same as a segment.

fragmentation: process of dividing a Protocol Data Unit (PDU) into more than one SDU for delivery to a lower layer. The reverse process is recombination.

NOTE 22: This is not the same as segmentation.

frame: see TDMA frame or DLC frame.

full slot (slot): one 24th of a TDMA frame which is used to support one physical channel.

generic: generalized set or general purpose set, often in the sense of basic or ordinary.

geographically unique: this term relates to FP identities, Primary Access Rights Identifiers (PARIs) and Radio Fixed Part Identifiers (RFPIs). It indicates that two FPs with the same PARI, or respectively two RFPIs with the same RFPI, can not be reached or listened to at the same geographical position.

Global NetWork (GNW): telecommunication network capable of offering a long distance telecommunication service.

NOTE 23: The term does not include legal or regulatory aspects, nor does it indicate if the network is a public or a private network.

globally unique identity: identity is unique within DECT (without geographical or other restrictions).

guard space: nominal interval between the end of a radio transmission in a given slot, and the start of a radio transmission in the next successive slot.

NOTE 24: This interval is included at the end of every slot, in order to prevent adjacent transmissions from overlapping even when they originate with slightly different timing references (e.g. from different radio end points).

half slot: one 48th of a TDMA frame which is used to support one physical channel.

handover: process of switching a call in progress from one physical channel to another physical channel. These processes can be internal (see internal handover) or external (see external handover).

NOTE 25: There are two physical forms of handover, intracell handover and intercell handover. Intracell handover is always internal, intercell handover can be internal or external.

incoming call: call received at a PP.

intercell handover: switching of a call in progress from one cell to another cell.

internal handover: handover processes that are completely internal to one FT. Internal handover reconnects the call at the lower layers, while maintaining the call at the NWK layer.

NOTE 26: The lower layer reconnection can either be at the DLC layer (see connection handover) or at the MAC layer (see bearer handover).

interoperability: capability of FPs and PPs, that enable a PP to obtain access to teleservices in more than one location area and/or from more than one operator (more than one service provider).

interoperator roaming: roaming between FP coverage areas of different operators (different service providers).

Interworking Unit (IWU): unit that is used to interconnect subnetworks.

NOTE 27: The IWU will contain the InterWorking Functions (IWF) necessary to support the required subnetwork interworking.

intracell handover: switching of a call in progress from one physical channel of one cell to another physical channel of the same cell.

intraoperator roaming: roaming between different FP coverage areas of the same operator (same service provider).

Isochronous: essential characteristic of a time-scale or a signal such that the time intervals between consecutive significant instants either have the same duration or durations that are integral multiples of the shortest duration (ITU-T Recommendation R.140: "Definition of essential terms in the field of Telegraph transmission", definition 6014).

link: see DLC data link.

Local Network (LNW): telecommunication network capable of offering local telecommunication services.

NOTE 28: The term does not include legal or regulatory aspects, nor does it indicate if the network is a public network or a private network.

locally unique identity: identity is unique within one FP or location area, depending on application.

location area: domain in which a PP may receive (and/or make) calls as a result of a single location registration.

location registration: process whereby the position of a DECT portable termination is determined to the level of one location area, and this position is updated in one or more databases.

NOTE 29: These databases are not included within the DECT FT.

logical channel: generic term for any distinct data path. Logical channels can be considered to operate between logical end points.