



**5G;
NR;
Base Station (BS) radio transmission and reception
(3GPP TS 38.104 version 16.4.0 Release 16)**



ReferenceRTS/TSGR-0438104vG40

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and LTE™ are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope	14
2 References	14
3 Definitions, symbols and abbreviations	15
3.1 Definitions	15
3.2 Symbols.....	19
3.3 Abbreviations	21
4 General	23
4.1 Relationship with other core specifications.....	23
4.2 Relationship between minimum requirements and test requirements	23
4.3 Conducted and radiated requirement reference points	23
4.3.1 BS type 1-C	23
4.3.2 BS type 1-H	24
4.3.3 BS type 1-O and BS type 2-O	25
4.4 Base station classes	25
4.5 Regional requirements.....	26
4.6 Applicability of requirements.....	26
4.7 Requirements for contiguous and <i>non-contiguous spectrum</i>	27
4.8 Requirements for BS capable of multi-band operation	27
4.9 OTA co-location with other base stations	29
5 Operating bands and channel arrangement	30
5.1 General	30
5.2 Operating bands	30
5.3 BS channel bandwidth	32
5.3.1 General.....	32
5.3.2 Transmission bandwidth configuration	32
5.3.3 Minimum guardband and transmission bandwidth configuration	33
5.3.4 RB alignment.....	34
5.3.5 BS channel bandwidth per operating band	35
5.3A BS channel bandwidth for CA	38
5.3A.1 Transmission bandwidth configuration for CA	38
5.3A.2 Minimum guardband and transmission bandwidth configuration for CA	38
5.4 Channel arrangement.....	40
5.4.1 Channel spacing.....	40
5.4.1.1 Channel spacing for adjacent NR carriers	40
5.4.1.2 Channel spacing for CA	41
5.4.2 Channel raster	42
5.4.2.1 NR-ARFCN and channel raster.....	42
5.4.2.1A NB-IoT carrier frequency numbering.....	42
5.4.2.2 Channel raster to resource element mapping.....	42
5.4.2.3 Channel raster entries for each <i>operating band</i>	43
5.4.3 Synchronization raster	45
5.4.3.1 Synchronization raster and numbering.....	45
5.4.3.3 Synchronization raster entries for each operating band.....	46
6 Conducted transmitter characteristics	48
6.1 General	48
6.2 Base station output power	48
6.2.1 General.....	48
6.2.2 Minimum requirement for BS type 1-C.....	49

6.2.3	Minimum requirement for <i>BS type 1-H</i>	49
6.2.4	Additional requirements (regional).....	49
6.3	Output power dynamics.....	49
6.3.1	General.....	49
6.3.2	RE power control dynamic range	49
6.3.2.1	General	49
6.3.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	49
6.3.3	Total power dynamic range	50
6.3.3.1	General	50
6.3.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	50
6.3.4	NB-IoT RB power dynamic range for NB-IoT operation in NR in-band	50
6.3.4.1	General	50
6.3.4.2	Minimum Requirement	51
6.4	Transmit ON/OFF power	51
6.4.1	Transmitter OFF power	51
6.4.1.1	General	51
6.4.1.2	Minimum requirement for <i>BS type 1-C</i>	51
6.4.1.3	Minimum requirement for <i>BS type 1-H</i>	51
6.4.2	Transmitter transient period	51
6.4.2.1	General	51
6.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	52
6.4.2.3	Void.....	52
6.5	Transmitted signal quality	52
6.5.1	Frequency error.....	52
6.5.1.1	General	52
6.5.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	53
6.5.2	Modulation quality.....	53
6.5.2.1	General	53
6.5.2.2	Minimum Requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	53
6.5.2.3	EVM frame structure for measurement.....	53
6.5.3	Time alignment error	54
6.5.3.1	General	54
6.5.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	54
6.6	Unwanted emissions.....	54
6.6.1	General.....	54
6.6.2	Occupied bandwidth	55
6.6.2.1	General	55
6.6.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	55
6.6.3	Adjacent Channel Leakage Power Ratio	55
6.6.3.1	General	55
6.6.3.2	Limits and <i>Basic limits</i>	56
6.6.3.3	Minimum requirement for <i>BS type 1-C</i>	58
6.6.3.4	Minimum requirement for <i>BS type 1-H</i>	58
6.6.4	Operating band unwanted emissions	59
6.6.4.1	General	59
6.6.4.2	<i>Basic limits</i>	61
6.6.4.2.1	<i>Basic limits</i> for Wide Area BS (Category A)	61
6.6.4.2.2	<i>Basic limits</i> for Wide Area BS (Category B)	61
6.6.4.2.2.1	Category B requirements (Option 1).....	61
6.6.4.2.2.2	Category B requirements (Option 2).....	63
6.6.4.2.3	<i>Basic limits</i> for Medium Range BS (Category A and B).....	63
6.6.4.2.4	<i>Basic limits</i> for Local Area BS (Category A and B).....	64
6.6.4.2.5	<i>Basic limits</i> for additional requirements	64
6.6.4.2.5.1	Limits in FCC Title 47	64
6.6.4.2.5.2	Protection of DTT	64
6.6.4.2.5.3	Additional operating band unwanted emissions limits for Band n48.....	65
6.6.4.2.5.4	Additional operating band unwanted emissions limits for Band n53.....	65
6.6.4.3	Minimum requirements for <i>BS type 1-C</i>	66
6.6.4.4	Minimum requirements for <i>BS type 1-H</i>	66
6.6.5	Transmitter spurious emissions.....	66
6.6.5.1	General	66
6.6.5.2	<i>Basic limits</i>	67

6.6.5.2.1	General transmitter spurious emissions requirements	67
6.6.5.2.2	Protection of the BS receiver of own or different BS	67
6.6.5.2.3	Additional spurious emissions requirements	68
6.6.5.2.4	Co-location with other base stations	76
6.6.5.3	Minimum requirements for <i>BS type 1-C</i>	81
6.6.5.4	Minimum requirements for <i>BS type 1-H</i>	81
6.7	Transmitter intermodulation	82
6.7.1	General	82
6.7.2	Minimum requirements for <i>BS type 1-C</i>	82
6.7.2.1	Co-location minimum requirements	82
6.7.2.2	Additional requirements	83
6.7.3	Minimum requirements for <i>BS type 1-H</i>	83
6.7.3.1	Co-location minimum requirements	83
6.7.3.2	Intra-system minimum requirements	84
6.7.3.3	Additional requirements	84
7	Conducted receiver characteristics	85
7.1	General	85
7.2	Reference sensitivity level	85
7.2.1	General	85
7.2.2	Minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	85
7.3	Dynamic range	87
7.3.1	General	87
7.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	87
7.4	In-band selectivity and blocking	93
7.4.1	Adjacent Channel Selectivity (ACS)	93
7.4.1.1	General	93
7.4.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	93
7.4.1.3	Void	94
7.4.1.4	Void	94
7.4.2	In-band blocking	94
7.4.2.1	General	94
7.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	95
7.4.2.3	Void	97
7.4.2.4	Void	97
7.5	Out-of-band blocking	97
7.5.1	General	97
7.5.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	97
7.5.3	Co-location minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	98
7.5.4	Void	99
7.6	Receiver spurious emissions	99
7.6.1	General	99
7.6.2	<i>Basic limits</i>	99
7.6.3	Minimum requirement for <i>BS type 1-C</i>	100
7.6.4	Minimum requirement for <i>BS type 1-H</i>	100
7.7	Receiver intermodulation	100
7.7.1	General	100
7.7.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	101
7.8	In-channel selectivity	105
7.8.1	General	105
7.8.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	105
8	Conducted performance requirements	109
8.1	General	109
8.1.1	Scope and definitions	109
8.1.2	Void	109
8.2	Performance requirements for PUSCH	109
8.2.1	Requirements for PUSCH with transform precoding disabled	109
8.2.1.1	General	109
8.2.1.2	Minimum requirements	110
8.2.2	Requirements for PUSCH with transform precoding enabled	118
8.2.2.1	General	118

8.2.2.2	Minimum requirements	118
8.2.3	Requirements for UCI multiplexed on PUSCH	119
8.2.3.1	General	119
8.2.3.2	Minimum requirements	120
8.2.4	Requirements for PUSCH for high speed train	121
8.2.4.1	General	121
8.2.4.2	Minimum requirements	122
8.2.5	Requirements for UL timing adjustment	123
8.2.5.1	Minimum requirements	124
8.3	Performance requirements for PUCCH	125
8.3.1	DTX to ACK probability	125
8.3.1.1	General	125
8.3.1.2	Minimum requirement	125
8.3.2	Performance requirements for PUCCH format 0	125
8.3.2.1	General	125
8.3.2.2	Minimum requirements	126
8.3.3	Performance requirements for PUCCH format 1	126
8.3.3.1	NACK to ACK requirements	126
8.3.3.1.1	General	126
8.3.3.1.2	Minimum requirements	127
8.3.3.2	ACK missed detection requirements	127
8.3.3.2.1	General	127
8.3.3.2.2	Minimum requirements	128
8.3.4	Performance requirements for PUCCH format 2	128
8.3.4.1	ACK missed detection requirements	128
8.3.4.1.1	General	128
8.3.4.1.2	Minimum requirements	129
8.3.4.2	UCI BLER performance requirements	129
8.3.4.2.1	General	129
8.3.4.2.2	Minimum requirements	130
8.3.5	Performance requirements for PUCCH format 3	130
8.3.5.1	General	130
8.3.5.2	Minimum requirements	131
8.3.6	Performance requirements for PUCCH format 4	132
8.3.6.1	General	132
8.3.6.2	Minimum requirement	133
8.3.7	Performance requirements for multi-slot PUCCH	134
8.3.7.1	General	134
8.3.7.2	Performance requirements for multi-slot PUCCH format 1	134
8.3.7.2.1	NACK to ACK requirements	134
8.3.7.2.1.1	General	134
8.3.7.2.1.2	Minimum requirements	135
8.3.7.2.2	ACK missed detection requirements	135
8.3.7.2.2.1	General	135
8.3.7.2.2.2	Minimum requirements	135
8.4	Performance requirements for PRACH	135
8.4.1	PRACH False alarm probability	135
8.4.1.1	General	135
8.4.1.2	Minimum requirement	136
8.4.2	PRACH detection requirements	136
8.4.2.1	General	136
8.4.2.2	Minimum requirements for Normal Mode	136
8.4.2.3	Minimum requirements for high speed train	137
9	Radiated transmitter characteristics	139
9.1	General	139
9.2	Radiated transmit power	139
9.2.1	General	139
9.2.2	Minimum requirement for BS type 1-H and BS type 1-O	139
9.2.3	Minimum requirement for BS type 2-O	140
9.3	OTA base station output power	140
9.3.1	General	140

9.3.2	Minimum requirement for <i>BS type 1-O</i>	140
9.3.3	Minimum requirement for <i>BS type 2-O</i>	141
9.3.4	Additional requirements (regional).....	141
9.4	OTA output power dynamics	141
9.4.1	General.....	141
9.4.2	OTA RE power control dynamic range	141
9.4.2.1	General	141
9.4.2.2	Minimum requirement for <i>BS type 1-O</i>	141
9.4.3	OTA total power dynamic range.....	141
9.4.3.1	General	141
9.4.3.2	Minimum requirement for <i>BS type 1-O</i>	141
9.4.3.3	Minimum requirement for <i>BS type 2-O</i>	142
9.5	OTA transmit ON/OFF power.....	142
9.5.1	General.....	142
9.5.2	OTA transmitter OFF power.....	142
9.5.2.1	General	142
9.5.2.2	Minimum requirement for <i>BS type 1-O</i>	142
9.5.2.3	Minimum requirement for <i>BS type 2-O</i>	142
9.5.3	OTA transient period	142
9.5.3.1	General	142
9.5.3.2	Minimum requirement for <i>BS type 1-O</i>	143
9.5.3.3	Minimum requirement for <i>BS type 2-O</i>	143
9.6	OTA transmitted signal quality	143
9.6.1	OTA frequency error	143
9.6.1.1	General	143
9.6.1.2	Minimum requirement for <i>BS type 1-O</i>	143
9.6.1.3	Minimum requirement for <i>BS type 2-O</i>	143
9.6.2	OTA modulation quality	144
9.6.2.1	General	144
9.6.2.2	Minimum Requirement for <i>BS type 1-O</i>	144
9.6.2.3	Minimum Requirement for <i>BS type 2-O</i>	144
9.6.2.3.1	EVM frame structure for measurement	144
9.6.3	OTA time alignment error	144
9.6.3.1	General	144
9.6.3.2	Minimum requirement for <i>BS type 1-O</i>	144
9.6.3.3	Minimum requirement for <i>BS type 2-O</i>	145
9.7	OTA unwanted emissions	145
9.7.1	General.....	145
9.7.2	OTA occupied bandwidth.....	146
9.7.2.1	General	146
9.7.2.2	Minimum requirement for <i>BS type 1-O</i> and <i>BS type 2-O</i>	146
9.7.3	OTA Adjacent Channel Leakage Power Ratio (ACLR)	146
9.7.3.1	General	146
9.7.3.2	Minimum requirement for <i>BS type 1-O</i>	146
9.7.3.3	Minimum requirement for <i>BS type 2-O</i>	146
9.7.4	OTA operating band unwanted emissions	148
9.7.4.1	General	148
9.7.4.2	Minimum requirement for <i>BS type 1-O</i>	148
9.7.4.2.1	Additional requirements	149
9.7.4.2.1.1	Protection of DTT.....	149
9.7.4.2.1.2	Limits in FCC Title 47.....	149
9.7.4.3	Minimum requirement for <i>BS type 2-O</i>	149
9.7.4.3.1	General	149
9.7.4.3.2	OTA operating band unwanted emission limits (Category A)	150
9.7.4.3.3	OTA operating band unwanted emission limits (Category B).....	151
9.7.4.3.4	Additional OTA operating band unwanted emission requirements	151
9.7.5	OTA transmitter spurious emissions.....	152
9.7.5.1	General	152
9.7.5.2	Minimum requirement for <i>BS type 1-O</i>	152
9.7.5.2.1	General	152
9.7.5.2.2	General OTA transmitter spurious emissions requirements	152
9.7.5.2.3	Protection of the BS receiver of own or different BS	152

9.7.5.2.4	Additional spurious emissions requirements	152
9.7.5.2.5	Co-location with other base stations	153
9.7.5.3	Minimum requirement for <i>BS type 2-O</i>	153
9.7.5.3.1	General	153
9.7.5.3.2	General OTA transmitter spurious emissions requirements	153
9.7.5.3.2.1	General	153
9.7.5.3.2.2	OTA transmitter spurious emissions (Category A)	153
9.7.5.3.2.3	OTA transmitter spurious emissions (Category B)	154
9.7.5.3.3	Additional OTA transmitter spurious emissions requirements	154
9.7.5.3.3.1	Limits for protection of Earth Exploration Satellite Service	154
9.8	OTA transmitter intermodulation	155
9.8.1	General	155
9.8.2	Minimum requirement for <i>BS type 1-O</i>	155
10	Radiated receiver characteristics	157
10.1	General	157
10.2	OTA sensitivity	158
10.2.1	<i>BS type 1-H</i> and <i>BS type 1-O</i>	158
10.2.1.1	General	158
10.2.1.2	Minimum requirement	158
10.2.2	<i>BS type 2-O</i>	158
10.3	OTA reference sensitivity level	159
10.3.1	General	159
10.3.2	Minimum requirement for <i>BS type 1-O</i>	159
10.3.3	Minimum requirement for <i>BS type 2-O</i>	160
10.4	OTA dynamic range	161
10.4.1	General	161
10.4.2	Minimum requirement for <i>BS type 1-O</i>	161
10.5	OTA in-band selectivity and blocking	170
10.5.1	OTA adjacent channel selectivity	170
10.5.1.1	General	170
10.5.1.2	Minimum requirement for <i>BS type 1-O</i>	170
10.5.1.3	Minimum requirement for <i>BS type 2-O</i>	171
10.5.2	OTA in-band blocking	172
10.5.2.1	General	172
10.5.2.2	Minimum requirement for <i>BS type 1-O</i>	172
10.5.2.3	Minimum requirement for <i>BS type 2-O</i>	175
10.6	OTA out-of-band blocking	175
10.6.1	General	175
10.6.2	Minimum requirement for <i>BS type 1-O</i>	175
10.6.2.1	General minimum requirement	175
10.6.2.2	Co-location minimum requirement	176
10.6.3	Minimum requirement for <i>BS type 2-O</i>	177
10.6.3.1	General minimum requirement	177
10.7	OTA receiver spurious emissions	177
10.7.1	General	177
10.7.2	Minimum requirement for <i>BS type 1-O</i>	177
10.7.3	Minimum requirement for <i>BS type 2-O</i>	178
10.8	OTA receiver intermodulation	179
10.8.1	General	179
10.8.2	Minimum requirement for <i>BS type 1-O</i>	179
10.8.3	Minimum requirement for <i>BS type 2-O</i>	183
10.9	OTA in-channel selectivity	184
10.9.1	General	184
10.9.2	Minimum requirement for <i>BS type 1-O</i>	184
10.9.3	Minimum requirement for <i>BS type 2-O</i>	187
11	Radiated performance requirements	189
11.1	General	189
11.1.1	Scope and definitions	189
11.1.2	OTA demodulation branches	189
11.1.3	Void	190

11.2	Performance requirements for PUSCH	190
11.2.1	Requirements for <i>BS type 1-O</i>	190
11.2.1.1	Requirements for PUSCH with transform precoding disabled	190
11.2.1.2	Requirements for PUSCH with transform precoding enabled	190
11.2.1.3	Requirements for UCI multiplexed on PUSCH	190
11.2.1.4	Requirements for PUSCH for high speed train	190
11.2.1.5	Requirements for UL timing adjustment	190
11.2.2	Requirements for <i>BS type 2-O</i>	190
11.2.2.1	Requirements for PUSCH with transform precoding disabled	190
11.2.2.1.1	General	190
11.2.2.1.2	Minimum requirements	191
11.2.2.2	Requirements for PUSCH with transform precoding enabled	194
11.2.2.2.1	General	194
11.2.2.2.2	Minimum requirements	194
11.2.2.3	Requirements for UCI multiplexed on PUSCH	195
11.2.2.3.1	General	195
11.2.2.3.2	Minimum requirements	196
11.3	Performance requirements for PUCCH	198
11.3.1	Requirements for <i>BS type 1-O</i>	198
11.3.1.1	DTX to ACK probability	198
11.3.1.2	Performance requirements for PUCCH format 0	198
11.3.1.3	Performance requirements for PUCCH format 1	198
11.3.1.4	Performance requirements for PUCCH format 2	198
11.3.1.5	Performance requirements for PUCCH format 3	198
11.3.1.6	Performance requirements for PUCCH format 4	198
11.3.2	Requirements for <i>BS type 2-O</i>	198
11.3.2.1	DTX to ACK probability	198
11.3.2.2	Performance requirements for PUCCH format 0	199
11.3.2.2.1	General	199
11.3.2.2.2	Minimum requirements	199
11.3.2.3	Performance requirements for PUCCH format 1	199
11.3.2.3.1	NACK to ACK requirements	199
11.3.2.3.1.1	General	199
11.3.2.3.1.2	Minimum requirements	200
11.3.2.3.2	ACK missed detection requirements	201
11.3.2.3.2.1	General	201
11.3.2.3.2.2	Minimum requirements	201
11.3.2.4	Performance requirements for PUCCH format 2	201
11.3.2.4.1	ACK missed detection requirements	201
11.3.2.4.1.1	General	201
11.3.2.4.1.2	Minimum requirements	202
11.3.2.4.2	UCI BLER performance requirements	202
11.3.2.4.2.1	General	202
11.3.2.4.2.2	Minimum requirements	202
11.3.2.5	Performance requirements for PUCCH format 3	203
11.3.2.5.1	General	203
11.3.2.5.2	Minimum requirements	203
11.3.2.6	Performance requirements for PUCCH format 4	204
11.3.2.6.1	General	204
11.3.2.6.2	Minimum requirements	205
11.4	Performance requirements for PRACH	205
11.4.1	Requirements for <i>BS type 1-O</i>	205
11.4.1.1	PRACH False alarm probability	205
11.4.1.2	PRACH detection requirements	205
11.4.2	Requirements for <i>BS type 2-O</i>	205
11.4.2.1	PRACH False alarm probability	205
11.4.2.1.1	General	205
11.4.2.1.2	Minimum requirement	205
11.4.2.2	PRACH detection requirements	205
11.4.2.2.1	General	205
11.4.2.2.2	Minimum requirements	206

Annex A (normative):	Reference measurement channels	207
A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, R=1/3).....	207
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3).....	208
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024)	208
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024)	214
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024)	218
A.6	PRACH Test preambles	220
A.7	Fixed Reference Channels for performance requirements (16QAM, R=434/1024)	221
Annex B (normative):	Error Vector Magnitude (FR1)	222
B.1	Reference point for measurement.....	222
B.2	Basic unit of measurement	222
B.3	Modified signal under test.....	223
B.4	Estimation of frequency offset	223
B.5	Estimation of time offset	223
B.5.1	General	223
B.5.2	Window length	224
B.6	Estimation of TX chain amplitude and frequency response parameters	225
B.7	Averaged EVM	226
Annex C (normative):	Error Vector Magnitude (FR2)	228
C.1	Reference point for measurement.....	228
C.2	Basic unit of measurement	228
C.3	Modified signal under test.....	229
C.4	Estimation of frequency offset	229
C.5	Estimation of time offset	229
C.5.1	General	229
C.5.2	Window length	230
C.6	Estimation of TX chain amplitude and frequency response parameters	230
C.7	Averaged EVM	232
Annex D (normative):	Characteristics of the interfering signals.....	234
Annex E:	Void	235
Annex F (normative):	Relationship between EIRP based regulatory requirements and 3GPP requirements.....	236
F.1	General	236
F.2	Relationship between EIRP based regulatory requirements and conducted requirements.....	236
F.3	Relationship between EIRP based regulatory requirements and OTA requirements.....	237
Annex G (Normative):	Propagation conditions.....	238
G.1	Static propagation condition.....	238
G.2	Multi-path fading propagation conditions	238
G.2.1	Delay profiles	238

G.2.1.1	Delay profiles for FR1	239
G.2.1.2	Delay profiles for FR2	240
G.2.2	Combinations of channel model parameters	241
G.2.3	MIMO Channel Correlation Matrices	242
G.2.3.1	MIMO Correlation Matrices using Uniform Linear Array (ULA)	242
G.2.3.1.1	Definition of MIMO Correlation Matrices.....	242
G.2.3.1.2	MIMO Correlation Matrices at High, Medium and Low Level	246
G.2.3.2	Multi-Antenna channel models using cross polarized antennas	248
G.2.3.2.1	Definition of MIMO Correlation Matrices using cross polarized antennas	249
G.2.3.2.2	Spatial Correlation Matrices at UE and gNB sides	249
G.2.3.2.2.1	Spatial Correlation Matrices at UE side	249
G.2.3.2.2.2	Spatial Correlation Matrices at gNB side	250
G.2.3.2.3	MIMO Correlation Matrices using cross polarized antennas	250
G.3	High speed train condition	250
G.4	Moving propagation conditions.....	255
Annex H (informative):	Change history	256
History		266

iTeh STANDARD PREVIEW
 (standards.iteh.ai)
 Full standard:
<https://standards.iteh.ai/catalog/standards/sist/78312760-558b-43df-ac1a-6ffedcb04407/etsi-ts-138-104-v16.4.0-2020-07>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- shall** indicates a mandatory requirement to do something
- shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- should** indicates a recommendation to do something
- should not** indicates a recommendation not to do something
- may** indicates permission to do something
- need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- can** indicates that something is possible
- cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document