



SLOVENSKI STANDARD
SIST EN 301 406-2 V3.1.1:2023

01-oktober-2023

Digitalne izboljšane brezvrvične telekomunikacije (DECT) - Harmonizirani standard za dostop do radijskega spektra - 2. del: DECT-2020 NR

Digital Enhanced Cordless Telecommunications (DECT) - Harmonised Standard for access to radio spectrum - Part 2: DECT-2020 NR

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 406-2 V3.1.1:2023](https://standards.iteh.ai/catalog/standards/sist/en-301-406-2-v3-1-1-2023)

Ta slovenski standard je istoveten z: ETSI EN 301 406-2 V3.1.1 (2023-08)

ICS:

33.070.30	Digitalne izboljšane brezvrvične telekomunikacije (DECT)	Digital Enhanced Cordless Telecommunications (DECT)
-----------	--	---

SIST EN 301 406-2 V3.1.1:2023

en

ETSI EN 301 406-2 V3.1.1 (2023-08)



Digital Enhanced Cordless Telecommunications (DECT); Harmonised Standard for access to radio spectrum; Part 2: DECT-2020 NR

[SIST EN 301 406-2 V3.1.1:2023](https://standards.iteh.ai/catalog/standards/sist/33553f31-6fae-49a5-b62e-5587bb7d2885/sist-en-301-406-2-v3-1-1-2023)

<https://standards.iteh.ai/catalog/standards/sist/33553f31-6fae-49a5-b62e-5587bb7d2885/sist-en-301-406-2-v3-1-1-2023>

ReferenceDEN/DECT-00359-2

KeywordsDECT, DECT-2020, radio, radio parameters,
regulation, testing

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://standards-portal.etsi.org/People/CommitteeSupportStaff.aspx?49a5-b62e->

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.

All rights reserved.

Contents

Intellectual Property Rights	8
Foreword.....	8
Modal verbs terminology.....	9
1 Scope	10
2 References	10
2.1 Normative references	10
2.2 Informative references.....	10
3 Definition of terms, symbols and abbreviations.....	11
3.1 Terms.....	11
3.2 Symbols.....	12
3.3 Abbreviations	12
4 Technical requirements specifications	13
4.1 Environmental profile.....	13
4.2 General requirements	13
4.3 Conformance requirements for transmitter.....	14
4.3.1 Transmitter RF Output Power.....	14
4.3.1.1 Definition	14
4.3.1.2 Limit.....	14
4.3.1.3 Conformance.....	14
4.3.2 Nominal Centre Frequencies.....	14
4.3.2.1 General	14
4.3.2.2 Definitions.....	14
4.3.2.3 Limit.....	15
4.3.2.4 Conformance.....	15
4.3.3 Nominal Channel Bandwidth.....	15
4.3.3.1 Definitions.....	15
4.3.3.2 Limit.....	15
4.3.3.3 Conformance.....	16
4.3.4 Transmitter unwanted emissions.....	16
4.3.4.1 Transmitter unwanted emissions in the spurious domain.....	16
4.3.4.1.1 Definition.....	16
4.3.4.1.2 Limits	16
4.3.4.1.3 Conformance	16
4.3.4.2 Transmitter unwanted emissions in the out of band domain	16
4.3.4.2.1 Definition.....	16
4.3.4.2.2 Limits	17
4.3.4.2.3 Conformance	17
4.4 Conformance requirements for receiver	17
4.4.1 Receiver Minimum Performance Criterion.....	17
4.4.2 Receiver Sensitivity	18
4.4.2.1 Definition	18
4.4.2.2 Limit.....	18
4.4.2.3 Conformance.....	18
4.4.3 Adjacent Channel Selectivity.....	18
4.4.3.1 Definition	18
4.4.3.2 Limit.....	18
4.4.3.3 Conformance.....	19
4.4.4 Receiver out of band blocking	19
4.4.4.1 Definition	19
4.4.4.2 Limit.....	20
4.4.4.3 Conformance.....	20
4.4.5 Spurious response	20
4.4.5.1 Definition	20
4.4.5.2 Limit.....	20

4.4.5.3	Conformance	21
4.4.6	Receiver Intermodulation	21
4.4.6.1	Definition	21
4.4.6.2	Limit	21
4.4.6.3	Conformance	21
4.4.7	Receiver unwanted emissions in the spurious domain	21
4.4.7.1	Definition	21
4.4.7.2	Limit	21
4.4.7.3	Conformance	22
4.5	Conformance requirements on Channel Access	22
4.5.1	General	22
4.5.1.1	Requirements	22
4.5.1.2	Conformance	22
4.5.2	Channel Access of a Radio Device in FT mode	22
4.5.2.1	Definition	22
4.5.2.2	Requirements	23
4.5.2.3	Conformance	23
4.5.3	Channel Access of a Radio Device in PT mode and Random Access	23
4.5.3.1	Definition	23
4.5.3.2	Requirements	23
4.5.3.3	Conformance	23
4.5.4	Channel Access of Radio Device in FT mode for Scheduled Access	23
4.5.4.1	Definition	23
4.5.4.2	Requirements	24
4.5.4.3	Conformance	24
4.5.5	Channel Access of Radio Device in PT mode for Scheduled Access	24
4.5.5.1	Definition	24
4.5.5.2	Requirements	24
4.5.5.3	Conformance	24
4.5.6	Maximum Transmission Time of a Radio Device	25
4.5.6.1	Definition	25
4.5.6.2	Requirements	25
4.5.6.3	Conformance	25
5	Testing for compliance with technical requirements	25
5.1	Environmental conditions for testing	25
5.1.1	General	25
5.1.2	Normal test conditions	25
5.1.2.1	Normal temperature and humidity	25
5.1.2.2	Normal power source	25
5.1.3	Extreme test conditions	26
5.2	Interpretation of the measurement results	26
5.3	Definition of other test conditions	26
5.3.1	Product information for testing	26
5.3.2	Test signals	27
5.3.2.1	Overview	27
5.3.2.2	Interfering signal for receiver performance tests	28
5.3.2.3	AWGN Interference signal used for Channel Access Tests	28
5.3.3	Test operational modes	29
5.3.3.1	Device under representative test signal	29
5.3.4	Antennas	29
5.3.4.1	Integrated and dedicated antennas	29
5.3.5	Tests of the receiver performance criterion	30
5.3.5.1	General	30
5.3.5.2	Receiver statistical testing	30
5.3.5.3	Receiver no loss of the wireless transmission function testing	30
5.3.6	Presentation of equipment	30
5.3.7	Conducted measurements, radiated measurements, relative measurements	30
5.4	Method of measurement for transmitters	30
5.4.1	Transmitter RF Output Power	30
5.4.1.1	Test conditions	30
5.4.1.2	Test method	31

5.4.1.2.1	Conducted measurement.....	31
5.4.1.2.2	Radiated measurement.....	32
5.4.2	Nominal Centre Frequencies.....	33
5.4.2.1	Test Conditions	33
5.4.2.2	Test Method	33
5.4.2.2.1	Conducted measurement.....	33
5.4.2.2.2	Radiated measurement.....	34
5.4.3	Transmitter unwanted emissions.....	34
5.4.3.1	Transmitter unwanted emissions in the spurious domain.....	34
5.4.3.1.1	Test Conditions.....	34
5.4.3.1.2	Test Method.....	34
5.4.3.2	Transmitter unwanted emissions in the out of band domain	36
5.4.3.2.1	Test Conditions.....	36
5.4.3.2.2	Test Method.....	37
5.5	Method of measurement for receiver.....	38
5.5.1	Receiver Sensitivity	38
5.5.1.1	Test Conditions	38
5.5.1.2	Test Method	38
5.5.1.2.1	Conducted measurement.....	38
5.5.1.2.2	Radiated measurement.....	39
5.5.2	Adjacent Channel Selectivity.....	39
5.5.2.1	Test Conditions	39
5.5.2.2	Test Method	40
5.5.2.2.1	Conducted measurement.....	40
5.5.2.2.2	Radiated measurement.....	41
5.5.3	Receiver out of band blocking	41
5.5.3.1	Test Conditions	41
5.5.3.2	Test Method	41
5.5.3.2.1	Conducted measurement.....	41
5.5.3.2.2	Radiated measurement.....	42
5.5.4	Receiver spurious response.....	43
5.5.4.1	Test Conditions	43
5.5.4.2	Test Method	43
5.5.4.2.1	Conducted measurement.....	43
5.5.4.2.2	Radiated measurement.....	44
5.5.5	Receiver Intermodulation	44
5.5.5.1	Test Conditions	44
5.5.5.2	Test Method	44
5.5.5.2.1	Conducted measurement.....	44
5.5.5.2.2	Radiated measurement.....	46
5.5.6	Receiver unwanted emissions in the spurious domain.....	46
5.5.6.1	Purpose.....	46
5.5.6.2	Test Conditions	46
5.5.6.3	Test Method	46
5.5.6.3.1	Conducted measurement.....	46
5.5.6.3.2	Radiated measurement.....	48
5.6	Test methods for Channel Access	48
5.6.1	Generic Test procedure for measuring channel or frequency use	48
5.6.1.1	Purpose.....	48
5.6.1.2	Test Conditions	48
5.6.1.3	Test Method	49
5.6.1.3.1	Conducted measurement.....	49
5.6.1.3.2	Radiated measurement.....	50
5.6.2	Channel Access of a Radio Device in FT mode	50
5.6.2.1	Purpose.....	50
5.6.2.2	Test Conditions	50
5.6.2.3	Test Method	50
5.6.2.3.1	Conducted measurement.....	50
5.6.2.3.2	Radiated measurement.....	51
5.6.3	Channel Access of a Radio Device in PT mode and Random Access	51
5.6.3.1	Purpose.....	51
5.6.3.2	Test Conditions	51

5.6.3.3	Test Method	51
5.6.3.3.1	Conducted measurement.....	51
5.6.3.3.2	Radiated measurement.....	52
5.6.4	Channel Access of a Radio Device in FT mode for Scheduled Access	52
5.6.4.1	Purpose.....	52
5.6.4.2	Test Conditions	52
5.6.4.3	Test Method	53
5.6.4.3.1	Conducted measurement.....	53
5.6.4.3.2	Radiated measurement.....	53
5.6.5	Channel Access of a Radio Device in PT mode for Scheduled Access	53
5.6.5.1	Purpose.....	53
5.6.5.2	Test Conditions	53
5.6.5.3	Test Method	53
5.6.5.3.1	Conducted measurement.....	53
5.6.5.3.2	Radiated measurement.....	54
5.6.6	Maximum Transmission Time of a Radio Device	55
5.6.6.1	Purpose.....	55
5.6.6.2	Test Conditions	55
5.6.6.3	Test Method	55
5.6.6.3.1	Conducted measurement.....	55
5.6.6.3.2	Radiated measurement.....	56
Annex A (informative):	Relationship between the present document and the essential requirements of Directive 2014/53/EU	57
Annex B (informative):	Maximum measurement uncertainty	59
Annex C (informative):	Physical layer measurement channel configuration	60
Annex D (normative):	Test sites and arrangements for radiated measurements.....	61
D.1	Introduction	61
D.2	Radiation test sites.....	61
D.2.1	Open Area Test Site (OATS)	61
D.2.2	Semi Anechoic Room (SAR)	62
D.2.3	Fully Anechoic Room (FAR)	63
D.2.4	Measurement Distance	64
D.3	Antennas.....	65
D.3.1	Introduction	65
D.3.2	Measurement antenna.....	65
D.3.3	Substitution antenna	65
D.4	Test fixture	65
D.4.1	Introduction	65
D.4.2	Description of the test fixture.....	66
D.4.3	Using the test fixture for relative measurements	66
D.5	Guidance on the use of radiation test sites	66
D.5.1	Introduction	66
D.5.2	Power supplies for the battery powered EUT.....	66
D.5.3	Site preparation	67
D.6	Coupling of signals.....	67
D.6.1	General	67
D.6.2	Data Signals.....	67
Annex E (normative):	Procedures for radiated measurements	68
E.1	Introduction	68
E.2	Radiated measurements in an OATS or SAR.....	68
E.3	Radiated measurements in a FAR	69

E.4	Substitution measurement	69
Annex F (normative):	Receiver Testing.....	70
F.1	Statistical testing of receiver characteristics.....	70
F.1.1	Description	70
F.1.2	Mapping the throughput to error ratio	70
F.1.2.1	Defining throughput and bitrate.....	70
F.1.2.2	Mapping the ACK/NACK to error ratio	70
F.1.2.3	Mapping the received packet count to error ratio	71
F.1.3	Design of the test.....	71
F.1.4	Numerical definition of the pass-fail limits	71
F.1.5	Pass-Fail decision rules	72
F.2	No loss of transmission testing of receiver characteristics.....	73
F.2.1	Description	73
F.2.2	Pass-Fail decision rules	73
Annex G (informative):	Checklist	74
Annex H (informative):	Change history	75
History		76

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 301 406-2 V3.1.1:2023

<https://standards.iteh.ai/catalog/standards/sist/33553f31-6fae-49a5-b62e-5587bb7d2885/sist-en-301-406-2-v3-1-1-2023>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This Harmonised European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document has been prepared under the Commission's standardisation request C(2015) 5376 final [i.1] to provide one voluntary means of conforming to the essential requirements of Directive 2014/53/EU on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC [i.2].

Once the present document is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of the present document given in Table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding essential requirements of that Directive and associated EFTA regulations.

The present document is part 2 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.15].

The present document covers DECT-2020 NR (New Radio) as defined by the multi-part technical specification ETSI TS 103 636 (see [i.12] for an overview).

National transposition dates

Date of adoption of this EN:	27 July 2023
Date of latest announcement of this EN (doa):	31 October 2023
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 April 2024
Date of withdrawal of any conflicting National Standard (dow):	30 April 2025

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 406-2 V3.1.1:2023](#)

<https://standards.iteh.ai/catalog/standards/sist/33553f31-6fae-49a5-b62e-5587bb7d2885/sist-en-301-406-2-v3-1-1-2023>

1 Scope

The present document specifies technical characteristics and methods of measurements for equipment employing DECT-2020 NR (New Radio) as specified in by the multi-part technical specification ETSI TS 103 636, see [i.12] for an overview.

Table 1: Radiocommunications service frequency bands

Radiocommunications service frequency bands	
Transmit	1 880 MHz to 1 900 MHz
Receive	1 880 MHz to 1 900 MHz

National regulation can allow additional frequency bands. The limits and test procedures included in the present document are applicable for DECT-2020 NR use in frequency ranges below 6 GHz.

NOTE: The relationship between the present document and essential requirements of article 3.2 of Directive 2014/53/EU [i.2] is given in annex A.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI TS 103 636-4 \(V1.4.1\)](#): "DECT-2020 New Radio (NR); Part 4: MAC layer; Release 1".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] [M/536 Commission implementing Decision C\(2015\) 5376](#) final of 4.8.2015 on a standardisation request to the European Committee for Electrotechnical Standardisation and to the European Telecommunications Standards Institute as regards radio equipment in support of Directive 2014/53/EU of the European Parliament and of the Council.
- [i.2] [Directive 2014/53/EU of the European Parliament](#) and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.3] Void.

- [i.4] [ERC Recommendation 74-01](#): "Unwanted emissions in the spurious domain", Edition May 2019.
- [i.5] Void.
- [i.6] ETSI EG 203 367 (V1.1.1) (06-2016): "Guide to the application of harmonised standards covering articles 3.1b and 3.2 of the Directive 2014/53/EU (RED) to multi-radio and combined radio and non-radio equipment".
- [i.7] ETSI TR 100 028-1 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1".
- [i.8] ETSI TR 100 028-2 (V1.4.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2".
- [i.9] ETSI TR 102 273-2 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 2: Anechoic chamber".
- [i.10] ETSI TR 102 273-3 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 3: Anechoic chamber with a ground plane".
- [i.11] ETSI TR 102 273-4 (V1.2.1) (12-2001): "Electromagnetic compatibility and Radio spectrum Matters (ERM); Improvement on Radiated Methods of Measurement (using test site) and evaluation of the corresponding measurement uncertainties; Part 4: Open area test site".
- [i.12] ETSI TS 103 636 (all parts): "DECT-2020 New Radio (NR)".
- [i.13] ETSI TS 103 636-2: "DECT-2020 New Radio (NR); Part 2: Radio reception and transmission requirements; Release 1".
- [i.14] ETSI TS 103 636-3: "DECT-2020 New Radio (NR); Part 3: Physical layer; Release 1".
- [i.15] ETSI EN 301 406-1: "Digital Enhanced Cordless Telecommunications (DECT); Harmonised Standard for access to radio spectrum; Part 1: DECT, DECT Evolution and DECT ULE".
- [i.16] ETSI EG 203 336: "Guide for the selection of technical parameters for the production of Harmonised Standards covering article 3.1(b) and article 3.2 of Directive 2014/53/EU".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

antenna assembly: combination of the antenna (integral or dedicated), its coaxial cable and if applicable, its antenna connector and associated switching components

NOTE 1: This term (antenna assembly) refers to an antenna connected to one transmit chain.

NOTE 2: The gain of an antenna assembly G in dBi, does not include the additional gain that may result out of beamforming techniques.

burst: one or multiple subslot(s) as defined in ETSI TS 103 636-3 [i.14], clause 4.4

channel plan: combination of the centre frequencies and for each of the centre frequencies, the declared nominal bandwidth(s)

dedicated antenna: antenna external to the equipment, using an antenna connector with a cable or a wave-guide and which has been designed or developed for one or more specific types of equipment

Fixed Termination (FT): operational mode of RD where RD initiates coordinates local radio resources, provides information how other RDs may connect and communicate with it

integral antenna: antenna designed as a fixed part of the equipment (without the use of an external connector) which cannot be disconnected from the equipment by a user with the intent to connect another antenna

NOTE: An integral antenna may be fitted internally or externally. In the case where the antenna is external, a non-detachable cable or wave-guide can be used.

nominal transmit power: mean transmitter output power at the antenna connector measured over the transmission bandwidth to deliver to a load with resistance equal to the nominal load impedance of the transmitter

operating channel: single continuous part of radio spectrum with a defined bandwidth where RDs transmit and/or receive

Portable Termination (PT): operational mode of RD where RD selects another RD, which is in FT mode, for association

Radio Device (RD): equipment with radio transmission and reception capability, which can operate in FT and/or PT mode

receive chain: receiver circuit with an associated antenna, which may be shared with a transmit chain

resource: variable length time unit defined in subslot(s) in single operating channel that RD is using for transmission or reception of physical layer packet

smart antenna systems: equipment that combines multiple transmit and/or receive chains with a signal processing function to increase the throughput and/or to optimize its radiation and/or reception capabilities

NOTE: These are techniques such as spatial multiplexing, beamforming, cyclic delay diversity, MIMO, etc.

transmission bandwidth: maximum bandwidth of active subcarriers of the transmitted signal

NOTE: As defined in ETSI TS 103 636-2 [i.13], clause 5.3.2.

transmit chain: transmitter circuit with an associated antenna, which may be shared with a receive chain

3.2 Symbols

For the purposes of the present document, the following symbols apply:

B	Nominal Channel Bandwidth
B_{occupied}	Occupied Channel Bandwidth
dB _i	dB(isotropic) - the forward gain of an antenna compared with the hypothetical isotropic antenna, which uniformly distributes energy in all directions
dBm	Absolute power level relative to 1 milliwatt, expressed in dB
f_c	Nominal Centre Frequency
$f_{c,a}$	Actual Centre Frequency
f_n	Nominal Centre Frequencies of the operating channel with absolute channel number n as defined in ETSI TS 103 636-2 [i.13]
log()	logarithm to base 10

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACK	Acknowledgement
ACS	Adjacent Channel Selectivity
AWGN	Additive White Gaussian Noise
BPSK	Binary Phase Shift Keying
BW	Bandwidth
CRC	Cyclic Redundancy Check

CW	Continuous Wave
e.i.r.p.	effective isotropic radiated power
e.r.p.	effective radiated power
EFTA	European Free Trade Association
ER	Error Rate
EUT	Equipment Under Test
FAR	Fully Anechoic Room
FT	Fixed Termination
HARQ	Hybrid Automatic Repeat Request
LPDA	Logarithmic Periodic Dipole Antennas
NACK	Negative Acknowledgement
NF	Noise Figure
NR	New Radio
OATS	Open Area Test Site
OOB	Out Of Band
PER	Packet Error Rate
PT	Portable Termination
QPSK	Quadrature Phase-Shift Keying
RBW	Resolution Bandwidth
RD	Radio Device
RF	Radio Frequency
RMS	Root Mean Square
RSSI-1	Radio Signal Strength Indicator 1
SAR	Semi Anechoic Room
SNR	Signal to Noise Ratio
VBW	Video Bandwidth
VSWR	Voltage Standing Wave Ratio

STANDARD PREVIEW

4 Technical requirements specifications

4.1 Environmental profile

The technical requirements of the present document apply under the environmental profile for operation of the equipment, which shall be in accordance with its intended use. The equipment shall comply with all the technical requirements of the present document at all times when operating within the boundary limits of the operational environmental profile defined by its intended use.

4.2 General requirements

The equipment shall be designed, constructed and manufactured in accordance with good engineering practice and with the aim of minimizing harmful interference to other equipment and services.

The equipment supplied for testing shall be market conform.

Equipment submitted for testing shall support operation with at least one Nominal Channel Bandwidth B as defined in clause 4.3.3.

Equipment submitted for testing, where applicable, shall fulfil the requirements of the present document on all frequencies over which it is intended to operate.

NOTE: Equipment operating on multiple RF channels concurrently (e.g. multi-transceiver operation) is handled like multiple, co-located equipment, where each have to assess the RF channel and operate on it independently from each other.