

SLOVENSKI STANDARD
oSIST prEN 300 176-2 V2.3.5:2022
01-april-2022

**Digitalne izboljšane brezvrvične telekomunikacije (DECT) - Specifikacija preskusa
- 2. del: Zvok in govor**

Digital Enhanced Cordless Telecommunications (DECT) - Test specification - Part 2:
Audio and speech

**iTeh STANDARD
PREVIEW
(standards.iteh.ai)**

Ta slovenski standard je istoveten z: ETSI EN 300 176-2 V2.3.5 (2022-02)
[oSIST prEN 300 176-2 V2.3.5:2022](#)

<https://standards.iteh.ai/catalog/standards/sist/06008cde-c25f-4cec-a452-f78fedc4d82e/osist-pr-en-300-176-2-v2-3-5-2022>

ICS: 3-5-2022

33.070.30 Digitalne izboljšane Digital Enhanced Cordless
 brezvrvične telekomunikacije Telecommunications (DECT)
 (DECT)

oSIST prEN 300 176-2 V2.3.5:2022 en

**iTeh STANDARD
PREVIEW
(standards.iteh.ai)**

[oSIST prEN 300 176-2 V2.3.5:2022](#)

<https://standards.iteh.ai/catalog/standards/sist/06008cde-c25f-4cec-a452-f78fedc4d82e/osist-pren-300-176-2-v2-3-5-2022>

Draft ETSI EN 300 176-2 v2.3.5 (2022-02)



Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 2: Audio and speech *(standards.iteh.ai)*

oSIST prEN 300 176-2 V2.3.5:2022
<https://standards.iteh.ai/catalog/standards/sist/06008cde-c25f-4cec-a452-f78fedc4d82e/osist-pren-300-176-2-v2-3-5-2022>



Reference
REN/DECT-00360
Keywords
7 kHz, audio, codec, DECT, handsfree, IMT-2000, LC3plus, loudspeaking, mobility, narrowband, quality, radio, regulation, speech, superwideband, TDD, TDMA, telephony, terminal, testing, voice, wideband
ETSI
650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

<https://standards.iteh.ai/catalog/standards/sist/06008cde-c25f-4ced-9e0e-33a2a3835702-y2>

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.
All rights reserved.

Contents

Intellectual Property Rights	16
Foreword.....	16
Modal verbs terminology.....	17
1 Scope	18
2 References	19
2.1 Normative references	19
2.2 Informative references.....	22
3 Definition of terms, symbols and abbreviations.....	24
3.1 Terms.....	24
3.2 Symbols.....	27
3.3 Abbreviations	27
4 Interpretation of the measurement results	29
5 General test requirements.....	30
5.0 General	30
5.1 Test philosophy	30
5.1.1 Testable items	30
5.1.2 Testing of the codecs	30
5.1.3 Testing of the audio types	30
5.1.4 Devices with analog line interfaces	31
5.1.5 Equipment supporting an ETSI approved profile	31
5.1.6 Equipment not supporting an ETSI approved profile	32
5.1.7 Applicant's declaration.....	32
6 General testing conditions	32
6.1 Acoustical environment.....	32
6.2 Lower Tester (LT).....	33
6.2.1 Description. https://standards.iteh.ai/catalog/standards/oist/06008cde-229488a4521781eae4d82/oist-pr-en-300-176-2-v2-3-5-2022	33
6.2.2 Connections between the EUT and the LT	33
6.2.3 Functions and abilities	33
6.2.4 Accuracy of measurements and test signal generation	33
6.3 Power and environment.....	34
6.3.1 Environment for tests.....	34
6.3.2 Power supply limitations	34
6.3.3 Power source.....	34
6.4 Test configurations	34
6.4.1 General.....	34
6.4.2 Testing a DECT system	34
6.4.3 Testing a separate PP or FP	35
6.4.4 Reference FP (ReFP) and Reference PP (RePP).....	36
6.5 Digital signal levels	37
6.5.1 Digital signal levels for codecs G.711 and G.726.....	37
6.6 General test conditions	37
6.7 Ideal codecs (for codecs G.726, G.711, G.722, G.729.1, MPEG-AAC and LC3plus).....	38
6.7.0 General.....	38
6.7.1 Ideal codec for codecs G.726, G.711 and LC3plus in NB mode	38
6.7.2 Ideal codec for codecs G.722, G.729.1, MPEG-4 and LC3plus (wideband mode)	39
6.7.3 Ideal codec for MPEG-4 or LC3plus (super-wideband mode)	40
6.7.4 Ideal codec for LC3plus in fullband, FBHR, FBLFE or ultra-band mode.....	40
6.8 Electro-acoustical equipment	40
6.8.0 General.....	40
6.8.1 Artificial mouth and artificial ear	40
6.8.2 Head And Torso Simulator (HATS)	40
6.9 Speech coding scheme.....	41
6.9.1 Requirement for speech coding algorithm	41

6.9.2	Applicant's declaration on speech coding algorithm.....	41
6.9.3	Requirement for the TAP in the FP	41
6.9.4	Applicant's declaration on the TAP in the FP	41
6.10	Test setup.....	41
6.10.1	Set-up for handset type 1a or 1b	41
6.10.2	Set-up for handset type 2a	41
6.10.3	Set-up for handset or headset other than type 1a, 1b or 2a	42
6.10.3.0	Super-wideband and fullband applications	42
6.10.3.1	Positioning handset or headset	42
6.10.3.2	Position and calibration of HATS	42
6.10.4	Set-up for hands-free measurements.....	43
6.10.4.0	Super-wideband and fullband applications	43
6.10.4.1	Positioning handsfree	44
6.10.4.2	Position and calibration of HATS	50
6.10.4.2.1	Sending.....	50
6.10.4.2.2	Receiving.....	50
6.10.5	Set-up for measurements in loudspeaking mode	51
6.10.6	Setup for background noise simulation.....	51
6.10.7	Setup of variable echo path.....	52
6.10.8	Setup for testing positional robustness of handsets.....	54
7	Test of audio specifications.....	55
7.1	Overall description	55
7.1.1	Introduction to DECT audio specifications	55
7.1.2	Introduction to the audio types	55
7.1.3	List of Audio types	56
7.1.4	Audio types for Portable Parts	57
7.1.5	Audio types for Fixed Parts	58
7.1.6	Complete DECT system	59
7.1.7	Structure of the specification of the audio types	59
7.1.8	Audio Types and codecs	67
7.1.9	Audio Types and physical interfaces	67
7.2	Audio types applicable to Portable Parts.....	67
7.2.0	General.....	67
7.2.1	Performance levels of DECT Portable Parts (handsets).....	67
7.2.2	Type 0: Reference PP (RePP).....	68
7.2.3	PP Type 1a: "Classic" GAP narrowband handset.....	69
7.2.3.1	Introduction	69
7.2.3.2	Compatible services and codecs.....	69
7.2.3.3	Specification.....	69
7.2.4	PP Type 1b: "Improved" GAP narrowband handset.....	69
7.2.4.1	Introduction	69
7.2.4.2	Compatible services and codecs.....	70
7.2.4.3	Specification.....	70
7.2.5	PP Type 1c: HATS-tested "standard" narrowband handset	70
7.2.5.1	Introduction	70
7.2.5.2	Compatible services and codecs	70
7.2.5.3	Specification.....	70
7.2.6	PP Type 1d: HATS-tested "improved" narrowband handset	71
7.2.6.1	Introduction	71
7.2.6.2	Compatible services and codecs	71
7.2.6.3	Specification.....	71
7.2.7	PP Type 3a: HATS tested narrowband "standard" loudspeaking handsfree	71
7.2.7.1	Introduction	71
7.2.7.2	Compatible services and codecs	71
7.2.7.3	Specification.....	72
7.2.8	PP Type 3b: HATS tested narrowband "improved" loudspeaking handsfree	72
7.2.8.1	Introduction	72
7.2.8.2	Compatible services and codecs	72
7.2.8.3	Specification.....	72
7.2.9	PP Type 2a: P.311-tested wideband handset.....	72
7.2.9.1	Introduction	72

7.2.9.2	Compatible services and codecs.....	72
7.2.9.3	Specification.....	72
7.2.10	PP Type 2b: HATS-tested "standard" wideband handset or headset	72
7.2.10.1	Introduction.....	72
7.2.10.2	Compatible services and codecs.....	73
7.2.10.3	Specification.....	73
7.2.11	PP Type 2c: HATS tested "improved" wideband handset or headset.....	73
7.2.11.1	Introduction.....	73
7.2.11.2	Compatible services and codecs.....	73
7.2.11.3	Specification.....	73
7.2.12	PP Type 4a: HATS tested wideband "standard" loudspeaking handsfree	73
7.2.12.1	Introduction.....	73
7.2.12.2	Compatible services and codecs.....	74
7.2.12.3	Specification.....	74
7.2.13	PP Type 4b: HATS tested wideband "improved" loudspeaking and handsfree.....	74
7.2.13.1	Introduction.....	74
7.2.13.2	Compatible services and codecs.....	74
7.2.13.3	Specification.....	74
7.2.14	PP Type 5a: super-wideband 14 kHz handset or headset.....	74
7.2.14.1	Introduction.....	74
7.2.14.2	Compatible services and codecs.....	75
7.2.14.3	Specification.....	75
7.2.15	PP Type 5b: super-wideband 14 kHz loudspeaking handsfree	75
7.2.15.1	Introduction.....	75
7.2.15.2	Compatible services and codecs.....	75
7.2.15.3	Specification.....	75
7.2.16	PP Type 6: PPs with external 2 wire, 3.1 kHz telephony interface.....	75
7.2.16.1	Introduction.....	75
7.2.16.2	Compatible services and codecs.....	75
7.2.16.3	Specification.....	75
7.2.17	PP Type 7a: fullband 20 kHz handset or headset.....	75
7.2.17.1	Introduction.....	75
7.2.17.2	Compatible services and codecs.....	75
7.2.17.3	Specification.....	75
7.2.18	PP Type 7b: fullband 20 kHz loudspeaking handsfree	76
7.2.18.1	Introduction.....	76
7.2.18.2	Compatible services and codecs.....	76
7.2.18.3	Specification.....	76
7.2.19	PP Types 7c, d, e, f: fullband 20 kHz stereo audio device.....	76
7.2.19.1	Introduction.....	76
7.2.19.2	Compatible services and codecs.....	76
7.2.19.3	Specification.....	76
7.2.20	PP Type 7g: FBHR 24 kHz headset device	76
7.2.20.1	Introduction.....	76
7.2.20.2	Compatible services and codecs.....	76
7.2.20.3	Specification.....	77
7.2.21	PP Type 7h: FBHR 24 kHz loudspeaking device	77
7.2.21.1	Introduction.....	77
7.2.21.2	Compatible services and codecs.....	77
7.2.21.3	Specification.....	77
7.2.22	PP Type 7i: FBLFE 250 Hz loudspeaking device	77
7.2.22.1	Introduction.....	77
7.2.22.2	Compatible services and codecs.....	77
7.2.22.3	Specification.....	77
7.2.23	PP Type 7j: fullband 20 kHz low-latency microphone device.....	77
7.2.23.1	Introduction.....	77
7.2.23.2	Compatible services and codecs.....	77
7.2.23.3	Specification.....	77
7.2.24	PP Type 8a: ultra-band 48 kHz headset device.....	78
7.2.24.1	Introduction.....	78
7.2.24.2	Compatible services and codecs.....	78
7.2.24.3	Specification.....	78

7.2.25	PP Type 8b: ultra-band 48 kHz loudspeaking device	78
7.2.25.1	Introduction	78
7.2.25.2	Compatible services and codecs	78
7.2.25.3	Specification	78
7.3	Audio transmission types applicable to Fixed Parts	78
7.3.0	General	78
7.3.1	FP Type 0: Reference FP (ReFP)	79
7.3.2	FP Type 1a: "classical" Fixed Part for ISDN Network	79
7.3.2.1	Introduction	79
7.3.2.2	Compatible services and codecs	79
7.3.2.3	Specifications	80
7.3.2.3.1	Transcoding and equalization	80
7.3.2.3.2	PP Type detection	80
7.3.2.3.3	Activation of audio processing functions	80
7.3.2.3.4	Transmission specification	80
7.3.3	FP Type 1b: Fixed Part for ISDN Network	81
7.3.3.1	Introduction	81
7.3.3.2	Compatible services and codecs	81
7.3.3.3	Specification	81
7.3.3.3.1	Transcoding and equalization	81
7.3.3.3.2	PP Type detection	81
7.3.3.3.3	Activation of audio processing functions	82
7.3.3.3.4	Transmission specification	82
7.3.4	FP Type 2: FP with analog 2-wire interface, 3,1 kHz service	82
7.3.4.1	Introduction	82
7.3.4.2	Compatible services, physical interfaces and codecs	82
7.3.4.3	Specification	83
7.3.4.3.1	Transcoding, equalization and conversion	83
7.3.4.3.2	PP Type detection and activation of audio processing functions	83
7.3.4.3.3	Transmission specification	83
7.3.5	FP Type 3: VoIP narrowband Fixed Part	83
7.3.5.1	Introduction	83
7.3.5.2	Compatible services, physical interfaces and codecs	83
7.3.5.3	Specification	84
7.3.5.3.1	Transcoding and equalization	84
7.3.5.3.2	PP Type detection	84
7.3.5.3.3	Activation of audio processing functions	85
7.3.5.3.4	Transmission specification	85
7.3.6	FP Type 4: ISDN wideband Fixed Part	85
7.3.6.1	Introduction	85
7.3.6.2	Compatible services and codecs	85
7.3.6.3	Specification	86
7.3.6.3.1	Transcoding and equalization	86
7.3.6.3.2	PP Type detection	86
7.3.6.3.3	Activation of audio processing functions	86
7.3.6.3.4	Transmission specification	86
7.3.7	FP Type 5: VoIP wideband, super-wideband, fullband, FBHR or ultra-band Fixed Part	87
7.3.7.1	Introduction	87
7.3.7.2	Compatible services, physical interfaces and codecs	87
7.3.7.3	Specification	87
7.3.7.3.1	Transcoding and equalization	87
7.3.7.3.2	PP type detection	88
7.3.7.3.3	Activation of audio processing functions	88
7.3.7.3.4	Transmission specification	88
7.3.8	FP Type 6a: FP handling an Internal call inside a DECT FP (any service)	88
7.3.8.1	Introduction	88
7.3.8.2	Compatible services, physical interfaces and codecs	89
7.3.8.3	Specification	89
7.3.9	FP Type 6b: FP handling an n-party conference inside a DECT FP (any service)	89
7.3.9.1	Introduction	89
7.3.9.2	Compatible services, physical interfaces and codecs	89
7.3.9.3	Specification for the conference bridge	89

7.3.10	FP Type 7: DECT Repeater Part (REP).....	89
7.3.10.1	Introduction.....	89
7.3.10.2	Compatible services, physical interfaces and codecs	89
7.3.10.3	Specification.....	90
7.4	Additional features	90
7.4.1	Introduction.....	90
7.4.2	Echo canceller in Fixed Part	90
7.4.3	Echo suppressor in Fixed Part.....	91
7.5	Transmission characteristics for Portable Parts	91
7.5.1	Transmission characteristics for Portable Part type 1a ("Classic GAP" handset).....	91
7.5.1.1	PP frequency responses.....	91
7.5.1.1.1	Sending.....	91
7.5.1.1.2	Receiving.....	92
7.5.1.2	PP sending and receiving loudness ratings.....	92
7.5.1.2.1	Nominal values.....	92
7.5.1.2.2	User-controlled volume control in PP	93
7.5.1.2.3	PP adaptive volume control.....	94
7.5.1.3	Sidetone.....	94
7.5.1.3.1	Talker sidetone	94
7.5.1.3.2	Listener sidetone.....	95
7.5.1.4	Terminal coupling loss	96
7.5.1.4.1	Weighted Terminal Coupling Loss (TCLw).....	96
7.5.1.4.2	Stability loss	97
7.5.1.5	Distortion	98
7.5.1.5.1	Sending.....	98
7.5.1.5.2	Receiving.....	99
7.5.1.5.3	Sidetone.....	99
7.5.1.6	Out of band signals.....	99
7.5.1.6.1	Sending (discrimination against out of band input signals).....	99
7.5.1.6.2	Receiving (spurious out of band signals).....	100
7.5.1.7	Noise	100
7.5.1.7.1	Sending.....	100
7.5.1.7.2	Band-limited noise.....	100
7.5.1.7.3	Receiving.....	101
7.5.1.7.4	Level of sampling frequency (receiving).....	101
7.5.1.8	Acoustic shock	101
7.5.1.8.1	Continuous signal	101
7.5.1.8.2	Peak signal.....	101
7.5.1.9	PP Delay.....	102
7.5.1.10	PP ambient noise rejection	103
7.5.2	Additional requirements for PP type 1b ("improved GAP" handset)	103
7.5.2.0	General	103
7.5.2.1	Terminal coupling loss	103
7.5.2.1.1	Weighted Terminal Coupling Loss (TCLw).....	103
7.5.2.2	Attenuation Range in Sending Direction during Double Talk A _{H,S,dt}	104
7.5.2.3	Attenuation Range in Receiving Direction during Double Talk A _{H,R,dt}	106
7.5.2.4	Activation in Sending Direction.....	106
7.5.2.5	Activation in Receiving Direction.....	108
7.5.3	Transmission characteristics for PP types 1c and 1d (HATS tested, narrowband telephony handsets)	109
7.5.3.1	Frequency responses	109
7.5.3.1.1	Sending.....	109
7.5.3.1.2	Receiving.....	110
7.5.3.2	Sending and receiving loudness ratings	113
7.5.3.2.1	Nominal values.....	113
7.5.3.2.2	Void.....	114
7.5.3.2.3	Void.....	114
7.5.3.2.4	Microphone mute.....	114
7.5.3.2.5	Positional robustness	115
7.5.3.2.6	Send Loudness Level.....	115
7.5.3.2.7	Receive Loudness Level.....	115
7.5.3.3	Sidetone.....	116

7.5.3.3.1	Sidetone masking rating (STMR).....	116
7.5.3.3.2	Void.....	116
7.5.3.3.3	Sidetone delay	116
7.5.3.4	Terminal coupling loss.....	117
7.5.3.4.1	Terminal Coupling Loss weighted (TCLw).....	117
7.5.3.4.2	Stability loss	118
7.5.3.5	Distortion	119
7.5.3.5.1	Sending Distortion.....	119
7.5.3.5.2	Receiving Distortion.....	120
7.5.3.6	Out of band signals.....	120
7.5.3.6.1	Out-of-Band Signals in Send direction.....	120
7.5.3.6.2	Out-of-band signals in receiving direction	121
7.5.3.7	Noise	121
7.5.3.7.1	Sending.....	121
7.5.3.7.2	Receiving.....	122
7.5.3.8	Acoustic shock	123
7.5.3.8.0	General	123
7.5.3.8.1	Continuous signal	123
7.5.3.8.2	Void.....	123
7.5.3.9	Delay	123
7.5.3.10	Void.....	124
7.5.3.11	Double Talk Performance	124
7.5.3.11.0	General	124
7.5.3.11.1	Attenuation Range in Sending Direction during Double Talk AH,S,dt	125
7.5.3.11.2	Attenuation Range in Receiving Direction during Double Talk A _{H,R,dt}	126
7.5.3.11.3	Detection of Echo Components during Double Talk.....	127
7.5.3.11.4	Minimum activation level and sensitivity of double talk detection	128
7.5.3.12	Switching characteristics.....	128
7.5.3.12.0	General	128
7.5.3.12.1	Activation in Sending Direction.....	128
7.5.3.12.2	Activation in Receiving Direction	129
7.5.3.12.3	Silence Suppression and Comfort Noise Generation	129
7.5.3.12.4	Performance in sending direction in the presence of background noise	129
7.5.3.12.5	Speech Quality in the Presence of Background Noise	130
7.5.3.12.6	Quality of Background Noise Transmission (with Far End Speech)	131
7.5.3.12.7	Void.....	132
7.5.3.12.8	Positional Robustness of Speech Quality in the Presence of Background Noise	132
7.5.3.13	Quality of echo cancellation.....	132
7.5.3.13.0	General	132
7.5.3.13.1	Temporal echo effects	132
7.5.3.13.2	Spectral Echo Attenuation	133
7.5.3.13.3	Variable echo path.....	133
7.5.4	Transmission characteristics for PP types 3a and 3b (narrowband loudspeaking and handsfree devices).....	134
7.5.4.1	Sending sensitivity/frequency response	134
7.5.4.2	Receive sensitivity/frequency response.....	135
7.5.4.3	Send loudness rating	137
7.5.4.4	Receive loudness rating.....	137
7.5.4.5	Sending distortion	138
7.5.4.6	Receiving distortion	139
7.5.4.7	Out-of-band signals in sending direction	139
7.5.4.8	Out-of-band signals in receiving direction	140
7.5.4.9	Sending noise	141
7.5.4.10	Receiving noise	141
7.5.4.11	Terminal Coupling Loss weighted (TCLw)	142
7.5.4.12	Stability Loss.....	142
7.5.4.13	Double Talk Performance	143
7.5.4.13.0	General	143
7.5.4.13.1	Attenuation Range in Sending Direction during Double Talk AH,S,dt	143
7.5.4.13.2	Attenuation Range in Receiving Direction during Double Talk A _{H,R,dt}	145
7.5.4.13.3	Detection of Echo Components during Double Talk.....	145
7.5.4.13.4	Minimum activation level and sensitivity of double talk detection	147

7.5.4.14	Switching characteristics.....	147
7.5.4.14.0	General	147
7.5.4.14.1	Activation in Sending Direction	147
7.5.4.14.2	Activation in Receiving Direction	148
7.5.4.14.3	Silence Suppression and Comfort Noise Generation	148
7.5.4.14.4	Performance in sending direction in the presence of background noise	148
7.5.4.14.5	Speech Quality in the Presence of Background Noise.....	149
7.5.4.14.6	Quality of Background Noise Transmission (with Far End Speech).....	150
7.5.4.15	Quality of echo cancellation.....	150
7.5.4.15.0	General	150
7.5.4.15.1	Temporal echo effects	151
7.5.4.15.2	Spectral Echo Attenuation.....	151
7.5.4.15.3	Variable echo path	152
7.5.4.16	Microphone mute	152
7.5.4.17	Delay	152
7.5.4.18	Send Loudness Level	153
7.5.4.19	Receive Loudness Level	153
7.5.5	Transmission characteristics for PP type 2a (P.311 tested, wideband handset).....	154
7.5.5.0	General	154
7.5.5.1	Sending characteristics	155
7.5.5.1.1	Loudness rating	155
7.5.5.1.2	Sensitivity/frequency characteristics	155
7.5.5.1.3	Noise.....	155
7.5.5.1.4	Distortion.....	155
7.5.5.1.5	Discrimination against out-of-band input signals	155
7.5.5.2	Receiving characteristics	156
7.5.5.2.1	Loudness rating	156
7.5.5.2.2	Sensitivity/frequency characteristics	156
7.5.5.2.3	Noise.....	156
7.5.5.2.4	Distortion.....	156
7.5.5.2.5	Spurious out-of-band receiving signals	157
7.5.5.3	Sidetone characteristics	157
7.5.5.3.1	Talker sidetone	157
7.5.5.3.2	Sidetone distortion.....	157
7.5.5.4	Echo path loss characteristics.....	157
7.5.5.4.1	Weighted terminal coupling loss	157
7.5.5.4.2	Stability loss	157
7.5.6	Transmission characteristics for PP types 2b and 2c (HATS tested wideband handsets).....	158
7.5.6.1	Frequency responses	158
7.5.6.1.1	Sending.....	158
7.5.6.1.2	Receiving.....	159
7.5.6.2	Send and receive loudness ratings.....	162
7.5.6.2.1	Nominal values	162
7.5.6.2.2	Void.....	164
7.5.6.2.3	Void.....	164
7.5.6.2.4	Microphone mute.....	164
7.5.6.2.5	Positional robustness	164
7.5.6.2.6	Send Loudness Level.....	164
7.5.6.2.7	Receive Loudness Level.....	165
7.5.6.3	Sidetone.....	165
7.5.6.3.1	SideTone Masking Rating (STMR).....	165
7.5.6.3.2	Void.....	166
7.5.6.3.3	Sidetone delay	166
7.5.6.4	Terminal coupling loss	166
7.5.6.4.1	Terminal Coupling Loss (TCL).....	166
7.5.6.4.2	Stability loss	167
7.5.6.5	Distortion	168
7.5.6.5.1	Sending Distortion.....	168
7.5.6.5.2	Receiving Distortion.....	169
7.5.6.6	Noise	170
7.5.6.6.1	Sending.....	170
7.5.6.6.2	Receiving.....	170

7.5.6.7	Acoustic shock	171
7.5.6.7.0	General	171
7.5.6.7.1	Continuous signal	171
7.5.6.8	Delay	171
7.5.6.9	Void.....	172
7.5.6.10	Double talk Performance.....	172
7.5.6.10.0	General	172
7.5.6.10.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	173
7.5.6.10.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	174
7.5.6.10.3	Detection of Echo Components during Double Talk.....	175
7.5.6.10.4	Minimum activation level and sensitivity of double talk detection	176
7.5.6.11	Switching characteristics.....	177
7.5.6.11.0	General	177
7.5.6.11.1	Activation in Sending Direction	177
7.5.6.11.2	Activation in Receiving Direction	177
7.5.6.11.3	Silence Suppression and Comfort Noise Generation.....	178
7.5.6.11.4	Performance in Sending in the Presence of Background Noise.....	178
7.5.6.11.5	Speech Quality in the Presence of Background Noise.....	178
7.5.6.11.6	Quality of Background Noise Transmission (with Far End Speech).....	179
7.5.6.11.7	Void.....	180
7.5.6.11.8	Positional Robustness of Speech Quality in the Presence of Background Noise	180
7.5.6.12	Quality of echo cancellation.....	180
7.5.6.12.0	General	180
7.5.6.12.1	Temporal echo effects	180
7.5.6.12.2	Spectral Echo Attenuation.....	181
7.5.6.12.3	Variable echo path.....	182
7.5.6.13	Out of band signals.....	182
7.5.6.13.1	Out-of-band signals in sending direction.....	182
7.5.6.13.2	Out-of-band signals in receiving direction	182
7.5.7	Transmission characteristics for PP types 4a and 4b (HATS Tested wideband loudspeaking and handsfree devices).....	183
7.5.7.1	Sending sensitivity/frequency response	183
7.5.7.2	Receive sensitivity/frequency response.....	184
7.5.7.3	Send loudness rating.....	187
7.5.7.4	Receive https://standards.iteh.ai/catalog/standards/sist/06008cde-25f4ec-a452-f78fedc4d82e/osist-pren-300-176-2-v2-3-5-2022 loudness rating.....	187
7.5.7.5	Sending distortion.....	188
7.5.7.6	Receiving distortion	189
7.5.7.7	Out-of-band signals in sending direction	190
7.5.7.8	Out-of-band signals in receiving direction	190
7.5.7.9	Sending noise	191
7.5.7.10	Receiving noise	191
7.5.7.11	Terminal Coupling Loss.....	192
7.5.7.12	Stability Loss.....	193
7.5.7.13	Double Talk Performance	194
7.5.7.13.0	General	194
7.5.7.13.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	194
7.5.7.13.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	196
7.5.7.13.3	Detection of Echo Components during Double Talk.....	196
7.5.7.13.4	Minimum activation level and sensitivity of double talk detection	198
7.5.7.14	Switching characteristics.....	198
7.5.7.14.0	General	198
7.5.7.14.1	Activation in Sending Direction	199
7.5.7.14.2	Activation in Receiving Direction	199
7.5.7.14.3	Silence Suppression and Comfort Noise Generation.....	199
7.5.7.14.4	Performance in sending direction in the presence of background noise	200
7.5.7.14.5	Speech Quality in the Presence of Background Noise.....	200
7.5.7.14.6	Quality of Background Noise Transmission (with Far End Speech).....	201
7.5.7.15	Quality of echo cancellation.....	202
7.5.7.15.1	Temporal echo effects	202
7.5.7.15.2	Spectral Echo Attenuation	202
7.5.7.15.3	Variable echo path.....	203
7.5.7.16	Microphone mute	203

7.5.7.17	Delay	203
7.5.7.18	Send Loudness Level	204
7.5.7.19	Receive Loudness Level	205
7.5.8	Transmission characteristics for PP type 5a ("super-wideband 14 kHz handset or headset")	206
7.5.8.1	Frequency responses	206
7.5.8.1.1	Sending.....	206
7.5.8.1.2	Receiving.....	207
7.5.8.2	Send and receive loudness ratings.....	209
7.5.8.2.1	Send Loudness Rating	209
7.5.8.2.2	Receive Loudness Rating	210
7.5.8.2.3	Send Loudness Level.....	211
7.5.8.2.4	Receive Loudness Level.....	212
7.5.8.3	Sidetone.....	212
7.5.8.3.1	Sidetone Masking Rating STMR (Mouth to ear).....	212
7.5.8.3.2	Sidetone Delay.....	213
7.5.8.4	Terminal Coupling Loss.....	213
7.5.8.4.1	Unweighted Terminal Coupling Loss.....	213
7.5.8.4.2	Stability Loss	214
7.5.8.5	Distortion	215
7.5.8.5.1	Sending Distortion.....	215
7.5.8.5.2	Receiving Distortion.....	216
7.5.8.6	Noise	217
7.5.8.6.1	Sending.....	217
7.5.8.6.2	Receiving.....	217
7.5.8.7	Acoustic shock	218
7.5.8.7.0	General	218
7.5.8.7.1	Continuous signal.....	218
7.5.8.8	Delay	218
7.5.8.9	Double talk Performance.....	218
7.5.8.9.0	General	218
7.5.8.9.1	Attenuation range in send direction during double talk $A_{H,S,dt}$	219
7.5.8.9.2	Attenuation range in receive direction during double talk $A_{H,R,dt}$	220
7.5.8.9.3	Detection of echo components during double talk	221
7.5.8.10	Switching Characteristics.....	222
7.5.8.10.0	Note https://standards.iteh.ai/catalog/standards/sist/06008cde-635f4cefca152-178fec4d82e/osit-pren-300-176-2-v2-2022	222
7.5.8.10.1	Activation in send direction.....	223
7.5.8.10.2	Silence suppression and comfort noise generation	223
7.5.8.10.3	Performance in Sending in the Presence of Background Noise.....	223
7.5.8.10.4	Speech quality in the presence of background noise	224
7.5.8.10.5	Positional Robustness of Speech Quality in the Presence of Background Noise	225
7.5.8.10.6	Quality of background noise transmission (with far end speech).....	225
7.5.8.11	Quality of echo cancellation.....	226
7.5.8.11.1	Temporal echo effects	226
7.5.8.11.2	Spectral echo attenuation.....	226
7.5.8.11.3	Variable echo path.....	227
7.5.9	Transmission characteristics for PP type 5b ("super-wideband 14 kHz loudspeaking and handsfree devices")	227
7.5.9.1	Sending sensitivity/frequency response	227
7.5.9.2	Receive sensitivity/frequency response.....	229
7.5.9.2.1	Handheld terminal	229
7.5.9.2.2	Desktop terminal	230
7.5.9.2.3	Terminals intended to be used simultaneously by several users.....	231
7.5.9.3	Sending loudness rating	231
7.5.9.3.1	Nominal Value.....	231
7.5.9.3.2	Microphone mute.....	231
7.5.9.4	Receive loudness rating.....	232
7.5.9.5	Sending distortion	233
7.5.9.5.1	Signal to harmonic distortion versus frequency	233
7.5.9.5.2	Signal to harmonic distortion for higher input level.....	234
7.5.9.6	Receiving distortion	234
7.5.9.7	Sending noise	235
7.5.9.8	Receiving noise	235

7.5.9.9	Terminal Coupling Loss.....	236
7.5.9.9.1	Unweighted Terminal Coupling Loss.....	236
7.5.9.9.2	Stability Loss.....	237
7.5.9.10	Double Talk Performance	237
7.5.9.10.0	General	237
7.5.9.10.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	238
7.5.9.10.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	239
7.5.9.10.3	Detection of Echo Components during Double Talk.....	240
7.5.9.10.4	Minimum activation level and sensitivity of double talk detection.....	241
7.5.9.11	Switching characteristics.....	242
7.5.9.11.0	Note	242
7.5.9.11.1	Activation in Sending Direction	242
7.5.9.11.2	Silence Suppression and Comfort Noise Generation.....	242
7.5.9.11.3	Performance in sending direction in the presence of background noise	243
7.5.9.11.4	Speech Quality in the Presence of Background Noise.....	243
7.5.9.11.5	Quality of Background Noise Transmission (with Far End Speech).....	244
7.5.9.12	Quality of echo cancellation.....	245
7.5.9.12.1	Temporal echo effects	245
7.5.9.12.2	Spectral Echo Attenuation.....	245
7.5.9.12.3	Variable echo path.....	246
7.5.9.13	Delay	246
7.5.9.14	Send Loudness Level	246
7.5.9.15	Receive Loudness Level	247
7.5.10	Transmission characteristics for PP type 7a ("fullband 20 kHz handset or headset").....	248
7.5.10.1	Frequency responses	248
7.5.10.1.1	Sending.....	248
7.5.10.1.2	Receiving.....	249
7.5.10.2	Send and receive loudness ratings.....	251
7.5.10.2.1	Send Loudness Rating	251
7.5.10.2.2	Receive Loudness Rating	252
7.5.10.2.3	Send Loudness Level.....	253
7.5.10.2.4	Receive Loudness Level.....	253
7.5.10.3	Sidetone.....	254
7.5.10.3.1	Sidetone Masking Rating STMR (Mouth to ear) http://standards.iteh.ai/catalog/standards/sist/06008cde-25f1ecf-a452-f78fecdc4d82e/osist-pren-300-176-2-v2-2022	254
7.5.10.3.2	Sidetone Delay.....	254
7.5.10.4	Terminal Coupling Loss.....	255
7.5.10.4.1	Unweighted Terminal Coupling Loss.....	255
7.5.10.4.2	Stability Loss.....	256
7.5.10.5	Distortion	257
7.5.10.5.1	Sending Distortion.....	257
7.5.10.5.2	Receiving Distortion.....	258
7.5.10.6	Noise	259
7.5.10.6.1	Sending.....	259
7.5.10.6.2	Receiving.....	259
7.5.10.7	Acoustic shock	260
7.5.10.7.0	General	260
7.5.10.7.1	Continuous signal	260
7.5.10.8	Delay	260
7.5.10.9	Double talk Performance.....	260
7.5.10.9.0	General	260
7.5.10.9.1	Attenuation range in send direction during double talk $A_{H,S,dt}$	261
7.5.10.9.2	Attenuation range in receive direction during double talk $A_{H,R,dt}$	262
7.5.10.9.3	Detection of echo components during double talk	263
7.5.10.10	Switching Characteristics	264
7.5.10.10.0	Note	264
7.5.10.10.1	Activation in send direction.....	265
7.5.10.10.2	Silence suppression and comfort noise generation	265
7.5.10.10.3	Performance in Sending in the Presence of Background Noise.....	265
7.5.10.10.4	Speech quality in the presence of background noise	266
7.5.10.10.5	Positional Robustness of Speech Quality in the Presence of Background Noise	267
7.5.10.10.6	Quality of background noise transmission (with far end speech).....	267
7.5.10.11	Quality of echo cancellation.....	268

7.5.10.11.1	Temporal echo effects	268
7.5.10.11.2	Spectral echo attenuation.....	268
7.5.10.11.3	Variable echo path.....	269
7.5.11	Transmission characteristics for PP type 7b ("fullband 20 kHz loudspeaking and handsfree devices")	269
7.5.11.1	Sending sensitivity/frequency response	269
7.5.11.2	Receive sensitivity/frequency response.....	271
7.5.11.2.0	General	271
7.5.11.2.1	Handheld terminal	271
7.5.11.2.2	Desktop terminal	272
7.5.11.2.3	Terminals intended to be used simultaneously by several users.....	273
7.5.11.3	Sending loudness rating	273
7.5.11.3.1	Nominal Value.....	273
7.5.11.3.2	Microphone Mute	273
7.5.11.4	Receive loudness rating.....	274
7.5.11.5	Sending distortion	275
7.5.11.5.1	Signal to harmonic distortion versus frequency	275
7.5.11.5.2	Signal to harmonic distortion for higher input level.....	276
7.5.11.6	Receiving distortion	276
7.5.11.7	Sending noise	277
7.5.11.8	Receiving noise	278
7.5.11.9	Terminal Coupling Loss.....	278
7.5.11.9.1	Unweighted Terminal Coupling Loss.....	278
7.5.11.9.2	Stability Loss.....	279
7.5.11.10	Double Talk Performance.....	280
7.5.11.10.0	General	280
7.5.11.10.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$	280
7.5.11.10.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$	282
7.5.11.10.3	Detection of Echo Components during Double Talk.....	282
7.5.11.10.4	Minimum activation level and sensitivity of double talk detection	284
7.5.11.11	Switching characteristics.....	284
7.5.11.11.0	Note	284
7.5.11.11.1	Activation in Sending Direction	285
7.5.11.11.2	Silence Suppression and Comfort Noise Generation.....	285
7.5.11.11.3	Performance in sending direction in the presence of background noise	285
7.5.11.11.4	Speech Quality in the Presence of Background Noise.....	286
7.5.11.11.5	Quality of Background Noise Transmission (with Far End Speech).....	287
7.5.11.12	Quality of echo cancellation.....	288
7.5.11.12.1	Temporal echo effects	288
7.5.11.12.2	Spectral Echo Attenuation.....	288
7.5.11.12.3	Variable echo path.....	289
7.5.11.13	Delay	289
7.5.11.14	Send Loudness Level	289
7.5.11.15	Receive Loudness Level	290
7.5.12	Transmission characteristics for PP types 7c, d, e, f ("fullband 20 kHz stereo audio device").....	290
7.5.13	Transmission characteristics for PP type 7g ("FBHR 24 kHz headset device")	291
7.5.14	Transmission characteristics for PP type 7h ("FBHR 24 kHz loudspeaking device").....	291
7.5.15	Transmission characteristics for PP type 7i ("FBLFE 250 Hz loudspeaking device")	291
7.5.16	Transmission characteristics for PP type 7j ("fullband 20 kHz low-latency microphone device") .	291
7.5.17	Transmission characteristics for PP type 8a ("ultra-band 48 kHz headset device")	291
7.5.18	Transmission characteristics for PP type 8b ("ultra-band 48 kHz loudspeaking device").....	291
7.6	Transmission characteristics for Fixed Parts	292
7.6.1	Transmission characteristics for FP type 1a ("Classic" Fixed Part with ISDN Network interface, 3,1 kHz service)	292
7.6.1.1	Reduction of echo from PP	292
7.6.1.2	FP Network echo control	294
7.6.1.3	FP adaptive volume control	295
7.6.1.4	FP Delay.....	295
7.6.2	Transmission characteristics for FP type 1b ("new" Fixed Part with ISDN Network interface, 3,1 kHz service)	297
7.6.2.0	General.....	297
7.6.2.1	FP Network echo control	297