



## iTeh STANDARD Digital Enhanced Cordless Telecommunications (DECT); Test specification; Part 2: Audio and speech (standards.iteh.ai)

ETSI EN 300 176-2 V2.3.5 (2022-02)  
<https://standards.iteh.ai/catalog/standards/sist/6ffc8a5e-d302-4efe-9dc6-c1d73691d41d/etsi-en-300-176-2-v2-3-5-2022-02>



Reference
REN/DECT-00360
Keywords
7 kHz, audio, codec, DECT, handsfree, IMT-2000, LC3plus, loudspeaking, mobility, narrowband, quality, radio, regulation, speech, superwideband, TDD, TDMA, telephony, terminal, testing, voice, wideband
<b>ETSI</b>
650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

### ***Important notice***

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at  
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

<https://standards.iteh.ai/catalog/standards/sist/6ffc8a5e-d302-4efeNotice of disclaimer & limitation of liability 2-3>

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.  
In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

### ***Copyright Notification***

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.  
All rights reserved.

## Contents

Intellectual Property Rights .....	16
Foreword.....	16
Modal verbs terminology.....	17
1 Scope .....	18
2 References .....	19
2.1 Normative references .....	19
2.2 Informative references.....	22
3 Definition of terms, symbols and abbreviations.....	24
3.1 Terms.....	24
3.2 Symbols.....	27
3.3 Abbreviations .....	27
4 Interpretation of the measurement results .....	29
5 General test requirements.....	30
5.0 General .....	30
5.1 Test philosophy .....	30
5.1.1 Testable items .....	30
5.1.2 Testing of the codecs .....	30
5.1.3 Testing of the audio types.....	30
5.1.4 Devices with analog line interfaces .....	31
5.1.5 Equipment supporting an ETSI approved profile .....	31
5.1.6 Equipment not supporting an ETSI approved profile .....	32
5.1.7 Applicant's declaration.....	32
6 General testing conditions .....	32
6.1 Acoustical environment.....	32
6.2 Lower Tester (LT).....	33
6.2.1 Description. <a href="https://standards.iteh.ai/catalog/standards/siat/6ffe8a5e-3021-4a06-9a05-ef473691d41d/etsi_en_300_176-2_v2-3-5-2022-02">https://standards.iteh.ai/catalog/standards/siat/6ffe8a5e-3021-4a06-9a05-ef473691d41d/etsi_en_300_176-2_v2-3-5-2022-02</a> .....	33
6.2.2 Connections between the EUT and the LT .....	33
6.2.3 Functions and abilities .....	33
6.2.4 Accuracy of measurements and test signal generation .....	33
6.3 Power and environment.....	34
6.3.1 Environment for tests.....	34
6.3.2 Power supply limitations .....	34
6.3.3 Power source.....	34
6.4 Test configurations .....	34
6.4.1 General.....	34
6.4.2 Testing a DECT system .....	34
6.4.3 Testing a separate PP or FP .....	35
6.4.4 Reference FP (ReFP) and Reference PP (RePP).....	36
6.5 Digital signal levels .....	37
6.5.1 Digital signal levels for codecs G.711 and G.726.....	37
6.6 General test conditions .....	37
6.7 Ideal codecs (for codecs G.726, G.711, G.722, G.729.1, MPEG-AAC and LC3plus).....	38
6.7.0 General.....	38
6.7.1 Ideal codec for codecs G.726, G.711 and LC3plus in NB mode .....	38
6.7.2 Ideal codec for codecs G.722, G.729.1, MPEG-4 and LC3plus (wideband mode) .....	39
6.7.3 Ideal codec for MPEG-4 or LC3plus (super-wideband mode) .....	40
6.7.4 Ideal codec for LC3plus in fullband, FBHR, FBLFE or ultra-band mode.....	40
6.8 Electro-acoustical equipment .....	40
6.8.0 General.....	40
6.8.1 Artificial mouth and artificial ear .....	40
6.8.2 Head And Torso Simulator (HATS) .....	40
6.9 Speech coding scheme.....	41
6.9.1 Requirement for speech coding algorithm .....	41

6.9.2	Applicant's declaration on speech coding algorithm.....	41
6.9.3	Requirement for the TAP in the FP .....	41
6.9.4	Applicant's declaration on the TAP in the FP .....	41
6.10	Test setup.....	41
6.10.1	Set-up for handset type 1a or 1b .....	41
6.10.2	Set-up for handset type 2a .....	41
6.10.3	Set-up for handset or headset other than type 1a, 1b or 2a .....	42
6.10.3.0	Super-wideband and fullband applications .....	42
6.10.3.1	Positioning handset or headset .....	42
6.10.3.2	Position and calibration of HATS .....	42
6.10.4	Set-up for hands-free measurements.....	43
6.10.4.0	Super-wideband and fullband applications .....	43
6.10.4.1	Positioning handsfree .....	44
6.10.4.2	Position and calibration of HATS .....	50
6.10.4.2.1	Sending.....	50
6.10.4.2.2	Receiving.....	50
6.10.5	Set-up for measurements in loudspeaking mode .....	51
6.10.6	Setup for background noise simulation.....	51
6.10.7	Setup of variable echo path.....	52
6.10.8	Setup for testing positional robustness of handsets.....	54
7	Test of audio specifications.....	55
7.1	Overall description .....	55
7.1.1	Introduction to DECT audio specifications .....	55
7.1.2	Introduction to the audio types .....	55
7.1.3	List of Audio types .....	56
7.1.4	Audio types for Portable Parts .....	57
7.1.5	Audio types for Fixed Parts .....	58
7.1.6	Complete DECT system .....	59
7.1.7	Structure of the specification of the audio types .....	59
7.1.8	Audio Types and codecs .....	67
7.1.9	Audio Types and physical interfaces .....	67
7.2	Audio types applicable to Portable Parts.....	67
7.2.0	General.....	67
7.2.1	Performance levels of DECT Portable Parts (handsets).....	67
7.2.2	Type 0: Reference PP (RePP).....	68
7.2.3	PP Type 1a: "Classic" GAP narrowband handset.....	69
7.2.3.1	Introduction .....	69
7.2.3.2	Compatible services and codecs.....	69
7.2.3.3	Specification.....	69
7.2.4	PP Type 1b: "Improved" GAP narrowband handset.....	69
7.2.4.1	Introduction .....	69
7.2.4.2	Compatible services and codecs.....	70
7.2.4.3	Specification.....	70
7.2.5	PP Type 1c: HATS-tested "standard" narrowband handset .....	70
7.2.5.1	Introduction .....	70
7.2.5.2	Compatible services and codecs.....	70
7.2.5.3	Specification.....	70
7.2.6	PP Type 1d: HATS-tested "improved" narrowband handset .....	71
7.2.6.1	Introduction .....	71
7.2.6.2	Compatible services and codecs.....	71
7.2.6.3	Specification.....	71
7.2.7	PP Type 3a: HATS tested narrowband "standard" loudspeaking handsfree .....	71
7.2.7.1	Introduction .....	71
7.2.7.2	Compatible services and codecs.....	71
7.2.7.3	Specification.....	72
7.2.8	PP Type 3b: HATS tested narrowband "improved" loudspeaking handsfree .....	72
7.2.8.1	Introduction .....	72
7.2.8.2	Compatible services and codecs.....	72
7.2.8.3	Specification.....	72
7.2.9	PP Type 2a: P.311-tested wideband handset.....	72
7.2.9.1	Introduction .....	72

7.2.9.2	Compatible services and codecs.....	72
7.2.9.3	Specification.....	72
7.2.10	PP Type 2b: HATS-tested "standard" wideband handset or headset .....	72
7.2.10.1	Introduction.....	72
7.2.10.2	Compatible services and codecs.....	73
7.2.10.3	Specification.....	73
7.2.11	PP Type 2c: HATS tested "improved" wideband handset or headset.....	73
7.2.11.1	Introduction.....	73
7.2.11.2	Compatible services and codecs.....	73
7.2.11.3	Specification.....	73
7.2.12	PP Type 4a: HATS tested wideband "standard" loudspeaking handsfree .....	73
7.2.12.1	Introduction.....	73
7.2.12.2	Compatible services and codecs.....	74
7.2.12.3	Specification.....	74
7.2.13	PP Type 4b: HATS tested wideband "improved" loudspeaking and handsfree.....	74
7.2.13.1	Introduction.....	74
7.2.13.2	Compatible services and codecs.....	74
7.2.13.3	Specification.....	74
7.2.14	PP Type 5a: super-wideband 14 kHz handset or headset.....	74
7.2.14.1	Introduction.....	74
7.2.14.2	Compatible services and codecs.....	75
7.2.14.3	Specification.....	75
7.2.15	PP Type 5b: super-wideband 14 kHz loudspeaking handsfree .....	75
7.2.15.1	Introduction.....	75
7.2.15.2	Compatible services and codecs.....	75
7.2.15.3	Specification.....	75
7.2.16	PP Type 6: PPs with external 2 wire, 3.1 kHz telephony interface.....	75
7.2.16.1	Introduction.....	75
7.2.16.2	Compatible services and codecs.....	75
7.2.16.3	Specification.....	75
7.2.17	PP Type 7a: fullband 20 kHz handset or headset.....	75
7.2.17.1	Introduction.....	75
7.2.17.2	Compatible services and codecs.....	75
7.2.17.3	Specification.....	75
7.2.18	PP Type 7b: fullband 20 kHz loudspeaking handsfree .....	76
7.2.18.1	Introduction.....	76
7.2.18.2	Compatible services and codecs.....	76
7.2.18.3	Specification.....	76
7.2.19	PP Types 7c, d, e, f: fullband 20 kHz stereo audio device.....	76
7.2.19.1	Introduction.....	76
7.2.19.2	Compatible services and codecs.....	76
7.2.19.3	Specification.....	76
7.2.20	PP Type 7g: FBHR 24 kHz headset device .....	76
7.2.20.1	Introduction.....	76
7.2.20.2	Compatible services and codecs.....	76
7.2.20.3	Specification.....	77
7.2.21	PP Type 7h: FBHR 24 kHz loudspeaking device .....	77
7.2.21.1	Introduction.....	77
7.2.21.2	Compatible services and codecs.....	77
7.2.21.3	Specification.....	77
7.2.22	PP Type 7i: FBLFE 250 Hz loudspeaking device .....	77
7.2.22.1	Introduction.....	77
7.2.22.2	Compatible services and codecs.....	77
7.2.22.3	Specification.....	77
7.2.23	PP Type 7j: fullband 20 kHz low-latency microphone device.....	77
7.2.23.1	Introduction.....	77
7.2.23.2	Compatible services and codecs.....	77
7.2.23.3	Specification.....	77
7.2.24	PP Type 8a: ultra-band 48 kHz headset device.....	78
7.2.24.1	Introduction.....	78
7.2.24.2	Compatible services and codecs.....	78
7.2.24.3	Specification.....	78

7.2.25	PP Type 8b: ultra-band 48 kHz loudspeaking device .....	78
7.2.25.1	Introduction .....	78
7.2.25.2	Compatible services and codecs .....	78
7.2.25.3	Specification .....	78
7.3	Audio transmission types applicable to Fixed Parts .....	78
7.3.0	General .....	78
7.3.1	FP Type 0: Reference FP (ReFP) .....	79
7.3.2	FP Type 1a: "classical" Fixed Part for ISDN Network .....	79
7.3.2.1	Introduction .....	79
7.3.2.2	Compatible services and codecs .....	79
7.3.2.3	Specifications .....	80
7.3.2.3.1	Transcoding and equalization .....	80
7.3.2.3.2	PP Type detection .....	80
7.3.2.3.3	Activation of audio processing functions .....	80
7.3.2.3.4	Transmission specification .....	80
7.3.3	FP Type 1b: Fixed Part for ISDN Network .....	81
7.3.3.1	Introduction .....	81
7.3.3.2	Compatible services and codecs .....	81
7.3.3.3	Specification .....	81
7.3.3.3.1	Transcoding and equalization .....	81
7.3.3.3.2	PP Type detection .....	81
7.3.3.3.3	Activation of audio processing functions .....	82
7.3.3.3.4	Transmission specification .....	82
7.3.4	FP Type 2: FP with analog 2-wire interface, 3,1 kHz service .....	82
7.3.4.1	Introduction .....	82
7.3.4.2	Compatible services, physical interfaces and codecs .....	82
7.3.4.3	Specification .....	83
7.3.4.3.1	Transcoding, equalization and conversion .....	83
7.3.4.3.2	PP Type detection and activation of audio processing functions .....	83
7.3.4.3.3	Transmission specification .....	83
7.3.5	FP Type 3: VoIP narrowband Fixed Part .....	83
7.3.5.1	Introduction .....	83
7.3.5.2	Compatible services, physical interfaces and codecs .....	83
7.3.5.3	Specification .....	84
7.3.5.3.1	<a href="https://standards.itech.ai/catalog/standards/sist/6ffc8a5e-1302-4ef5-9dc6-c1d73691d41d/etsi-en-300-176-2-v2-3-5-2022-02">https://standards.itech.ai/catalog/standards/sist/6ffc8a5e-1302-4ef5-9dc6-c1d73691d41d/etsi-en-300-176-2-v2-3-5-2022-02</a>	84
7.3.5.3.2	Transcoding and equalization .....	84
7.3.5.3.3	PP Type detection .....	84
7.3.5.3.4	Activation of audio processing functions .....	85
7.3.5.3.5	Transmission specification .....	85
7.3.6	FP Type 4: ISDN wideband Fixed Part .....	85
7.3.6.1	Introduction .....	85
7.3.6.2	Compatible services and codecs .....	85
7.3.6.3	Specification .....	86
7.3.6.3.1	Transcoding and equalization .....	86
7.3.6.3.2	PP Type detection .....	86
7.3.6.3.3	Activation of audio processing functions .....	86
7.3.6.3.4	Transmission specification .....	86
7.3.7	FP Type 5: VoIP wideband, super-wideband, fullband, FBHR or ultra-band Fixed Part .....	87
7.3.7.1	Introduction .....	87
7.3.7.2	Compatible services, physical interfaces and codecs .....	87
7.3.7.3	Specification .....	87
7.3.7.3.1	Transcoding and equalization .....	87
7.3.7.3.2	PP type detection .....	88
7.3.7.3.3	Activation of audio processing functions .....	88
7.3.7.3.4	Transmission specification .....	88
7.3.8	FP Type 6a: FP handling an Internal call inside a DECT FP (any service) .....	88
7.3.8.1	Introduction .....	88
7.3.8.2	Compatible services, physical interfaces and codecs .....	89
7.3.8.3	Specification .....	89
7.3.9	FP Type 6b: FP handling an n-party conference inside a DECT FP (any service) .....	89
7.3.9.1	Introduction .....	89
7.3.9.2	Compatible services, physical interfaces and codecs .....	89
7.3.9.3	Specification for the conference bridge .....	89

7.3.10	FP Type 7: DECT Repeater Part (REP).....	89
7.3.10.1	Introduction.....	89
7.3.10.2	Compatible services, physical interfaces and codecs .....	89
7.3.10.3	Specification.....	90
7.4	Additional features .....	90
7.4.1	Introduction.....	90
7.4.2	Echo canceller in Fixed Part .....	90
7.4.3	Echo suppressor in Fixed Part.....	91
7.5	Transmission characteristics for Portable Parts .....	91
7.5.1	Transmission characteristics for Portable Part type 1a ("Classic GAP" handset).....	91
7.5.1.1	PP frequency responses.....	91
7.5.1.1.1	Sending.....	91
7.5.1.1.2	Receiving.....	92
7.5.1.2	PP sending and receiving loudness ratings.....	92
7.5.1.2.1	Nominal values.....	92
7.5.1.2.2	User-controlled volume control in PP .....	93
7.5.1.2.3	PP adaptive volume control.....	94
7.5.1.3	Sidetone.....	94
7.5.1.3.1	Talker sidetone .....	94
7.5.1.3.2	Listener sidetone.....	95
7.5.1.4	Terminal coupling loss .....	96
7.5.1.4.1	Weighted Terminal Coupling Loss (TCLw).....	96
7.5.1.4.2	Stability loss .....	97
7.5.1.5	Distortion .....	98
7.5.1.5.1	Sending.....	98
7.5.1.5.2	Receiving.....	99
7.5.1.5.3	Sidetone.....	99
7.5.1.6	Out of band signals.....	99
7.5.1.6.1	Sending (discrimination against out of band input signals).....	99
7.5.1.6.2	Receiving (spurious out of band signals) .....	100
7.5.1.7	Noise .....	100
7.5.1.7.1	Sending.....	100
7.5.1.7.2	Band-limited noise.....	100
7.5.1.7.3	Receiving.....	101
7.5.1.7.4	Level of sampling frequency (receiving).....	101
7.5.1.8	Acoustic shock .....	101
7.5.1.8.1	Continuous signal .....	101
7.5.1.8.2	Peak signal.....	101
7.5.1.9	PP Delay.....	102
7.5.1.10	PP ambient noise rejection .....	103
7.5.2	Additional requirements for PP type 1b ("improved GAP" handset) .....	103
7.5.2.0	General .....	103
7.5.2.1	Terminal coupling loss .....	103
7.5.2.1.1	Weighted Terminal Coupling Loss (TCLw).....	103
7.5.2.2	Attenuation Range in Sending Direction during Double Talk A <sub>H,S,dt</sub> .....	104
7.5.2.3	Attenuation Range in Receiving Direction during Double Talk A <sub>H,R,dt</sub> .....	106
7.5.2.4	Activation in Sending Direction.....	106
7.5.2.5	Activation in Receiving Direction.....	108
7.5.3	Transmission characteristics for PP types 1c and 1d (HATS tested, narrowband telephony handsets) .....	109
7.5.3.1	Frequency responses .....	109
7.5.3.1.1	Sending.....	109
7.5.3.1.2	Receiving.....	110
7.5.3.2	Sending and receiving loudness ratings .....	113
7.5.3.2.1	Nominal values.....	113
7.5.3.2.2	Void.....	114
7.5.3.2.3	Void.....	114
7.5.3.2.4	Microphone mute.....	114
7.5.3.2.5	Positional robustness .....	115
7.5.3.2.6	Send Loudness Level.....	115
7.5.3.2.7	Receive Loudness Level.....	115
7.5.3.3	Sidetone.....	116

7.5.3.3.1	Sidetone masking rating (STMR) .....	116
7.5.3.3.2	Void.....	116
7.5.3.3.3	Sidetone delay .....	116
7.5.3.4	Terminal coupling loss .....	117
7.5.3.4.1	Terminal Coupling Loss weighted (TCLw).....	117
7.5.3.4.2	Stability loss .....	118
7.5.3.5	Distortion .....	119
7.5.3.5.1	Sending Distortion.....	119
7.5.3.5.2	Receiving Distortion.....	120
7.5.3.6	Out of band signals.....	120
7.5.3.6.1	Out-of-Band Signals in Send direction.....	120
7.5.3.6.2	Out-of-band signals in receiving direction .....	121
7.5.3.7	Noise .....	121
7.5.3.7.1	Sending.....	121
7.5.3.7.2	Receiving.....	122
7.5.3.8	Acoustic shock .....	123
7.5.3.8.0	General .....	123
7.5.3.8.1	Continuous signal .....	123
7.5.3.8.2	Void.....	123
7.5.3.9	Delay .....	123
7.5.3.10	Void.....	124
7.5.3.11	Double Talk Performance .....	124
7.5.3.11.0	General .....	124
7.5.3.11.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$ .....	125
7.5.3.11.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$ .....	126
7.5.3.11.3	Detection of Echo Components during Double Talk.....	127
7.5.3.11.4	Minimum activation level and sensitivity of double talk detection .....	128
7.5.3.12	Switching characteristics.....	128
7.5.3.12.0	General .....	128
7.5.3.12.1	Activation in Sending Direction.....	128
7.5.3.12.2	Activation in Receiving Direction.....	129
7.5.3.12.3	Silence Suppression and Comfort Noise Generation.....	129
7.5.3.12.4	Performance in sending direction in the presence of background noise .....	129
7.5.3.12.5	Speech Quality in the Presence of Background Noise .....	130
7.5.3.12.6	Quality of Background Noise Transmission (with Far End Speech).....	131
7.5.3.12.7	Void <del>d302-4efe-9dc6-c1d73691d41d/etsi-en-300-176-2-v2-3-</del> .....	132
7.5.3.12.8	Positional Robustness of Speech Quality in the Presence of Background Noise .....	132
7.5.3.13	Quality of echo cancellation.....	132
7.5.3.13.0	General .....	132
7.5.3.13.1	Temporal echo effects .....	132
7.5.3.13.2	Spectral Echo Attenuation.....	133
7.5.3.13.3	Variable echo path .....	133
7.5.4	Transmission characteristics for PP types 3a and 3b (narrowband loudspeaking and handsfree devices) .....	134
7.5.4.1	Sending sensitivity/frequency response .....	134
7.5.4.2	Receive sensitivity/frequency response.....	135
7.5.4.3	Send loudness rating .....	137
7.5.4.4	Receive loudness rating.....	137
7.5.4.5	Sending distortion .....	138
7.5.4.6	Receiving distortion .....	139
7.5.4.7	Out-of-band signals in sending direction .....	139
7.5.4.8	Out-of-band signals in receiving direction .....	140
7.5.4.9	Sending noise .....	141
7.5.4.10	Receiving noise .....	141
7.5.4.11	Terminal Coupling Loss weighted (TCLw) .....	142
7.5.4.12	Stability Loss.....	142
7.5.4.13	Double Talk Performance .....	143
7.5.4.13.0	General .....	143
7.5.4.13.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$ .....	143
7.5.4.13.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$ .....	145
7.5.4.13.3	Detection of Echo Components during Double Talk.....	145
7.5.4.13.4	Minimum activation level and sensitivity of double talk detection .....	147

7.5.4.14	Switching characteristics.....	147
7.5.4.14.0	General .....	147
7.5.4.14.1	Activation in Sending Direction .....	147
7.5.4.14.2	Activation in Receiving Direction .....	148
7.5.4.14.3	Silence Suppression and Comfort Noise Generation .....	148
7.5.4.14.4	Performance in sending direction in the presence of background noise .....	148
7.5.4.14.5	Speech Quality in the Presence of Background Noise.....	149
7.5.4.14.6	Quality of Background Noise Transmission (with Far End Speech).....	150
7.5.4.15	Quality of echo cancellation.....	150
7.5.4.15.0	General .....	150
7.5.4.15.1	Temporal echo effects .....	151
7.5.4.15.2	Spectral Echo Attenuation.....	151
7.5.4.15.3	Variable echo path.....	152
7.5.4.16	Microphone mute .....	152
7.5.4.17	Delay .....	152
7.5.4.18	Send Loudness Level .....	153
7.5.4.19	Receive Loudness Level .....	153
7.5.5	Transmission characteristics for PP type 2a (P.311 tested, wideband handset).....	154
7.5.5.0	General.....	154
7.5.5.1	Sending characteristics.....	155
7.5.5.1.1	Loudness rating .....	155
7.5.5.1.2	Sensitivity/frequency characteristics .....	155
7.5.5.1.3	Noise.....	155
7.5.5.1.4	Distortion.....	155
7.5.5.1.5	Discrimination against out-of-band input signals .....	155
7.5.5.2	Receiving characteristics.....	156
7.5.5.2.1	Loudness rating .....	156
7.5.5.2.2	Sensitivity/frequency characteristics .....	156
7.5.5.2.3	Noise.....	156
7.5.5.2.4	Distortion.....	156
7.5.5.2.5	Spurious out-of-band receiving signals .....	157
7.5.5.3	Sidetone characteristics .....	157
7.5.5.3.1	Talker sidetone .....	157
7.5.5.3.2	Sidetone distortion .....	157
7.5.5.4	Echo path loss characteristics.....	157
7.5.5.4.1	Weighted terminal coupling loss .....	157
7.5.5.4.2	Stability loss .....	157
7.5.6	Transmission characteristics for PP types 2b and 2c (HATS tested wideband handsets).....	158
7.5.6.1	Frequency responses .....	158
7.5.6.1.1	Sending.....	158
7.5.6.1.2	Receiving.....	159
7.5.6.2	Send and receive loudness ratings.....	162
7.5.6.2.1	Nominal values .....	162
7.5.6.2.2	Void.....	164
7.5.6.2.3	Void.....	164
7.5.6.2.4	Microphone mute.....	164
7.5.6.2.5	Positional robustness .....	164
7.5.6.2.6	Send Loudness Level.....	164
7.5.6.2.7	Receive Loudness Level.....	165
7.5.6.3	Sidetone.....	165
7.5.6.3.1	SideTone Masking Rating (STMR).....	165
7.5.6.3.2	Void.....	166
7.5.6.3.3	Sidetone delay .....	166
7.5.6.4	Terminal coupling loss .....	166
7.5.6.4.1	Terminal Coupling Loss (TCL).....	166
7.5.6.4.2	Stability loss .....	167
7.5.6.5	Distortion .....	168
7.5.6.5.1	Sending Distortion.....	168
7.5.6.5.2	Receiving Distortion.....	169
7.5.6.6	Noise .....	170
7.5.6.6.1	Sending.....	170
7.5.6.6.2	Receiving.....	170

7.5.6.7	Acoustic shock .....	171
7.5.6.7.0	General .....	171
7.5.6.7.1	Continuous signal .....	171
7.5.6.8	Delay .....	171
7.5.6.9	Void.....	172
7.5.6.10	Double talk Performance.....	172
7.5.6.10.0	General .....	172
7.5.6.10.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$ .....	173
7.5.6.10.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$ .....	174
7.5.6.10.3	Detection of Echo Components during Double Talk.....	175
7.5.6.10.4	Minimum activation level and sensitivity of double talk detection .....	176
7.5.6.11	Switching characteristics.....	177
7.5.6.11.0	General .....	177
7.5.6.11.1	Activation in Sending Direction .....	177
7.5.6.11.2	Activation in Receiving Direction .....	177
7.5.6.11.3	Silence Suppression and Comfort Noise Generation.....	178
7.5.6.11.4	Performance in Sending in the Presence of Background Noise.....	178
7.5.6.11.5	Speech Quality in the Presence of Background Noise.....	178
7.5.6.11.6	Quality of Background Noise Transmission (with Far End Speech).....	179
7.5.6.11.7	Void.....	180
7.5.6.11.8	Positional Robustness of Speech Quality in the Presence of Background Noise .....	180
7.5.6.12	Quality of echo cancellation.....	180
7.5.6.12.0	General .....	180
7.5.6.12.1	Temporal echo effects .....	180
7.5.6.12.2	Spectral Echo Attenuation.....	181
7.5.6.12.3	Variable echo path.....	182
7.5.6.13	Out of band signals.....	182
7.5.6.13.1	Out-of-band signals in sending direction.....	182
7.5.6.13.2	Out-of-band signals in receiving direction .....	182
7.5.7	Transmission characteristics for PP types 4a and 4b (HATS Tested wideband loudspeaking and handsfree devices).....	183
7.5.7.1	Sending sensitivity/frequency response .....	183
7.5.7.2	Receive sensitivity/frequency response .....	184
7.5.7.3	Send loudness rating .....	187
7.5.7.4	Receive loudness rating.....	187
7.5.7.5	<i>ETSI EN 300 176-2 V2.3.5 (2022-02) https://standards.iteh.ai/catalog/standards/sist/6ffc8a5e- 3024-4fe-9dc6-c1d73691d41d/etsi-en-300-176-2-v2-3- 5-2022-02</i>	188
7.5.7.6	Sending distortion .....	188
7.5.7.7	Receiving distortion .....	189
7.5.7.8	Out-of-band signals in sending direction .....	190
7.5.7.9	Out-of-band signals in receiving direction .....	190
7.5.7.10	Sending noise .....	191
7.5.7.11	Receiving noise .....	191
7.5.7.12	Terminal Coupling Loss.....	192
7.5.7.13	Stability Loss.....	193
7.5.7.13.0	Double Talk Performance .....	194
7.5.7.13.1	General .....	194
7.5.7.13.2	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$ .....	194
7.5.7.13.3	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$ .....	196
7.5.7.13.4	Detection of Echo Components during Double Talk.....	196
7.5.7.14	Minimum activation level and sensitivity of double talk detection .....	198
7.5.7.14.0	Switching characteristics.....	198
7.5.7.14.1	General .....	198
7.5.7.14.2	Activation in Sending Direction .....	199
7.5.7.14.3	Activation in Receiving Direction .....	199
7.5.7.14.4	Silence Suppression and Comfort Noise Generation.....	199
7.5.7.14.5	Performance in sending direction in the presence of background noise .....	200
7.5.7.14.6	Speech Quality in the Presence of Background Noise.....	200
7.5.7.15	Quality of Background Noise Transmission (with Far End Speech).....	201
7.5.7.15.1	Quality of echo cancellation.....	202
7.5.7.15.2	Temporal echo effects .....	202
7.5.7.15.3	Spectral Echo Attenuation.....	202
7.5.7.16	Variable echo path.....	203
	Microphone mute .....	203

7.5.7.17	Delay .....	203
7.5.7.18	Send Loudness Level .....	204
7.5.7.19	Receive Loudness Level .....	205
7.5.8	Transmission characteristics for PP type 5a ("super-wideband 14 kHz handset or headset") .....	206
7.5.8.1	Frequency responses .....	206
7.5.8.1.1	Sending.....	206
7.5.8.1.2	Receiving.....	207
7.5.8.2	Send and receive loudness ratings.....	209
7.5.8.2.1	Send Loudness Rating .....	209
7.5.8.2.2	Receive Loudness Rating .....	210
7.5.8.2.3	Send Loudness Level.....	211
7.5.8.2.4	Receive Loudness Level.....	212
7.5.8.3	Sidetone.....	212
7.5.8.3.1	Sidetone Masking Rating STMR (Mouth to ear).....	212
7.5.8.3.2	Sidetone Delay.....	213
7.5.8.4	Terminal Coupling Loss.....	213
7.5.8.4.1	Unweighted Terminal Coupling Loss.....	213
7.5.8.4.2	Stability Loss .....	214
7.5.8.5	Distortion .....	215
7.5.8.5.1	Sending Distortion.....	215
7.5.8.5.2	Receiving Distortion.....	216
7.5.8.6	Noise .....	217
7.5.8.6.1	Sending.....	217
7.5.8.6.2	Receiving.....	217
7.5.8.7	Acoustic shock .....	218
7.5.8.7.0	General .....	218
7.5.8.7.1	Continuous signal .....	218
7.5.8.8	Delay .....	218
7.5.8.9	Double talk Performance.....	218
7.5.8.9.0	General .....	218
7.5.8.9.1	Attenuation range in send direction during double talk $A_{H,S,dt}$ .....	219
7.5.8.9.2	Attenuation range in receive direction during double talk $A_{H,R,dt}$ .....	220
7.5.8.9.3	Detection of echo components during double talk .....	221
7.5.8.10	Switching Characteristics.....	222
7.5.8.10.0	Note <a href="https://standards.iteh.ai/catalog/standards/sist/6ffc8a5e-d302-4efc-9e6-61d73691d41d/etsi-en-300-176-2-v2-3-2022-02">https://standards.iteh.ai/catalog/standards/sist/6ffc8a5e-d302-4efc-9e6-61d73691d41d/etsi-en-300-176-2-v2-3-2022-02</a> .....	222
7.5.8.10.1	Activation in send direction .....	223
7.5.8.10.2	Silence suppression and comfort noise generation .....	223
7.5.8.10.3	Performance in Sending in the Presence of Background Noise.....	223
7.5.8.10.4	Speech quality in the presence of background noise .....	224
7.5.8.10.5	Positional Robustness of Speech Quality in the Presence of Background Noise .....	225
7.5.8.10.6	Quality of background noise transmission (with far end speech).....	225
7.5.8.11	Quality of echo cancellation.....	226
7.5.8.11.1	Temporal echo effects .....	226
7.5.8.11.2	Spectral echo attenuation.....	226
7.5.8.11.3	Variable echo path .....	227
7.5.9	Transmission characteristics for PP type 5b ("super-wideband 14 kHz loudspeaking and handsfree devices") .....	227
7.5.9.1	Sending sensitivity/frequency response .....	227
7.5.9.2	Receive sensitivity/frequency response.....	229
7.5.9.2.1	Handheld terminal .....	229
7.5.9.2.2	Desktop terminal .....	230
7.5.9.2.3	Terminals intended to be used simultaneously by several users.....	231
7.5.9.3	Sending loudness rating .....	231
7.5.9.3.1	Nominal Value.....	231
7.5.9.3.2	Microphone mute.....	231
7.5.9.4	Receive loudness rating.....	232
7.5.9.5	Sending distortion .....	233
7.5.9.5.1	Signal to harmonic distortion versus frequency .....	233
7.5.9.5.2	Signal to harmonic distortion for higher input level.....	234
7.5.9.6	Receiving distortion .....	234
7.5.9.7	Sending noise .....	235
7.5.9.8	Receiving noise .....	235

7.5.9.9	Terminal Coupling Loss.....	236
7.5.9.9.1	Unweighted Terminal Coupling Loss.....	236
7.5.9.9.2	Stability Loss.....	237
7.5.9.10	Double Talk Performance .....	237
7.5.9.10.0	General .....	237
7.5.9.10.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$ .....	238
7.5.9.10.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$ .....	239
7.5.9.10.3	Detection of Echo Components during Double Talk.....	240
7.5.9.10.4	Minimum activation level and sensitivity of double talk detection.....	241
7.5.9.11	Switching characteristics.....	242
7.5.9.11.0	Note .....	242
7.5.9.11.1	Activation in Sending Direction .....	242
7.5.9.11.2	Silence Suppression and Comfort Noise Generation.....	242
7.5.9.11.3	Performance in sending direction in the presence of background noise .....	243
7.5.9.11.4	Speech Quality in the Presence of Background Noise.....	243
7.5.9.11.5	Quality of Background Noise Transmission (with Far End Speech).....	244
7.5.9.12	Quality of echo cancellation.....	245
7.5.9.12.1	Temporal echo effects .....	245
7.5.9.12.2	Spectral Echo Attenuation.....	245
7.5.9.12.3	Variable echo path.....	246
7.5.9.13	Delay .....	246
7.5.9.14	Send Loudness Level .....	246
7.5.9.15	Receive Loudness Level .....	247
7.5.10	Transmission characteristics for PP type 7a ("fullband 20 kHz handset or headset").....	248
7.5.10.1	Frequency responses .....	248
7.5.10.1.1	<i>iTeh STANDARD</i>	248
7.5.10.1.2	<i>PREVIEW</i>	249
7.5.10.2	Send and receive loudness ratings.....	251
7.5.10.2.1	Send Loudness Rating .....	251
7.5.10.2.2	Receive Loudness Rating .....	252
7.5.10.2.3	Send Loudness Level.....	253
7.5.10.2.4	Receive Loudness Level.....	253
7.5.10.3	Sidetone.....	254
7.5.10.3.1	<i>ETSI EN 300 176-2 V2.3.5 (2022-02)</i>	254
7.5.10.3.2	<i>Sidetone Masking Rating STMR (Mouth to ear)</i>	254
7.5.10.4	<i><a href="https://standards.iteh.ai/catalog/standards/sist/6ffc8a5e-3002-4efc-9dc6-c1d73691d41d/etsi-en-300-176-2-v2-3-2022-02">https://standards.iteh.ai/catalog/standards/sist/6ffc8a5e-3002-4efc-9dc6-c1d73691d41d/etsi-en-300-176-2-v2-3-2022-02</a></i>	255
7.5.10.4.1	<i>Sidetone Delay</i>	255
7.5.10.4.2	<i>Terminal Coupling Loss</i>	255
7.5.10.4.3	<i>Unweighted Terminal Coupling Loss</i>	255
7.5.10.4.4	<i>Stability Loss</i>	256
7.5.10.5	Distortion .....	257
7.5.10.5.1	Sending Distortion.....	257
7.5.10.5.2	Receiving Distortion.....	258
7.5.10.6	Noise .....	259
7.5.10.6.1	Sending.....	259
7.5.10.6.2	Receiving.....	259
7.5.10.7	Acoustic shock .....	260
7.5.10.7.0	General .....	260
7.5.10.7.1	Continuous signal .....	260
7.5.10.8	Delay .....	260
7.5.10.9	Double talk Performance.....	260
7.5.10.9.0	General .....	260
7.5.10.9.1	Attenuation range in send direction during double talk $A_{H,S,dt}$ .....	261
7.5.10.9.2	Attenuation range in receive direction during double talk $A_{H,R,dt}$ .....	262
7.5.10.9.3	Detection of echo components during double talk .....	263
7.5.10.10	Switching Characteristics .....	264
7.5.10.10.0	Note .....	264
7.5.10.10.1	Activation in send direction.....	265
7.5.10.10.2	Silence suppression and comfort noise generation .....	265
7.5.10.10.3	Performance in Sending in the Presence of Background Noise.....	265
7.5.10.10.4	Speech quality in the presence of background noise .....	266
7.5.10.10.5	Positional Robustness of Speech Quality in the Presence of Background Noise .....	267
7.5.10.10.6	Quality of background noise transmission (with far end speech).....	267
7.5.10.11	Quality of echo cancellation.....	268

7.5.10.11.1	Temporal echo effects .....	268
7.5.10.11.2	Spectral echo attenuation.....	268
7.5.10.11.3	Variable echo path.....	269
7.5.11	Transmission characteristics for PP type 7b ("fullband 20 kHz loudspeaking and handsfree devices") .....	269
7.5.11.1	Sending sensitivity/frequency response .....	269
7.5.11.2	Receive sensitivity/frequency response.....	271
7.5.11.2.0	General .....	271
7.5.11.2.1	Handheld terminal .....	271
7.5.11.2.2	Desktop terminal .....	272
7.5.11.2.3	Terminals intended to be used simultaneously by several users.....	273
7.5.11.3	Sending loudness rating .....	273
7.5.11.3.1	Nominal Value.....	273
7.5.11.3.2	Microphone Mute .....	273
7.5.11.4	Receive loudness rating.....	274
7.5.11.5	Sending distortion .....	275
7.5.11.5.1	Signal to harmonic distortion versus frequency .....	275
7.5.11.5.2	Signal to harmonic distortion for higher input level.....	276
7.5.11.6	Receiving distortion .....	276
7.5.11.7	Sending noise .....	277
7.5.11.8	Receiving noise .....	278
7.5.11.9	Terminal Coupling Loss.....	278
7.5.11.9.1	Unweighted Terminal Coupling Loss.....	278
7.5.11.9.2	Stability Loss.....	279
7.5.11.10	Double Talk Performance.....	280
7.5.11.10.0	General .....	280
7.5.11.10.1	Attenuation Range in Sending Direction during Double Talk $A_{H,S,dt}$ .....	280
7.5.11.10.2	Attenuation Range in Receiving Direction during Double Talk $A_{H,R,dt}$ .....	282
7.5.11.10.3	Detection of Echo Components during Double Talk.....	282
7.5.11.10.4	Minimum activation level and sensitivity of double talk detection .....	284
7.5.11.11	Switching characteristics.....	284
7.5.11.11.0	Note .....	284
7.5.11.11.1	Activation in Sending Direction.....	285
7.5.11.11.2	Silence Suppression and Comfort Noise Generation.....	285
7.5.11.11.3	Performance in sending direction in the presence of background noise.....	285
7.5.11.11.4	Speech Quality in the Presence of Background Noise.....	286
7.5.11.11.5	Quality of Background Noise Transmission (with Far End Speech).....	287
7.5.11.12	Quality of echo cancellation.....	288
7.5.11.12.1	Temporal echo effects .....	288
7.5.11.12.2	Spectral Echo Attenuation.....	288
7.5.11.12.3	Variable echo path.....	289
7.5.11.13	Delay .....	289
7.5.11.14	Send Loudness Level .....	289
7.5.11.15	Receive Loudness Level .....	290
7.5.12	Transmission characteristics for PP types 7c, d, e, f ("fullband 20 kHz stereo audio device").....	290
7.5.13	Transmission characteristics for PP type 7g ("FBHR 24 kHz headset device") .....	291
7.5.14	Transmission characteristics for PP type 7h ("FBHR 24 kHz loudspeaking device").....	291
7.5.15	Transmission characteristics for PP type 7i ("FBLFE 250 Hz loudspeaking device") .....	291
7.5.16	Transmission characteristics for PP type 7j ("fullband 20 kHz low-latency microphone device") .	291
7.5.17	Transmission characteristics for PP type 8a ("ultra-band 48 kHz headset device") .....	291
7.5.18	Transmission characteristics for PP type 8b ("ultra-band 48 kHz loudspeaking device").....	291
7.6	Transmission characteristics for Fixed Parts .....	292
7.6.1	Transmission characteristics for FP type 1a ("Classic" Fixed Part with ISDN Network interface, 3,1 kHz service) .....	292
7.6.1.1	Reduction of echo from PP .....	292
7.6.1.2	FP Network echo control .....	294
7.6.1.3	FP adaptive volume control .....	295
7.6.1.4	FP Delay.....	295
7.6.2	Transmission characteristics for FP type 1b ("new" Fixed Part with ISDN Network interface, 3,1 kHz service) .....	297
7.6.2.0	General.....	297
7.6.2.1	FP Network echo control .....	297

7.6.2.2	FP adaptive volume control .....	298
7.6.2.3	FP Delay.....	298
7.6.3	Transmission characteristics for FP type 2 (Fixed Part with analog 2-wire interface, 3,1 kHz service).....	300
7.6.3.1	FP adaptive volume control .....	300
7.6.3.2	Network echo control.....	300
7.6.3.3	Additional requirements for DECT FP provided with a 2-wire PSTN interface.....	302
7.6.3.3.0	Test methods.....	302
7.6.3.3.1	General requirements.....	303
7.6.3.3.2	Speech performance characteristics.....	303
7.6.3.4	FP Delay.....	304
7.6.4	Transmission characteristics for FP type 3 (Fixed Part with VoIP interface, 3,1 kHz service) .....	305
7.6.4.1	Void.....	305
7.6.4.2	Void.....	305
7.6.4.3	Adaptive volume control.....	305
7.6.4.4	Clock accuracy.....	306
7.6.4.5	Send Jitter.....	306
7.6.4.6	Delay .....	307
7.6.5	Transmission characteristics for FP type 4 (Fixed Part with ISDN network interface, wideband service).....	307
7.6.5.1	FP adaptive volume control .....	307
7.6.5.2	FP Delay.....	307
7.6.6	Transmission characteristics for FP type 5 (Fixed Part with VoIP interface, wideband, super-wideband, fullband, FBHR or ultra-band service) .....	309
7.6.6.1	Void.....	309
7.6.6.2	Void.....	309
7.6.6.3	FP adaptive volume control .....	309
7.6.6.4	Clock accuracy .....	309
7.6.6.5	Send Jitter.....	310
7.6.6.6	Delay .....	310
7.7	Transmission characteristics for a complete DECT system consisting of PP and FP with VoIP interface .....	310
7.7.1	Send and receive delay round trip delay.....	310
8	Testing of the audio codecs standards.iteh.ai/catalog/standards/sist/6ffa8a5e.....	312
8.1	Test philosophy.....	312
8.2	Testing requirements for speech coding and packet loss concealment algorithms.....	312
8.2.1	G.726 ADPCM codec operating at 32 kbit/s .....	312
8.2.2	G.711 PCM codec operating at 64 kbit/s .....	313
8.2.3	G.722 wideband codec operating at 64 kbit/s .....	313
8.2.4	Packet Loss Concealment (PLC) for codec G.722.....	313
8.2.5	G.729.1 wideband codec operating at 30 kbit/s with PLC algorithm .....	313
8.2.6	MPEG-4 ER AAC-LD super-wideband codec operating at 64 kbit/s.....	314
8.2.7	MPEG-4 ER AAC-LD wideband codec operating at 32 kbit/s .....	314
8.2.8	LC3plus narrowband, wideband, super-wideband, fullband, FBHR, ultra-band codec operating at 32 to 512 kbit/s .....	314
9	Additional features .....	316
9.1	Loudspeaking hands-free and headset facilities .....	316
9.1.1	Loudspeaking hands-free facility.....	316
9.1.2	Headset facility .....	316
9.2	Tandem with mobile radio network.....	316
9.2.0	General.....	316
9.2.1	Tandem with GSM .....	317
9.2.1.0	Configuration .....	317
9.2.1.1	Network echo control.....	317
9.2.1.2	Terminal coupling loss .....	317
9.2.1.3	The GSM mobile transmitter operates in continuous mode .....	317
9.2.1.4	The GSM mobile transmitter operates in discontinuous mode, DTX .....	317
9.3	DECT connected to the GSM fixed network.....	317
9.3.0	General.....	317
9.3.1	Network echo control.....	318

9.3.2	Terminal coupling loss.....	318
9.4	Wireless Relay Stations (WRS).....	318
9.4.0	General.....	318
9.4.1	Modified FP network echo control requirements for implementation of 2 and 3 CRFP links in cascade.....	319
<b>Annex A (informative):</b>	<b>Key parameters .....</b>	<b>320</b>
<b>Annex B (informative):</b>	<b>Description of the CSS.....</b>	<b>321</b>
B.1	General .....	321
B.2	Test signal .....	321
B.3	Measurement .....	322
B.4	Calculation .....	322
<b>Annex C (normative):</b>	<b>Description of the cross-correlation method .....</b>	<b>325</b>
C.1	Test signal .....	325
C.2	Calculation .....	325
<b>Annex D (informative):</b>	<b>Acoustic shock requirements .....</b>	<b>326</b>
D.0	General .....	326
D.1	Continuous signal.....	326
D.2	Peak signal.....	326
<b>Annex E (informative):</b>	<b>Echo related topics.....</b>	<b>327</b>
E.1	Summary table on echo parameters for PPs and FPs .....	327
E.2	General information about Delay-Echo interaction for DECT terminals.....	334
<b>Annex F (informative):</b>	<b>Guidelines on specific requirements.....</b>	<b>336</b>
F.1	Delay considerations for FPs with VoIP interface .....	336
F.1.1	Delay considerations for FP type 3 (Fixed Part with VoIP interface, 3,1 kHz service) .....	336
F.1.1.0	General.....	336
F.1.1.1	Send delay.....	336
F.1.1.2	Receive delay.....	337
F.1.2	Delay considerations for FP type 5 (Fixed Part with VoIP interface, wideband, super-wideband, fullband, FBHR or ultra-band service) .....	338
F.1.2.0	General.....	338
F.1.2.1	Send Delay.....	338
F.1.2.2	Receive delay.....	339
F.2	Guidelines for audio codec testing of MPEG-4 ER AAC-LD implementations at 64 kbps .....	340
F.2.1	Guidelines for Decoder testing .....	340
F.2.2	Guidelines for Encoder testing .....	341
F.3	Derivation of Delay requirements for PPs and FPs with VoIP interface .....	342
<b>Annex G (normative):</b>	<b>Allowed tolerances .....</b>	<b>344</b>
G.1	Description of the allowed frequency gap in the lower limit frequency response mask for wideband, super-wideband and fullband applications.....	344
<b>Annex H (informative):</b>	<b>Bibliography .....</b>	<b>345</b>
History .....	346	