INTERNATIONAL STANDARD



Second edition 2015-09-15

Tractors and machinery for agriculture and forestry — Serial control and communications data network —

Part 10: **Task controller and management information system data interchange**

Tracteurs et matériels agricoles et forestiers — Réseaux de commande et de communication de données en série —

Partie 10: Contrôleur de tâches et échange de données des systèmes d'information de gestion

ISO 11783-10:2015

https://standards.iteh.ai/catalog/standards/iso/f91f0337-b441-4c58-9821-67fe8e7c4060/iso-11783-10-2015



Reference number ISO 11783-10:2015(E)

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 11783-10:2015

https://standards.iteh.ai/catalog/standards/iso/f91f0337-b441-4c58-9821-67fe8e7c4060/iso-11783-10-2015



© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Contents

| Page |
|------|
|------|

| Forew | vord | v |
|-------|--|---------------------------------------|
| Intro | duction | vi i |
| 1 | Scope | |
| 2 | Normative references | |
| 3 | Terms and definitions | 2 |
| 4 | Abbreviations | 3 |
| 5 | Conoral description | - |
| J | 5.1 Task management | |
| | 5.2 Task management on FMIS computer | ייייייייייייייייייייייייייייייייייייי |
| | 5.3 Preselection and assignment of Devices | 6 |
| | 5.4 Task controller interface driver | 6 |
| | 5.5 Task controller user interface | 6 |
| | 5.6 Data logger function | |
| 6 | Task controller requirements | 7 |
| | 6.1 Task selection and execution | |
| | 6.2 Logging of time and position | |
| | 6.3 Logging parameters from parameter groups | |
| | 6.4 Logging of task events | |
| | 6.5 Language, formats, and measurement units selection | |
| | 6.6 Connection management | |
| | 6.6.1 Task controller initialization | |
| | 6.6.2 Client initialization with the task controller | |
| | 6.6.3 Connection maintenance | |
| | 6.6.4 Task controller connection shutdown | |
| | 6.7 Task controller number | |
| | 6.7.1 Client initialization on networks with multiple task controlle | rs14 |
| | 6.8 Data exchange on the network | 15 180-11783-10-2011c |
| | 6.8.1 Site-specific application | |
| | 6.8.2 Data logging | |
| | 6.9.4 Data log triggors | |
| | 6.8.5 Peer Control | |
| 7 | Data loggor requirements | |
| / | 7.1 Conoral | |
| | 7.1 Generation management | |
| | 7.3 Measurements and totals | 28 |
| Q | Data transfor | 20 |
| 8 | 81 Caparal | 20 2໘ |
| | 0.1 Utilei di | |
| | 8.3 Extensible schema definition | |
| | 8.4 XML schema definition | 30 |
| | 8.4.1 Proprietary XML schema extensions | 32 |
| | 8.5 XML data transfer files | 32 |
| | 8.6 Binary data transfer files | 35 |
| | 8.6.1 General | 35 |
| | 8.6.2 Grid binary file structure | 35 |
| | 8.6.3 Log data binary file structure | 38 |
| | 8.6.4 Point data binary file structure | |
| | 8.7 Device descriptor object pool | |
| Anno | x (normativa) Davica descriptor objects | 4 🗖 |
| лше | | |

ISO 11783-10:2015(E)

| Annex B (normative) Message definitions | 52 |
|--|-----|
| Annex C (normative) XML elements relationship diagram | 71 |
| Annex D (normative) XML elements and attributes | 74 |
| Annex E (normative) Predefined ISO-11783 attachments | 156 |
| Annex F (normative) TC Functionalities and Device Descriptor Object Pool definitions | 163 |
| Annex G (normative) Task Based Time Registration | |
| Bibliography | 205 |

iTeh Standards (https://standards.iteh.ai) Document Preview

ISO 11783-10:2015

https://standards.iteh.ai/catalog/standards/iso/f91f0337-b441-4c58-9821-67fe8e7c4060/iso-11783-10-2015

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 19, *Agricultural electronics*.

This second edition cancels and replaces the first edition (ISO 11783-10:2009) which has been technically revised.

ISO 11783 consists of the following parts, under the general title *Tractors and machinery for agriculture and forestry* — *Serial control and communications data network*:

- Part 1: General standard for mobile data communication
- Part 2: Physical layer
- Part 3: Data link layer
- Part 4: Network layer
- Part 5: Network management
- Part 6: Virtual terminal
- Part 7: Implement messages application layer
- Part 8: Power train messages
- Part 9: Tractor ECU
- Part 10: Task controller and management information system data interchange
- Part 11: Mobile data element dictionary
- Part 12: Diagnostics services
- Part 13: File server

ISO 11783-10:2015(E)

— Part 14: Sequence control

iTeh Standards (https://standards.iteh.ai) Document Preview

<u>ISO 11783-10:2015</u> https://standards.iteh.ai/catalog/standards/iso/f91f0337-b441-4c58-9821-67fe8e7c4060/iso-11783-10-2015

Introduction

This International Standard specifies a communications system for agricultural equipment based on the ISO 11898-1 protocol. SAE J1939^[1] documents, on which parts of ISO 11783 are based, were developed jointly for use in truck and bus applications and for construction and agriculture applications. Joint documents were completed to allow electronic units that meet the truck and bus SAE J1939^[1] specifications to be used by agricultural and forestry equipment with minimal changes.

General information on this International Stamdard is to be found in ISO 11783-1. The purpose of this International Standard is to provide an open, interconnected system for on-board electronic systems. It is intended to enable electronic control units (ECUs) to communicate with each other, providing a standardized system.

The International Organization for Standardization (ISO) draws attention to the fact that it is claimed that compliance with this part of ISO 11783 may involve the use of a patent concerning the controller area network (CAN) protocol referred to throughout the document.

ISO takes no position concerning the evidence, validity, and scope of this patent.

The holder of this patent has ensured ISO that he is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with ISO. Information may be obtained from:

Robert Bosch GmbH

Wernerstrasse 51

Postfach 30 02 20

D-70442 Stuttgart-Feuerbach

Germany

Attention is drawn to the possibility that some of the elements of this part of ISO 11783 may be the subject of patent rights other than those identified above. ISO shall not be held responsible for identifying any or all such patent rights.

iTeh Standards (https://standards.iteh.ai) Document Preview

<u>ISO 11783-10:2015</u> https://standards.iteh.ai/catalog/standards/iso/f91f0337-b441-4c58-9821-67fe8e7c4060/iso-11783-10-2015

Tractors and machinery for agriculture and forestry — Serial control and communications data network —

Part 10: **Task controller and management information system data interchange**

1 Scope

This International Standard as a whole specifies a serial data network for control and communications on forestry or agricultural tractors and mounted, semi-mounted, towed, or self-propelled implements. Its purpose is to standardize the method and format of transfer of data between sensors, actuators, control elements, and information storage and display units, whether mounted on, or part of, the tractor or implement. This part of ISO 11783 describes the task controller applications layer, which defines the requirements and services needed for communicating between the task controller (TC) and electronic control units. The data format to communicate with the farm-management computer, the calculations required for control, and the message format sent to the control function are defined in this part of ISO 11783.

2 Normative references ://standards.iteh.ai)

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 11783-1, Tractors and machinery for agriculture and forestry — Serial control and communications data network — Part 1: General standard for mobile data communication

ISO 11783-3, Tractors and machinery for agriculture and forestry — Serial control and communications data network — Part 3: Data link layer

ISO 11783-5, Tractors and machinery for agriculture and forestry — Serial control and communications data network — Part 5: Network management

ISO 11783-6, Tractors and machinery for agriculture and forestry — Serial control and communications data network — Part 6: Virtual terminal

ISO 11783-7, Tractors and machinery for agriculture and forestry — Serial control and communications data network — Part 7: Implement messages application layer

ISO 11783-11, Tractors and machinery for agriculture and forestry — Serial control and communications data network — Part 11: Mobile data element dictionary

ISO 11783-12, Tractors and machinery for agriculture and forestry — Serial control and communications data network — Part 12: Diagnostics services

ISO 11898-1, Road vehicles — Controller area network (CAN) — Part 1: Data link layer and physical signalling

ISO/IEC 10646, Information technology — Universal Coded Character Set (UCS)

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 11783-1 apply.

3.1

client

control function (CF) that establishes a connection with a task controller (TC) or a data logger (DL) and provides data for data logging by the DL or TC and/or accepts control commands from the TC

Note 1 to entry: This term has been introduced in version 4 to replace the term working set for the CF that connects to a TC or DL. The multi member working set concept is not applied to TC or DL clients. The communication between a TC or DL and their clients is limited to transmission of messages between TC or DL and the working set master

3.2

coding data

data that changes infrequently, such as machine or chemical data, or data which is referenced in a task for the purpose of allocating tasks administratively

3.3

data dictionary entity

description of the data dictionary identifier, definition, value range, value resolution, and units specifications used by process data variables

3.4

data logger

DL

3.5

control function (CF) defined specifically to perform data logging functionality

(https://standards.iteh

data logger (DL) client

CF that establishes a connection with a data logger (DL) and provides data for data logging by the DL

3.6

data transfer file set

collection of files in the extensible markup language format and binary formats, which are used for the data transfer between the farm management information system and the task controller of an ISO 11783 network

3.7

device descriptor object pool

DDOP

collection of device-related objects and their relationships which together describe the functionality and structure of a device for the purposes of task control and data logging

3.8

device element

any addressable item on a device

EXAMPLE Nozzle on sprayer boom where the nozzle has individually addressable process data variables.

3.9

field

area of land managed by a farmer, represented by either a single partfield or a collection of more than one partfield

Note 1 to entry: The field is only of importance within the farm management information system for business management considerations and is not necessarily related to a single crop.

3.10

grid cell

rectangular areas defined by overlaying a grid on a partfield

3.11

management computer gateway

CF that interfaces to the management computer system and to the ISO 11783 network

Note 1 to entry: A management computer gateway can store data for transmission at a later time.

3.12

partfield

area characterized by the cultivation of only one agricultural crop

Note 1 to entry: Partfield is the XML element to which tasks are allocated to obtain smallest granularity.

3.13

polygon

planar surface defined by one exterior boundary and by zero or more interior boundaries

Note 1 to entry: Each interior boundary describes a hole in the surface.

Note 2 to entry: A single or group of polygons can be used to define a treatment zone.

3.14

process data variable

element of information that has a value that describes the state of a process

Note 1 to entry: Process data variables consist of the attributes range, resolution, and units, as defined in the data dictionary.

iTeh Standards

3.15 setpoint value source

CF that can determine a setpoint value during a task for use by another CF and contains one or more Device Process Data object(s) with the property attribute set to the "control source" value

3.16

setpoint value user

CF that accepts a setpoint value from either the TC or another source to modify its real-time performance such as rate control and contains one or more Device Process Data object(s) with the property attribute set to the "settable" value

3.17

task controller (TC) client

CF that establishes a connection with a task controller (TC) and provides data for data logging and/or accepts control commands from the TC

3.18

task controller (TC) number

identification number that is derived from the function instance of the task controller (TC)

3.19

XML element

representation of the data of a domain object and consists at least of an opening tag, a number of attributes, and a closing tag

4 Abbreviations

For the purposes of this document, the abbreviations given in ISO 11783-1 apply.

5 General description

5.1 Task management

There are two main purposes of task management in the mobile implement control system.

The first is the management of the farm resources, including tractors, implements, sensor systems, workers, and the products used. It is possible for the farmer to plan and evaluate the use of the resources. He is then able to automatically control the use of his inventory of products and can keep track of the status and conditions of his machinery. Resource designators are globally transferred as coding data and are part of the data transfer file set as detailed in <u>Clause 7</u>.

The second purpose is the management of the farm activities carried out in the fields. These activities are described by tasks to distinguish all the work that is planned, is in execution, or has been done by the farmer or by a contractor for one customer in one partfield.

The data transfer is possible in two directions. The planned tasks are sent to the task controller (TC) on the mobile implement control system (MICS) and the results of the work are sent back to the farmmanagement information system (FMIS). Tasks can be generated both on the FMIS and on the MICS.

Task management has the following workflow.

- a) Planning field tasks and maintaining coding data using the software of an FMIS computer operated by the farmers or contractors, as detailed in <u>5.2</u>.
- b) Converting the task data into XML format.
- c) Assigning the task data produced by the planning software to the data required for the implements or sensor systems to be used to complete the planned tasks. This step is optional.
- d) Transferring the task data from the FMIS system to the TC of the MICS, as detailed in <u>5.4</u>.
- e) The TC uses the task data to transmit process data messages to the ECUs on the implement.
- f) The TC collects data according to the DataLogTriggers specified in the task data.
- g) Transferring the collected data to the FMIS. Collected data can be in the XML format or in a proprietary format. When a proprietary format is used, this step involves converting the proprietary format into the XML format.
- h) Reading the XML files and converting into the FMIS format for storage and evaluation of the data.

Figure 1 illustrates the interfaces between the software on the FMIS computer and the ECUs mounted on an ISO 11783-configured implement.



Figure 1 — Task management entities and interfaces

5.2 Task management on FMIS computer

Task management is defined as a part of an FMIS, responsible for planning and evaluation of field work. Tasks specify what, where, how, by whom, and when work is planned to be carried out.

The amount of data transferred between the FMIS and the MICS is dictated by the administrative requirements of a farming enterprise. For the recording of field activities only, the task management can be used to file the data in a working journal. For this purpose, only the coding data need be transferred from FMIS to MICS, and the tasks are created on the MICS by selection of the involved resources. In this case, only the data transfer file set from MICS to FMIS contain tasks. In enterprises where tasks are planned on the FMIS, these will be included, together with the coding data, in the data transfer file set from FMIS to MICS. These planned tasks can range from mere planned allocations of resources to geographical information for site-specific field operations.

5.3 Preselection and assignment of Devices

Any client device in the mobile system can only be identified uniquely by its CF NAME. For FMIS purposes, the client CF NAME needs to be unique worldwide. This implies that the device manufacturer has the responsibility to ensure that the Identity Number in combination with the other fields in the NAME uniquely identifies the device.

At the FMIS, the preselection of devices depends on the planned task. It can be necessary to assign a type of device or function, a specific device, or even the device of a particular manufacturer. The DeviceAllocation XML elements may include planned assignments about the devices to be used. This information ranges between specific and indistinct.

The XML attribute ClientNAMEValue contains the eight-byte NAME of a control function as it is defined in ISO 11783-5. Not all parts of a NAME need be specified and only certain elements of a NAME need to be defined to determine a device on the mobile network. Those parts of ClientNAMEValue containing information to be used on the mobile system to select a proper device are masked by a bitset structure stored in the XML attribute, ClientNAMEMask. All different combinations of elements of the NAME structure can be marked as valid for device selection (logical AND). On the FMIS, these masks could be coded as symbols. Once the preselection information is set in a task on the FMIS, it is not overwritten on the mobile system because the device that is used during task processing on the mobile system is stored as the XML attribute DeviceIdRef.

5.4 Task controller interface driver

After generating the interface files, the TC driver of the manufacturer of the TC is activated on the ²⁰¹⁵ farm computer. This driver is responsible for the data transfer to the TC, which is part of the MICS using its proprietary data format or the ISO 11783-10 XML format and data carrier, such as any type of memory card or radio link. The translation of the data from the data transfer file set in messages on the ISO 11783 network, as well as the kind of transfer between the mobile system and the FMIS, is not subject to a standardized procedure as part of this International Standard. To make implement-specific set point data, this driver can add and use device descriptor data supplied by the manufacturers.

5.5 Task controller user interface

A TC can provide a means for the user to interact with the TC. User interaction can be through a virtual terminal (VT) or other interface. Operator interfaces can range from very simple to elaborate, depending on the designer's intent. For example, a simple TC that only supports single tasks that run automatically might not require any user interaction. More advanced TCs can offer additional operator interface capabilities, such as

- select a task from a list,
- start/stop/resume/complete a task,
- modify a task,
- create a task, and
- add new coding data.