
ü]fc_cdUgcj bc`X][]HJbc`ca fYy`Y`n`]bhY[f]fUbj]a]`g]cf]h] Ua]`f6 !-G8 BŁĚ`Dfcltc_c`
X][]HJbY`bUfc b]ý_Y`g][bU]nUW`Y`ýH`&`fB GG&ŁĚ`? UfU_hYf]gh_Y`nj YnY`Ě`Df]U[cX]`b]
dcg]cd_]`nUdUfUa YfY`fU`bY`W`] bY\]]fcgh]`Ě`%`XY.`GdYWZ_UW`Udfcltc_c`U
Q]f]dcfc]`c`+H !H`E`"&`*`" &`f]%- +ŁžgdfYa Yb`YbcQ

Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; Modification procedures for sustainable cell rate parameters; Part 1: Protocol specification [ITU-T Recommendation Q.2963.2 (1997), modified]

(standards.iteh.ai)

[SIST EN 301 276-1 V1.1.3:2005](https://standards.iteh.ai/catalog/standards/sist/b877a480-5635-4ba2-9df4-887c58443ab4/sist-en-301-276-1-v1-1-3-2005)

<https://standards.iteh.ai/catalog/standards/sist/b877a480-5635-4ba2-9df4-887c58443ab4/sist-en-301-276-1-v1-1-3-2005>

Ta slovenski standard je istoveten z: EN 301 276-1 Version 1.1.3

ICS:

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
--------	---	--

SIST EN 301 276-1 V1.1.3:2005 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 276-1 V1.1.3:2005](https://standards.iteh.ai/catalog/standards/sist/b877a480-5635-4ba2-9df4-887c58443ab4/sist-en-301-276-1-v1-1-3-2005)

<https://standards.iteh.ai/catalog/standards/sist/b877a480-5635-4ba2-9df4-887c58443ab4/sist-en-301-276-1-v1-1-3-2005>

EN 301 276-1 V1.1.3 (1999-03)

European Standard (Telecommunications series)

**Broadband Integrated Services Digital Network (B-ISDN);
Digital Subscriber Signalling System No. two (DSS2) protocol;
Connection characteristics;
Modification procedures for sustainable cell rate parameters;
Part 1: Protocol specification**

[ITU-T Recommendation Q.2963.2 (1997), modified]

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 301 276-1 V1.1.3:2005](https://standards.iteh.ai/catalog/standards/sist/b877a480-5635-4ba2-9df4-887c58443ab4/sist-en-301-276-1-v1-1-3-2005)

<https://standards.iteh.ai/catalog/standards/sist/b877a480-5635-4ba2-9df4-887c58443ab4/sist-en-301-276-1-v1-1-3-2005>



Reference

DEN/SPS-05147-1 (btc90ie0.PDF)

Keywords

ISDN, broadband, B-ISDN, DSS2, protocol

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C

Association à but non lucratif enregistrée à la
Sous-Prefecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr

Individual copies of this ETSI deliverable
can be downloaded from

<http://www.etsi.org>

If you find errors in the present document, send your
comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1999.
All rights reserved.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available **free of charge** from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Signalling Protocols and Switching (SPS).

The present document is part 1 of a multi-part standard covering the Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; Modification procedures for sustainable cell rate parameters, as identified below:

- Part 1:** "Protocol specification [ITU-T Recommendation Q.2963.2 (1997), modified]";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";
- Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";
- Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

NOTE: The final structure of the parts containing the test specifications is currently under study.

In accordance with CCITT Recommendation I.130, the following three level structure is used to describe the supplementary telecommunication services as provided by European public telecommunications operators under the pan-European B-ISDN:

- Stage 1: is an overall service description, from the user's standpoint;
- Stage 2: identifies the functional capabilities and information flows needed to support the service described in stage 1; and
- Stage 3: defines the signalling system protocols and switching functions needed to implement the service described in stage 1.

The present document details the stage 3 aspects (signalling system protocols and switching functions) needed to support the Modification of Sustainable Cell Rate.

National transposition dates	
Date of adoption of this EN:	5 March 1999
Date of latest announcement of this EN (doa):	30 June 1999
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 December 1999
Date of withdrawal of any conflicting National Standard (dow):	31 December 1999

Endorsement notice

The elements of ITU-T Recommendation Q.2963-2 (1997) apply, with the following modifications:

Clause 1

Replace clause 1 by:

1 Scope

The present document specifies the signalling protocol for ATM Traffic Descriptor modification for the Broadband-Integrated Services Digital Network (B-ISDN) at the T_B reference point or coincident S_B and T_B reference point (as defined in ITU-T Recommendation I.413 [1]) by means of the Digital Subscriber Signalling System No. 2 (DSS 2). The present document extends the Peak Cell Rate (PCR) parameters modification capability specified in EN 301 003-1 to include the modification of the Sustainable Cell Rate (SCR) and the Maximum Burst Size (MBS) parameters

<https://standards.iteh.ai/catalog/standards/sist/b877a480-5635-4ba2-9df4-33014ad0243d/en-301-276-1-v1-1-3-2005>

In addition, the present document specifies the protocol requirements at the T_B reference point where the service is provided to the user via a private B-ISDN.

The capability described in the present document enables the connection owner to modify the ATM Traffic Descriptor for call/connections that have already been established.

ATM Traffic Descriptor modification is applicable to all connection oriented telecommunication services that are based on single point-to-point calls/connections, however, modification is not applicable to emulated N-ISDN services. The peak cell rate modification for point to multipoint calls/connections is outside the scope of the present document.

The present document is applicable to equipment, supporting ATM Traffic Descriptor modification, to be attached at either side of a T_B reference point or coincident S_B and T_B reference point when used as an access to the public B-ISDN.

Further ENs (or further parts of the present document) provide the method of testing and detailed application specific requirements to determine conformance to the present document.

The provision of this service requires the support of the protocol for the basic point-to-point call/bearer connections as defined in EN 300 443-1 [5].

Clause 2

Insert the following references at the end of clause 2:

- [5] EN 300 443-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. Two (DSS2) protocol; B-ISDN user-network interface layer 3 specification for basic call/bearer control; Part1: Protocol specification [ITU-T Recommendation Q.2931 (1995), modified]".
- [6] EN 301 068-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; ATM transfer capability and traffic parameter indication; Part 1: Protocol specification [ITU-T Recommendations Q.2961.1 (1995), Q.2961.2 (1997), Q.2961.3 (1997), Q.2961.4 (1997), modified]".

Throughout the text of ITU-T Recommendation Q.2963.2

Replace references as shown in table 1.

Table 1

Reference in ITU-T Recommendation Q.2963.2	Modified reference
ITU-T Recommendation Q.2931	ITU-T Recommendation Q.2931 as modified by EN 300 443-1
ITU-T Recommendation Q.2961.1	ITU-T Recommendation Q.2961.1 as modified by EN 301 068-1
ITU-T Recommendation Q.2963.1	ITU-T Recommendation Q.2963.1 as modified by EN 301 003-1

Appendix I

iTeh STANDARD PREVIEW

Appendix I has the status of an informative annex.

(standards.iteh.ai)

SIST EN 301 276-1 V1.1.3:2005

<https://standards.iteh.ai/catalog/standards/sist/b877a480-5635-4ba2-9df4-887c58443ab4/sist-en-301-276-1-v1-1-3-2005>

History

Document history				
V1.1.1	June 1998	Public Enquiry	PE 9843:	1998-06-03 to 1998-10-30
V1.1.2	December 1998	Vote	V 9909:	1998-12-29 to 1999-02-26
V1.1.3	March 1999	Publication		

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 301 276-1 V1.1.3:2005](https://standards.iteh.ai/catalog/standards/sist/b877a480-5635-4ba2-9df4-887c58443ab4/sist-en-301-276-1-v1-1-3-2005)

<https://standards.iteh.ai/catalog/standards/sist/b877a480-5635-4ba2-9df4-887c58443ab4/sist-en-301-276-1-v1-1-3-2005>