

ETSI TS 124 501 V16.6.0 (2020-10)



5G; Non-Access-Stratum (NAS) protocol for 5G System (5GS); Stage 3 (3GPP TS 24.501 version 16.6.0 Release 16)



ReferenceRTS/TSGC-0124501vg60

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	22
1 Scope	23
2 References	23
3 Definitions and abbreviations.....	27
3.1 Definitions	27
3.2 Abbreviations	34
4 General	37
4.1 Overview	37
4.2 Coordination between the protocols for 5GS mobility management and 5GS session management	37
4.3 UE domain selection	38
4.3.1 UE's usage setting	38
4.3.2 Domain selection for UE originating sessions / calls.....	38
4.3.3 Change of UE's usage setting.....	40
4.3.4 Change or determination of IMS voice availability.....	40
4.4 NAS security	41
4.4.1 General.....	41
4.4.2 Handling of 5G NAS security contexts.....	41
4.4.2.1 General	41
4.4.2.2 Establishment of a mapped 5G NAS security context during inter-system change from S1 mode to N1 mode in 5GMM-CONNECTED mode.....	43
4.4.2.3 Establishment of a 5G NAS security context during N1 mode to N1 mode handover	44
4.4.2.4 Establishment of an EPS security context during inter-system change from N1 mode to S1 mode in 5GMM-CONNECTED mode	45
4.4.2.5 Establishment of secure exchange of NAS messages	46
4.4.2.6 Change of security keys	47
4.4.3 Handling of NAS COUNT and NAS sequence number	48
4.4.3.1 General	48
4.4.3.2 Replay protection	49
4.4.3.3 Integrity protection and verification.....	49
4.4.3.4 Ciphering and deciphering	49
4.4.3.5 NAS COUNT wrap around	50
4.4.4 Integrity protection of NAS signalling messages.....	50
4.4.4.1 General	50
4.4.4.2 Integrity checking of NAS signalling messages in the UE	51
4.4.4.3 Integrity checking of NAS signalling messages in the AMF	51
4.4.5 Ciphering of NAS signalling messages	53
4.4.6 Protection of initial NAS signalling messages.....	54
4.5 Unified access control	56
4.5.1 General.....	56
4.5.2 Determination of the access identities and access category associated with a request for access for UEs not operating in SNPN access mode	57
4.5.2A Determination of the access identities and access category associated with a request for access for UEs operating in SNPN access mode	63
4.5.3 Operator-defined access categories.....	67
4.5.4 Access control and checking.....	69
4.5.4.1 Access control and checking in 5GMM-IDLE mode and in 5GMM-IDLE mode with suspend indication.....	69
4.5.4.2 Access control and checking in 5GMM-CONNECTED mode and in 5GMM-CONNECTED mode with RRC inactive indication	71
4.5.5 Exception handling and avoiding double barring	73
4.5.6 Mapping between access categories/access identities and RRC establishment cause	77

4.6	Network slicing	78
4.6.1	General.....	78
4.6.2	Mobility management aspects.....	79
4.6.2.1	General	79
4.6.2.2	NSSAI storage.....	80
4.6.2.3	Provision of NSSAI to lower layers in 5GMM-IDLE mode.....	82
4.6.2.4	Network slice-specific authentication and authorization.....	84
4.6.3	Session management aspects	85
4.7	NAS over non-3GPP access	85
4.7.1	General.....	85
4.7.2	5GS mobility management aspects.....	86
4.7.2.1	General	86
4.7.2.2	Establishment cause for non-3GPP access.....	86
4.7.3	5GS session management aspects.....	87
4.7.4	Limited service state over non-3GPP access	87
4.7.5	NAS signalling using trusted WLAN access network.....	88
4.8	Interworking with E-UTRAN connected to EPC	88
4.8.1	General.....	88
4.8.2	Single-registration mode.....	88
4.8.2.1	General	88
4.8.2.2	Single-registration mode with N26 interface	89
4.8.2.3	Single-registration mode without N26 interface	89
4.8.2.3.1	Interworking between NG-RAN and E-UTRAN	89
4.8.2.3.2	Interworking between TNGF or N3IWF connected to 5GCN and E-UTRAN.....	90
4.8.3	Dual-registration mode	91
4.8.4	Core Network selection for UEs not using ClIoT 5GS optimizations	92
4.8.4A	Core Network selection and redirection for UEs using ClIoT optimizations.....	93
4.8.4A.1	Core network selection.....	93
4.8.4A.2	Redirection of the UE by the core network.....	93
4.9	Disabling and re-enabling of UE's N1 mode capability	94
4.9.1	General.....	94
4.9.2	Disabling and re-enabling of UE's N1 mode capability for 3GPP access.....	94
4.9.3	Disabling and re-enabling of UE's N1 mode capability for non-3GPP access.....	96
4.10	Interworking with ePDG connected to EPC	97
4.11	UE configuration parameter updates	97
4.12	Access traffic steering, switching and splitting (ATSSS).....	97
4.13	Support of NAS signalling using wireline access network.....	98
4.14	Non-public network.....	98
4.14.1	General.....	98
4.14.2	Stand-alone non-public network	98
4.14.3	Public network integrated non-public network (PNI-NPN).....	100
4.15	Time sensitive communication.....	100
4.15.1	General.....	100
4.15.2	Integration with TSN network	100
4.15.2.1	General	100
4.15.2.2	Time synchronization.....	100
4.15.2.3	TSN bridge management.....	101
4.16	UE radio capability signalling optimisation	101
4.17	5GS mobility management in NB-N1 mode	102
4.18	5GS session management in NB-N1 mode	102
4.19	5GS mobility management in WB-N1 mode for IoT	103
4.20	5GS session management in WB-N1 mode for IoT	103
5	Elementary procedures for 5GS mobility management	104
5.1	Overview	104
5.1.1	General.....	104
5.1.2	Types of 5GMM procedures.....	104
5.1.3	5GMM sublayer states	105
5.1.3.1	General	105
5.1.3.2	5GMM sublayer states	105
5.1.3.2.1	5GMM sublayer states in the UE.....	105
5.1.3.2.1.1	General.....	105

5.1.3.2.1.2	Main states	106
5.1.3.2.1.2.1	5GMM-NULL	106
5.1.3.2.1.2.2	5GMM-DEREGISTERED	106
5.1.3.2.1.2.3	5GMM-REGISTERED-INITIATED	106
5.1.3.2.1.2.4	5GMM-REGISTERED	106
5.1.3.2.1.2.5	5GMM-DEREGISTERED-INITIATED	106
5.1.3.2.1.2.6	5GMM-SERVICE-REQUEST-INITIATED	106
5.1.3.2.1.3	Substates of state 5GMM-DEREGISTERED	107
5.1.3.2.1.3.1	General	107
5.1.3.2.1.3.2	5GMM-DEREGISTERED.NORMAL-SERVICE	107
5.1.3.2.1.3.3	5GMM-DEREGISTERED.LIMITED-SERVICE	107
5.1.3.2.1.3.4	5GMM-DEREGISTERED.ATTEMPTING-REGISTRATION	107
5.1.3.2.1.3.5	5GMM-DEREGISTERED.PLMN-SEARCH	107
5.1.3.2.1.3.6	5GMM-DEREGISTERED.NO-SUPI	107
5.1.3.2.1.3.7	5GMM-DEREGISTERED.NO-CELL-AVAILABLE	107
5.1.3.2.1.3.8	5GMM-DEREGISTERED.eCALL-INACTIVE	107
5.1.3.2.1.3.9	5GMM-DEREGISTERED.INITIAL-REGISTRATION-NEEDED	108
5.1.3.2.1.4	Substates of state 5GMM-REGISTERED	108
5.1.3.2.1.4.1	General	108
5.1.3.2.1.4.2	5GMM-REGISTERED.NORMAL-SERVICE	108
5.1.3.2.1.4.3	5GMM-REGISTERED.NON-ALLOWED-SERVICE	108
5.1.3.2.1.4.4	5GMM-REGISTERED.ATTEMPTING-REGISTRATION-UPDATE	108
5.1.3.2.1.4.5	5GMM-REGISTERED.LIMITED-SERVICE	109
5.1.3.2.1.4.6	5GMM-REGISTERED.PLMN-SEARCH	109
5.1.3.2.1.4.7	5GMM-REGISTERED.NO-CELL-AVAILABLE	109
5.1.3.2.1.4.8	5GMM-REGISTERED.UPDATE-NEEDED	109
5.1.3.2.2	5GS update status in the UE	109
5.1.3.2.3	5GMM sublayer states in the network side	110
5.1.3.2.3.1	General	110
5.1.3.2.3.2	5GMM-DEREGISTERED	110
5.1.3.2.3.3	5GMM-COMMON-PROCEDURE-INITIATED	110
5.1.3.2.3.4	5GMM-REGISTERED	110
5.1.3.2.3.5	5GMM-DEREGISTERED-INITIATED	111
5.1.4	Coordination between 5GMM and EMM	111
5.1.4.1	General	111
5.1.4.2	Coordination between 5GMM for 3GPP access and EMM with N26 interface	111
5.1.4.3	Coordination between 5GMM for 3GPP access and EMM without N26 interface	111
5.1.5	Coordination between 5GMM and GMM	112
5.2	Behaviour of the UE in state 5GMM-DEREGISTERED and state 5GMM-REGISTERED	112
5.2.1	General	112
5.2.2	UE behaviour in state 5GMM-DEREGISTERED	112
5.2.2.1	General	112
5.2.2.2	Primary substate selection	112
5.2.2.2.1	Selection of the substate after power on	112
5.2.2.3	Detailed description of UE behaviour in state 5GMM-DEREGISTERED	113
5.2.2.3.1	NORMAL-SERVICE	113
5.2.2.3.2	LIMITED-SERVICE	113
5.2.2.3.3	ATTEMPTING-REGISTRATION	113
5.2.2.3.4	PLMN-SEARCH	114
5.2.2.3.5	NO-SUPI	114
5.2.2.3.6	NO-CELL-AVAILABLE	114
5.2.2.3.7	eCALL-INACTIVE	114
5.2.2.3.8	INITIAL-REGISTRATION-NEEDED	115
5.2.2.4	Substate when back to state 5GMM-DEREGISTERED from another 5GMM state	115
5.2.3	UE behaviour in state 5GMM-REGISTERED	115
5.2.3.1	General	115
5.2.3.2	Detailed description of UE behaviour in state 5GMM-REGISTERED	115
5.2.3.2.1	NORMAL-SERVICE	115
5.2.3.2.2	NON-ALLOWED-SERVICE	116
5.2.3.2.3	ATTEMPTING-REGISTRATION-UPDATE	116
5.2.3.2.4	LIMITED-SERVICE	117
5.2.3.2.5	PLMN-SEARCH	117

5.2.3.2.6	NO-CELL-AVAILABLE	117
5.2.3.2.7	UPDATE-NEEDED	117
5.3	General on elementary 5GMM procedures	118
5.3.1	5GMM modes and N1 NAS signalling connection	118
5.3.1.1	Establishment of the N1 NAS signalling connection	118
5.3.1.2	Re-establishment of the N1 NAS signalling connection	119
5.3.1.3	Release of the N1 NAS signalling connection	120
5.3.1.4	5GMM-CONNECTED mode with RRC inactive indication	123
5.3.1.5	Suspend and resume of the N1 NAS signalling connection	125
5.3.2	Permanent identifiers	126
5.3.3	Temporary identities	128
5.3.4	Registration areas	128
5.3.5	Service area restrictions	129
5.3.5.1	General	129
5.3.5.2	3GPP access service area restrictions	129
5.3.5.3	Wireline access service area restrictions	132
5.3.6	Mobile initiated connection only mode	133
5.3.7	Handling of the periodic registration update timer and mobile reachable timer	134
5.3.8	Handling of timer T3502	136
5.3.9	Handling of NAS level mobility management congestion control	137
5.3.10	Handling of DNN based congestion control	137
5.3.11	Handling of S-NSSAI based congestion control	138
5.3.12	Handling of local emergency numbers	138
5.3.12A	Handling of local emergency numbers received via 3GPP access and non-3GPP access	139
5.3.12A.1	General	139
5.3.12A.2	Receiving a REGISTRATION ACCEPT message via non-3GPP access	139
5.3.13	Lists of 5GS forbidden tracking areas	140
5.3.13A	Forbidden PLMN lists	140
5.3.14	List of equivalent PLMNs	141
5.3.15	Transmission failure abnormal case in the UE	141
5.3.16	Extended DRX cycle for UEs in 5GMM-IDLE	141
5.3.17	Service Gap Control	142
5.3.18	Restriction on use of enhanced coverage	144
5.3.19	Handling of congestion control for transport of user data via the control plane	144
5.3.19a	Specific requirements for UE configured to use timer T3245	145
5.3.19a.1	UE not operating in SNPN access mode	145
5.3.19a.2	UE operating in SNPN access mode	145
5.3.20	Specific requirements for UE when receiving non-integrity protected reject messages	146
5.3.20.1	General	146
5.3.20.2	Requirements for UE in a PLMN	146
5.3.20.3	Requirements for UE in an SNPN	150
5.3.21	CIoT 5GS optimizations	153
5.3.22	Interaction between MICO mode with active time and extended idle mode DRX cycle	155
5.3.23	Forbidden wireline access area	155
5.3.24	WUS assistance	156
5.4	5GMM common procedures	156
5.4.1	Primary authentication and key agreement procedure	156
5.4.1.1	General	156
5.4.1.2	EAP based primary authentication and key agreement procedure	157
5.4.1.2.1	General	157
5.4.1.2.2	EAP-AKA' related procedures	159
5.4.1.2.2.1	General	159
5.4.1.2.2.2	Initiation	159
5.4.1.2.2.3	UE successfully authenticates network	159
5.4.1.2.2.4	Errors when handling EAP-request/AKA'-challenge message	160
5.4.1.2.2.5	Network successfully authenticates UE	160
5.4.1.2.2.6	UE handling EAP-AKA' notification message	160
5.4.1.2.2.6A	EAP based Identification initiation by the network	160
5.4.1.2.2.6B	EAP based Identification response by the UE	161
5.4.1.2.2.7	Network sending EAP-success message	161
5.4.1.2.2.8	UE handling EAP-success message	161
5.4.1.2.2.9	Network not successfully authenticates UE	161

5.4.1.2.2.10	Network sending EAP-failure message	161
5.4.1.2.2.11	UE handling EAP-failure message	162
5.4.1.2.2.12	Abnormal cases in the UE.....	164
5.4.1.2.3	EAP-TLS related procedures.....	164
5.4.1.2.3.1	General.....	164
5.4.1.2.3A	Procedures related to EAP methods other than EAP-AKA' and EAP-TLS.....	166
5.4.1.2.3A.1	General.....	166
5.4.1.2.3B	Procedures related to EAP methods used for primary authentication of an N5GC device...	169
5.4.1.2.3B.1	General.....	169
5.4.1.2.4	EAP message reliable transport procedure	170
5.4.1.2.4.1	General.....	170
5.4.1.2.4.2	EAP message reliable transport procedure initiation by the network	170
5.4.1.2.4.3	EAP message reliable transport procedure accepted by the UE.....	171
5.4.1.2.4.4	Abnormal cases on the network side.....	171
5.4.1.2.4.5	Abnormal cases in the UE.....	171
5.4.1.2.5	EAP result message transport procedure	173
5.4.1.2.5.1	General.....	173
5.4.1.2.5.2	EAP result message transport procedure initiation by the network	174
5.4.1.3	5G AKA based primary authentication and key agreement procedure	174
5.4.1.3.1	General	174
5.4.1.3.2	Authentication initiation by the network	175
5.4.1.3.3	Authentication response by the UE	175
5.4.1.3.4	Authentication completion by the network.....	176
5.4.1.3.5	Authentication not accepted by the network.....	176
5.4.1.3.6	Authentication not accepted by the UE	178
5.4.1.3.7	Abnormal cases	179
5.4.2	Security mode control procedure	183
5.4.2.1	General	183
5.4.2.2	NAS security mode control initiation by the network.....	183
5.4.2.3	NAS security mode command accepted by the UE.....	186
5.4.2.4	NAS security mode control completion by the network	188
5.4.2.5	NAS security mode command not accepted by the UE.....	189
5.4.2.6	Abnormal cases in the UE.....	189
5.4.2.7	Abnormal cases on the network side	189
5.4.3	Identification procedure.....	190
5.4.3.1	General	190
5.4.3.2	Identification initiation by the network.....	190
5.4.3.3	Identification response by the UE	190
5.4.3.4	Identification completion by the network	190
5.4.3.5	Abnormal cases in the UE.....	191
5.4.3.6	Abnormal cases on the network side	191
5.4.4	Generic UE configuration update procedure.....	192
5.4.4.1	General	192
5.4.4.2	Generic UE configuration update procedure initiated by the network.....	194
5.4.4.3	Generic UE configuration update accepted by the UE.....	196
5.4.4.4	Generic UE configuration update completion by the network	199
5.4.4.5	Abnormal cases in the UE.....	200
5.4.4.6	Abnormal cases on the network side	201
5.4.5	NAS transport procedure(s)	202
5.4.5.1	General	202
5.4.5.2	UE-initiated NAS transport procedure	202
5.4.5.2.1	General	202
5.4.5.2.2	UE-initiated NAS transport procedure initiation	203
5.4.5.2.3	UE-initiated NAS transport of messages accepted by the network	204
5.4.5.2.4	UE-initiated NAS transport of messages not accepted by the network	208
5.4.5.2.5	Abnormal cases on the network side	211
5.4.5.2.6	Abnormal cases in the UE	215
5.4.5.3	Network-initiated NAS transport procedure	216
5.4.5.3.1	General	216
5.4.5.3.2	Network-initiated NAS transport procedure initiation	217
5.4.5.3.3	Network-initiated NAS transport of messages	221
5.4.6	5GMM status procedure	224

5.4.6.1	General	224
5.4.6.2	5GMM status received in the UE	224
5.4.6.3	5GMM status received in the network	224
5.4.7	Network slice-specific authentication and authorization procedure	224
5.4.7.1	General	224
5.4.7.2	Network slice-specific EAP message reliable transport procedure	225
5.4.7.2.1	Network slice-specific EAP message reliable transport procedure initiation	225
5.4.7.2.2	Network slice-specific EAP message reliable transport procedure accepted by the UE	226
5.4.7.2.3	Abnormal cases on the network side	226
5.4.7.2.4	Abnormal cases in the UE	227
5.4.7.3	Network slice-specific EAP result message transport procedure	227
5.4.7.3.1	Network slice-specific EAP result message transport procedure initiation	227
5.5	5GMM specific procedures	228
5.5.1	Registration procedure	228
5.5.1.1	General	228
5.5.1.2	Registration procedure for initial registration	229
5.5.1.2.1	General	229
5.5.1.2.2	Initial registration initiation	229
5.5.1.2.3	5GMM common procedure initiation	234
5.5.1.2.4	Initial registration accepted by the network	234
5.5.1.2.5	Initial registration not accepted by the network	247
5.5.1.2.6	Initial registration for emergency services not accepted by the network	255
5.5.1.2.6A	Initial registration for initiating an emergency PDU session not accepted by the network ..	256
5.5.1.2.7	Abnormal cases in the UE	257
5.5.1.2.8	Abnormal cases on the network side	260
5.5.1.3	Registration procedure for mobility and periodic registration update	261
5.5.1.3.1	General	261
5.5.1.3.2	Mobility and periodic registration update initiation	262
5.5.1.3.3	5GMM common procedure initiation	270
5.5.1.3.4	Mobility and periodic registration update accepted by the network	271
5.5.1.3.5	Mobility and periodic registration update not accepted by the network	289
5.5.1.3.6	Mobility and periodic registration update for initiating an emergency PDU session not accepted by the network	298
5.5.1.3.7	Abnormal cases in the UE	298
5.5.1.3.8	Abnormal cases on the network side	302
5.5.2	De-registration procedure	304
5.5.2.1	General	304
5.5.2.2	UE-initiated de-registration procedure	305
5.5.2.2.1	UE-initiated de-registration procedure initiation	305
5.5.2.2.2	UE-initiated de-registration procedure completion	306
5.5.2.2.3	UE-initiated de-registration procedure completion for 5GS services over 3GPP access	306
5.5.2.2.4	UE-initiated de-registration procedure completion for 5GS services non-3GPP access	307
5.5.2.2.5	UE-initiated de-registration procedure completion for 5GS services over both 3GPP access and non-3GPP access	307
5.5.2.2.6	Abnormal cases in the UE	307
5.5.2.2.7	Abnormal cases in the network side	309
5.5.2.3	Network-initiated de-registration procedure	309
5.5.2.3.1	Network-initiated de-registration procedure initiation	309
5.5.2.3.2	Network-initiated de-registration procedure completion by the UE	310
5.5.2.3.3	Network-initiated de-registration procedure completion by the network	316
5.5.2.3.4	Abnormal cases in the UE	316
5.5.2.3.5	Abnormal cases in the network side	317
5.5.3	eCall inactivity procedure	318
5.6	5GMM connection management procedures	319
5.6.1	Service request procedure	319
5.6.1.1	General	319
5.6.1.2	Service request procedure initiation	322
5.6.1.2.1	UE is not using 5GS services with control plane CIoT 5GS optimization	322
5.6.1.2.2	UE is using 5GS services with control plane CIoT 5GS optimization	325
5.6.1.3	Common procedure initiation	327
5.6.1.4	Service request procedure accepted by the network	327
5.6.1.4.1	UE is not using 5GS services with control plane CIoT 5GS optimization	327

5.6.1.4.2	UE is using 5GS services with control plane CIoT 5GS optimization	329
5.6.1.5	Service request procedure not accepted by the network.....	332
5.6.1.6	Service request procedure for initiating an emergency PDU session not accepted by the network	341
5.6.1.7	Abnormal cases in the UE.....	341
5.6.1.8	Abnormal cases on the network side.....	345
5.6.2	Paging procedure	346
5.6.2.1	General.....	346
5.6.2.2	Paging for 5GS services.....	347
5.6.2.2.1	General	347
5.6.2.2.2	Abnormal cases on the network side	348
5.6.2.2.3	Abnormal cases in the UE	348
5.6.3	Notification procedure	348
5.6.3.1	General.....	348
5.6.3.2	Notification procedure initiation	349
5.6.3.3	Notification procedure completion.....	350
5.6.3.4	Abnormal cases on the network side.....	351
5.6.3.5	Abnormal cases on the UE side.....	351
6	Elementary procedures for 5GS session management	351
6.1	Overview	351
6.1.1	General.....	351
6.1.2	Types of 5GSM procedures	352
6.1.3	5GSM sublayer states	352
6.1.3.1	General	352
6.1.3.2	5GSM sublayer states in the UE	353
6.1.3.2.1	Overview	353
6.1.3.2.2	PDU SESSION INACTIVE	353
6.1.3.2.3	PDU SESSION ACTIVE PENDING	353
6.1.3.2.4	PDU SESSION ACTIVE	353
6.1.3.2.5	PDU SESSION INACTIVE PENDING.....	353
6.1.3.2.6	PDU SESSION MODIFICATION PENDING	353
6.1.3.2.7	PROCEDURE TRANSACTION INACTIVE.....	353
6.1.3.2.8	PROCEDURE TRANSACTION PENDING.....	354
6.1.3.3	5GSM sublayer states in the network side	354
6.1.3.3.1	Overview	354
6.1.3.3.2	PDU SESSION INACTIVE	354
6.1.3.3.3	PDU SESSION ACTIVE	354
6.1.3.3.4	PDU SESSION INACTIVE PENDING.....	354
6.1.3.3.5	PDU SESSION MODIFICATION PENDING	355
6.1.3.3.6	PROCEDURE TRANSACTION INACTIVE.....	355
6.1.3.3.7	PROCEDURE TRANSACTION PENDING.....	355
6.1.4	Coordination between 5GSM and ESM.....	355
6.1.4.1	Coordination between 5GSM and ESM with N26 interface	355
6.1.4.2	Coordination between 5GSM and ESM without N26 interface	367
6.1.4a	Coordination between 5GSM and SM.....	369
6.1.5	Coordination for interworking with ePDG connected to EPC	369
6.2	General on elementary 5GSM procedures.....	370
6.2.1	Principles of PTI handling for 5GSM procedures.....	370
6.2.2	PDU session types	371
6.2.3	PDU session management	371
6.2.4	IP address allocation	372
6.2.4.1	General.....	372
6.2.4.2	IP address allocation via NAS signalling	372
6.2.4.3	Additional RG related requirements for IP address allocation.....	373
6.2.5	Quality of service.....	374
6.2.5.1	General	374
6.2.5.1.1	QoS rules	374
6.2.5.1.1.1	General.....	374
6.2.5.1.1.2	Signalled QoS rules	374
6.2.5.1.1.3	Derived QoS rules.....	375
6.2.5.1.1.4	QoS flow descriptions.....	376

6.2.5.1.2	Session-AMBR.....	376
6.2.5.1.2A	Void.....	376
6.2.5.1.3	UL user data packet matching	376
6.2.5.1.4	Reflective QoS.....	377
6.2.5.1.4.1	General.....	377
6.2.5.1.4.2	Derivation of packet filter for UL direction from DL user data packet	377
6.2.5.1.4.3	Creating a derived QoS rule by reflective QoS in the UE.....	379
6.2.5.1.4.4	Updating a derived QoS rule by reflective QoS in the UE	379
6.2.5.1.4.5	Deleting a derived QoS rule in the UE	379
6.2.5.1.4.6	Ignoring RQI in the UE.....	380
6.2.5.2	QoS in MA PDU session.....	380
6.2.6	Local area data network (LADN)	380
6.2.7	Handling of DNN based congestion control	381
6.2.8	Handling of S-NSSAI based congestion control.....	381
6.2.9	Interaction with upper layers	383
6.2.9.1	General	383
6.2.9.2	URSP.....	383
6.2.10	Handling of 3GPP PS data off	383
6.2.11	Multi-homed IPv6 PDU session	384
6.2.12	Handling of network rejection not due to congestion control.....	385
6.2.13	Handling of Small data rate control	386
6.2.14	Handling of Serving PLMN rate control.....	386
6.2.15	Handling of Reliable Data Service	387
6.2.16	Handling of header compression for control plane CIoT optimizations.....	387
6.3	Network-requested 5GSM procedures	388
6.3.1	PDU session authentication and authorization procedure.....	388
6.3.1.1	General	388
6.3.1.2	PDU EAP message reliable transport procedure.....	389
6.3.1.2.1	PDU EAP message reliable transport procedure initiation.....	389
6.3.1.2.2	PDU EAP message reliable transport procedure accepted by the UE	390
6.3.1.2.3	Abnormal cases on the network side	391
6.3.1.2.4	Abnormal cases in the UE	391
6.3.1.3	PDU EAP result message transport procedure.....	391
6.3.1.3.1	PDU EAP result message transport procedure initiation.....	391
6.3.2	Network-requested PDU session modification procedure	391
6.3.2.1	General	391
6.3.2.2	Network-requested PDU session modification procedure initiation	392
6.3.2.3	Network-requested PDU session modification procedure accepted by the UE.....	394
6.3.2.4	Network-requested PDU session modification procedure not accepted by the UE.....	400
6.3.2.5	Abnormal cases on the network side	404
6.3.2.6	Abnormal cases in the UE	405
6.3.3	Network-requested PDU session release procedure	406
6.3.3.1	General	406
6.3.3.2	Network-requested PDU session release procedure initiation	406
6.3.3.3	Network-requested PDU session release procedure accepted by the UE.....	408
6.3.3.4	N1 SM delivery skipped.....	414
6.3.3.5	Abnormal cases on the network side	414
6.3.3.6	Abnormal cases in the UE	415
6.4	UE-requested 5GSM procedures.....	415
6.4.1	UE-requested PDU session establishment procedure	415
6.4.1.1	General	415
6.4.1.2	UE-requested PDU session establishment procedure initiation	416
6.4.1.3	UE-requested PDU session establishment procedure accepted by the network	422
6.4.1.4	UE requested PDU session establishment procedure not accepted by the network	430
6.4.1.4.1	General	430
6.4.1.4.2	Handling of network rejection due to congestion control.....	433
6.4.1.4.3	Handling of network rejection not due to congestion control.....	439
6.4.1.5	Handling the maximum number of established PDU sessions.....	444
6.4.1.5A	Handling the maximum number of allowed active user-plane resources for PDU sessions of UEs in NB-N1 mode	445
6.4.1.6	Abnormal cases in the UE.....	445
6.4.1.7	Abnormal cases on the network side.....	446

6.4.2	UE-requested PDU session modification procedure.....	447
6.4.2.1	General	447
6.4.2.2	UE-requested PDU session modification procedure initiation.....	448
6.4.2.3	UE-requested PDU session modification procedure accepted by the network	451
6.4.2.4	UE-requested PDU session modification procedure not accepted by the network	451
6.4.2.4.1	General	451
6.4.2.4.2	Handling of network rejection due to congestion control.....	452
6.4.2.4.3	Handling of network rejection not due to congestion control.....	458
6.4.2.5	Abnormal cases in the UE	461
6.4.2.6	Abnormal cases on the network side	462
6.4.3	UE-requested PDU session release procedure	463
6.4.3.1	General	463
6.4.3.2	UE-requested PDU session release procedure initiation	463
6.4.3.3	UE-requested PDU session release procedure accepted by the network.....	464
6.4.3.4	UE-requested PDU session release procedure not accepted by the network.....	464
6.4.3.5	Abnormal cases in the UE	464
6.4.3.6	Abnormal cases on the network side	465
6.5	5GSM status procedure	465
6.5.1	General.....	465
6.5.2	5GSM status received in the UE	465
6.5.3	5GSM status received in the SMF	466
6.6	Miscellaneous procedures	466
6.6.1	Exchange of extended protocol configuration options.....	466
7	Handling of unknown, unforeseen, and erroneous protocol data	467
7.1	General	467
7.2	Message too short or too long	467
7.2.1	Message too short	467
7.2.2	Message too long	467
7.3	Unknown or unforeseen procedure transaction identity or PDU Session identity.....	467
7.3.1	Procedure transaction identity.....	467
7.3.2	PDU Session identity.....	468
7.4	Unknown or unforeseen message type.....	469
7.5	Non-semantic mandatory information element errors	469
7.5.1	Common procedures	469
7.5.2	5GS mobility management	470
7.5.3	5GS session management	470
7.6	Unknown and unforeseen IEs in the non-imperative message part.....	471
7.6.1	IEs unknown in the message	471
7.6.2	Out of sequence IEs	471
7.6.3	Repeated IEs	471
7.7	Non-imperative message part errors.....	471
7.7.1	Syntactically incorrect optional IEs	471
7.7.2	Conditional IE errors	471
7.8	Messages with semantically incorrect contents	472
8	Message functional definitions and contents.....	472
8.1	Overview	472
8.2	5GS mobility management messages	472
8.2.1	Authentication request	472
8.2.1.1	Message definition	472
8.2.1.2	Authentication parameter RAND.....	472
8.2.1.3	Authentication parameter AUTN.....	473
8.2.1.4	Void.....	473
8.2.1.5	EAP message.....	473
8.2.2	Authentication response.....	473
8.2.2.1	Message definition	473
8.2.2.2	Authentication response parameter	473
8.2.2.3	EAP message.....	473
8.2.3	Authentication result.....	473
8.2.3.1	Message definition	473
8.2.3.2	ABBA	474

8.2.4	Authentication failure	474
8.2.4.1	Message definition	474
8.2.4.2	Authentication failure parameter.....	475
8.2.5	Authentication reject.....	475
8.2.5.1	Message definition	475
8.2.5.2	EAP message.....	475
8.2.6	Registration request	475
8.2.6.1	Message definition	475
8.2.6.2	Non-current native NAS key set identifier.....	478
8.2.6.3	5GMM capability.....	478
8.2.6.4	UE security capability.....	478
8.2.6.5	Requested NSSAI	478
8.2.6.6	Last visited registered TAI.....	478
8.2.6.7	S1 UE network capability	478
8.2.6.8	Uplink data status.....	478
8.2.6.9	PDU session status	478
8.2.6.10	MICO indication	478
8.2.6.11	UE status	479
8.2.6.12	Additional GUTI.....	479
8.2.6.13	Allowed PDU session status	479
8.2.6.14	UE's usage setting	479
8.2.6.15	Requested DRX parameters	479
8.2.6.16	EPS NAS message container.....	479
8.2.6.17	LADN indication.....	479
8.2.6.17A	Payload container type	479
8.2.6.18	Payload container.....	479
8.2.6.19	Network slicing indication	480
8.2.6.20	5GS update type	480
8.2.6.21	NAS message container	480
8.2.6.22	Requested extended DRX parameters.....	480
8.2.6.23	EPS bearer context status.....	480
8.2.6.24	T3324 value.....	480
8.2.6.25	Mobile station classmark 2.....	480
8.2.6.26	Supported codecs	480
8.2.6.27	UE radio capability ID	480
8.2.6.28	Requested mapped NSSAI.....	480
8.2.6.29	Additional information requested.....	481
8.2.6.30	Requested WUS assistance information.....	481
8.2.6.31	Void.....	481
8.2.6.32	N5GC indication	481
8.2.6.33	Requested NB-N1 mode DRX parameters.....	481
8.2.7	Registration accept.....	481
8.2.7.1	Message definition	481
8.2.7.2	5G-GUTI.....	484
8.2.7.3	Equivalent PLMNs.....	484
8.2.7.4	TAI list	484
8.2.7.5	Allowed NSSAI	484
8.2.7.6	Rejected NSSAI	485
8.2.7.7	Configured NSSAI.....	485
8.2.7.8	5GS network feature support.....	485
8.2.7.9	PDU session status	485
8.2.7.10	PDU session reactivation result.....	485
8.2.7.11	PDU session reactivation result error cause	485
8.2.7.12	LADN information.....	485
8.2.7.13	MICO indication	485
8.2.7.14	Network slicing indication	485
8.2.7.15	Service area list	485
8.2.7.16	T3512 value.....	486
8.2.7.17	Non-3GPP de-registration timer value	486
8.2.7.18	T3502 value.....	486
8.2.7.19	Emergency number list	486
8.2.7.20	Extended emergency number list	486