

ETSI TS 126 114 V16.7.0 (2020-10)



**Universal Mobile Telecommunications System (UMTS);
LTE;
5G;
IP Multimedia Subsystem (IMS);
Multimedia telephony;
Media handling and interaction
(3GPP TS 26.114 version 16.7.0 Release 16)**



ReferenceRTS/TSGS-0426114vg70

Keywords

5G,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	16
Introduction	16
1 Scope	17
2 References	17
3 Definitions and abbreviations.....	25
3.1 Definitions	25
3.2 Abbreviations	26
4 System description	28
4.1 System	28
4.2 Client	29
4.3 MRFP and MGW	30
5 Media codecs.....	30
5.1 Media components	30
5.2 Codecs for MTSI clients in terminals.....	31
5.2.1 Speech.....	31
5.2.1.1 General codec requirements	31
5.2.1.2 Detailed codec requirements, AMR.....	32
5.2.1.3 Detailed codec requirements, AMR-WB	32
5.2.1.4 Detailed codec requirements, EVS.....	32
5.2.1.5 Offering multiple audio bandwidths and multiple channels.....	32
5.2.1.6 Codec preference order	32
5.2.2 Video	33
5.2.3 Real-time text.....	34
6 Media configuration	35
6.1 General	35
6.2 Session setup procedures.....	35
6.2.1 General.....	35
6.2.1a RTP profile negotiation	36
6.2.1a.1 General	36
6.2.1a.2 Using SDPCapNeg in SDP offer.....	36
6.2.1a.3 Answering to an SDP offer using SDPCapNeg	36
6.2.2 Speech.....	37
6.2.2.1 General	37
6.2.2.2 Generating SDP offers	38
6.2.2.3 Generating SDP answer	40
6.2.3 Video	49
6.2.3.1 Introduction	49
6.2.3.2 Common Session Setup Procedures.....	50
6.2.3.3 Coordination of Video Orientation (CVO)	51
6.2.3.4 Video Region-of-Interest (ROI)	51
6.2.3.5 RTP Retransmission.....	54
6.2.3.6 Forward Error Correction (FEC).....	54
6.2.4 Text.....	54
6.2.5 Bandwidth negotiation.....	55
6.2.5.1 General	55
6.2.5.2 Speech	57
6.2.5.3 Video.....	60
6.2.6 The Synchronization Info attribute "3gpp_sync_info"	60
6.2.7 Negotiated QoS parameters	61

6.2.7.1	General	61
6.2.7.2	Alignment of negotiated QoS parameters and b=AS bandwidth modifier	61
6.2.7.3	Alignment of negotiated QoS parameters and a=bw-info attribute	62
6.2.7.4.1	General	63
6.2.7.4.2	3gpp-qos-hint ABNF syntax and semantics	63
6.2.7.4.3	Creating an SDP offer	64
6.2.7.4.4	Creating an SDP answer	64
6.2.7.4.5	Offerer receiving an SDP answer	66
6.2.8	Delay Budget Information (DBI) Signaling	67
6.2.9	ANBR Support attribute "anbr"	67
6.2.10	Data channel	68
6.3	Session control procedures	71
7	Data transport	71
7.1	General	71
7.2	RTP profiles	72
7.3	RTCP usage	72
7.3.1	General	72
7.3.2	Speech	73
7.3.3	Video	74
7.3.4	Real-time text	75
7.3.5	Void	75
7.3.6	Reduced-Size RTCP	75
7.3.7	Video Region-of-Interest (ROI) Signaling	76
7.3.8	Delay Budget Information (DBI) Signaling	78
7.4	RTP payload formats for MTSI clients	81
7.4.1	General	81
7.4.2	Speech	81
7.4.3	Video	82
7.4.4	Real-time text	83
7.4.5	Coordination of Video Orientation	83
7.4.6	RTP Retransmission	85
7.4.7	Forward Error Correction (FEC)	85
7.5	Media flow	85
7.5.1	General	85
7.5.2	Media specific	85
7.5.2.1	Speech	85
7.5.2.1.1	General	85
7.5.2.1.2	Default operation	85
7.5.2.1.2.1	General	85
7.5.2.1.2.2	Codec Mode Requests	86
7.5.2.1.2.3	Frame aggregation and redundancy	86
7.5.2.1.3	HSPA	86
7.5.2.1.4	EGPRS	87
7.5.2.1.5	GIP	87
7.5.2.1.6	Initial codec mode for AMR and AMR-WB	87
7.5.2.1.7	E-UTRAN and NR	88
7.5.2.1.8	Initial codec mode for EVS	88
7.5.2.1.9	Dual-mono	88
7.5.2.2	Video	88
7.5.2.3	Text	88
7.5.3	Media synchronization	89
7.5.3.1	General	89
7.5.3.2	Text	89
7.5.4	ECN usage in RTP sessions	89
7.5.5	Handling of bit-rate variations	89
7.5.5.1	General	89
7.5.5.2	Video	90
7.5.5.3	Speech	90
8	Jitter buffer management in MTSI clients in terminals	90
8.1	General	90

8.2	Speech	90
8.2.1	Terminology	90
8.2.2	Functional requirements for jitter-buffer management	92
8.2.3	Minimum performance requirements for jitter-buffer management	92
8.2.3.1	General	92
8.2.3.2	Objective performance requirements	93
8.2.3.2.1	General	93
8.2.3.2.2	Jitter buffer delay criteria	93
8.2.3.2.3	Jitter induced concealment operations	94
8.2.3.3	Delay and error profiles	95
8.2.3.4	Speech material for JBM minimum performance evaluation	95
8.3	Video	95
8.4	Text	95
9	Packet-loss handling	96
9.1	General	96
9.2	Speech	96
9.2.1	General	96
9.2.2	Transmitting redundant frames	96
9.2.3	Receiving redundant frames	99
9.3	Video	100
9.3.1	General	100
9.3.2	Receiver behaviour	100
9.3.3	Sender behaviour	100
9.3.4	Recommendations for packet loss recovery mechanisms usage	101
9.4	Text	102
10	Adaptation	102
10.1	General	102
10.2	Speech	102
10.2.0	General	102
10.2.1	RTCP-APP with codec control requests	104
10.2.1.1	General	104
10.2.1.2	General Format of RTCP-APP packet with codec control requests	104
10.2.1.2a	Padding	105
10.2.1.3	Redundancy Request	105
10.2.1.4	Frame Aggregation Request	106
10.2.1.5	Codec Mode Request	106
10.2.1.6	Generation of RTP payloads for multiple codec control requests	107
10.2.1.7	EVS Primary Rate Request	108
10.2.1.8	EVS Bandwidth Request	109
10.2.1.9	EVS Channel Aware Request	109
10.2.1.10	EVS Primary mode to EVS AMR-WB IO mode Switching Request	110
10.2.1.11	EVS AMR-WB IO mode to EVS Primary mode Switching Request	111
10.2.2	Example use cases	111
10.2.3	SDP negotiation for RTCP-APP	113
10.3	Video	115
10.3.1	General	115
10.3.2	Signaling mechanisms	115
10.3.3	Adaptation triggers	116
10.3.4	Sender behavior, downswitching	117
10.3.4.1	Downswitching divided into phases	117
10.3.4.2	Rate reduction phase	117
10.3.4.3	Delay recovery phase	118
10.3.5	Sender behavior, up-switching	118
10.3.6	Receiver behavior, down-switching	118
10.3.7	Receiver behavior, up-switch	118
10.3.8	ECN triggered adaptation	119
10.4	Text	120
10.5	Explicit Congestion Notification	120
10.6	Using the a=bw-info attribute for adaptation	120
10.7	Access network bitrate recommendation	121

10.7.1	General.....	121
10.7.2	Relation to session signaling bitrate information.....	122
10.7.3	Use with dynamic bitrate adaptation.....	122
10.7.3.1	General.....	122
10.7.3.2	Adaptation of sent media	122
10.7.3.3	Adaptation of received media	125
10.7.4	Message mapping for LTE access	126
10.7.5	Message mapping for NR access	126
11	Front-end handling	126
11.1	General	126
12	Inter-working.....	127
12.1	General	127
12.2	3G-324M	128
12.2.1	General.....	128
12.2.2	Codec usage	128
12.2.2.1	General	128
12.2.2.2	Text	128
12.2.3	Payload format.....	128
12.2.4	MTSI media gateway trans-packetization.....	128
12.2.4.1	General	128
12.2.4.2	Speech de-jitter buffer.....	128
12.2.4.3	Video bitrate equalization	128
12.2.4.4	Data loss detection	129
12.2.4.5	Data integrity indication.....	129
12.2.4.6	Packet size considerations.....	129
12.2.4.6.0	General	129
12.2.4.6.1	The Maximum Receive SDU Size attribute "3gpp_MaxRecvSDUSize".....	129
12.2.4.7	Setting RTP timestamps	130
12.2.4.8	Protocol termination.....	130
12.2.4.9	Media synchronization	130
12.2.5	Session control.....	130
12.3	GERAN/UTRAN CS inter-working	131
12.3.0	3G-324M	131
12.3.1	Codecs for MTSI media gateways	131
12.3.1.1	Speech interworking between 3GPP PS access and CS GERAN/UTRAN.....	131
12.3.1.1a	Speech inter-working between fixed access and CS GERAN/UTRAN.....	132
12.3.1.2	Text	132
12.3.2	RTP payload formats for MTSI media gateways.....	132
12.3.2.1	Speech	132
12.3.2.2	Text	133
12.3.3	Explicit Congestion Notification	134
12.3.4	Codec switching procedures with SRVCC	134
12.4	PSTN.....	135
12.4.1	3G-324M	135
12.4.2	Text.....	135
12.5	GIP inter-working.....	135
12.5.1	Text.....	135
12.5.2	Speech.....	135
12.6	Void.....	135
12.6.1	Void	135
12.6.2	Void	135
12.7	Inter-working with other IMS and non-IMS IP networks	135
12.7.1	General.....	135
12.7.2	Speech.....	136
12.7.2.1	General	136
12.7.2.2	Speech codecs and formats	136
12.7.2.2.1	MTSI MGW for interworking between MTSI client in terminal using 3GPP access and other IMS or non-IMS IP networks	136
12.7.2.2.2	MTSI MGW for interworking between MTSI client in terminal using fixed access and other IMS or non-IMS IP networks	136

12.7.2.2.3	Common procedures.....	137
12.7.2.3	Codec preference order for session negotiation	137
12.7.2.4	RTP profiles	137
12.7.2.5	RTP payload formats.....	137
12.7.2.6	Packetization	138
12.7.2.7	RTCP usage and adaptation	138
12.7.2.8	RTP usage	139
12.7.2.9	Session setup and session modification.....	139
12.7.2.10	Audio level alignment.....	140
12.7.3	Explicit Congestion Notification	140
12.7.4	Text.....	140
12.7.5	Inter-working IPv4 and IPv6 networks.....	140
12.8	MGW handling for NO_REQ interworking.....	141
13	Void.....	141
13a	Media types, codecs and formats used for MSRP transport.....	141
13a.1	General	141
13a.2	Difference relative to 3GPP TS 26.141	142
13a.2.1	Video	142
14	Supplementary services.....	142
14.1	General	142
14.2	Media formats and transport.....	142
14.3	Media handling in hold procedures	142
15	Network preference management object.....	143
15.1	General	143
15.2	Nodes Definition	143
15.3	Example Configuration of 3GPP MTSINP MO.....	155
16	Quality of Experience.....	156
16.1	General	156
16.2	Metrics Definition	157
16.2.1	Corruption duration metric	157
16.2.2	Successive loss of RTP packets	157
16.2.3	Frame rate	158
16.2.4	Jitter duration.....	158
16.2.5	Sync loss duration.....	158
16.2.6	Round-trip time.....	159
16.2.7	Average codec bitrate	159
16.2.8	Codec information	159
16.3	Metric Configuration.....	160
16.3.1	QoE metrics reporting management object.....	160
16.3.2	QoE metric reporting configuration.....	166
16.3.3	QoE reporting rule definition.....	166
16.4	Metrics Reporting.....	167
16.4.1	XML schema for QoE report message.....	168
16.4.2	Example XML for QoE report message	169
16.5	QoE Measurement Collection Functionalities.....	170
16.5.1	Configuration and reporting.....	170
16.5.2	XML configuration	172
17	Management of Media Adaptation.....	173
17.1	General	173
17.2	Media adaptation management object	174
17.3	Management procedures.....	200
17.3.1	Management of speech adaptation.....	200
17.3.2	Management of video adaptation.....	202
17.4	Management of media robustness adaptation.....	204
17.4.1	General.....	204
18	MTSI client in terminal using fixed access	205
18.1	General	205

18.2	Media codecs.....	205
18.2.1	General.....	205
18.2.2	Speech.....	205
18.2.2.1	Speech codecs	205
18.2.2.2	Error concealment procedures.....	205
18.2.2.3	Source controlled rate operation	206
18.2.3	Video	206
18.2.4	Real-time text.....	206
18.3	Media configuration	206
18.3.1	General.....	206
18.3.2	Session setup procedures	207
18.3.2.1	General	207
18.3.2.2	Speech.....	207
18.3.2.3	Video.....	208
18.3.2.4	Text	208
18.3.2.5	Bandwidth negotiation	208
18.3.3	Session control procedures	208
18.4	Data transport	208
18.4.1	General.....	208
18.4.2	Packetization.....	208
18.4.3	RTP payload format.....	209
18.5	Jitter buffer management.....	209
18.6	Packet-loss handling.....	209
18.7	Adaptation	210
18.8	Front-end handling	210
18.9	Supplementary services	210
19	Additional bandwidth information	210
19.1	General	210
19.2	Bandwidth properties	210
19.2.1	General description.....	210
19.2.2	Maximum Supported Bandwidth.....	211
19.2.3	Maximum Desired Bandwidth.....	212
19.2.4	Minimum Desired Bandwidth.....	212
19.2.5	Minimum Supported Bandwidth.....	212
19.2.6	IP version	213
19.2.7	Maximum Packet Rate.....	213
19.2.8	Minimum Packet Rate	213
19.3	SDP attribute	214
19.3.1	Definition.....	214
19.3.2	SDP grammar.....	214
19.3.3	Declarative use.....	215
19.3.4	Usage in offer/answer	215
19.4	Modifications of the bandwidth information by intermediate network nodes.....	216
Annex A (informative):	Examples of SDP offers and answers.....	218
A.1	SDP offers for speech sessions initiated by MTSI client in terminal	218
A.1.1	HSPA or unknown access technology.....	218
A.1.1.1	Only AMR-NB supported by MTSI client in terminal	218
A.1.1.2	AMR and AMR-WB are supported by MTSI client in terminal.....	219
A.1.1.2.1	One-phase approach.....	219
A.1.1.2.2	Two-phase approach	220
A.1.2	EGPRS	221
A.1.3	Generic Access	222
A.2	SDP offers for speech sessions initiated by media gateway.....	222
A.2.1	General	222
A.2.2	MGW between GERAN UE and MTSI	222
A.2.3	MGW between legacy UTRAN UE and MTSI.....	223
A.2.4	MGW between CS UE and MTSI.....	223
A.2.5	MGW between GERAN UE and MTSI when wideband speech is supported	224

A.3	SDP answers to SDP speech session offers.....	224
A.3.1	General	224
A.3.1a	SDP answer from an MTSI client in terminal when only narrowband speech was offered	225
A.3.2	SDP answer from an MTSI client in terminal	225
A.3.2a	SDP answer from a non-MTSI UE with AVP	226
A.3.3	SDP answer from an MTSI client in terminal supporting only AMR	227
A.3.4	SDP answer from an MTSI client in terminal using EGPRS access when both AMR and AMR-WB are supported	228
A.3.4a	SDP answer from an MTSI client in terminal using EGPRS access when only AMR is supported	229
A.3.4b	SDP answer from an MTSI client in terminal using WLAN.....	229
A.3.5	SDP answer from MTSI MGW supporting only one codec mode set for AMR and AMR-WB each	230
A.3.5a	SDP answer from MTSI MGW supporting only one codec mode set for AMR	232
A.3.6	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing UE on GERAN.....	232
A.3.7	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing legacy UE on UTRAN	233
A.4	SDP offers and answers for video sessions	234
A.4.1	Void.....	234
A.4.2	Void.....	234
A.4.2a	H.264/AVC	234
A.4.2b	High Granularity CVO example.....	236
A.4.2c	RTP Retransmission.....	236
A.4.2d	RTP Forward Error Correction (FEC).....	237
A.4.2e	SDP Examples with ROI.....	238
A.4.3	Void.....	244
A.4.4	Void.....	244
A.4.4a	H.264/AVC with "imageattr" attribute.....	244
A.4.4a.1	H.264/AVC with "imageattr" attribute – different image sizes in SDP offer and answer	246
A.4.4a.2	H.264/AVC with "imageattr" attribute – different payload type numbers in offer and answer	247
A.4.4b	H.264/AVC with "imageattr" attribute with multiple rtpmaps.....	248
A.4.5	H.264 with asymmetric video streams	250
A.4.6	H.264/AVC with "imageattr" attribute for non-CVO operation.....	251
A.4.7	H.264 (AVC) and H.265 (HEVC).....	253
A.4.7.1	MTSI client with 848x480 resolution 5 inch display	253
A.4.7.2	MTSI client with 1280x720 resolution 5 inch display	254
A.4.7.3	MTSI client with 848x480 resolution 10 inch display	255
A.4.7.4	MTSI client with 1280x720 resolution 10 inch display	256
A.4.8	H.264 (AVC) and H.265 (HEVC) with asymmetric video streams	257
A.5	SDP offers for text.....	258
A.5.1	T.140 with and without redundancy	258
A.6	SDP example with bandwidth information	260
A.6.1	General	260
A.6.2	SDP examples with bandwidth information declared with bandwidth modifiers.....	260
A.6.3	SDP examples giving additional bandwidth information using the a=bw-info attribute.....	261
A.7	SDP examples with "3gpp_sync_info" attribute	264
A.7.1	Synchronized streams.....	264
A.7.2	Nonsynchronized streams.....	264
A.8	SDP example with QoS negotiation.....	265
A.9	Void.....	269
A.9a	SDP offer/answer regarding the use of Reduced-Size RTCP.....	269
A.10	Examples of SDP offers and answers for inter-working with other IMS or non-IMS IP networks.....	270
A.10.1	General	270
A.10.2	Session initiated by MTSI client in terminal	270
A.10.2.1	SDP offers from an MTSI client in terminal.....	270
A.10.2.2	SDP offers modified by MTSI MGW when pre-emptively adding inter-working formats	271
A.10.2.3	SDP modified by MGW when adding inter-working formats only when the original SDP offer was rejected.....	272

A.11	Adding or removing a video component to/from an on-going video call session.....	274
A.12	SDP examples when using ECN	278
A.12.1	SDP examples when using ECN for speech	278
A.12.1.1	With RTP/AVP and zero RTCP bandwidth.....	278
A.12.1.2	With RTP/AVPF and non-zero RTCP bandwidth	279
A.12.1.3	With RTCP ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients	280
A.12.2	SDP examples when using ECN for video in RTP.....	281
A.12.2.1	Without RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports	281
A.12.2.2	With RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients	282
A.13	SDP examples for MTSI client in terminal using fixed access	283
A.13.1	General	283
A.13.2	SDP examples for PCM	283
A.13.3	SDP example for G.722.....	284
A.13.4	SDP example for EVS, AMR-WB, G.722, AMR, PCM and DTMF	284
A.14	SDP offers and answers for speech sessions with EVS	285
A.14.1	SDP offers initiated by MTSI client in terminal.....	285
A.14.1.1	Unknown access technology.....	285
A.14.1.2	EGPRS.....	286
A.14.1.3	NR/E-UTRAN/HSPA.....	287
A.14.1.4	Dual-mono	287
A.14.2	SDP offers initiated by media gateway	288
A.14.2.1	Network between MTSI using fixed access and MTSI modifying SDP offer to configure EVS AMR-WB IO mode.....	289
A.14.3	SDP answers from MTSI client in terminal	290
A.14.3.1	SDP answer from MTSI client in terminal when narrowband speech is negotiated	290
A.14.3.2	SDP answer from MTSI client in terminal when up to wideband speech is negotiated	290
A.14.3.3	SDP answer from MTSI client in terminal when only wideband speech is negotiated	291
A.14.3.4	SDP answer from MTSI client in terminal when up to super-wideband speech is negotiated	291
A.14.3.5	SDP answer from MTSI client in terminal when only super-wideband speech is negotiated	291
A.14.3.6	SDP answer from MTSI client in terminal using WLAN	292
A.14.3.7	SDP answer from MTSI client in terminal supporting dual-mono	292
A.14.3.8	SDP answer from MTSI client in terminal supporting dual-mono for send direction	292
A.14.3.9	SDP answer from MTSI client in terminal when SC-VBR is negotiated	293
A.14.4	SDP answers from MTSI client in terminal using fixed access.....	293
A.14.4.1	SDP answer from MTSI client in terminal using fixed access when narrowband speech is negotiated ...	293
A.14.4.2	SDP answer from MTSI client in terminal using fixed access when only wideband speech is negotiated.....	294
A.14.4.3	SDP answer from MTSI client in terminal using fixed access when only super-wideband speech is negotiated.....	294
A.15	SDP offers and answers with ANBR capability signaling	295
A.16	SDP offers and answers with QoS hint signaling.....	296
A.17	SDP offers and answers with data channel capability signaling	298
Annex B (informative):	Examples of adaptation scenarios	300
B.1	Video bitrate adaptation	300
Annex C (informative):	Example adaptation mechanisms for speech.....	301
C.1	Example of feedback and adaptation for speech and video.....	301
C.1.1	Introduction	301
C.1.2	Signalling state considerations	302
C.1.3	Adaptation state machine implementations	304
C.1.3.1	General.....	304
C.1.3.2	Adaptation state machine with four states	306
C.1.3.3	Adaptation state machine with four states (simplified version without frame aggregation).....	309
C.1.3.4	Adaptation state machine with two states	311

C.1.3.5	Adaptation when using ECN	312
C.2	Example criteria for video bit rate feedback and adaptation	314
C.2.1	Introduction	314
C.2.2	Media sender side	315
C.2.3	Media receiver side	315
C.2.4	Video encoder bitrate adaptation, down-switch	315
C.2.5	Video encoder bitrate adaptation, receiver-driven up-switch	317
C.2.6	Video encoder bitrate adaptation, recovery phase	317
Annex D (informative):	Reference delay computation algorithm.....	319
Annex E (informative):	QoS profiles	321
E.1	General	321
E.2	Bi-directional speech (AMR12.2, IPv4, RTCP and MBR=GBR bearer).....	321
E.3	Void.....	322
E.4	Bi-directional real-time text (3 kbps, IPv4 or IPv6, RTCP and MBR=GBR bearer).....	323
E.5	Bi-directional speech (AMR-WB23.85, IPv4, RTCP and MBR=GBR bearer).....	325
E.6	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv4, RTCP and MBR=GBR bearer)	325
E.7	Bi-directional speech (AMR12.2, IPv6, RTCP and MBR=GBR bearer).....	326
E.8	Bi-directional speech (AMR-WB23.85, IPv6, RTCP and MBR=GBR bearer).....	327
E.9	Void.....	328
E.10	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv6, RTCP and MBR=GBR bearer)	328
E.11	Bi-directional speech (AMR, IPv4, RTCP and MBR>GBR bearer).....	329
E.12	Bi-directional speech (AMR-WB, IPv4, RTCP and MBR>GBR bearer).....	330
E.13	Void.....	331
E.14	Bi-directional video (H.264 AVC level 1.1, IPv4, RTCP and MBR>GBR bearer).....	331
E.15	Bi-directional speech (AMR, IPv6, RTCP and MBR>GBR bearer).....	332
E.16	Bi-directional speech (AMR-WB, IPv6, RTCP and MBR>GBR bearer).....	333
E.17	Void.....	334
E.18	Bi-directional video (H.264 AVC level 1.1, IPv6, RTCP and MBR>GBR bearer).....	334
E.19	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv4, RTCP and MBR=GBR bearer)	335
E.20	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv6, RTCP and MBR=GBR bearer)	336
E.21	Bi-directional video (H.264 AVC level 1.2, IPv4, RTCP and MBR>GBR bearer).....	338
E.22	Bi-directional video (H.264 AVC level 1.2, IPv6, RTCP and MBR>GBR bearer).....	341
E.23	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500 kbps, IPv6, RTCP and MBR=GBR bearer)	342
E.24	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500/40 kbps, IPv6, RTCP and MBR>GBR bearer)	343
E.25	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600 kbps, IPv6, RTCP and MBR=GBR bearer)	344
E.26	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600/40 kbps, IPv6, RTCP and MBR>GBR bearer)	345
E.27	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650 kbps, IPv6, RTCP and MBR=GBR bearer)	346

E.28	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650/40 kbps, IPv6, RTCP and MBR>GBR bearer)	347
E.29	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750 kbps, IPv6, RTCP and MBR=GBR bearer)	348
E.30	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750/40 kbps, IPv6, RTCP and MBR>GBR bearer)	349
E.31	Bi-directional speech (EVS 13.2, IPv4, RTCP and MBR=GBR bearer)	350
E.32	Bi-directional speech (EVS 24.4, IPv4, RTCP and MBR=GBR bearer)	351
E.33	Bi-directional speech (EVS 13.2, IPv6, RTCP and MBR=GBR bearer)	352
E.34	Bi-directional speech (EVS 24.4, IPv6, RTCP and MBR=GBR bearer)	353
Annex F (Normative):	Void	355
Annex G (Normative):	DTMF events	356
G.1	General	356
G.2	Encoding of DTMF events	356
G.3	Session setup	356
G.4	Data transport for DTMF events	358
Annex H (informative):	Network Preference Management Object Device Description Framework	360
Annex I (informative):	QoE Reporting Management Object Device Description Framework ...	361
Annex J (informative):	Media Adaptation Management Object Device Description Framework	362
Annex K (informative):	Computation of b=AS for AMR and AMR-WB	363
K.1	General	363
K.2	Procedure for computing the bandwidth	363
K.3	Computation of RTP payload size	363
K.4	Detailed computation	364
Annex L (Normative):	Facsimile transmission	373
L.1	General	373
L.2	FoIP support in MTSI clients	373
L.2.1	FoIP support in MTSI client in terminal	373
L.2.2	FoIP support in MTSI MGW	373
L.2.3	Recommended configuration	373
L.3	Session setup	374
L.3.1	Session setup for any MTSI client supporting facsimile transmission	374
L.3.2	Session setup when the recommended profile is supported	374
L.4	Data transport using UDP/IP	375
L.5	CS GERAN inter-working	375
L.6	PSTN inter-working	376
L.7	SDP examples	376
L.7.1	Facsimile-only session	376
Annex M (informative):	IANA registration information for SDP attributes	378