
**Road vehicles — Vehicle to grid
communication interface —**

**Part 4:
Network and application protocol
conformance test**

iTeh STANDARD PREVIEW
*Véhicules routiers — Interface de communication entre véhicule et
réseau électrique —
(standards.iteh.ai)
Partie 4: Essai de conformité du protocole d'application et du réseau*

[ISO 15118-4:2018](https://standards.iteh.ai/catalog/standards/sist/64ef675a-6c38-45dc-9bfc-6c367937ab87/iso-15118-4-2018)

<https://standards.iteh.ai/catalog/standards/sist/64ef675a-6c38-45dc-9bfc-6c367937ab87/iso-15118-4-2018>



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 15118-4:2018

<https://standards.iteh.ai/catalog/standards/sist/64ef675a-6c38-45dc-9bfc-6c367937ab87/iso-15118-4-2018>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents	Page
Foreword.....	vii
Introduction.....	viii
1 Scope	1
2 Normative references	2
3 Terms and definitions.....	2
4 Symbols (and abbreviated terms)	7
5 Conventions	8
5.1 Requirement structure.....	8
5.2 Test system description	9
6 Test architecture reference model.....	9
6.1 General information	9
6.2 Platform adapter interface.....	10
6.3 SUT adapter interfaces	10
6.4 Codecs	11
7 Test suite conventions	11
7.1 General information	11
7.2 Test suite structure (TSS).....	11
7.3 Test profiles.....	13
7.4 Test suite identifiers.....	62
7.5 Test suite coverage	67
7.6 Test case description.....	184
7.7 Test case specification	185
8 Test case descriptions for 15118-2 V2GTP	198
8.1 General information	198
8.2 SECC test cases	198
8.3 EVCC test cases.....	202
9 Test case descriptions for 15118-2 SDP messages.....	208
9.1 General information	208
9.2 SECC test cases	208
9.3 EVCC test cases.....	211
10 Test case descriptions for 15118-2 V2G application layer messages.....	236
10.1 General information	236
10.2 SECC test cases	236
10.3 EVCC test cases.....	405
Annex A (normative) Configuration specifications	671
A.1 Timer configuration	671
A.2 PICS configuration.....	671

A.3	PIXIT configuration	673
Annex B (normative) Control part specification.....		675
B.1	SECC control parts.....	675
B.1.1	AC specific control parts.....	675
B.1.2	DC specific control parts.....	675
B.2	EVCC control parts	688
B.2.1	AC specific control parts	702
B.2.2	DC specific control parts.....	702
Annex C (normative) Test-case specifications for 15118-2 V2GTP		745
C.1	SECC test cases.....	745
C.2	EVCC test cases	745
Annex D (normative) Test-case specifications for 15118-2 SDP messages		752
D.1	SECC test cases.....	752
D.2	EVCC test cases	752
Annex E (normative) Test-case specifications for 15118-2 V2G application layer messages.....		773
E.1	SECC test cases.....	773
E.1.1	V2G protocol handshake	773
E.1.1.1	SECC test cases for SupportedAppProtocol.....	773
E.1.2	V2G messages	773
E.1.2.1	SECC test cases for SessionSetup.....	775
E.1.2.2	SECC test cases for ServiceDiscovery	775
E.1.2.3	SECC test cases for ServiceDetail	782
E.1.2.4	SECC test cases for PaymentServiceSelection	784
E.1.2.5	SECC test cases for PaymentDetails	788
E.1.2.6	SECC test cases for Authorization.....	794
E.1.2.7	SECC test cases for ChargeParameterDiscovery	794
E.1.2.8	SECC test cases for PowerDelivery	799
E.1.2.9	SECC test cases for CertificateUpdate.....	824
E.1.2.10	SECC test cases for CertificateInstallation	839
E.1.2.11	SECC test cases for SessionStop.....	839
E.1.2.12	SECC test cases for ChargingStatus	842
E.1.2.13	SECC test cases for MeteringReceipt	846
E.1.2.14	SECC test cases for CableCheck	848
E.1.2.15	SECC test cases for PreCharge	852
E.1.2.16	SECC test cases for CurrentDemand	855
E.1.2.17	SECC test cases for WeldingDetection	859
E.2	EVCC test cases	860
Annex F (normative) Function specifications for supporting test execution		1009

ITeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 15118-4:2018
<https://standards.iteh.ai/catalog/standards/sist/64ef675a-6c38-45dc-9bfc-6c367937ab87/iso-15118-4-2018>

F.1	Configuration functions	1009
F.2	Pre-condition functions	1009
F.2.1	SECC functions	1011
F.2.2	EVCC functions	1027
F.3	Post-condition functions	1027
F.3.1	SECC functions	1038
F.3.2	EVCC functions	1038
F.4	Common behavior functions	1039
F.4.1	SECC functions	1040
F.4.2	EVCC functions	1042
F.5	Library functions	1044
Annex G (normative)	Function specifications for 15118-2 V2GTP	1051
G.1	SECC functions	1051
G.2	EVCC functions	1053
Annex H (normative)	Function specifications for 15118-2 SDP messages	1056
H.1	SECC functions	1056
H.2	EVCC functions	1057
Annex I (normative)	Function specifications for 15118-2 V2G application layer messages	1061
I.1	SECC functions	1061
I.1.1	V2G protocol handshake	1061
I.1.1.1	SECC functions for SupportedAppProtocol	1061
I.1.2	V2G messages	1063
I.1.2.1	SECC functions for SessionSetup	1063
I.1.2.2	SECC functions for ServiceDiscovery	1064
I.1.2.3	SECC functions for ServiceDetail	1072
I.1.2.4	SECC functions for PaymentServiceSelection	1080
I.1.2.5	SECC functions for PaymentDetails	1087
I.1.2.6	SECC functions for Authorization	1091
I.1.2.7	SECC functions for ChargeParameterDiscovery	1104
I.1.2.8	SECC functions for PowerDelivery	1140
I.1.2.9	SECC functions for CertificateUpdate	1154
I.1.2.10	SECC functions for CertificateInstallation	1167
I.1.2.11	SECC functions for SessionStop	1176
I.1.2.12	SECC functions for ChargingStatus	1176
I.1.2.13	SECC functions for MeteringReceipt	1185
I.1.2.14	SECC functions for CableCheck	1197
I.1.2.15	SECC functions for PreCharge	1203
I.1.2.16	SECC functions for CurrentDemand	1207

I.1.2.17	SECC functions for WeldingDetection.....	1213
I.2	EVCC functions.....	1217
Annex J (normative) Template specifications for V2G TCP/TLS Port Control		1373
Annex K (normative) Template specifications for 15118-2 V2GTP.....		1375
K.1	Common templates.....	1375
Annex L (normative) Template specifications for 15118-2 SDP messages.....		1376
L.1	Common templates.....	1376
Annex M (normative) Template specifications for 15118-2 V2G application layer messages		1377
M.1	Common templates.....	1377
M.1.1	V2G protocol handshake	1378
M.1.1.1	CMN templates for SupportedAppProtocol	1378
M.1.2	V2G messages	1378
M.1.2.1	CMN templates for SessionSetup.....	1378
M.1.2.2	CMN templates for ServiceDiscovery.....	1378
M.1.2.3	CMN templates for Authorization	1381
M.1.2.4	CMN templates for PowerDelivery	1381
M.1.2.5	CMN templates for SessionStop	1383
M.1.2.6	CMN templates for ChargingStatus.....	1384
M.1.2.7	CMN templates for CableCheck.....	1384
M.1.2.8	CMN templates for PreCharge.....	1385
M.1.2.9	CMN templates for CurrentDemand.....	1385
M.1.2.10	CMN templates for WeldingDetection	1387
M.2	SECC templates.....	1387
M.3	EVCC templates	1397
Annex N (normative) Template specifications for Security.....		1430
N.1	Common templates.....	1430
Annex O (normative) Data type definitions.....		1434
O.1	Data types for PICS.....	1434
O.2	Data types for PIXIT	1434
O.3	Data types for V2G TCP/TLS Port Control	1436
O.4	Data types for V2GTP	1437
O.5	Data types for SDP messages.....	1438
O.6	Data types for V2G messages	1438
O.7	Data types for Security.....	1457

iTech STANDARD PREVIEW
 (standards.iteh.ai)
 ISO 15118-4:2018
 https://standards.iteh.ai/catalog/standards/sist/64ef675a-6c38-45dc-9bfc-6c367937ab87/iso-15118-4-2018

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html
catalog/standards/sist/64ef675a-6c38-45dc-9bfc-6c367937ab87/iso-15118-4-2018

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Electrical and electronic equipment*, and Technical Committee IEC/TC 69 *Electric road vehicles and electric industrial trucks*. The draft was circulated for voting to the national bodies of both ISO and IEC.

A list of all parts in the ISO 15118 series can be found on the ISO website.

Introduction

The first three parts of ISO 15118 describe the use cases and the technical specification of the Vehicle-to-Grid Communication Interface which is intended for the optimized use of energy resources so that electric road vehicles can recharge in the most economic or most energy efficient way. It is furthermore required to develop efficient and convenient billing systems in order to cover the resulting micro-payments. The necessary communication channel may serve in the future to contribute to the stabilization of the electrical grid as well as to support additional information services required to operate electric vehicles efficiently and economically.

The complexity resulting from the network and application protocol requirements defined in the second part of the standard requires a considerable amount of testing in order to enable interoperability between independent implementations. This document therefore defines a conformance test suite for the network and application layer protocols in order to derive a common and agreed basis for conformance tests. The resulting test suite is a necessary prerequisite for downstream interoperability tests. Since interoperability furthermore involves the actual application logic of an implementation those tests are beyond the scope of this document. Hence this document focuses on the interface aspects and the corresponding requirements given in part two only.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 15118-4:2018](https://standards.iteh.ai/catalog/standards/sist/64ef675a-6c38-45dc-9bfc-6c367937ab87/iso-15118-4-2018)

<https://standards.iteh.ai/catalog/standards/sist/64ef675a-6c38-45dc-9bfc-6c367937ab87/iso-15118-4-2018>

Road vehicles — Vehicle to grid communication interface — Part 4: Network and application protocol conformance test

1 Scope

This document specifies conformance tests in the form of an Abstract Test Suite (ATS) for a System Under Test (SUT) implementing an EVCC or SECC according to ISO 15118-2. These conformance tests specify the testing of capabilities and behaviors of an SUT as well as checking what is observed against the conformance requirements specified in ISO 15118-2 and against what the supplier states the SUT implementation's capabilities are.

The capability tests within the ATS check that the observable capabilities of the SUT are in accordance with the static conformance requirements defined in ISO 15118-2. The behavior tests of the ATS examine an implementation as thoroughly as is practical over the full range of dynamic conformance requirements defined in ISO 15118-2 and within the capabilities of the SUT (see NOTE).

A test architecture is described in correspondence to the ATS. The conformance test cases in this document are described leveraging this test architecture and are specified in TTCN-3 Core Language for ISO/OSI Network Layer (Layer 3) and above. The conformance test cases for the Data Link Layer (Layer 2) and Physical Layer (Layer 1) are described in ISO 15118-5. Test cases with overlapping scopes are explicitly detailed.

This document does not include specific tests of other standards referenced within ISO 15118-2, e.g. IETF RFCs. Furthermore, the conformance tests specified in this document do not include the assessment of performance nor robustness or reliability of an implementation. They cannot provide judgments on the physical realization of abstract service primitives, how a system is implemented, how it provides any requested service, nor the environment of the protocol implementation. Furthermore, the test cases defined in this document only consider the communication protocol defined ISO 15118-2. Power flow between the EVSE and the EV is not considered.

NOTE 1 Practical limitations make it impossible to define an exhaustive test suite, and economic considerations can restrict testing even further. Hence, the purpose of this document is to increase the probability that different implementations are able to interwork. This is achieved by verifying them by means of a protocol test suite, thereby increasing the confidence that each implementation conforms to the protocol specification. However, the specified protocol test suite cannot guarantee conformance to the specification since it detects errors rather than their absence. Thus conformance to a test suite alone cannot guarantee interworking. What it does do is give confidence that an implementation has the required capabilities and that its behavior conforms consistently in representative instances of communication.

NOTE 2 This document has some interdependencies to the conformance tests defined in ISO 15118-5 which result from ISO/OSI cross layer dependencies in the underlying protocol specification (e.g. for sleep mode)

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61851-1:2017, *Electric vehicle conductive charging system — Part 1: General requirements*

ISO 15118-1:2013, *Road vehicles — Vehicle to grid communication interface — Part 1: General information and use-case definition*

ISO 15118-2:2014, *Road vehicles — Vehicle-to-Grid Communication Interface — Part 2: Network and application protocol requirements*

ISO 15118-3:2015, *Road vehicles — Vehicle-to-Grid Communication Interface — Part 3: Physical and data link layer requirements*

ETSI ES 201 873-5 V4.6.1, *TTCN-3: TTCN-3 Runtime Interface (June 2014)*

ETSI ES 201 873-6 V4.6.1, *TTCN-3: TTCN-3 Control Interface (June 2014)*

NOTE 1 Even though the technical specification ISO 15118-2:2014, which is the baseline for this conformance test document, explicitly references IEC 61851-1:2011, this document references IEC 61851-1:2017 because of applicability on the market.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

3 Terms and definitions

For the purpose of this document, the terms and definitions given in ISO 15118-1, ISO 15118-2, ISO 15118-3 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

3.1

abstract test case

complete and independent specification of the actions required to achieve a specific test purpose

Note 1 to entry: This specification is defined at the level of abstraction of a particular Abstract Test Method, starting in a stable testing state and ending in a stable testing state and may involve one or more consecutive or concurrent connections.

Note 2 to entry: The specification should be complete in the sense that it is sufficient to enable a test verdict to be assigned unambiguously to each potentially observable test outcome (i.e. sequence of test events).

Note 3 to entry: The specification should be independent in the sense that it should be possible to execute the derived executable test case in isolation from other such test cases (i.e. the specification should always include the possibility of starting and finishing in the “idle” state).

Note 4 to entry: Compare with ITU-T X.290.

3.2

abstract test suite

ATS

test suite composed of abstract test cases

Note 1 to entry: Compare with ITU-T X.290.

3.3

black box testing

method of testing that examines the behavior of an SUT without considering the internal implementation and structure of the SUT, thus relying on the SUT's open interface for testing

3.4

conformance requirements

conformance of a real system consisting of conformance to each requirement and conformance to the set

Note 1 to entry: Set of interrelated requirements which together define the behavior of the system and its communication. Conformance of a real system will, therefore, be expressed at two levels, conformance to each individual requirement and conformance to the set. Applicable ISO 15118-4 conformance tests include requirements and transfer syntax requirements as far as they can be validated by black box testing.

Note 2 to entry: See also *static conformance requirements* and *dynamic conformance requirements*.

3.5

conforming implementation

IUT which satisfies both static and dynamic conformance requirements, consistent with the capabilities stated in the PICS(s)

Note 1 to entry: Compare with ITU-T X.290.

3.6

dynamic conformance requirements

one of the requirements which specifies what observable behavior is permitted by the relevant specification(s) in instances of communication

Note 1 to entry: The requirements for this conformance specification are defined in ISO 15118-2.

Note 2 to entry: Compare with ITU-T X.290.

3.7

executable test case

realization of an abstract test case

Note 1 to entry: Compare with ITU-T X.290.

3.8

expected behavior

exact response of the SUT according to the underlying protocol specification to the stimulus defined in the test behavior

3.9

implementation conformance statement

ICS

statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented

Note 1 to entry: The given specification for this conformance specification is ISO 15118-2.

Note 2 to entry: Compare with ITU-T X.290.

3.10

implementation extra information for testing

IXIT

statement made by a supplier or implementer of an IUT which contains or references all of the information (in addition to that given in the ICS) related to the IUT and its testing environment, which will enable the test laboratory to run an appropriate test suite against the IUT

Note 1 to entry: Compare with ITU-T X.290.

3.11 implementation under test

IUT

implementation of one or more OSI protocols in an adjacent user/provider relationship, being that part of a real open system which is to be studied by testing

Note 1 to entry: Compare with ITU-T X.290.

3.12 main test component

MTC

single test component in a test component configuration responsible for creating and controlling *parallel test components* and computing and assigning the test verdict

Note 1 to entry: Compare with ITU-T X.290.

3.13 parallel test component

PTC

test component created by the main test component

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Note 1 to entry: Compare with ITU-T X.292.

[ISO 15118-4:2018](https://standards.iteh.ai/catalog/standards/sist/64ef675a-6c38-45dc-9bfc-6c367937ab87/iso-15118-4-2018)

<https://standards.iteh.ai/catalog/standards/sist/64ef675a-6c38-45dc-9bfc-6c367937ab87/iso-15118-4-2018>

3.14 post-condition

test steps needed to define the path from the end of the *test behavior* up to the finishing stable state for the test case

Note 1 to entry: See also *Test behavior*.

3.15 pre-condition

test steps needed to define the path from the starting stable state of the test case up to the initial state from which the *test behavior* will start

Note 1 to entry: See also *Test behavior*.

3.16 protocol implementation conformance statements

PICS

ICS for an implementation or system claimed to conform to a given protocol specification

Note 1 to entry: The given protocol specification for this conformance specification is ISO 15118-2.

Note 2 to entry: Compare with ITU-T X.290.

3.17 protocol implementation extra information for testing

PIXIT

IXIT related to testing for conformance to a given protocol specification

Note 1 to entry: The given protocol specification for this conformance specification is ISO 15118-2.

Note 2 to entry: Compare with ITU-T X.290.

3.18 runtime environment

environment that describes the operating system and corresponding platform requirements of a system

EXAMPLE Test system.

3.19 semantically invalid test behavior SemITB

test steps where the test system sends stimuli to the SUT that are semantically invalid according to the protocol requirements

Note 1 to entry: This type of test behavior is defined in this conformance standard and explicitly includes requirements which define the appropriate error handling of the SUT.

3.20 static conformance requirements

one of the requirements that specify the limitations on the combinations of implemented capabilities permitted in a real open system which is claimed to conform to the relevant specification(s)

Note 1 to entry: Compare with ITU-T X.290.

3.21 system under test SUT

real open system in which the IUT resides

<https://standards.iteh.ai/catalog/standards/sist/64ef675a-6c38-45dc-9bfc-6c367937ab87/iso-15118-4-2018>

Note 1 to entry: Compare with ITU-T X.290.

3.22 syntactically invalid test behavior SynITB

test steps where the test system sends stimuli to the SUT that are syntactically invalid according to the protocol requirements

Note 1 to entry: This type of test behavior is not defined in this conformance standard, see codec requirements.

3.23 test behavior

set of test steps (test body) which are essential in order to achieve the test purpose and assign verdicts to the possible outcomes

3.24 test execution

interpretation or execution of an abstract test suite

Note 1 to entry: Conceptually, the TE can be decomposed into three interacting entities: an Executable Test Suite (ETS), a Test Framework (TFW) and an optional internal Encoding/Decoding System (EDS) entity.

Note 2 to entry: See also ETSI ES 201 873-5 V4.6.1.

3.25 test framework TFW

entity to perform all actions of test cases or functions

Note 1 to entry: The Test Framework interacts with the Test Management (TM), SUT Adaptor (SA) and Platform Adaptor (PA) entities via Test Control Interface (TCI) and Test Runtime Interface (TRI) and additionally manages the Executable Test Suite (ETS) and Encoding/Decoding System (EDS) entities. It initializes adaptors as well as ETS and EDS entities. This entity performs all the actions necessary to properly start the execution of a test case or function with parameters in the ETS entity. It queries the TM entity for module parameter values required by the ETS and sends logging information to it. It also collects and resolves associated verdicts returned by the ETS entity.

Note 2 to entry: See also ETSI ES 201 873-5 V4.6.1.

Note 3 to entry: In this document, the Test Framework TTCN-3 Runtime System (T3RTS) is used to explain a Test Framework functionality.

3.26

test purpose

prose description of a well-defined objective of testing, focusing on a single conformance requirement or a set of related conformance requirements as specified in the appropriate OSI specification

EXAMPLE Verifying the support of a specific value of a specific parameter

Note 1 to entry: Compare with ITU-T X.290.

3.27

test system

real system combining the test framework, abstract test suite, test execution and adapters as well as codecs

Note 1 to entry: Typically also containing a common runtime environment based on an operating system.

3.28

test control interface

TCI

four interfaces that define the interaction of the TTCN-3 Executable with the test management, the coding and decoding, the test component handling and the logging in a test system

Note 1 to entry: Compare with ETSI ES 201 873-6 V4.6.1.

3.29

test runtime interface

TRI

two interfaces that define the interaction of the TTCN-3 Executable between the SUT and the Platform Adaptor (PA) and the System Adaptor (SA) in a test system

Note 1 to entry: Compare with ETSI ES 201 873-5 V4.6.1.

3.30

test system interface

TSI

test component that provides a mapping of the ports available in the (abstract) TTCN-3 test system to those offered by a real test system

Note 1 to entry: Compare with ETSI ES 201 873-6 V4.6.1.

3.31

valid test behavior

VTB

test steps where the test system sends stimuli to the SUT that are valid (syntactically and semantically) according to the protocol requirements

Note 1 to entry: This type of test behavior is defined in this conformance document.

Note 2 to entry: The protocol requirements for this conformance specification are defined in ISO 15118-2.

3.32

verdict

test verdict

statement of “pass”, “fail” or “inconclusive”, as specified in an abstract test case, concerning conformance of an IUT with respect to that test case when it is executed

Note 1 to entry: Compare with ITU-T X.290.

4 Symbols and abbreviated terms

For the purpose of this document, the following abbreviations apply.

ALM	Application Layer Message
ATS	Abstract Test Suite
BEV	Battery Electric Vehicle
CA	Certificate Authority
CPL	Control Pilot Line
CRL	Certificate Revocation List
DH	Diffie Hellman
DER	Distinguished Encoding Rules
ECDSA	Elliptic Curve Digital Signature Algorithm
EDS	Encoding/Decoding System
EIM	External Identification Means
EMAID	E-Mobility Account Identifier
ETS	Executable Test Suite
EV	Electric Vehicle
EVCC	Electric Vehicle Communication Controller
EVSE	Electric Vehicle Supply Equipment
EXI	Efficient XML Interchange
HAL	Hardware Abstraction Layer
ICS	Implementation Conformance Statement
ID(s)	Identifier(s)
ITB	Invalid Test Behavior
IUT	Implementation under Test
IXIT	Implementation eXtra Information for Testing
OCSP	Online Certificate Status Protocol
OEM	Original Equipment Manufacturer