

## SLOVENSKI STANDARD oSIST prEN 300 019-2-6 V3.0.7:2023

01-oktober-2023

# Okoljski inženiring (EE) - Okoljski pogoji in preskusi okoljskih vplivov na telekomunikacijsko opremo - 2. del: Specifikacija preskusov vplivov okolja - 6. poddel: Ladijsko okolje

Environmental Engineering (EE) - Environmental conditions and environmental tests for telecommunications equipment - Part 2: Specification of environmental tests - Sub-part 6: Ship environments

# (standards.iteh.ai)

#### SIST prEN 300 019-2-6 V3.0.7:2023

https://standards.iteh.ai/catalog/standards/sist/fd9a2a85-13ce-48e5-8138-3f5b5eb0e3fc/osist-pren-300-019-2-6-v3-0-7-2023

Ta slovenski standard je istoveten z: ETSI EN 300 019-2-6 V3.0.7 (2023-07)

#### ICS:

19.040	Preskušanje v zvezi z okoljem	Environmental testing
33.050.01	Telekomunikacijska terminalska oprema na splošno	Telecommunication terminal equipment in general

oSIST prEN 300 019-2-6 V3.0.7:2023

en

oSIST prEN 300 019-2-6 V3.0.7:2023

# iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>oSIST\_prEN 300 019-2-6 V3.0.7:2023</u> https://standards.iteh.ai/catalog/standards/sist/fd9a2a85-13ce-48e5-8138-3f5b5eb0e3fc/osist-pren-300-019-2-6-v3-0-7-2023 oSIST prEN 300 019-2-6 V3.0.7:2023

# Draft ETSI EN 300 019-2-6 V3.0.7 (2023-07)



Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2: Specification of environmental tests; Sub-part 6: Ship environments

3f5b5eb0e3fc/osist-pren-300-019-2-6-v3-0-7-2023

#### oSIST prEN 300 019-2-6 V3.0.7:2023

2

#### Draft ETSI EN 300 019-2-6 V3.0.7 (2023-07)

Reference

REN/EE-017011

Keywords

environment, maritime, testing

**ETSI** 

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° w061004871

#### Important notice

The present document can be downloaded from: <u>https://www.etsi.org/standards-search</u>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at <a href="http://www.etsi.org/deliver">www.etsi.org/deliver</a>.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <u>https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx</u>

If you find errors in the present document, please send your comment to one of the following services: <u>https://portal.etsi.org/People/CommiteeSupportStaff.aspx</u>

If you find a security vulnerability in the present document, please report it through our Coordinated Vulnerability Disclosure Program: https://www.etsi.org/standards/coordinated-vulnerability-disclosure

#### Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

#### **Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023. All rights reserved.

## Contents

Intelle	ectual Property Rights	4
Forew	vord	4
Moda	l verbs terminology	5
1	Scope	6
2	References	6
2.1	Normative references	6
2.2	Informative references	6
3	Definition of terms, symbols and abbreviations	7
3.1	Terms	7
3.2	Symbols	7
3.3	Abbreviations	7
4	Environmental test specification	7
4.0	General	
4.1	Equipment setup and configuration	
4.2	Performance criteria	
4.3	Specification T 6.1: Totally weatherprotected locations	
4.4	Specification T 6.2: Partly weatherprotected locations	
4.5	Specification T 6.3: Non-weatherprotected locations	
4.6	Specification T 6.1: Totally weatherprotected locations climatic test	9
4.7	Specification T 6.2: Partly weatherprotected locations climatic test	10
4.8	Specification T 6.3: Non-weatherprotected locations climatic tests	
4.9	Specification T 6.1, T 6.2 and T 6.3: protected and partly protected installation, mechanical tests	15
Anne	x A (informative): Bibliography	18
Histor	ryoSIST.nrEN.300.019-2-6.V3.0.7:2023	19

3f5b5eb0e3fc/osist-pren-300-019-2-6-v3-0-7-2023

Draft ETSI EN 300 019-2-6 V3.0.7 (2023-07)

## Intellectual Property Rights

#### **Essential patents**

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

#### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT<sup>TM</sup>**, **PLUGTESTS<sup>TM</sup>**, **UMTS<sup>TM</sup>** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP<sup>TM</sup>** and **LTE<sup>TM</sup>** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M<sup>TM</sup>** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM**<sup>®</sup> and the GSM logo are trademarks registered and owned by the GSM Association.

### Foreword

## standards.iten.al)

This draft European Standard (EN) has been produced by ETSI Technical Committee Environmental Engineering (EE), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

The present document is part 2, sub-part 6 of a multi-part deliverable covering the Environmental conditions and environmental tests for telecommunications equipment, as identified below:

Part 1:	"Classification	of environmental	conditions";

#### Part 2: "Specification of environmental tests";

Sub-part 0:	"Introduction";
Sub-part 1:	"Storage";
Sub-part 2:	"Transportation";
Sub-part 3:	"Stationary use at weatherprotected locations";
Sub-part 4:	"Stationary use at non-weatherprotected locations";
Sub-part 5:	"Ground vehicle installations";
Sub-part 6:	"Ship environments";
Sub-part 7:	"Portable and non-stationary use";
Sub-part 8:	"Stationary use at underground locations".

Part 1 specifies different standardized environmental classes covering climatic and biological conditions, chemically and mechanically active substances and mechanical conditions during storage, transportation and in use.

Part 2 specifies the recommended test severities and test methods for the different environmental classes.

Draft ETSI EN 300 019-2-6 V3.0.7 (2023-07)

Part 2-0 [i.1] forms a general overview of part 2. The present document deals with ship environments.

Proposed national transposition dates				
Date of latest announcement of this EN (doa):	3 months after ETSI publication			
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa			
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa			

## Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the <u>ETSI Drafting Rules</u> (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>oSIST prEN 300 019-2-6 V3.0.7:2023</u> https://standards.iteh.ai/catalog/standards/sist/fd9a2a85-13ce-48e5-8138-3f5b5eb0e3fc/osist-pren-300-019-2-6-v3-0-7-2023

## 1 Scope

The present document specifies test severities and methods for the verification of the required resistibility of equipment according to the relevant environmental class.

The tests defined in the present document apply to the use of telecommunication equipment installed permanently or temporarily in ships and cover the environments and the vessels stated in ETSI EN 300 019-1-6 [1].

## 2 References

## 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <a href="https://docbox.etsi.org/Reference/">https://docbox.etsi.org/Reference/</a>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

[1]	ETSI EN 300 019-1-6: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-6: Classification of environmental conditions; Ship environments".
[2]	IEC 60068-2-1 (03-2007): "Environmental testing - Part 2-1: Tests - Test A: Cold".
[3]	IEC 60068-2-2 (07-2007): "Environmental testing - Part 2-2: Tests - Test B: Dry heat".
[4]	IEC 60068-2-78 (10-2012): "Environmental testing - Part 2-78: Tests - Test Cab: Damp heat, steady state".
[5]	IEC 60068-2-14 (01-2009): "Environmental testing - Part 2-14: Tests - Test N: Change of temperature".
[6]	<u>IEC 60068-2-30 (08-2005)</u> : "Environmental testing - Part 2-30: Tests - Test Db: Damp heat, cyclic $(12 h + 12 h cycle)$ ".
[7]	IEC 60068-2-18 (03-2017): "Environmental testing - Part 2-18: Tests - Test R and guidance: Water".
[8]	IEC 60068-2-6 (12-2007): "Environmental testing - Part 2-6: Tests - Test Fc: Vibration (sinusoidal)".
[9]	IEC 60068-2-27 (02-2008): "Environmental testing - Part 2-27: Tests - Test Ea and guidance: Shock".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI EN 300 019-2-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2: Specification of environmental tests; Sub-part 0: Introduction".
- [i.2] IEC 60068-2 (all parts): "Environmental testing Part 2: Tests".
- [i.3] ETSI EN 300 019-1-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-0: Classification of environmental conditions; Introduction".
- [i.4] IEC 60068-2-52:2017: "Environmental testing Part 2-52: Tests Test Kb: Salt mist, cyclic (sodium chloride solution)".
- [i.5] IEC 60068-2-68:1994: "Environmental testing Part 2-68: Tests Test L: Dust and sand".

## 3 Definition of terms, symbols and abbreviations

#### 3.1 Terms

For the purposes of the present document, the terms given in ETSI EN 300 019-1-0 [i.3] apply.

## 3.2 Symbolsh STANDARD PREVIEW

For the purposes of the present document, the symbols given in ETSI EN 300 019-1-0 [i.3] apply.

#### 3.3 Abbreviations SIST prEN 300 019-2-6 V3.0.7:2023

For the purposes of the present document, the abbreviations given in ETSI EN 300 019-1-0 [i.3] apply.

## 4 Environmental test specification

#### 4.0 General

The equipment shall be tested in its operational state throughout the test conditions described in the present document. The detailed descriptions of the environmental conditions shall refer to clauses 4 and 5 of ETSI EN 300 019-1-6 [1].

ETSI EN 300 019-2-0 [i.1] forms a general overview of part 2 of this multi-part deliverable.

## 4.1 Equipment setup and configuration

The equipment shall be tested in its operational state throughout the test conditions described in the present document unless otherwise stated. Input and load conditions of the equipment shall be chosen to obtain full utilization of the equipment under test. The heat dissipation shall be maximized, except for the steady state, low temperature test, where it shall be minimized.

#### Draft ETSI EN 300 019-2-6 V3.0.7 (2023-07)

## 4.2 Performance criteria

The following performance criteria shall apply in the tests defined by the present document.

#### **Performance criterion A:**

The equipment shall function according to the manufacturer specifications before, during and after the tests. No degradation of performance or loss of function is allowed below the performance level specified by the manufacturer when the equipment is used as intended. If the minimum performance level is not specified by the manufacturer, then this may be deduced from the product description and documentation and what the user may reasonably expect from the equipment if used as intended.

#### **Performance criterion B:**

The equipment shall function according to the manufacturer specifications before and after the tests. During the test it is not required to monitor the equipment functionality. No degradation of performance or loss of function is allowed below the performance level specified by the manufacturer when the equipment is used as intended. If the minimum performance level is not specified by the manufacturer, then this may be deduced from the product description and documentation and what the user may reasonably expect from the equipment if used as intended.

#### **Performance criterion C:**

The equipment shall function according to the manufacturer specifications before and after the tests. No degradation of performance or loss of function is allowed below the performance level specified by the manufacturer when the equipment is used as intended. If the minimum performance level is not specified by the manufacturer, then this may be deduced from the product description and documentation and what the user may reasonably expect from the equipment if used as intended.

During the application of the test, temporary loss of function is allowed but after the test the equipment shall restore to the normal functionality without replacement of components, manual rebooting or human intervention.

The equipment shall sustain the test without permanent structural or mechanical damage.

#### **Performance criterion D:**

SIST prEN 300 019-2-6 V3.0.7:2023

This performance criterion applies to the enclosure of the equipment. No corrosion traces (e.g. rust) or deterioration of the enclosure shall occur at the end of the test.

## 4.3 Specification T 6.1: Totally weatherprotected locations

The tests specifications T 6.1 of the present document shall apply to equipment, depending on the selected IEC mechanical class, installed in totally weatherprotected, heated and ventilated locations following warm-up on board engine-powered vessels but excluding refrigerated cargo spaces, machinery spaces and locations containing equipment dissipating considerable amounts of heat. This class does not cover Warm Damp and Warm Damp Equable climates. See tables 1 and 4.

## 4.4 Specification T 6.2: Partly weatherprotected locations

The tests specifications T 6.2 of the present document shall apply to equipment, depending on the selected IEC the mechanical class chosen, to equipment installed in any location on board engine-powered vessels - excluding refrigerated cargo spaces. The class applies in all climates with the exception of Cold climates and areas with abnormal rain intensities and hurricanes. The equipment may occasionally be subjected to heavy seas, See tables 2, 4 and 5.

## 4.5 Specification T 6.3: Non-weatherprotected locations

The tests specifications T 6.3 of the present document shall apply to equipment to equipment installed in any location on board engine-powered vessels, including refrigerated cargo spaces. This class applies in all climates including areas with abnormal rain intensities and hurricanes. The equipment may also be subjected to heavy seas, depending on the selected IEC mechanical class, see tables 3, 4 and 5.

## 4.6 Specification T 6.1: Totally weatherprotected locations climatic test

This specification in table 1 shall apply to a totally weatherprotected use in ships excluding described in ETSI EN 300 019-1-6 [1]. Warm Damp and Warm Damp Equable climates, see tables 1 and 4.

Environmental parameter			Environmental Class 6.1	Environmental test specification T6.1: Ship, totally weatherprotected locations					
Туре	Parameter	Detail parameter	Characteristic severity	Test severity	Duration	Reference	Method	Performance Criterion	Notes
	low	(°C)	+5 7	+5	16 h	IEC 60068-2-1 [2]	Ab/Ad/Ae: Cold	A	1
Air temperature	high	(°C)	+40	+40	16 h	IEC 60068-2-2 [3]	Bb/Bd/Be: Dry heat	A	2
	change	air/water (°C)	no 💆 🦉						
	surface	high (°C)	no						
		low (%)	10 <sup>10</sup>	none					3
	relative	high; (%) slow temperature change (°C)	95 +30	93 +30	96 h	IEC 60068-2-78 [4]	Cb: Damp heat steady state	A	4
Humidity		high; (%) rapid temperature change (°C)	no						
	absolute	high; (g/m <sup>3</sup> ) rapid temperature change (°C)	no ren-						
Air	speed	(m/s)	no						
	temperature	high (°C)	+30 🔶	none					3
		low (°C)	no 🔤	- <u>6</u>					
	rain	intensity (mm/min)	no 🕠 🧿						
Water		volume (m <sup>3</sup> /min)	-2-						
		pressure (kPa)	<u>б</u>						
	other sources	velocity (m/s)							
	wetness		no						
Radiation	solar	(W/m <sup>2</sup> )	no	) 2 <u>3</u>					
	heat	(W/m <sup>2</sup> )	no 占 🖯						
	sulphur	SO <sub>2</sub> (mg/m <sup>3</sup> )		none	R				5
		H <sub>2</sub> S (mg/m <sup>3</sup> )		none					5
Chemically	chlorine	sea salts	negligible		V				
active substances		HCI (mg/m <sup>3</sup> )	0,1	none	1				5
	nitrogen	NO <sub>X</sub> (mg/m <sup>3</sup> )		none					5
		NH <sub>3</sub> (mg/m <sup>3</sup> )		none					5
	hydrogen fluoride	HF (mg/m <sup>3</sup> )	0,003	none					5
	ozone	O <sub>3</sub> (mg/m <sup>3</sup> )	0,01	none					5

#### Table 1: Test specification T 6.1: Totally weatherprotected locations - climatic tests

9