

SLOVENSKI STANDARD

SIST EN 50121-1:2017

01-april-2017

Nadomešča:

SIST EN 50121-1:2015

Železniške naprave - Elektromagnetna združljivost - 1. del: Splošno

Railway applications - Electromagnetic compatibility - Part 1: General

Bahnanwendungen - Elektromagnetische Verträglichkeit - Teil 1: Allgemeines

Applications ferroviaires - Compatibilité électromagnétique - Partie 1: Généralités
iTeh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: EN 50121-1:2017

<https://standards.iteh.ai/catalog/standards/sist/efd8c276-f3d3-42de-850e-eeb0089e2beb/sist-en-50121-1-2017>

ICS:

33.100.01	Elektromagnetna združljivost na splošno	Electromagnetic compatibility in general
45.020	Železniška tehnika na splošno	Railway engineering in general

SIST EN 50121-1:2017

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 50121-1:2017

<https://standards.iteh.ai/catalog/standards/sist/efd8c276-f3d3-42de-850e-ccb0089c2bcb/sist-en-50121-1-2017>

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 50121-1

January 2017

ICS 29.280; 45.020; 33.100.01

Supersedes EN 50121-1:2015

English Version

**Railway applications - Electromagnetic compatibility - Part 1:
General**

Applications ferroviaires - Compatibilité électromagnétique -
Partie 1: Généralités

Bahnanwendungen - Elektromagnetische Verträglichkeit -
Teil 1: Allgemeines

This European Standard was approved by CENELEC on 2016-11-07. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

SIST EN 50121-1:2017

<https://standards.iteh.ai/catalog/standards/sist/efd8c276-bd3-42de-850e-ccb0089c2bcb/sist-en-50121-1-2017>



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents	Page
European foreword.....	3
Introduction.....	4
1 Scope	6
2 Normative references	6
3 Abbreviations	6
4 Performance criteria	7
5 Management of EMC	7
Annex A (informative) The railway system	8
A.1 Introduction.....	8
A.2 General coupling mechanisms	8
A.3 Principal electromagnetic phenomena for immunity.....	9
A.3.1 Conducted low frequency phenomena.....	9
A.3.2 Low frequency field phenomena.....	9
A.3.3 Conducted high frequency phenomena.....	9
A.3.4 Radiated high frequency phenomena.....	9
A.4 Principal electromagnetic phenomena for emission.....	9
A.5 Description of the different electric traction systems	9
A.6 Components of electric traction systems.....	10
A.7 Internal sources of electromagnetic noise	10
A.7.1 General.....	10
A.8 Summary of main characteristics of railway systems	12
A.9 External sources of disturbance.....	12
Bibliography.....	13

European foreword

This document (EN 50121-1:2017) has been prepared by CLC/TC 9X, "Electrical and electronic applications for railways".

The following dates are fixed:

- latest date by which this document has to be implemented at (dop) [2017-11-07]
national level by publication of an identical national standard
or by endorsement
- latest date by which the national standards conflicting with (dow) [2019-11-07]
this document have to be withdrawn

This document supersedes EN 50121-1:2015.

EN 50121-1:2017 includes the following significant technical changes with respect to EN 50121-1:2015:

— deletion of Annex ZZ.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

EN 50121, *Railway applications — Electromagnetic compatibility*, consists of the following parts:

- *Part 1: General* [the present document];
- *Part 2: Emission of the whole railway system to the outside world*;
- *Part 3-1: Rolling stock — Train and complete vehicle*;
- *Part 3-2: Rolling stock — Apparatus*;
- *Part 4: Emission and immunity of the signalling and telecommunications apparatus*;
- *Part 5: Emission and immunity of fixed power supply installations and apparatus*.

EN 50121-1:2017 (E)

Introduction

The railway system EMC set of product-specific European Standards is intended, in the main, to permit compliance with the EMC Directive, but also to provide a means of prescribing compatibility between internal parts of the railway system. It consists of five parts described at the end of this Introduction.

The set of standards provides both a framework for managing the EMC for railway systems and also specifies the limits for the electromagnetic (EM) emission of the railway system as a whole to the outside world and for the EM emission and immunity for equipment operating within the railway system. The latter is intended to be compatible with the emission limits set for the railway system as a whole and also provides for establishing confidence in equipment being Fit For Purpose in the Railway environment. There are different stationary emission limits set for trams/trolleybuses and for metro/mainline railway systems. The frequency covered by the standards is in the range from DC to 400 GHz. No measurements need to be performed at frequencies where no requirement is specified. The limits for EMC phenomena are set so that the railway system as a whole satisfies the Directive on electromagnetic compatibility with the outside world, and so that EMC is achieved between the various parts of the railway system. Any specific problems in complying with the limits are intended to be addressed by the procedures given in the EMC Directive. Throughout the set of standards, the immunity levels are chosen to ensure a reasonable level of EMC with other apparatus within the local railway environment and with emissions which enter the railway system from the outside world. Limits are also placed on EM emission by railway systems into the outside world.

The compatibility between railway system emissions and their external environment is based upon emission limits from the railway systems being set by considering the results from measurements at the time that the EMC Directive became enforceable. Given that the general compatibility between railway systems and their environment was satisfactory at the time these measurements were made and subsequent experience of applying the limits has confirmed their acceptability, compliance with this Standard has been judged to give satisfactory compatibility. The immunity and emission levels do not of themselves guarantee that the railway system will have satisfactory compliance with its neighbours. In exceptional circumstances, for instance near a "special location" which has unusually high levels of EM interference, the railway system may require additional measures to be taken to ensure proper compatibility. Particular care should be taken when in proximity to equipment not covered by the EMC Directive such as radio transmission equipment, military or medical installations. Attention is particularly drawn to any magnetic imaging equipment in hospitals that may be near to urban transport. In all these cases, compatibility should be achieved with consultation and co-operation between the interested parties.

The immunity and emission levels themselves do not guarantee that integration of the apparatus within the railway system will necessarily be satisfactory. The standard cannot cover all the possible configurations of apparatus, but the test levels are sufficient to achieve satisfactory EMC in the majority of cases. In exceptional circumstances, for instance near a "special location" which has unusually high levels of EM interference, the system may require additional measures to be taken to ensure proper operation. The resolution of this is a matter for discussion between the equipment supplier and the project manager, infrastructure manager or equivalent.

The railway apparatus is assembled into large systems and installations, such as trains and signalling control centres. Details are given in Annex A. It is not, therefore, possible to establish immunity tests and limits for these large assemblies. The immunity levels for the apparatus will normally ensure reliable operation, but it is important to prepare an EMC management plan to deal with complex situations or to deal with specific circumstances; for example, the passage of the railway line close to a high power radio-transmitter which produces abnormally high field strengths. Special conditions may have to be applied for railway equipment which has to work near such a transmitter and these will be accepted as National Conditions for the specification.

The series of standards EN 50121, *Railway applications — Electromagnetic compatibility*, contains the following parts:

- **Part 1: General:** This part gives a description of the electromagnetic behaviour of a railway system; it specifies the performance criteria for the whole set. A management process to achieve EMC at the interface between the railway infrastructure and trains is referenced.
- **Part 2: Emission of the whole railway system to the outside world:** This part sets the emission limits from the railway system to the outside world at radio frequencies. It defines the applied test methods and gives information on typical field strength values at traction and radio frequency (cartography).
- **Part 3-1: Rolling stock — Train and complete vehicle:** This part specifies the emission and immunity requirements for all types of rolling stock. It covers traction rolling stock and trainsets, as well as independent hauled rolling stock. The scope of this part of the series ends at the interface of the rolling stock with its respective energy inputs and outputs.
- **Part 3-2: Rolling stock — Apparatus:** This part applies to emission and immunity aspects of EMC for electrical and electronic apparatus intended for use on railway rolling stock. It is also used as a means of dealing with the impracticality of immunity testing a complete vehicle.
- **Part 4: Emission and immunity of the signalling and telecommunications apparatus:** This part specifies limits for electromagnetic emission and immunity for signalling and telecommunications apparatus installed within a Railway system. The EMC plan needs to state, if this part is also applicable for railway operational equipment mounted trackside or at platforms.
- **Part 5: Emission and immunity of fixed power supply installations and apparatus:** This part applies to emission and immunity aspects of EMC for electrical and electronic apparatus and components intended for use in railway fixed installations associated with power supply.

EN 50121-1 and EN 50121-2 are product family standards which take precedence over generic standards.

EN 50121-3-1, EN 50121-3-2, EN 50121-4, and EN 50121-5 are product standards.

EN 50121-1:2017 (E)**1 Scope**

This European standard outlines the structure and the content of the whole set.

It specifies the performance criteria applicable to the whole standards series.

Clause 5 provides information about the EMC management.

This part alone is not sufficient to give presumption of conformity to the essential requirements of the EMC-Directive and is intended to be used in conjunction with other parts of this standard.

Annex A describes the characteristics of the railway system which affect electromagnetic compatibility (EMC) behaviour.

Phenomena excluded from the set are Nuclear EM pulse, abnormal operating conditions (e.g. fault conditions) and the induction effects of direct lightning strike.

Emission limits at the railway system boundary do not apply to intentional transmitters within the railway system boundaries.

Safety considerations are not covered by this set of standards.

The biological effects of non-ionizing radiation as well as apparatus for medical assistance, such as pacemakers, are not considered here.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50121 (all parts), *Railway applications — Electromagnetic compatibility*

EN 61000 (all parts), *Electromagnetic compatibility (EMC) (IEC 61000 series)*

3 Abbreviations

AC	alternating current
DC	direct current
E	electric (field)
EM	electromagnetic
EMC	electromagnetic compatibility
GTO	gate turnoff (transistor)
H	magnetic (field)
IGBT	insulated gate bipolar transistor
MVA	megavoltampere
RF	radio frequency

For the purpose of this document, definitions related to EMC and to relevant phenomena may be found in IEC 60050-161.

Other parts of this European Standard may contain specific definitions.

4 Performance criteria

NOTE This clause is based on EN 61000-6-2.

The variety and the diversity of the apparatus within the scope of this set of standards makes it difficult to define precise criteria for the evaluation of the immunity test results.

A functional description and a definition of performance criteria, during or as a consequence of the EMC testing, shall be provided by the manufacturer and noted in the test report, based on the following criteria:

- **Performance criterion A:** The apparatus shall continue to operate as intended during and after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, either of these may be derived from the product description and documentation, and from what the user may reasonably expect from the apparatus if used as intended.
- **Performance criterion B:** The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed. No change of actual operating state or stored data are allowed. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, either of these may be derived from the product description and documentation, and from what the user may reasonably expect from the apparatus if used as intended.
- **Performance criterion C:** Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls.

5 Management of EMC

The railway system is a complex installation with moving sources of electromagnetic energy and the application of the EMC standards in the EN 50121 series is not a guarantee of satisfactory performance. There may be cases where the apparatus has to be positioned in restricted spaces or added to an existing assembly, with the possible creation of environments of unusual severity. All cases shall be considered with respect to a formal plan for the management of EMC. This plan should be established at as early a stage of the project as is possible.

For any new subsystem introduced within the railway systems boundary, potential sources and victims as well the coupling mechanisms between these sources and victims shall be considered.

The EMC plan shall make reference to the basic EMC phenomena described in the EN 61000 series as applicable.