



Designation: ~~D 4943–95~~ Designation: D4943 – 08

Standard Test Method for Shrinkage Factors of Soils by the Wax Method¹

This standard is issued under the fixed designation D 4943; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

INTRODUCTION

Given the concern that mercury is a hazardous substance, this test method is offered as an alternative to Test Method D 427~~D 427~~, which is used to determine the shrinkage limit and other shrinkage factors of soils using mercury (see Caution statement in Test Method D 427~~D 427~~). Since this test method has been performed by only a few organizations to date, others are encouraged to perform both test methods and to report their findings to Subcommittee D18.03. (See Appendix X1 for a rationale of this test method.)

This standard is issued under the fixed designation D4943; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This test method covers the procedure for determining the shrinkage limit of soils.

1.2 The data obtained using this test method may also be used to calculate shrinkage ratio, volumetric shrinkage, and linear shrinkage.

1.3 This test method is applicable only for cohesive soils.

1.4 Since this test method is performed only on that portion of a soil which passes the No. 40 (425- μ m) sieve, the relative consistency of this portion of the soil to the properties of the sample as a whole must be considered when using these procedures to evaluate the properties of a soil.

1.5 The shrinkage limit along with the liquid limit and plastic limit of soils are often collectively referred to as the Atterberg limits in recognition of their formation by Swedish soil scientist, A. Atterberg. These limits distinguish the boundaries of the several consistency states of cohesive soils.

1.6 The values stated in SI units are to be regarded as the standard. The values given in parentheses are for information only.

1.7 <https://standards.iteh.ai/catalog/standards/sist/7313381-1bd7-4c0e-8fd-edebcd9a1e0/astm-d4943-08>

1.6 All recorded and calculated values shall conform to the guide for significant digits and rounding established in Practice D6026.

1.6.1 The procedures used to specify how data are collected/recorded and calculated in this standard are regarded as the industry standard. In addition, they are representative of the significant digits that should generally be retained. The procedures used do not consider material variation, purpose for obtaining the data, special purpose studies, or any considerations for the user's objectives; and it is common practice to increase or reduce significant digits of reported data to be commensurate with these considerations. It is beyond the scope of this standard to consider significant digits used in analysis methods for engineering design.

1.7 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.8 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use. For specific safety hazards, see Section 7, Note 1, and Note X1.1, and Note 4.

2. Referenced Documents

2.1 *ASTM Standards*:²

¹ This test method is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.03 on Texture, Plasticity and Density Characteristics of Soils.

Current edition approved Sept. 10, 1995. Published November 1995. Originally published as D 4943–89. Last previous edition D 4943–89.

Current edition approved June 1, 2008. Published July 2008. Originally approved in 1989. Last previous edition approved in 2002 as D4943 – 02. DOI: 10.1520/D4943-08.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* Volume information, refer to the standard's Document Summary page on the ASTM website.

*A Summary of Changes section appears at the end of this standard.

- C670 Practice for Preparing Precision and Bias Statements for Test Methods for Construction Materials
- C702 Practice for Reducing Samples of Aggregate to Testing Size
- D75 Practice for Sampling Aggregates
- D420 ~~Guide to Site Characterization for Engineering, Design, and Construction Purposes~~
- ~~D427 Test Method for Shrinkage Factors of Soil by the Mercury Method~~⁴ Guide to Site Characterization for Engineering Design and Construction Purposes
- D653 Terminology Relating to Soil, Rock, and Contained Fluids
- ~~D854 Test Method for Specific Gravity of Soils~~⁴
- 854 Test Methods for Specific Gravity of Soil Solids by Water Pycnometer
- ~~D2726 Test Method for Bulk Specific Gravity and Density of Compacted Bituminous Mixtures Using Saturated Surface-Dry Specimens~~³ 3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction
- D4318 Test Methods for Liquid Limit, Plastic Limit, and Plasticity Index of Soils
- ~~D4753 Specification for Evaluating, Selecting, and Specifying Balances and Scales for Use in Soil, Rock, and Related Construction Materials~~ Guide for Evaluating, Selecting, and Specifying Balances and Standard Masses for Use in Soil, Rock, and Construction Materials Testing
- D6026 Practice for Using Significant Digits in Geotechnical Data
- ~~E1 Specification for ASTM Thermometers~~ 2251 Specification for Liquid-in-Glass ASTM Thermometers with Low-Hazard Precision Liquids
- E11 ~~Specification for Wire-Cloth Sieves for Testing Purposes~~ Specification for Woven Wire Test Sieve Cloth and Test Sieves

3. Terminology

3.1 *Definitions*—All definitions are in accordance with Terminology ~~D-653~~D653.

4. Summary of Test Method

~~4.1 The moisture content of a pat of wet soil is determined. Then the moisture content loss to dry the soil to a constant volume is determined and subtracted from the initial moisture content to calculate the shrinkage limit. The volume of the dry soil pat is determined from its mass in air and its indicated mass when submerged in water. A coating of wax is used to prevent water absorption by the dry soil pat.~~

4.1 A sample of fine-grained soil is thoroughly remolded with water to form a paste that is at approximately the liquid limit consistency. This paste is used to fill a small dish to form a soil pat. The initial moisture content of the wet soil pat is determined. The soil pat is slowly dried to constant mass. The volume of the dry soil is determined using a water submersion technique. A coating of wax is used to prevent water absorption by the dry soil pat. Then the moisture-content loss to dry the soil to a constant volume is determined and subtracted from the initial moisture content to calculate the shrinkage limit. The measurements are used to compute the soil constants.

5. Significance and Use

~~5.1 The term shrinkage limit, expressed as a moisture content in percent, represents the amount of water required just to fill all of the voids of a given cohesive soil at its minimum void ratio obtained by oven drying. The shrinkage limit can be used to evaluate the shrinkage potential, crack development potential, and swell potential of earthwork involving cohesive soils.~~

5.1 The term shrinkage limit, expressed as a moisture content in percent to the nearest whole number, represents the amount of water required just to fill all of the voids of a given cohesive soil at its minimum void ratio obtained by oven drying. The shrinkage limit can be used to evaluate the shrinkage potential, crack development potential, and swell potential of earthwork involving cohesive soils.

NOTE 1—The quality of the result produced by this standard is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice D3740 are generally considered capable of competent and objective testing/sampling/inspection/and the like. Users of this standard are cautioned that compliance with Practice D3740 does not in itself assure reliable results. Reliable results depend on many factors; Practice D3740 provides a means of evaluating some of those factors.

6. Apparatus

6.1 *Balance or Scale*—A balance or scale having a minimum capacity of 500 g and meeting the requirements of Specification ~~D 4753~~D 4753 for a balance of 0.01-g readability. The balance or scale shall be equipped with suitable apparatus for suspending the soil specimen in water from the center of the platform or pan.

6.2—A balance or scale having a minimum capacity of 500 g and meeting the requirements of Specification D4753 for a balance of 0.01-g readability.

6.2 *Suspension Apparatus (optional)*—A device centered on the balance suitable for suspending the soil specimen in a container of water located next to or below the balance or scale.

6.3 *Dish, Shrinkage*—A circular porcelain or monel metal milk dish having a flat bottom about 40 to 45 mm in diameter and about 12 to 15 mm deep.

6.3

6.4 *Drying Oven*—An oven, thermostatically controlled, preferably of the forced draft type, and capable of maintaining a uniform temperature of $110 \pm 5^\circ\text{C}$ throughout the drying chamber.

6.4

6.5 *Humidity Enclosure (optional)*—Small closed container large enough for shrinkage dishes and a small container of water used in dry climates to slow the initial rate of drying.

6.6 *Mortar and Pestle*—Mortar, iron or porcelain, about 125 to 150-mm diameter with rubber tipped pestle.

6.5

6.7 *Spatula*—A spatula or pill knife having a blade about 100 mm long by about 20 mm wide.

6.6

6.8 *Straightedge*—A stiff metal straightedge of convenient length. The scraping edge must be beveled if it is thicker than 3 mm.

6.7

6.9 *Sieve*—U.S.A. Standard series No. 40 (425- μm) sieve conforming to the requirements of Specification E-HE11.

6.8 *Microcrystalline Wax*—Sufficient quantity to cover the soil pat.

6.9

6.10 *Wax*—Microcrystalline or other suitable wax mixture which is not brittle when dry and does not shrink during solidification. Sufficient quantity when melted in the wax warmer to submerge the soil pat.

NOTE 2—A 50/50 mixture of paraffin wax and petroleum jelly will provide an adequate alternative.

6.11 *Sewing Thread*—Fine thread to hold the specimen to dip into the wax.

6.10

6.12 *Water, Distilled*.

6.11, *distilled*.

6.13 *Water Bath*—Of sufficient size to allow the soil pat to be submerged when determining mass in water.

6.12—*Of sufficient size (for example, 250 mL beaker) to submerge the soil pat when determining indicated mass in water.*

6.14 *Wax Warmer*—Sufficient temperature control to avoid overheating.

6.13

6.15 *Thermometer (optional)*—A thermometer, 0 to 50°C range, 0.5° gradations, conforming to the requirements of Specification E-HE 1—A thermometer, in the room temperature range, 0.5° gradations, conforming to the requirements of Specification E2251.

6.14

6.16 *Glass or Clear Plastic Plate*, used for calibrating the shrinkage dish, about 80 by 80 mm, about 5 mm thick.

6.15

6.17 *Petroleum Base Lubricant*, used in calibrating the shrinkage dish.

6.16, *used to grease the shrinkage dish.*

6.18 *Liquid Limit Device and Grooving Tool*, as described in Test Method D-4318D4318.

7. Safety Hazards

7.1 Wax melting equipment or hot wax may burn unprotected skin. Overheated wax may burst into flames; therefore, extreme care should be taken when working with hot wax. Do not use an open flame device to heat wax.

8. Sampling

8.1 Take samples from any location that satisfies testing needs. However, use Practices C-702 and D-75C702 and D75, as well as Guide D-420D420, as guides for selecting and preserving samples from various types of sampling operations.

8.2 Where sampling operations have preserved the natural stratification of a sample, keep the various strata separated and ~~tests performed~~perform tests on the particular stratum of interest with as little contamination as possible from other strata. Where a mixture of materials will be used in construction, combine the various components in such proportions that the resultant sample represents the actual construction case.

8.3 Where data from this test method are to be used for correlation with other laboratory or field test data, use the same material as used for these tests where possible.

8.4 Obtain a representative portion from the total sample sufficient to provide 150 to 200 g of material passing the No. 40 (425- μm) sieve. Mix samples thoroughly in a pan with a spatula or scoop and scoop a representative portion from the total mass by making one or more sweeps with a scoop through the mixed mass.

9. Calibration and Standardization

9.1 Calibrate each shrinkage dish used in accordance with Annex A1. Since the dishes may have different volumes, each dish must be permanently identified.

9.2 The specific gravity (or density) of the ~~microcrystalline~~wax must be known in advance to at least two significant digits. This can usually be obtained from the manufacturer. If not, determine the specific gravity in accordance with ~~Test Method D-2726D~~2726Annex A2. In either case, the specific gravity value should be checked initially and then periodically.

~~9.3 Maintain the water bath, testing apparatus, and the laboratory environment at about the same temperature while performing this procedure.~~

9.3 Maintain the water bath, testing apparatus, and the laboratory environment at about the same temperature while performing both the dish calibrations and the individual test measurement. Temperature differences as large as 5°C will not adversely impact the shrinkage limit when reported to the nearest whole number.

10. Preparation of Test Specimen

10.1 Prepare the test specimen in accordance with the directions in Test Method D 4318D4318, using either the wet or dry preparation procedure, except that the moisture content of the soil is adjusted to a consistency that would require about ten blows of the liquid limit device to close the groove along a distance of 13 mm. The amount of water required may exceed the liquid limit by as much as 10 percentage points.

11. Procedure

11.1 Select a shrinkage dish and record its identification designation and its volume (V). The volume of the shrinkage dish is used as the volume of the wet soil pat. Lightly grease the inside of the shrinkage dish.

11.2 Determine the mass of the greased shrinkage dish and record the value as the mass of the empty shrinkage dish (m).

11.3 Place, in the center of the dish, an amount of the wetted soil equal to about one-third the volume of the dish and cause the soil to flow to the edges by tapping the dish on a firm surface cushioned by several layers of blotting paper or similar material. Add an amount of soil approximately equal to the first portion, and tap the dish until the soil is thoroughly compacted and all included air has been brought to the surface. Add more soil and continue the tapping until the dish is completely filled and excess soil stands out about its edge. Strike off the excess soil with a straightedge and wipe off all soil adhering to the outside of the dish.

~~11.4 Determine the mass of the dish immediately after it is filled and record the struck measure value as the mass of dish plus wet soil.~~

~~11.5 Allow the soil pat to dry in air until the color of the pat turns from dark to light. Oven dry the pat to constant mass at $110 \pm 5^\circ\text{C}$. Determine and record the mass of dish plus dry soil.~~

~~11.5.1 Drying the soil pat in air may produce cracking of the soil due to rapid moisture losses in dry climates. If this problem is encountered, it may be necessary to dry the soil in a humidity controlled environment. In this case, it may take from 1 to 2 weeks for the color of the soil to turn from dark to light.~~

~~11.6 Determine the volume of the dry soil pat as follows:~~

~~11.6.1 Securely tie the sewing thread around the soil pat.~~

~~11.6.2 Immerse the dry pat of soil in molten wax, holding the dry pat with the sewing thread, completely coating the pat. Do not allow air bubbles to develop in the wax coating. If air bubbles are present, use a sharp object to cut out the bubble; refill the hole with wax.~~

~~11.4 Determine the mass of the dish immediately after it is filled and record the struck measure value as the mass of dish plus wet soil pat (m_w).~~

~~11.5 Allow the soil pat to dry in air until the color of the pat turns from dark to light.~~

~~11.5.1 Drying the soil pat in air may produce cracking of the soil pat due to rapid moisture loss. This is a concern in dry climates. If this problem is encountered, slow the rate of moisture loss by drying the soil pat in a humidity controlled environment.~~

NOTE 1— 3—The time required to air dry the soil pat will depend on the plasticity of the soil, the initial water content, and the relative humidity. In some cases it may take from 1 to 2 weeks for the color of the soil to turn from dark to light.

~~11.6 Oven dry the soil pat to constant mass at $110 \pm 5^\circ\text{C}$.~~

~~11.7 Determine and record the mass of dish plus dry soil pat (m_d).~~

~~11.8 Coat the dry soil pat with wax as follows:~~

~~11.8.1 Securely tie the sewing thread (about 30 cm long is adequate) around the soil pat.~~

~~11.8.2 Immerse the dry soil pat in molten wax, holding the dry pat with the sewing thread, completely coating the pat. Use a continuous motion into and immediately out of the wax. The immersion should only take a few seconds. Do not allow air bubbles to develop in the wax coating. If air bubbles are present, use a sharp object to cut out the bubble; refill the hole with wax. Repeat the dipping process two or three times to create a smooth wax coating.~~

NOTE 4—Precaution: The melted wax and associated equipment are hot and care should be exercised to avoid burns.

~~11.6.3 Remove the pat of soil from the melted wax and allow the wax coating to cool.~~

~~11.6.4 Determine the mass of the wax-coated pat of soil in air and record the value as the mass in air of the dry soil and wax.~~

~~11.6.5 Determine the mass indicated when the wax-coated pat of soil is suspended from a balance while submerged in a water bath. Make sure that there are no air bubbles clinging to the surface of the wax-coated pat or thread. Record this as the mass in water of the dry soil and wax.~~

~~11.8.3 Allow the wax coating and soil pat to cool to room temperature.~~

~~11.9 Determine the mass of the wax-coated pat of soil in air and record the value as the mass in air of the dry soil and wax (m_{sxa}).~~

~~11.10 Determine the mass of water displaced by the submerged wax-coated pat using either Section 11.10.1 or 11.10.2. Make~~