



# SLOVENSKI STANDARD

## SIST EN 300 286-6 V1.3.3:2005

01-april-2005

8 ][ ]HJbc`ca fYyYn`bhM[ f]fUb]a ]`glcf]hj Ua ]`flG8 BŁE`8 cdc`b]bUglcf]hYj .  
a YXi dcfUVb]ý\_Ug][ bU]nUWYUfl I GŁE`Dfcfc\_c`X][ ]HJbYbUfc b]ý\_Yg][ bU]nUWYU  
ýHr%fb GG%LÉ\* "XY . 5 VghfU\_hb]`dfYg\_i ýUb]`b]n`f5 HGL]b`XcXUhU]bZfa UWYU  
dfYg\_i ýUb^YXYbY]nj YXVY`dfcfc\_c`UfdL+LÉ`DfcZfa UgdYWY] UWYU  
nUca fYyY

Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS)  
supplementary service; Digital Subscriber Signaling System No-one (DSS1) protocol;  
Part 6: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information  
for Testing (PIXIT) proforma specification for the network

**STANDARD AND REVIEW**  
**(standards.iteh.ai)**

[SIST EN 300 286-6 V1.3.3:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/7d337058-287a-466e-874c-c5021837ce36/sist-en-300-286-6-v1-3-3-2005>

Ta slovenski standard je istoveten z: **EN 300 286-6 Version 1.3.3**

### ICS:

|        |   |  |
|--------|---|--|
| 33.080 | Digitalno omrežje z integriranimi storitvami (ISDN) | Integrated Services Digital Network (ISDN) |
|--------|---|--|

**SIST EN 300 286-6 V1.3.3:2005**

**en**

**iTeh STANDARD PREVIEW  
(standards.iteh.ai)**

[SIST EN 300 286-6 V1.3.3:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/7d337058-287a-466e-874c-c5021837ce36/sist-en-300-286-6-v1-3-3-2005>

# ETSI EN 300 286-6 V1.3.3 (2000-05)

European Standard (Telecommunications series)

**Integrated Services Digital Network (ISDN);  
User-to-User Signalling (UUS) supplementary service;  
Digital Subscriber Signalling System No. one (DSS1) protocol;  
Part 6: Abstract Test Suite (ATS) and partial Protocol  
Implementation eXtra Information for Testing (PIXIT)  
proforma specification for the network**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 300 286-6 V1.3.3:2005

<https://standards.iteh.ai/catalog/standards/sist-en-300-286-6-v1-3-3-2005>



---

Reference

REN/SPS-05168-6

---

KeywordsATS, DSS1, ISDN, network, PIXIT,  
supplementary service, UUS***ETSI***

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

---

[SIST EN 300 286-6 V1.3.3:2005](#)  
<https://standards.iteh.ai/catalog/standards/sist/7d337058-287a-466e-874c-c5021837ce36/sist-en-300-286-6-v1-3-3-2005>

---

***Important notice***

Individual copies of the present document can be downloaded from:  
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF).  
In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.  
Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:  
[editor@etsi.fr](mailto:editor@etsi.fr)

---

***Copyright Notification***

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.  
All rights reserved.

---

## Contents

|   |    |
|---|----|
| Intellectual Property Rights .....                                | 6  |
| Foreword .....  | 6  |
| 1 Scope .....   | 7  |
| 2 References .....  | 7  |
| 3 Definitions and abbreviations .....                             | 8  |
| 3.1 Definitions .....   | 8  |
| 3.2 Abbreviations .....   | 8  |
| 4 Abstract Test Method (ATM) .....                                | 9  |
| 4.1 Description of ATM used .....                                 | 9  |
| 4.1.1 Conventions for test components and PCOs .....              | 10 |
| 4.1.2 Conventions for variables and parameters .....              | 12 |
| 4.1.3 Special conventions for the UUS supplementary service ..... | 13 |
| 4.1.4 Conventions for point-to-multipoint configurations .....    | 13 |
| 4.2 Alternative ATM .....   | 14 |
| 5 Untestable Test Purposes (TPs) .....                            | 15 |
| 6 ATS conventions .....   | 15 |
| 6.1 Declarations part .....                                       | 16 |
| 6.1.1 Type definitions .....                                      | 16 |
| 6.1.1.1 Simple type definitions .....                             | 16 |
| 6.1.1.2 Structured type definitions .....                         | 16 |
| 6.1.1.2.1 TTCN structured type definitions .....                  | 16 |
| 6.1.1.2.2 ASN.1 structured type definitions .....                 | 16 |
| 6.1.1.3 Abstract Service Primitive (ASP) type definitions .....   | 17 |
| 6.1.1.3.1 TTCN ASP type definitions .....                         | 17 |
| 6.1.1.3.2 ASN.1 ASP type definitions .....                        | 18 |
| 6.1.1.4 PDU type definitions .....                                | 18 |
| 6.1.1.4.1 TTCN PDU type definitions .....                         | 18 |
| 6.1.1.4.2 ASN.1 PDU type definitions .....                        | 18 |
| 6.1.2 Test suite constants .....                                  | 18 |
| 6.1.3 Test suite parameters .....                                 | 18 |
| 6.1.4 Variables .....   | 18 |
| 6.1.4.1 Test suite variables .....                                | 18 |
| 6.1.4.2 Test case variables .....                                 | 18 |
| 6.1.5 Test suite operation definitions .....                      | 19 |
| 6.2 Constraints part .....  | 19 |
| 6.2.1 Structured type constraint declaration .....                | 19 |
| 6.2.2 ASN.1 type constraint declaration .....                     | 19 |
| 6.2.2.1 Specification of encoding rules .....                     | 20 |
| 6.2.3 ASP type constraint declaration .....                       | 21 |
| 6.2.3.1 ASN.1 ASP type constraint declaration .....               | 21 |
| 6.2.3.2 TTCN ASP type constraint declaration .....                | 21 |
| 6.2.4 PDU type constraint declaration .....                       | 21 |
| 6.2.4.1 ASN.1 PDU type constraint declaration .....               | 21 |
| 6.2.4.2 TTCN PDU type constraint declaration .....                | 21 |
| 6.2.5 Chaining of constraints .....                               | 22 |
| 6.2.5.1 Static chaining .....                                     | 22 |
| 6.2.5.2 Dynamic chaining .....                                    | 22 |
| 6.2.6 Derived constraints .....                                   | 22 |
| 6.2.7 Parameterized constraints .....                             | 22 |
| 6.2.8 Value assignment .....                                      | 22 |
| 6.2.8.1 Specific values .....                                     | 22 |

|         |                        |    |
|---------|------------------------|----|
| 6.2.8.2 | Matching values .....  | 23 |
| 6.3     | Dynamic part .....     | 23 |
| 6.3.1   | Test cases.....        | 23 |
| 6.3.2   | Test steps .....       | 23 |
| 6.3.2.1 | PTC1_IN.....           | 23 |
| 6.3.2.2 | PTC1_OUT.....          | 23 |
| 6.3.3   | Defaults.....          | 23 |
| 7       | ATS to TP map.....     | 24 |
| 8       | PCTR conformance.....  | 24 |
| 9       | PIXIT conformance..... | 24 |
| 10      | ATS conformance .....  | 24 |

**Annex A (normative):      Protocol Conformance Test Report (PCTR) proforma.....25**

|       |                                       |    |
|-------|---------------------------------------|----|
| A.1   | Identification summary .....          | 25 |
| A.1.1 | Protocol conformance test report..... | 25 |
| A.1.2 | IUT identification.....               | 25 |
| A.1.3 | Testing environment.....              | 25 |
| A.1.4 | Limits and reservations.....          | 26 |
| A.1.5 | Comments.....                         | 26 |
| A.2   | IUT conformance status .....          | 26 |
| A.3   | Static conformance summary .....      | 26 |
| A.4   | Dynamic conformance summary.....      | 26 |
| A.5   | Static conformance review report..... | 27 |
| A.6   | Test campaign report.....             | 28 |
| A.7   | Observations.....                     | 32 |

iTech STANDARD PREVIEW

(standards.itech.ai)

**Annex B (normative):      Partial PIXIT proforma.....33**

|       |   |    |
|-------|---|----|
| B.1   | Identification summary .....                        | 33 |
| B.2   | ATS summary .....                                   | 33 |
| B.3   | Test laboratory .....                               | 33 |
| B.4   | Client (of the test laboratory).....                | 34 |
| B.5   | System Under Test (SUT).....                        | 34 |
| B.6   | Protocol information .....                          | 35 |
| B.6.1 | Protocol identification .....                       | 35 |
| B.6.2 | Parameter values.....                               | 35 |
| B.6.3 | Codings of information elements.....                | 35 |
| B.6.4 | Configuration of IUT.....                           | 36 |
| B.6.5 | Timer values .....                                  | 36 |
| B.7   | Basic call PIXIT items .....                        | 37 |
| B.7.1 | Parameter values - information element codings..... | 37 |

|                               |   |           |
|-------------------------------|---|-----------|
| <b>Annex C (normative):</b>   | <b>Abstract Test Suite (ATS).....</b>                     | <b>38</b> |
| C.1                           | The TTCN Graphical form (TTCN.GR).....                    | 38        |
| C.2                           | The TTCN Machine Processable form (TTCN.MP) .....         | 38        |
| <b>Annex D (informative):</b> | <b>General structure of ATS.....</b>                      | <b>39</b> |
| <b>Annex E (informative):</b> | <b>Change record.....</b>                                 | <b>40</b> |
| E.1                           | Changes between EN 300 286-6 V1.2 and 1.3 .....           | 40        |
| E.2                           | Changes between ETS 300 286-6 and EN 300 286-6 V1.2 ..... | 40        |
| History .....                 | .....   | 41        |

## iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 300 286-6 V1.3.3:2005

<https://standards.iteh.ai/catalog/standards/sist/7d337058-287a-466e-874c-c5021837ce36/sist-en-300-286-6-v1-3-3-2005>

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN).

The present document is part 6 of a multi-part standard covering the Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol, as described below:

- Part 1: "Protocol specification";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";  
<https://standards.iteh.ai/catalog/standards/sist/7d337058-287a-466e-874c-5021857c50/sist-en-300-286-6-v1.3.3-2005>
- Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";
- Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".**

| <b>National transposition dates</b>  |                  |
|--|------------------|
| Date of adoption of this EN:   | 5 May 2000       |
| Date of latest announcement of this EN (doa):  | 31 August 2000   |
| Date of latest publication of new National Standard or endorsement of this EN (dop/e): | 28 February 2001 |
| Date of withdrawal of any conflicting National Standard (dow):                         | 28 February 2001 |

## 1 Scope

This sixth part of EN 300 286 specifies the Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the Network side of the T reference point or coincident S and T reference point (as defined in ITU-T Recommendation I.411 [11]) of implementations conforming to the stage three standard for the User-to-User Signalling (UUS) supplementary service for the pan-European Integrated Services Digital Network (ISDN) by means of the Digital Subscriber Signalling System No. one (DSS1) protocol, EN 300 286-1 [3].

EN 300 286-5 [5] specifies the Test Suite Structure and Test Purposes (TSS&TP) related to this ATS and partial PIXIT proforma specification. Other parts specify the TSS&TP and the ATS and partial PIXIT proforma for the User side of the T reference point or coincident S and T reference point of implementations conforming to EN 300 286-1 [3].

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

- [1] ETSI EN 300 403-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".  
SIST EN 300 286-6 V1.3.3:2005  
c5021837ce36/sist-en-300-286-6-v1-3-3-2005
- [2] ETSI EN 300 196-1: "Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [3] ETSI EN 300 286-1 (V1.2): "Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [4] ETSI EN 300 286-2 (V1.2): "Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [5] ETSI EN 300 286-5 (V1.2): "Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 5: Test Suite Structure and Test Purposes (TSS&TP) specification for the network".
- [6] ISO/IEC 9646-1: "Information technology - Open System Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [7] ISO/IEC 9646-2: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 2: Abstract test suite specification".
- [8] ISO/IEC 9646-3: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 3: The Tree and Tabular Combined Notation (TTCN)".
- [9] ISO/IEC 9646-4: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 4: Test realization".

- [10] ISO/IEC 9646-5: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 5: Requirements on test laboratories and clients for the conformance assessment process".
- [11] ITU-T Recommendation I.411 (1993): "ISDN user-network interfaces - Reference configurations".
- [12] CCITT Recommendation X.209 (1988): "Specification of basic encoding rules for Abstract Syntax Notation One (ASN.1)".
- [13] ETSI ETS 300 102 (all parts): "Integrated Services Digital Network (ISDN); User-network interface layer 3; Specifications for basic call control".

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**Abstract Test Suite (ATS):** see ISO/IEC 9646-1 [6].

**Implementation Under Test (IUT):** see ISO/IEC 9646-1 [6].

**Lower Tester (LT):** see ISO/IEC 9646-1 [6].

**Point of Control and Observation (PCO):** see ISO/IEC 9646-1 [6].

**Protocol Implementation Conformance Statement (PICS):** see ISO/IEC 9646-1 [6].

**PICS proforma:** see ISO/IEC 9646-1 [6].

**Protocol Implementation Extra Information for Testing (PIXIT):** see ISO/IEC 9646-1 [6].  
<https://standards.iteh.ai/catalog/standards/sist/7d337058-287a-466e-874c-5f1837ce36/sist-en-300-286-6-v1-3-3-2005>

**System Under Test (SUT):** see ISO/IEC 9646-1 [6].

**Upper Tester (UT):** see ISO/IEC 9646-1 [6].

### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

|       |   |
|-------|---|
| ASP   | Abstract Service Primitive                            |
| ATM   | Abstract Test Method                                  |
| ATS   | Abstract Test Suite                                   |
| BER   | Basic Encoding Rules                                  |
| CM    | Co-ordination Message                                 |
| CP    | Co-ordination Point                                   |
| DSS1  | Digital Subscriber Signalling System No. one          |
| ExTS  | Executable Test Suite                                 |
| ISDN  | Integrated Services Digital Network                   |
| IUT   | Implementation Under Test                             |
| LT    | Lower Tester  |
| MOT   | Means Of Testing                                      |
| MTC   | Main Test Component                                   |
| PCO   | Point of Control and Observation                      |
| PDU   | Protocol Data Unit                                    |
| PICS  | Protocol Implementation Conformance Statement         |
| PIXIT | Protocol Implementation eXtra Information for Testing |
| PTC   | Parallel Test Component                               |

|      |                                    |
|------|------------------------------------|
| SUT  | System Under Test                  |
| TP   | Test Purpose                       |
| TTCN | Tree and Tabular Combined Notation |
| UT   | Upper Tester                       |
| UUS  | User-to-User Signalling            |

## 4 Abstract Test Method (ATM)

### 4.1 Description of ATM used

The requirement for testing the network Implementation Under Test (IUT) is to focus on the behaviour of the network IUT at the user-network interface where a T reference point or coincident S and T reference point applies. Thus the IUT is the network DSS1 protocol entity at a particular user-network interface and is not the whole network.


It is possible to specify an Abstract Test Suite (ATS) based on a single party (remote) test method for such an IUT. However, it is considered that an ATS based on such an approach is of limited use as the only way to specify IUT generated Protocol Data Units (PDUs) is to use the "implicit send" statement. Many users of such an ATS would replace the "implicit send" statements with descriptions of the behaviour at other interfaces.

An ATS based on a multi-party test method is considered to be more useful in that it is closer to how a real test suite would be constructed. Such a test method specifies behaviour at multiple network interfaces. One very important limitation here is that tests are focused on one particular interface. Thus the test system is made up one Main Test Component (MTC) and one or more Parallel Test Components (PTCs), see figure 1.

### iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 286-6 V1.3.3:2005](https://standards.iteh.ai/catalog/standards/sist/7d337058-287a-466e-874c-c5021837ce36/sist-en-300-286-6-v1-3-3-2005)  
<https://standards.iteh.ai/catalog/standards/sist/7d337058-287a-466e-874c-c5021837ce36/sist-en-300-286-6-v1-3-3-2005>

#### 4.1.1 Conventions for test components and PCOs




**Figure 1: Multi-party test method**

In a master/slave arrangement, the MTC is considered to be the master while the PTCs are the slaves. The "slave" testers are only an explicit description of how to deal with the "other" interfaces during the testing process, i.e. "how to make the IUT send the required message".

This means, in particular, that the verdict will only be assigned from the protocol aspects observed on the interface under test (i.e. by the "master" tester), as it would be observed by a terminal connected to this interface. A failure in the correlation between the protocol at the different interfaces to which the different testers are connected, i.e. in the mechanism of the functional service itself, will not cause a FAIL verdict. For instance, if the IUT fails to send a message on the tested interface after another interface has received the proper stimulus, the verdict will be INCONCLUSIVE.

The MTC MTCA has two functions in this configuration. Firstly, it has the MTC function of controlling the one or more PTCs. Thus it is responsible for starting the PTCs and afterwards co-ordinates activities by exchanging Co-ordination Messages (CMs) with the PTCs. Secondly it is responsible for the behaviour of the Lower Tester (LT) at Point of Control and Observation (PCO) L0.

A combination of the remote and multi-party test methods is applied. As can be seen from figure 1, several PCOs are used. All PCOs reside at the service access points between layers 2 and 3.



**Figure 2: Combination of the remote and multi-party test methods**

The MTC PCO is named "L0" ("L" for Lower). The L0 PCO is used to control and observe the behaviour of the IUT and test case verdicts are assigned depending on the behaviour observed at this PCO. The PTCs PTC1, PTC2 etc. use PCOs L1, L2, etc. These PCOs are used to control and, in a limited way, observe the behaviour of the network equipment at interfaces other than the one under test. No verdicts are assigned at these PCOs.

As stated in a previous paragraph, the non-receipt of network generated messages at L0, which are stimulated by events at the L1, L2, etc., will result in INCONCLUSIVE rather than FAIL verdicts being assigned.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 286-6 V1.3.3:2005](#)

<https://standards.iteh.ai/catalog/standards/sist/7d337058-287a-466e-874c-c5021837ce36/sist-en-300-286-6-v1-3-3-2005>