



SLOVENSKI STANDARD

SIST EN 300 207-1 V2.0.1:2003

01-december-2003

8 [[]HJbc`ca fYy`Y`n`]bHY[f]fUb]a]`g]c]f]h] Ua]`f]G8 BŁĚ`8 cdc`b]`bY`g]c]f]h] Y.
]nga Yf]Hj `Ě`Dfclt_c`X]]]HJbY`bUfc b]ý_Y`g]] bU]nUWY`Y`ýH`r`%fB GG`ŁĚ`%`XY.
GdYWZ_ UWY`Udfclt_c`U

Integrated Services Digital Network (ISDN); Diversion supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification

iTeh STANDARD PREVIEW (standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-cc1502c27fa2/sist-en-300-207-1-v2-0-1-2003>

Ta slovenski standard je istoveten z: **EN 300 207-1 Version 2.0.1**

ICS:

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
--------	-----------------------------------------------------	--------------------------------------------

SIST EN 300 207-1 V2.0.1:2003

en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 207-1 V2.0.1:2003

<https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-ce1502e27fa2/sist-en-300-207-1-v2-0-1-2003>

ETSI EN 300 207-1 V2.0.1 (2000-04)

European Standard (Telecommunications series)

**Integrated Services Digital Network (ISDN);
Diversion supplementary services;
Digital Subscriber Signalling System No. one (DSS1) protocol;
Part 1: Protocol specification**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 300 207-1 V2.0.1:2003](https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-ce1502e27fa2/sist-en-300-207-1-v2-0-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-ce1502e27fa2/sist-en-300-207-1-v2-0-1-2003>



Reference

REN/SPAN-05170-1

Keywords

ISDN, DSS1, supplementary service, CF, SCF, SCFB, SCFNR, SCFU, DDI, protocol

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C

Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr

Individual copies of this ETSI deliverable
can be downloaded from<http://www.etsi.org>If you find errors in the present document, send your
comment to: editor@etsi.fr

Important notice

This ETSI deliverable may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of this document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword	5
1 Scope	7
2 References	8
3 Definitions	9
4 Abbreviations	11
5 Description	12
6 Operational requirements	13
6.1 Provision and withdrawal	13
6.2 Requirements on the calling user's network side	15
6.3 Requirements on the served user's network side	15
6.4 Requirements on the diverted-to user's network side	15
7 Coding requirements	16
7.1 Coding of the Facility information element components	16
7.2 Coding of the information elements	22
7.2.1 Coding of the Notification indicator information element	22
7.2.2 Coding of the Redirecting number information element	23
7.2.3 Coding of the Redirection number information element	23
8 State definitions	24
9 Signalling procedures at the coincident S and T reference point	25
9.1 Activation, deactivation and interrogation	25
9.1.1 Activation	25
9.1.1.1 Normal operation for diversion services other than selective call forwarding service	25
9.1.1.2 Exceptional procedures for diversion services other than selective call forwarding services	27
9.1.1.3 Normal operation for the selective call forwarding services	28
9.1.1.4 Exceptional procedures for the selective call forwarding services	30
9.1.2 Deactivation	31
9.1.2.1 Normal operation for diversion services other than selective call forwarding services	31
9.1.2.2 Exceptional procedures for diversion services other than selective call forwarding services	32
9.1.2.3 Normal operation for the selective call forwarding services	33
9.1.2.4 Exceptional procedures for the selective call forwarding services	34
9.1.3 Interrogation of the served user numbers	35
9.1.3.1 Normal procedures	35
9.1.3.2 Exceptional procedures	35
9.1.4 Interrogation of a single or multiple instances of the supplementary service	36
9.1.4.1 Normal operation for diversion services other than the selective call forwarding services	36
9.1.4.2 Exceptional procedures for diversion services other than the selective call forwarding services	37
9.1.4.3 Normal operations for selective call forwarding services	38
9.1.4.4 Exceptional procedures for the selective call forwarding services	38
9.1.5 Procedures for interrogation of a specific screening list	39
9.1.5.1 Normal procedures	39
9.1.5.2 Exceptional procedures	40
9.2 Invocation and operation	40
9.2.1 Collection and analysis of diversion information at the calling network	40
9.2.1.1 Normal operation	40
9.2.1.2 Exceptional procedures	41
9.2.2 Notification of diversion to the calling user	41
9.2.2.1 Normal operation	41
9.2.2.2 Exceptional procedures	41
9.2.3 Identification of the diverted-to user to the calling user	42

9.2.3.1	Normal operation	42
9.2.3.2	Exceptional procedures	42
9.2.4	Operation at the served user.....	43
9.2.4.1	Procedures for the CFU supplementary service	43
9.2.4.1.1	Normal operation.....	43
9.2.4.1.2	Exceptional procedures	44
9.2.4.2	Network Determined User Busy (NDUB) procedures for the CFB supplementary service	44
9.2.4.2.1	Normal operation.....	44
9.2.4.2.2	Exceptional procedures	45
9.2.4.3	User Determined User Busy (UDUB) procedures for the CFB supplementary service	45
9.2.4.3.1	Normal operation.....	45
9.2.4.3.2	Exceptional procedures	46
9.2.4.4	Procedures for the CFNR supplementary service.....	46
9.2.4.4.1	Normal operation.....	46
9.2.4.4.2	Exceptional procedures	47
9.2.4.5	Procedures for the CD supplementary service.....	47
9.2.4.5.1	Normal operation.....	47
9.2.4.5.2	Exceptional procedures	49
9.2.4.6	Procedures for the SCF supplementary service.....	49
9.2.5	Operation at the diverted-to user.....	50
9.2.5.1	Normal operation	50
9.2.5.2	Exceptional procedures	51
9.3	Reminder notification to the served user	51
9.3.1	Normal operation.....	51
9.3.2	Exceptional procedures.....	51
10	Procedures for interworking with private ISDNs.....	52
10.1	Procedures where a call from the public ISDN is diverted within or beyond the private ISDN.....	52
10.1.1	Normal operation.....	52
10.1.2	Exceptional procedures.....	52
10.2	Presentation of a diverted call from a public ISDN to the private ISDN.....	53
10.2.1	Normal operation.....	53
10.2.2	Exceptional procedures.....	53
10.3	Procedures where a call from the private ISDN is diverted within or beyond the public ISDN.....	53
10.4	Presentation of a diverted call from a private ISDN to the public ISDN.....	54
10.4.1	Normal operation.....	54
10.4.2	Exceptional procedures.....	54
10.5	Procedures where a call from the public ISDN is diverted within or beyond the private ISDN and partial rerouting takes place in the public ISDN.....	55
10.5.1	Normal operation.....	55
10.5.2	Exceptional procedures.....	57
10.6	Procedures where a call from the public ISDN to the private ISDN is diverted by the public ISDN when Diversion service enhancements based on DDI ranges do not apply.....	58
10.7	Procedures where a call from the public ISDN to the private ISDN is diverted by the public ISDN when Diversion service enhancements based on DDI ranges apply.....	58
11	Interactions with other networks.....	59
12	Interaction with other supplementary services.....	59
13	Parameter values (timers).....	59
14	Dynamic description (SDL diagrams).....	60
Annex A (informative): Change history		61
A.1	Changes from ETS 300 207-1 (1994) to EN 300 207-1 (1998).....	61
A.2	Changes from EN 300 207-1 (1998).....	61
History		62

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN).

The present document is part 1 of a multi-part EN covering the Digital Subscriber Signalling System No. one (DSS1) protocol specification for the Integrated Services Digital Network (ISDN) diversion supplementary services, as described below:

Part 1: "Protocol specification";

Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";

Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";

Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";

Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";

Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".

In accordance with CCITT Recommendation I.130 [4], the following three level structure is used to describe the supplementary telecommunication services as provided by European public telecommunications operators under the pan-European ISDN:

- stage one: is an overall service description, from the user's standpoint;
- stage two: identifies the functional capabilities and information flows needed to support the service described in stage one; and
- stage three: defines the signalling system protocols and switching functions needed to implement the service described in stage one.

The present document details the stage three aspects (signalling system protocols and switching functions) needed to support the diversion supplementary services. The stage one aspects are detailed in ETS 300 199 [14] (1994) [14] ETS 300 200 [15] (1994) [15], ETS 300 201 [16] (1994) [16], ETS 300 202 [17] (1994) [17] and EN 301 133 [18]. The stage two aspects are detailed in ETS 300 203 [22] (1994) [22], ETS 300 204 [23] (1994) [23], ETS 300 205 [24] (1994) [24] and ETS 300 206 [25] (1994) [25].

Changes from the previous version of the present document are shown in annex A.

National transposition dates	
Date of adoption of this EN:	21 April 2000
Date of latest announcement of this EN (doa):	31 July 2000
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 January 2001
Date of withdrawal of any conflicting National Standard (dow):	31 January 2001

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 207-1 V2.0.1:2003](https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-ce1502e27fa2/sist-en-300-207-1-v2-0-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-ce1502e27fa2/sist-en-300-207-1-v2-0-1-2003>

1 Scope

This first part of EN 300 207 specifies the stage three of the diversion supplementary services for the pan-European Integrated Services Digital Network (ISDN) as provided by European public telecommunications operators at the T reference point or coincident S and T reference point (as defined in ITU-T Recommendation I.411 [9]) by means of the Digital Subscriber Signalling System No. one (DSS1). Stage three identifies the protocol procedures and switching functions needed to support a telecommunication service (see CCITT Recommendation I.130 [4]).

In addition, the present document specifies the protocol requirements at the T reference point where the service is provided to the user via an intermediate private ISDN.

The present document does not specify the additional protocol requirements where the service is provided to the user via a telecommunications network that is not an ISDN.

The diversion supplementary services comprise the following services:

- Call Forwarding Unconditional (CFU) supplementary service;
- Call Forwarding Busy (CFB) supplementary service;
- Call Forwarding No Reply (CFNR) supplementary service;
- Selective Call Forwarding Unconditional (SCFU) supplementary service;
- Selective Call Forwarding Busy (SCFB) supplementary service;
- Selective Call Forwarding No Reply (SCFNR) supplementary service;
- Call Deflection (CD) supplementary service.

The CFU supplementary service enables a served user to have the network redirect to another user calls which are addressed to the served user's ISDN number. The CFU supplementary service may operate on all calls, or just those associated with specified basic services. The served user's ability to originate calls is unaffected by the CFU supplementary service. After the CFU supplementary service has been activated, calls are forwarded independent of the status of the served user.

The CFB supplementary service enables a served user to have the network redirect to another user calls which are addressed to the served user's ISDN number and meet busy. The CFB supplementary service may operate on all calls, or just those associated with specified basic services. The served user's ability to originate calls is unaffected by the CFB supplementary service.

The CFNR supplementary service enables a served user to have the network redirect to another user calls which are addressed to the served user's ISDN number, and for which the connection is not established within a defined period of time. The CFNR supplementary service may operate on all calls, or just those associated with specified basic services. The served user's ability to originate calls is unaffected by the CFNR supplementary service.

The SCF supplementary service enables a served user to specify the forwarding of their incoming calls to a selected destination subject to certain conditions or circumstances e.g. the calling line identity of the calling user. The user is also allowed to interrogate the screening list.

The CD supplementary service enables the served user to respond to an incoming call by requesting redirection of that call to another user. The CD supplementary service can only be invoked before the connection is established by the served user, i.e. in response to the offered call, or during the period that the served user is being informed of the call. The served user's ability to originate calls is unaffected by the CD supplementary service. The present document also describes interactions for Service enhancements based on DDI ranges for Diversion services detailed in ES 201 481 [20]. The diversion supplementary services are applicable to all circuit-switched telecommunication services.

Further parts of EN 300 207 specify the method of testing required to identify conformance to the present document.

The present document is applicable to equipment supporting at least one of the diversion supplementary services, to be attached at either side of a T reference point or coincident S and T reference point when used as an access to the public ISDN.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] CCITT Recommendation X.208 (1988): "Specification of Abstract Syntax Notation One (ASN.1)".
- [2] CCITT Recommendation X.219 (1988): "Remote operations: Model, notation and service definitions".
- [3] CCITT Recommendation Z.100 (1988): "Specification and Description Language (SDL)".
- [4] CCITT Recommendation I.130 (1988): "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [5] ITU-T Recommendation E.164 (1997): "The international public telecommunication numbering plan"
<https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-ce1592e37f62/sist-en-300-207-1-v2-0-1-2003>
- [6] ITU-T Recommendation I.112 (1993): "Vocabulary of terms for ISDNs".
- [7] ITU-T Recommendation I.210 (1993): "Principles of telecommunication services supported by an ISDN and the means to describe them".
- [8] ITU-T Recommendation I.221 (1993): "Common specific characteristics of services".
- [9] ITU-T Recommendation I.411 (1993): "ISDN user-network interfaces; Reference configurations".
- [10] ENV 41007-1 (1991): "Definition of terms in private telecommunication networks; Part 1: Definition of general terms".
- [11] ETSI EN 300 403-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".
- [12] ETSI EN 300 195-1: "Integrated Services Digital Network (ISDN); Supplementary service interactions; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [13] ETSI EN 300 196-1: "Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [14] ETSI ETS 300 199 (1994): "Integrated Services Digital Network (ISDN); Call Forwarding Busy (CFB) supplementary service; Service description".
- [15] ETSI ETS 300 200 (1994): "Integrated Services Digital Network (ISDN); Call Forwarding Unconditional (CFU) supplementary service; Service description".

- [16] ETSI ETS 300 201 (1994): "Integrated Services Digital Network (ISDN); Call Forwarding No Reply (CFNR) supplementary service; Service description".
- [17] ETSI ETS 300 202 (1994): "Integrated Services Digital Network (ISDN); Call Deflection (CD) supplementary service; Service description".
- [18] ETSI EN 301 133 (V1.1): "Integrated Services Digital Network (ISDN); Selective Call Forwarding (SCF) supplementary services (unconditional, busy and no reply); Service description".
- [19] ETSI EN 300 286-1: "Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [20] ETSI ES 201 481: "Integrated Services Digital Network (ISDN); ISDN service enhancements based on DDI ranges for call diversion supplementary services".
- [21] Void.
- [22] ETSI ETS 300 203: "Integrated Services Digital Network (ISDN); Call Forwarding Busy (CFB) supplementary service; Functional capabilities and information flows".
- [23] ETSI ETS 300 204: "Integrated Services Digital Network (ISDN); Call Forwarding Unconditional (CFU) supplementary service; Functional capabilities and information flows".
- [24] ETSI ETS 300 205: "Integrated Services Digital Network (ISDN); Call Forwarding No Reply (CFNR) supplementary service; Functional capabilities and information flows".
- [25] ETSI ETS 300 206: "Integrated Services Digital Network (ISDN); Call Deflection (CD) supplementary service; Functional capabilities and information flows".
- [26] ETSI ETS 300 062: "Integrated Services Digital Network (ISDN); Direct Dialling In (DDI) supplementary service; Service Description".

<https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-ce1502e271a2/sist-en-300-207-1-v2-0-1-2003>

3 Definitions

For the purposes of the present document, the following terms and definitions apply:

address: address is an ISDN number, with optionally an associated subaddress

alerting phase: period where the connection at the remote access is such that if it is an ISDN interface, it is in call state N7, Call Received, and if it is an analogue interface, an alerting indication is being provided

all numbers: if for the control of the call forwarding supplementary services the parameter servedUserNr is set to "allNumbers", then all the ISDN numbers are affected that the user is subscribed to and for which the call forwarding supplementary service is subscribed to, at the point in time that the request is received in the network

all services: if for the control of the call forwarding supplementary services the parameter basicService is set to "allServices" then all basic services are affected that the user is subscribed to, and for which the call forwarding supplementary service applies and is subscribed to, at the point in time that the request is received in the network

basic service: bearer service or teleservice. When used in the present document it refers only to circuit-switched basic services

bearer service: see ITU-T Recommendation I.112 [6], definition 202

call control message: message as defined in EN 300 403-1 [11], subclause 3.1, which on sending or receipt causes a change of the call state at either the network or the user. Call control messages also include the INFORMATION message and the PROGRESS message

call reference: see EN 300 196-1 [13], subclause 3.1

call state: state as defined in EN 300 403-1 [11], for either the user or the network as appropriate. A call state may exist for each call reference value (and for each additional responding Connection Endpoint Identifier (CEI) in the incoming call states)

calling network: network to which the calling user is attached

calling user: user who initiated a call that has been diverted

data link connection endpoint identifier; Connection Endpoint Identifier (CEI): see EN 300 196-1 [13], subclause 3.1

DDI number: see ETS 300 062 [26], definitions

DDI range: see ES 201 481 [20], definitions

DDI range identifier: see ES 201 481 [20], definitions

deflected-to number: ISDN number of the deflected-to user

deflected-to user: user to which the call is redirected as a result of deflection

deflecting number: ISDN number of the deflecting user

diverted-to user: refers either to the forwarded-to user or to the deflected-to user

diverted-to network: network to which the diverted-to user is attached

diverted-to number: ISDN number of the forwarded-to or the deflected-to user

diverting network: network to which the served user (diverting user) is attached

diverting number: ISDN number of the forwarding/deflecting user

diversion profile: set of data containing all the parameters pertaining to subscription and activation, involved in the decision process which leads to the diversion of an incoming call.

dummy call reference: see EN 300 196-1 [13], subclause 3.1

explicit forwarding: forward all calls from specified calling number(s)

forwarded-to address: address of the forwarded-to user

forwarded-to network: network to which the forwarded-to user is attached

forwarded-to number: ISDN number of the forwarded-to user

forwarded-to user: user to which the call is redirected as a result of forwarding

forwarding network: network to which the served user (forwarding user) is attached

forwarding number: ISDN number of the forwarding user

implicit forwarding: forward all calls except from the specified calling number(s)

Integrated Services Digital Network (ISDN): see ITU-T Recommendation I.112 [6], definition 308

invoke component: see EN 300 196-1 [13], subclause 8.2.2.1. Where reference is made to an "xxxx" invoke component, an invoke component is meant with its operation value set to the value of the operation "xxxx"

ISDN number: number conforming to the numbering plan and structure specified in ITU-T Recommendation E.164 [5]

network: DSS1 protocol entity at the network side of the user-network interface

Network Determined User Busy (NDUB): see ITU-T Recommendation I.221 [8]

private network: DSS1 protocol entity at the user-side of the user-network interface when a T reference point applies

Private Telecommunication Network eXchange (PTNX): see ENV 41007-1 [10], subclause 4.4

point-to-point terminal configuration: terminal configuration in which there is one user signalling entity

reject component: see EN 300 196-1 [13], subclause 8.2.2.4

return error component: see EN 300 196-1 [13], subclause 8.2.2.3. Where reference is made to an "xxxx" return error component, a return error component is meant which is related to an "xxxx" invoke component

return result component: see EN 300 196-1 [13], subclause 8.2.2.2. Where reference is made to an "xxxx" return result component, a return result component is meant which is related to an "xxxx" invoke component

screening list: list containing conditions for forwarding or not forwarding a call

served user: user which activates, deactivates or interrogates the CFB, CFNR, CFU, SCF, SCFB, SCFNR or SCFU supplementary services or invokes the CD supplementary service

service; telecommunication service: see ITU-T Recommendation I.112 [6], definition 201

subaddress: see ITU-T Recommendation E.164 [5], subclause 12.2

supplementary service: see ITU-T Recommendation I.210 [7], subclause 2.4

teleservice: see ITU-T Recommendation I.112 [6], definition 203

user: DSS1 protocol entity at the user side of the user-network interface when a coincident S and T reference point applies

User Determined User Busy (UDUB): is specified for the case that the network offers the call to the user and if no compatible terminal responds "positively" but one or more compatible terminal respond "user busy"

(standards.iteh.ai)

4 Abbreviations

SIST EN 300 207-1 V2.0.1:2003

<https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c->

For the purposes of the present document the following abbreviations apply:

ASN.1	Abstract Syntax Notation one
CD	Call Deflection
CEI	Connection Endpoint Identifier
CFB	Call Forwarding Busy
CFNR	Call Forwarding No Reply
CFU	Call Forwarding Unconditional
CLI	Calling Line Identity
CLIP	Calling Line Identification Presentation
CLIR	Calling Line Identification Restriction
COLR	Connected Line Identification Restriction
DDI	Direct Dialling In
DSS1	Digital Subscriber Signalling System No. one
DTN	Diverted-To Number
ISDN	Integrated Services Digital Network
LE	Local Exchange
MSN	Multiple Subscriber Number
NDUB	Network Determined User Busy
PTNX	Private Telecommunication Network eXchange
SCF	Selective Call Forwarding
SCFB	Selective Call Forwarding Busy
SCFNR	Selective Call Forwarding No Reply
SCFU	Selective Call Forwarding Unconditional
SDL	Specification and Description Language
UDUB	User Determined User Busy

5 Description

As a network provider option the diversion supplementary services can be provided on a per ISDN number basis, on a DDI Range or to the whole access. In addition, and as a network provider option, the call forwarding supplementary services (including options) may be subscribed to for each basic service to which the user(s) of the number subscribes, or collectively for all the basic services to which the user(s) subscribes.

The CD supplementary service applies to all of the basic services subscribed to by the user.

The served user may register a different forwarded-to address for each basic service subscription parameter value and call forwarding supplementary service to which he has subscribed.

An indication that a call forwarding supplementary service is activated may, as a subscription option, be given to the forwarding user who has forwarding activated, each time an outgoing call is made.

The CFNR supplementary service only applies when a SETUP message is sent by the network and at least one user responds with an ALERTING message, possibly subsequent to other valid call control messages.

The functions of the CD supplementary service are implemented in the network and they are invoked by the terminal on a call by call basis.

The SCF supplementary service is an incoming call management feature to the defined Call Forwarding supplementary services that allows the served user to define one or more screening lists. Incoming calls that satisfy the conditions identified by the screening list are forwarded to the forward-to ISDN address, which is registered on activation of the SCF supplementary service. The served user's ability to originate calls is unaffected by the SCF supplementary service.

The Calling Line Identity (CLI) is the only forwarding condition defined in the present document for use in the screening lists. As a service provider option, the served user may specify the forwarding of their incoming calls to destinations according to additional forwarding conditions, e.g.:

- time of day, day of week etc.;
- area of call origination.

[SIST EN 300 207-1 V2.0.1:2003](https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-ce1502e3762/sist-en-300-207-1-v2-0-1-2003)

[https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-](https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-ce1502e3762/sist-en-300-207-1-v2-0-1-2003)

[ce1502e3762/sist-en-300-207-1-v2-0-1-2003](https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-ce1502e3762/sist-en-300-207-1-v2-0-1-2003)

NOTE 1: The specification of these conditions is outside the scope of the present document.

The served user can have multiple instances of the activation of the SCF supplementary service i.e. more than one screening list may be in use. This enables calls to be forwarded to different destinations, according to different criteria in the screening lists.

At activation time, for each screening list, the served user specifies whether forwarding is to be done unconditionally or on busy and/or on no reply.

At registration, the status of each screening list, i.e. explicit or implicit is stated.

NOTE 2: If applicable, the priority of the screening lists may be indicated at registration.

The format of the CLIs in the screening lists (e.g. complete E.164 [5] numbers or part E.164 [5] numbers) will be as specified in stage one. All parameters specified by the served user in a screening list are independent from those specified in the other screening lists belonging to the served user.

The SCF service does not apply to the Call Deflection (CD) supplementary service.

6 Operational requirements

6.1 Provision and withdrawal

The CFU, CFB, CFNR, SCFU, SCFB, SCFNR and/or CD supplementary services shall be provided after prior arrangement with the network provider.

Each diversion supplementary service may be withdrawn separately by the network provider at the subscriber's request or for administrative reasons.

The diversion supplementary services may be offered separately with subscription options.

The subscription options for the CFU supplementary service are given in ETS 300 200 [15], subclause 6.1.

The subscription options for the CFB supplementary service are given in ETS 300 199 [14], subclause 6.1.

The subscription options for the CFNR supplementary service are given in ETS 300 201 [16], subclause 6.1.

The subscription options for the SCF supplementary service are given in EN 301 133 [18], subclause 6.1.

The subscription options for the CD supplementary service are given in ETS 300 202 [17], subclause 6.1.

The subscription options for Diversion service enhancements based on DDI ranges are given in ES 201 481 [20], subclause 6.1.

The actual items in the SCF served user's screening list shall be agreed between the served user and at the discretion of the network provider at subscription time.

Each subscription option may be provided as a network provider option. For each subscription option, only one value shall be selected. Subscription options having impact on the protocol are summarized in table 1.

[SIST EN 300 207-1 V2.0.1:2003](https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-ce1502e27fa2/sist-en-300-207-1-v2-0-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/a3df43b2-60da-4671-946c-ce1502e27fa2/sist-en-300-207-1-v2-0-1-2003>