
**Hydrometry — Selection,
establishment and operation of a
gauging station**

*Hydrométrie — Sélection, établissement et exploitation d'une station
hydrométrique*

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 18365:2013](https://standards.iteh.ai/catalog/standards/sist/4dec74a2-73c2-4c03-a859-d3c448590024/iso-18365-2013)

[https://standards.iteh.ai/catalog/standards/sist/4dec74a2-73c2-4c03-a859-
d3c448590024/iso-18365-2013](https://standards.iteh.ai/catalog/standards/sist/4dec74a2-73c2-4c03-a859-d3c448590024/iso-18365-2013)



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 18365:2013

<https://standards.iteh.ai/catalog/standards/sist/4dec74a2-73c2-4c03-a859-d3c448590024/iso-18365-2013>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms, definitions and symbols	1
4 General requirements and considerations	1
4.1 Requirements.....	1
4.2 Other constraints.....	2
5 Water level (Stage) only gauging stations	2
5.1 Preliminary survey and selection criteria.....	2
5.2 Stage measurement and recording.....	3
6 Stage-discharge gauging stations	4
6.1 General.....	4
6.2 Main elements of a stage-discharge gauging station.....	5
7 Stage-discharge gauging stations using hydraulic structures	6
7.1 General.....	6
7.2 Site selection.....	6
7.3 Types of hydraulic structures.....	6
8 Velocity-discharge gauging stations	7
8.1 Applications and types of instrument.....	7
8.2 Site selection.....	8
8.3 Calibration.....	8
8.4 Transit time (acoustic) method.....	8
8.5 Doppler.....	9
8.6 Acoustic (echo) correlation velocity meters.....	10
8.7 Electromagnetic method (Full channel width coil).....	10
9 Measurement under difficult conditions	10
9.1 Ice and frost conditions.....	10
9.2 Weed growth.....	11
9.3 Extreme sedimentation conditions.....	11
10 Operation and maintenance	11
10.1 General.....	11
10.2 Water level (Stage) only gauging stations.....	11
10.3 Stage-discharge gauging stations.....	12
10.4 Stage-discharge gauging stations using hydraulic structures.....	12
10.5 Velocity-discharge gauging stations.....	12
Annex A (informative) Applicable conditions for selection of discharge measurement method	13
Bibliography	16

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 113, *Hydrometry*, Subcommittee SC 1, Velocity area methods.

ISO 18365 cancels and replaces ISO 1100-1:1996 and ISO/TR 8363:1997, which have been merged and technically revised.

Hydrometry — Selection, establishment and operation of a gauging station

1 Scope

This International Standard gives requirements for the establishment and operation of a gauging station for the measurement of stage, or stage and discharge, of a lake, reservoir, river or canal or other artificial open channel. It also describes how a gauging station utilizing one of the measurement methods listed should be operated and maintained.

Requirements are provided for stage only measurement stations, stage–discharge stations and direct–discharge measurement stations in natural channels, as well as for stage–discharge stations with artificial structures. Additionally, some requirements are given for measurements under difficult conditions, such as under ice conditions.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 772, *Hydrometry — Vocabulary and symbols*

3 Terms, definitions and symbols

For the purposes of this document, the terms, definitions and symbols given in ISO 772 apply.

4 General requirements and considerations

4.1 Requirements

Before commencing work on establishment and operation of a gauging station, the following requirements shall be identified:

- a) range of levels required to be measured;
- b) range of flows required to be measured;
- c) customer's requirements for type of data;
- d) customer's requirements for timeliness of data;
- e) allowable uncertainty in the results;
- f) other potential users of the data;
- g) life expectancy of the station;
- h) available budget;
- i) agreements for access to land and construction permits.

4.2 Other constraints

In addition to the requirements as in 4.1, other constraints shall be identified including the following:

- a) local environmental issues;
- b) accessibility of the site under all conditions of flow;
- c) availability of power and communication links;
- d) stability of the watercourse embankments;
- e) stability of the watercourse bed;
- f) identification of any proposed hydraulic modifications planned for the future;
e.g. bridges, tunnels (including pipe crossings), harbours or piers;
- g) potential of vandalism;
- h) influence of submergence of the gauging site due to downstream impounding structures (lakes, dams, weirs);
- i) potential stream losses in karst areas;
- j) aquatic weed growth in the watercourse;
- k) ice conditions during winter in cold and arctic regions.

Knowledge of the above requirements and local constraints will ensure the provision of appropriate measurement and recording facilities as well as the adoption of an appropriate maintenance philosophy.

<https://standards.iteh.ai/catalog/standards/sist/4dec74a2-73c2-4c03-a859-193101000000/iso-18365-2013>

5 Water level (Stage) only gauging stations

5.1 Preliminary survey and selection criteria

5.1.1 General

The site selected for determination of stage shall be selected according to the purpose for which the readings are required. Accessibility of the site and the availability of an observer if the gauge is to be non-recording are important criteria as is the availability of an appropriate power supply and data communication capabilities if the gauge is to be recording.

Gauges on lakes and reservoirs are normally located near the outlet, but shall be located sufficiently far away from the zone where an increase in velocity causes a drawdown in water level. Gauges on large bodies of water shall also be located so as to reduce the effect of strong winds which may cause misleading data which may not be representative of the body of water being measured. Hydraulic conditions (preferably a sufficiently long uniform stretch of water channel with uniform bed topography) are important factors in site selection in open channels, particularly where water levels may later be used in the computation of discharge. To ensure repeatability of the readings, ideally a bed or channel control shall be present, which itself shall be stable and sensitive to changes in the level of the water. For the purpose of monitoring water levels e.g. for flood warning purposes, this may not be a strict requirement.

5.1.2 Preliminary survey

A detailed examination of a 1:50,000 or larger scale map of the area is required in the first instance. Aerial surveys, satellite imagery, or maps available in the public domain such as Google Earth can be used as a basis for selecting potential sites, which can then be evaluated more precisely by ground reconnaissance. This will include a detailed visual examination. Enquiries shall be made to determine

whether or not any plans exist for the modification of the river reach which would modify the stream bed regime and would have an impact on the proposed gauging station.

Enquiries shall also be made into any known past flow history including low water events, floods and other high water events, existence of any overflow area leading to flow by-passing the site, and very importantly, any knowledge of bed instability.

It may be appropriate to discuss and outline proposals at an early stage with the owners of the site identified to ensure they are amenable to the proposed installation.

Surveys of channel geometry and flow velocity patterns using an Acoustic Doppler Current Profiler may provide useful information.

Collection of data from hydrometric measurement stations is dominated by the use of telemetry; availability and quality of methods of data transmission shall be investigated.

5.1.3 Selection criteria

A list of potential sites shall be established with their advantages and disadvantages identified. Site selection can then be made according to the criteria identified in [Clause 4](#). The establishment of the gauge zero shall be chosen so as to avoid negative readings. Thus it shall be set well below the level of the control feature. This zero point shall be correlated with a national datum through a station benchmark and should be checked annually with respect to this benchmark. This will ensure that, should loss or damage to the reference gauge occur, it can be replaced at exactly the same level.

The benchmark itself shall be checked regularly in order to confirm that it still represents the national datum. The frequency of such checks shall be dependent on local soil dynamics.

5.2 Stage measurement and recording

ISO 18365:2013

5.2.1 General <https://standards.iteh.ai/catalog/standards/sist/4dec74a2-73c2-4c03-a859-d3c448590024/iso-18365-2013>

The reading of stage may be required as a single instantaneous measurement, as a short series of instantaneous measurements or as a continuous or practically continuous record of the fluctuations of stage. The basis of any of the above shall include the installation of a vertical staff gauge, a ramp gauge, or a wire-weight gauge.

5.2.2 Vertical staff gauge

A vertical staff gauge comprises a scale (normally 1 metre in length with graduations or scale divisions of 5 or 10 mm) marked on or securely attached to a suitable and stable vertical surface. The gauge shall be made of material with a low coefficient of expansion. Where the range of measurement required exceeds the capacity of a single vertical gauge, other gauges shall be installed on the line of a cross-section normal to the direction of flow. The scales on such a series of stepped staff gauges shall overlap by not less than 15 cm in order to safeguard continuity of readings and also to confirm their consistency with each other.

5.2.3 Ramp or inclined gauge

A ramp or inclined gauge consists of a scale marked on or securely attached to a suitable and stable inclined surface, which conforms closely to the contour of the river bank. The gauge shall be made of material with a low coefficient of expansion. Throughout its length the gauge may lie on one continuous slope or may be a compound of two or more slopes. The gauge shall lie on a line of a cross-section normal to the direction of flow.

5.2.4 Wire or tape weight gauge

A wire or tape weight gauge consists of a weight which is manually lowered until the weight touches the surface of the water. The wire or tape may be wound on a drum attached to a winding mechanism

or it may be a hand reel. The wire or tape gauge can be equipped with electrical contacts to improve measurements, when there is a large vertical distance between the measuring point and the water surface.

5.2.5 Other methods

It may be appropriate in some cases to use alternative methods for single or continuous determinations of water level. Such methods, including maximum level gauges, are described in ISO 4373.

5.2.6 Stage recording

Customer requirements shall dictate the method of recording stage. It may be that a single record of stage taken daily and read manually will suffice in which case a suitable person to do this work should be identified.

It is more common to provide a continuous record of stage utilizing water level sensors, such as floats, pressure transducers, and echo sounders, interfaced with a digital recorder (logger or telemetry) or analog recorder (chart). Details of such systems, including the use of stilling wells, can be found in ISO 4373. Modern gauging stations typically have two independent systems for stage measurement to avoid or reduce data losses.

When a recorder is used, visits by the observer should be made from time to time to ensure satisfactory performance of the sensor and recorder. It is recommended that the observer notes the time and date of such checks along with the staff gauge and recorder values. It is essential that the staff gauge itself is maintained in such a way as to be safely accessible and directly legible to the observer.

Comments on the state of the channel, river banks, presence of any obstruction, prevailing flow conditions, etc. shall also be noted.

The frequency of such visits shall be subject to country-specific requirements but it is important that a site visit shall follow a major hydraulic event to confirm continued measurement and recording of data.

d3c448590024/iso-18365-2013

6 Stage-discharge gauging stations

6.1 General

When records of water level are to be used as a basis for computation of discharge, the relation between water level and flow must be determined.

In a stable channel with an appropriate control feature which is stable and sensitive, a single relation may exist between water level and discharge. In this case, the relation can be determined by taking discharge measurements throughout the range of levels and flows required to be measured.

Several techniques are available for this purpose including, but not limited to, current meter gauging and float gauging (see ISO 748), dilution gauging (see ISO 9555-1, ISO 9555-3 and ISO 9555-4), transit time acoustic methods (see ISO 6416), Doppler velocity meters (see ISO 15769), electromagnetic current meters (see ISO/TS 15768) or acoustic Doppler current meters (see ISO/TR 24578).

The frequency of any maintenance or operational performance shall be such that the accuracy and timeliness of data provision meets the user's requirements.

6.2 Main elements of a stage-discharge gauging station

6.2.1 General

The main elements required for the purpose of determining discharge in a stream from water level records are as follows:

- a) a stage measuring device (see 5.2.1);
- b) a stage sensing and recording device (see 5.2.6);
- c) a control section or reach (see 6.2.2);
- d) a section suitable for discharge measurements (see 6.1 and 6.2.3);
- e) discharge measurements for defining a stage-discharge relation (see 6.2.4).

6.2.2 Control section or control reach

A control section or control reach of a channel is a natural or artificial section or reach whose physical characteristics can be measured and used to determine the relationship between stage and discharge.

In a control section any change in the stage downstream of the control does not affect the stage upstream of the control. Whatever the discharge in the control section, a critical stage can be determined.

It shall be stable, i.e. no change shall occur over time to its physical characteristics. Regular inspection of the control section shall be carried out to ensure that no changes have taken place which would alter the relationship between stage and discharge at this site.

More than one control section may be required for discharge measurement at one gauging station particularly when the range of levels and flows is substantial. For example, under certain flow conditions a downstream control reach may create a water level which submerges an upstream weir which had been acting as a control.

The sensitivity of a control section or reach shall be such that any significant change in discharge shall result in either a measurable change in stage (for control sections) or a measurable change in stage at one extremity of the control reach.

6.2.3 Section suitable for discharge measurements

Regardless of the method of measurement, the discharge through the discharge measuring section shall be the same as the discharge normal to the reference staff gauge, over the range of flows to be measured. Different measuring sections or different methods of measurement may be used to cover the range of flows required.

A full description of a site suitable for measurement of discharge using current meters or floats is given in ISO 748. Site requirements for dilution gauging are given in ISO 9555 Parts 1, 3, and 4. Site requirements for the application of acoustic transit time velocity measurement techniques are given in ISO 6416. Site requirements for the application of acoustic velocity meters using the Doppler and echo correlation techniques are given in ISO 15769. Site requirements for the application of electromagnetic techniques are given in ISO 9213.

6.2.4 Discharge measurements

Discharge measurements using the above techniques shall be related to a stage reading taken at the beginning and end of the discharge measurement and during the measurement if the stage is changing rapidly or inconsistently. When sufficient numbers of discharge measurements have been taken, a stage-discharge relationship can be computed (see ISO 1100-2). Subsequent to the formulation of this stage-discharge relationship, only occasional discharge measurements need be taken at flows in the normal range to confirm the robustness of the relationship unless the site is subject to shifting control

conditions. Opportunities should be taken to carry out discharge measurements in extreme events in order to extend the stage–discharge relationship.

Discharge measurements made using the velocity-area methods can be performed using rotating-element current meters, electromagnetic current meters, acoustic Doppler velocimeters, or acoustic Doppler current profilers. These can be made by wading the stream or small river with the meter mounted to a wading rod or by suspending the meter and a sounding weight from a bridge, cableway (see ISO 4375) or stationary boat. Velocity-area methods using floats are another option when the presence of floating debris or very turbulent conditions precludes the use of current meters. Acoustic Doppler current profilers deployed from powerboats, remote-control boats, or tethered rafts also can be used (see ISO/TR 24578). Tethered rafts typically are deployed from bridges or cableways. Another variation of velocity area methods is the slope-area method, which is typically used to compute flood discharge indirectly by surveying the cross-sectional properties and water-surface profile after the flood (see ISO 1070). The applicable conditions for using the different equipment and techniques are listed in Annex-A.

Where a pre-surveyed cross-section is used for the purpose of discharge measurement, then the section shall be checked following any major hydraulic events e.g. over and above a bank full flow.

6.2.5 Tracer dilution methods for measuring discharge

Dilution techniques using chemical or fluorescent tracers can be used in small and medium-sized turbulent streams, which do not have suitable reaches for making a discharge measurement using velocity-area methods. See [Table A.1](#) for applicable conditions.

iTeh STANDARD PREVIEW
(standards.iten.ai)

7 Stage- discharge gauging stations using hydraulic structures

7.1 General

When physical and hydraulic conditions permit, an artificial control consisting of a fixed, undeformable hydraulic structure may be constructed. The stage-discharge relation shall then depend on the geometrical characteristics of such a structure and shall be defined by either

- a) the application of the relevant International Standard or
- b) by calibration using other methods.

7.2 Site selection

A preliminary survey shall be made of the physical and hydraulic features of the proposed site to check that it conforms (or may be constructed or modified so as to conform) to the requirements necessary for measurement of discharge by the structure as specified in the relevant International Standard.

If the site does not possess the characteristics necessary for adequate measurements, or if an inspection of the watercourse shows that the velocity distribution in the approach channel deviates substantially from uniformity, the site should not be used.

7.3 Types of hydraulic structures

There are a number of hydraulic measuring structures which are the subject of International Standards and these are listed below and in Annex -A.

- a) thin-plate, sharp crest, v-notch weirs;
- b) thin-plate, sharp crest, rectangular weirs;
- c) broad-crested weirs with a sharp upstream edge;
- d) broad-crested weirs with a rounded upstream edge;

- e) triangular profile weirs;
- f) streamlined, triangular profile weirs;
- g) triangular profile, flat-V weirs;
- h) v-shaped, broad-crested weirs;
- i) trapezoidal profile weirs;
- j) rectangular flumes;
- k) trapezoidal flumes;
- l) u-shaped flumes;
- m) Parshall flumes;
- n) SANIIRI flumes;
- o) rectangular free overfalls;
- p) non-rectangular free overfalls;
- q) vertical underflow gates;
- r) compound gauging structures.

The choice of structure may be influenced by the criteria set out in Clause 4 and ISO 8368. Structures that have negative ecological or environmental effects on the natural stream channels should be avoided.

Non-standard structures are also permissible provided they are calibrated by an approved method. A combination of different structures is also permissible.

Normally a water level recorder is installed to provide a continuous record of stage from which discharge can be computed. The position of the water level sensor is discussed in the relevant International Standard.

8 Velocity-discharge gauging stations

8.1 Applications and types of instrument

Conventional methods of flow measurement using stage-discharge relationships from either open channel rated sections or calibrated structures are not always feasible. This may be because of channel size, unstable stage-discharge relationships, or other physical, hydraulic, or environmental considerations (such as aesthetic, navigation and fisheries impacts) and costs. This clause deals with the following acoustic and electromagnetic velocity measurement techniques.

- a) Transit time (ISO 6416)
- b) Ultrasonic Doppler
 - bed mounted systems (ISO 15769)
 - side looking systems
- c) Acoustic (echo) correlation velocity meters (ISO 15769)
- d) Electromagnetic river flow gauges (ISO 9213)