

ETSI TS 124 501 V16.7.0 (2021-01)



5G;
Non-Access-Stratum (NAS) protocol for 5G System (5GS);
Stage 3
(3GPP TS 24.501 version 16.7.0 Release 16)

<https://standards.iteh.ai/catalog/standards/sist/7115d591-b614-4555-a20a-1e6da96a3a7b/etsi-ts-124-501-v16-7-0-2021-01>



Reference

RTS/TSGC-0124501vg70

Keywords

5G**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Important notice

<https://standards.iteh.ai/catalog/standards/sist/7115d591-b614-4555-a20a-1e0d493a-0124-501-v16-7-0-2021-01>
The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

<https://standards.iteh.ai/catalog/standards/sist/7115d591-b614-4555-a20a-1e6da96a3a7b/etsi-ts-124-501-v16-7-0-2021-01>

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	22
1 Scope	23
2 References	23
3 Definitions and abbreviations.....	27
3.1 Definitions	27
3.2 Abbreviations	34
4 General	37
4.1 Overview	37
4.2 Coordination between the protocols for 5GS mobility management and 5GS session management	37
4.3 UE domain selection	38
4.3.1 UE's usage setting	38
4.3.2 Domain selection for UE originating sessions / calls.....	38
4.3.3 Change of UE's usage setting.....	40
4.3.4 Change or determination of IMS voice availability	40
4.4 NAS security	41
4.4.1 General.....	41
4.4.2 Handling of 5G NAS security contexts.....	41
4.4.2.1 General	41
4.4.2.2 Establishment of a mapped 5G NAS security context during inter-system change from S1 mode to N1 mode in 5GMM-CONNECTED mode.....	43
4.4.2.3 Establishment of a 5G NAS security context during N1 mode to N1 mode handover	44
4.4.2.4 Establishment of an EPS security context during inter-system change from N1 mode to S1 mode in 5GMM-CONNECTED mode.....	45
4.4.2.5 Establishment of secure exchange of NAS messages	46
4.4.2.6 Change of security keys	47
4.4.3 Handling of NAS COUNT and NAS sequence number	48
4.4.3.1 General	48
4.4.3.2 Replay protection	49
4.4.3.3 Integrity protection and verification.....	49
4.4.3.4 Cipherng and deciphering	49
4.4.3.5 NAS COUNT wrap around.....	50
4.4.4 Integrity protection of NAS signalling messages.....	50
4.4.4.1 General	50
4.4.4.2 Integrity checking of NAS signalling messages in the UE	51
4.4.4.3 Integrity checking of NAS signalling messages in the AMF	51
4.4.5 Cipherng of NAS signalling messages	53
4.4.6 Protection of initial NAS signalling messages.....	54
4.5 Unified access control	56
4.5.1 General.....	56
4.5.2 Determination of the access identities and access category associated with a request for access for UEs not operating in SNPN access mode	57
4.5.2A Determination of the access identities and access category associated with a request for access for UEs operating in SNPN access mode	63
4.5.3 Operator-defined access categories.....	67
4.5.4 Access control and checking.....	69
4.5.4.1 Access control and checking in 5GMM-IDLE mode and in 5GMM-IDLE mode with suspend indication.....	69
4.5.4.2 Access control and checking in 5GMM-CONNECTED mode and in 5GMM-CONNECTED mode with RRC inactive indication	71
4.5.5 Exception handling and avoiding double barring	73
4.5.6 Mapping between access categories/access identities and RRC establishment cause	77

4.6	Network slicing	78
4.6.1	General.....	78
4.6.2	Mobility management aspects.....	79
4.6.2.1	General.....	79
4.6.2.2	NSSAI storage.....	80
4.6.2.3	Provision of NSSAI to lower layers in 5GMM-IDLE mode.....	83
4.6.2.4	Network slice-specific authentication and authorization.....	84
4.6.3	Session management aspects	86
4.7	NAS over non-3GPP access	86
4.7.1	General.....	86
4.7.2	5GS mobility management aspects.....	86
4.7.2.1	General.....	86
4.7.2.2	Establishment cause for non-3GPP access.....	87
4.7.3	5GS session management aspects.....	87
4.7.4	Limited service state over non-3GPP access	88
4.7.5	NAS signalling using trusted WLAN access network.....	88
4.8	Interworking with E-UTRAN connected to EPC	89
4.8.1	General.....	89
4.8.2	Single-registration mode.....	89
4.8.2.1	General.....	89
4.8.2.2	Single-registration mode with N26 interface	89
4.8.2.3	Single-registration mode without N26 interface	89
4.8.2.3.1	Interworking between NG-RAN and E-UTRAN	89
4.8.2.3.2	Interworking between TNGF or N3IWF connected to 5GCN and E-UTRAN.....	91
4.8.3	Dual-registration mode	92
4.8.4	Core Network selection for UEs not using ClIoT 5GS optimizations	93
4.8.4A	Core Network selection and redirection for UEs using ClIoT optimizations.....	93
4.8.4A.1	Core network selection.....	93
4.8.4A.2	Redirection of the UE by the core network.....	94
4.9	Disabling and re-enabling of UE's N1 mode capability	94
4.9.1	General.....	94
4.9.2	Disabling and re-enabling of UE's N1 mode capability for 3GPP access.....	94
4.9.3	Disabling and re-enabling of UE's N1 mode capability for non-3GPP access.....	97
4.10	Interworking with ePDG connected to EPC.....	97
4.11	UE configuration parameter updates	97
4.12	Access traffic steering, switching and splitting (ATSSS).....	98
4.13	Support of NAS signalling using wireline access network.....	98
4.14	Non-public network.....	99
4.14.1	General.....	99
4.14.2	Stand-alone non-public network.....	99
4.14.3	Public network integrated non-public network (PNI-NPN).....	100
4.15	Time sensitive communication.....	100
4.15.1	General.....	100
4.15.2	Integration with TSN network	101
4.15.2.1	General	101
4.15.2.2	Time synchronization.....	101
4.15.2.3	TSN bridge management.....	101
4.16	UE radio capability signalling optimisation	101
4.17	5GS mobility management in NB-N1 mode	103
4.18	5GS session management in NB-N1 mode	103
4.19	5GS mobility management in WB-N1 mode for IoT	103
4.20	5GS session management in WB-N1 mode for IoT.....	104
5	Elementary procedures for 5GS mobility management	104
5.1	Overview	104
5.1.1	General.....	104
5.1.2	Types of 5GMM procedures.....	104
5.1.3	5GMM sublayer states	106
5.1.3.1	General	106
5.1.3.2	5GMM sublayer states	106
5.1.3.2.1	5GMM sublayer states in the UE.....	106
5.1.3.2.1.1	General.....	106

5.1.3.2.1.2	Main states	106
5.1.3.2.1.2.1	5GMM-NULL	106
5.1.3.2.1.2.2	5GMM-DEREGISTERED	106
5.1.3.2.1.2.3	5GMM-REGISTERED-INITIATED	107
5.1.3.2.1.2.4	5GMM-REGISTERED	107
5.1.3.2.1.2.5	5GMM-DEREGISTERED-INITIATED	107
5.1.3.2.1.2.6	5GMM-SERVICE-REQUEST-INITIATED	107
5.1.3.2.1.3	Substates of state 5GMM-DEREGISTERED	107
5.1.3.2.1.3.1	General	107
5.1.3.2.1.3.2	5GMM-DEREGISTERED.NORMAL-SERVICE	107
5.1.3.2.1.3.3	5GMM-DEREGISTERED.LIMITED-SERVICE	107
5.1.3.2.1.3.4	5GMM-DEREGISTERED.ATTEMPTING-REGISTRATION	107
5.1.3.2.1.3.5	5GMM-DEREGISTERED.PLMN-SEARCH	107
5.1.3.2.1.3.6	5GMM-DEREGISTERED.NO-SUPI	108
5.1.3.2.1.3.7	5GMM-DEREGISTERED.NO-CELL-AVAILABLE	108
5.1.3.2.1.3.8	5GMM-DEREGISTERED.eCALL-INACTIVE	108
5.1.3.2.1.3.9	5GMM-DEREGISTERED.INITIAL-REGISTRATION-NEEDED	108
5.1.3.2.1.4	Substates of state 5GMM-REGISTERED	108
5.1.3.2.1.4.1	General	108
5.1.3.2.1.4.2	5GMM-REGISTERED.NORMAL-SERVICE	108
5.1.3.2.1.4.3	5GMM-REGISTERED.NON-ALLOWED-SERVICE	109
5.1.3.2.1.4.4	5GMM-REGISTERED.ATTEMPTING-REGISTRATION-UPDATE	109
5.1.3.2.1.4.5	5GMM-REGISTERED.LIMITED-SERVICE	109
5.1.3.2.1.4.6	5GMM-REGISTERED.PLMN-SEARCH	109
5.1.3.2.1.4.7	5GMM-REGISTERED.NO-CELL-AVAILABLE	109
5.1.3.2.1.4.8	5GMM-REGISTERED.UPDATE-NEEDED	109
5.1.3.2.2	5GS update status in the UE	110
5.1.3.2.3	5GMM sublayer states in the network side	110
5.1.3.2.3.1	General	110
5.1.3.2.3.2	5GMM-DEREGISTERED	111
5.1.3.2.3.3	5GMM-COMMON-PROCEDURE-INITIATED	111
5.1.3.2.3.4	5GMM-REGISTERED	111
5.1.3.2.3.5	5GMM-DEREGISTERED-INITIATED	111
5.1.4	Coordination between 5GMM and EMM	111
5.1.4.1	General	111
5.1.4.2	Coordination between 5GMM for 3GPP access and EMM with N26 interface	112
5.1.4.3	Coordination between 5GMM for 3GPP access and EMM without N26 interface	112
5.1.5	Coordination between 5GMM and GMM	112
5.2	Behaviour of the UE in state 5GMM-DEREGISTERED and state 5GMM-REGISTERED	113
5.2.1	General	113
5.2.2	UE behaviour in state 5GMM-DEREGISTERED	113
5.2.2.1	General	113
5.2.2.2	Primary substate selection	113
5.2.2.2.1	Selection of the substate after power on	113
5.2.2.3	Detailed description of UE behaviour in state 5GMM-DEREGISTERED	113
5.2.2.3.1	NORMAL-SERVICE	113
5.2.2.3.2	LIMITED-SERVICE	114
5.2.2.3.3	ATTEMPTING-REGISTRATION	114
5.2.2.3.4	PLMN-SEARCH	115
5.2.2.3.5	NO-SUPI	115
5.2.2.3.6	NO-CELL-AVAILABLE	115
5.2.2.3.7	eCALL-INACTIVE	115
5.2.2.3.8	INITIAL-REGISTRATION-NEEDED	115
5.2.2.4	Substate when back to state 5GMM-DEREGISTERED from another 5GMM state	115
5.2.3	UE behaviour in state 5GMM-REGISTERED	116
5.2.3.1	General	116
5.2.3.2	Detailed description of UE behaviour in state 5GMM-REGISTERED	116
5.2.3.2.1	NORMAL-SERVICE	116
5.2.3.2.2	NON-ALLOWED-SERVICE	116
5.2.3.2.3	ATTEMPTING-REGISTRATION-UPDATE	116
5.2.3.2.4	LIMITED-SERVICE	117
5.2.3.2.5	PLMN-SEARCH	118

5.2.3.2.6	NO-CELL-AVAILABLE	118
5.2.3.2.7	UPDATE-NEEDED	118
5.3	General on elementary 5GMM procedures	118
5.3.1	5GMM modes and N1 NAS signalling connection	118
5.3.1.1	Establishment of the N1 NAS signalling connection	118
5.3.1.2	Re-establishment of the N1 NAS signalling connection	120
5.3.1.3	Release of the N1 NAS signalling connection	121
5.3.1.4	5GMM-CONNECTED mode with RRC inactive indication	124
5.3.1.5	Suspend and resume of the N1 NAS signalling connection	126
5.3.2	Permanent identifiers	127
5.3.3	Temporary identities	129
5.3.4	Registration areas	130
5.3.5	Service area restrictions	131
5.3.5.1	General	131
5.3.5.2	3GPP access service area restrictions	131
5.3.5.3	Wireline access service area restrictions	134
5.3.6	Mobile initiated connection only mode	134
5.3.7	Handling of the periodic registration update timer and mobile reachable timer	136
5.3.8	Handling of timer T3502	138
5.3.9	Handling of NAS level mobility management congestion control	138
5.3.10	Handling of DNN based congestion control	139
5.3.11	Handling of S-NSSAI based congestion control	139
5.3.12	Handling of local emergency numbers	139
5.3.12A	Handling of local emergency numbers received via 3GPP access and non-3GPP access	140
5.3.12A.1	General	140
5.3.12A.2	Receiving a REGISTRATION ACCEPT message via non-3GPP access	141
5.3.13	Lists of 5GS forbidden tracking areas	141
5.3.13A	Forbidden PLMN lists	142
5.3.14	List of equivalent PLMNs	142
5.3.15	Transmission failure abnormal case in the UE	142
5.3.16	Extended DRX cycle for UEs in 5GMM-IDLE	142
5.3.17	Service Gap Control	143
5.3.18	Restriction on use of enhanced coverage	145
5.3.19	Handling of congestion control for transport of user data via the control plane	146
5.3.19a	Specific requirements for UE configured to use timer T3245	146
5.3.19a.1	UE not operating in SNPN access mode	146
5.3.19a.2	UE operating in SNPN access mode	147
5.3.20	Specific requirements for UE when receiving non-integrity protected reject messages	147
5.3.20.1	General	147
5.3.20.2	Requirements for UE in a PLMN	147
5.3.20.3	Requirements for UE in an SNPN	151
5.3.21	CIoT 5GS optimizations	154
5.3.22	Interaction between MICO mode with active time and extended idle mode DRX cycle	156
5.3.23	Forbidden wireline access area	157
5.3.24	WUS assistance	157
5.4	5GMM common procedures	158
5.4.1	Primary authentication and key agreement procedure	158
5.4.1.1	General	158
5.4.1.2	EAP based primary authentication and key agreement procedure	158
5.4.1.2.1	General	158
5.4.1.2.2	EAP-AKA' related procedures	161
5.4.1.2.2.1	General	161
5.4.1.2.2.2	Initiation	161
5.4.1.2.2.3	UE successfully authenticates network	161
5.4.1.2.2.4	Errors when handling EAP-request/AKA'-challenge message	162
5.4.1.2.2.5	Network successfully authenticates UE	162
5.4.1.2.2.6	UE handling EAP-AKA' notification message	162
5.4.1.2.2.6A	EAP based Identification initiation by the network	162
5.4.1.2.2.6B	EAP based Identification response by the UE	163
5.4.1.2.2.7	Network sending EAP-success message	163
5.4.1.2.2.8	UE handling EAP-success message	163
5.4.1.2.2.9	Network not successfully authenticates UE	163

5.4.1.2.2.10	Network sending EAP-failure message	163
5.4.1.2.2.11	UE handling EAP-failure message	164
5.4.1.2.2.12	Abnormal cases in the UE.....	166
5.4.1.2.3	EAP-TLS related procedures.....	166
5.4.1.2.3.1	General.....	166
5.4.1.2.3A	Procedures related to EAP methods other than EAP-AKA' and EAP-TLS.....	168
5.4.1.2.3A.1	General.....	168
5.4.1.2.3B	Procedures related to EAP methods used for primary authentication of an N5GC device.....	171
5.4.1.2.3B.1	General.....	171
5.4.1.2.4	EAP message reliable transport procedure	172
5.4.1.2.4.1	General.....	172
5.4.1.2.4.2	EAP message reliable transport procedure initiation by the network	172
5.4.1.2.4.3	EAP message reliable transport procedure accepted by the UE.....	173
5.4.1.2.4.4	Abnormal cases on the network side.....	173
5.4.1.2.4.5	Abnormal cases in the UE.....	173
5.4.1.2.5	EAP result message transport procedure	175
5.4.1.2.5.1	General.....	175
5.4.1.2.5.2	EAP result message transport procedure initiation by the network	176
5.4.1.3	5G AKA based primary authentication and key agreement procedure	176
5.4.1.3.1	General	176
5.4.1.3.2	Authentication initiation by the network	177
5.4.1.3.3	Authentication response by the UE	177
5.4.1.3.4	Authentication completion by the network.....	178
5.4.1.3.5	Authentication not accepted by the network.....	178
5.4.1.3.6	Authentication not accepted by the UE	180
5.4.1.3.7	Abnormal cases	181
5.4.2	Security mode control procedure.....	185
5.4.2.1	General	185
5.4.2.2	NAS security mode control initiation by the network	185
5.4.2.3	NAS security mode command accepted by the UE.....	188
5.4.2.4	NAS security mode control completion by the network	190
5.4.2.5	NAS security mode command not accepted by the UE.....	191
5.4.2.6	Abnormal cases in the UE.....	191
5.4.2.7	Abnormal cases on the network side.....	191
5.4.3	Identification procedure.....	192
5.4.3.1	General	192
5.4.3.2	Identification initiation by the network	192
5.4.3.3	Identification response by the UE	192
5.4.3.4	Identification completion by the network	192
5.4.3.5	Abnormal cases in the UE.....	193
5.4.3.6	Abnormal cases on the network side.....	193
5.4.4	Generic UE configuration update procedure.....	194
5.4.4.1	General	194
5.4.4.2	Generic UE configuration update procedure initiated by the network	196
5.4.4.3	Generic UE configuration update accepted by the UE.....	198
5.4.4.4	Generic UE configuration update completion by the network	201
5.4.4.5	Abnormal cases in the UE.....	202
5.4.4.6	Abnormal cases on the network side.....	203
5.4.5	NAS transport procedure(s).....	204
5.4.5.1	General	204
5.4.5.2	UE-initiated NAS transport procedure	204
5.4.5.2.1	General	204
5.4.5.2.2	UE-initiated NAS transport procedure initiation	205
5.4.5.2.3	UE-initiated NAS transport of messages accepted by the network	207
5.4.5.2.4	UE-initiated NAS transport of messages not accepted by the network	211
5.4.5.2.5	Abnormal cases on the network side	213
5.4.5.2.6	Abnormal cases in the UE	217
5.4.5.3	Network-initiated NAS transport procedure	219
5.4.5.3.1	General	219
5.4.5.3.2	Network-initiated NAS transport procedure initiation	219
5.4.5.3.3	Network-initiated NAS transport of messages	223
5.4.6	5GMM status procedure	226

5.4.6.1	General	226
5.4.6.2	5GMM status received in the UE	226
5.4.6.3	5GMM status received in the network	226
5.4.7	Network slice-specific authentication and authorization procedure	227
5.4.7.1	General	227
5.4.7.2	Network slice-specific EAP message reliable transport procedure	228
5.4.7.2.1	Network slice-specific EAP message reliable transport procedure initiation	228
5.4.7.2.2	Network slice-specific EAP message reliable transport procedure accepted by the UE	229
5.4.7.2.3	Abnormal cases on the network side	229
5.4.7.2.4	Abnormal cases in the UE	229
5.4.7.3	Network slice-specific EAP result message transport procedure	230
5.4.7.3.1	Network slice-specific EAP result message transport procedure initiation	230
5.5	5GMM specific procedures	230
5.5.1	Registration procedure	230
5.5.1.1	General	230
5.5.1.2	Registration procedure for initial registration	231
5.5.1.2.1	General	231
5.5.1.2.2	Initial registration initiation	232
5.5.1.2.3	5GMM common procedure initiation	237
5.5.1.2.4	Initial registration accepted by the network	237
5.5.1.2.5	Initial registration not accepted by the network	250
5.5.1.2.6	Initial registration for emergency services not accepted by the network	258
5.5.1.2.6A	Initial registration for initiating an emergency PDU session not accepted by the network	260
5.5.1.2.7	Abnormal cases in the UE	260
5.5.1.2.8	Abnormal cases on the network side	263
5.5.1.3	Registration procedure for mobility and periodic registration update	265
5.5.1.3.1	General	265
5.5.1.3.2	Mobility and periodic registration update initiation	265
5.5.1.3.3	5GMM common procedure initiation	273
5.5.1.3.4	Mobility and periodic registration update accepted by the network	274
5.5.1.3.5	Mobility and periodic registration update not accepted by the network	292
5.5.1.3.6	Mobility and periodic registration update for initiating an emergency PDU session not accepted by the network	302
5.5.1.3.7	Abnormal cases in the UE	302
5.5.1.3.8	Abnormal cases on the network side	306
5.5.2	De-registration procedure	308
5.5.2.1	General	308
5.5.2.2	UE-initiated de-registration procedure	309
5.5.2.2.1	UE-initiated de-registration procedure initiation	309
5.5.2.2.2	UE-initiated de-registration procedure completion	310
5.5.2.2.3	UE-initiated de-registration procedure completion for 5GS services over 3GPP access	310
5.5.2.2.4	UE-initiated de-registration procedure completion for 5GS services non-3GPP access	310
5.5.2.2.5	UE-initiated de-registration procedure completion for 5GS services over both 3GPP access and non-3GPP access	311
5.5.2.2.6	Abnormal cases in the UE	311
5.5.2.2.7	Abnormal cases in the network side	313
5.5.2.3	Network-initiated de-registration procedure	313
5.5.2.3.1	Network-initiated de-registration procedure initiation	313
5.5.2.3.2	Network-initiated de-registration procedure completion by the UE	314
5.5.2.3.3	Network-initiated de-registration procedure completion by the network	320
5.5.2.3.4	Abnormal cases in the UE	320
5.5.2.3.5	Abnormal cases in the network side	321
5.5.3	eCall inactivity procedure	322
5.6	5GMM connection management procedures	323
5.6.1	Service request procedure	323
5.6.1.1	General	323
5.6.1.2	Service request procedure initiation	326
5.6.1.2.1	UE is not using 5GS services with control plane CIoT 5GS optimization	326
5.6.1.2.2	UE is using 5GS services with control plane CIoT 5GS optimization	329
5.6.1.3	Common procedure initiation	331
5.6.1.4	Service request procedure accepted by the network	331
5.6.1.4.1	UE is not using 5GS services with control plane CIoT 5GS optimization	331

5.6.1.4.2	UE is using 5GS services with control plane CIoT 5GS optimization	333
5.6.1.5	Service request procedure not accepted by the network.....	336
5.6.1.6	Service request procedure for initiating an emergency PDU session not accepted by the network	345
5.6.1.7	Abnormal cases in the UE.....	346
5.6.1.8	Abnormal cases on the network side.....	349
5.6.2	Paging procedure	351
5.6.2.1	General	351
5.6.2.2	Paging for 5GS services	351
5.6.2.2.1	General	351
5.6.2.2.2	Abnormal cases on the network side	352
5.6.2.2.3	Abnormal cases in the UE	352
5.6.3	Notification procedure	353
5.6.3.1	General	353
5.6.3.2	Notification procedure initiation	353
5.6.3.3	Notification procedure completion.....	354
5.6.3.4	Abnormal cases on the network side.....	355
5.6.3.5	Abnormal cases on the UE side.....	355
6	Elementary procedures for 5GS session management	356
6.1	Overview	356
6.1.1	General.....	356
6.1.2	Types of 5GSM procedures	356
6.1.3	5GSM sublayer states	357
6.1.3.1	General	357
6.1.3.2	5GSM sublayer states in the UE	357
6.1.3.2.1	Overview	357
6.1.3.2.2	PDU SESSION INACTIVE	357
6.1.3.2.3	PDU SESSION ACTIVE PENDING.....	358
6.1.3.2.4	PDU SESSION ACTIVE	358
6.1.3.2.5	PDU SESSION INACTIVE PENDING.....	358
6.1.3.2.6	PDU SESSION MODIFICATION PENDING	358
6.1.3.2.7	PROCEDURE TRANSACTION INACTIVE.....	358
6.1.3.2.8	PROCEDURE TRANSACTION PENDING.....	358
6.1.3.3	5GSM sublayer states in the network side	358
6.1.3.3.1	Overview	358
6.1.3.3.2	PDU SESSION INACTIVE	359
6.1.3.3.3	PDU SESSION ACTIVE	359
6.1.3.3.4	PDU SESSION INACTIVE PENDING.....	359
6.1.3.3.5	PDU SESSION MODIFICATION PENDING	359
6.1.3.3.6	PROCEDURE TRANSACTION INACTIVE.....	359
6.1.3.3.7	PROCEDURE TRANSACTION PENDING.....	359
6.1.4	Coordination between 5GSM and ESM.....	360
6.1.4.1	Coordination between 5GSM and ESM with N26 interface	360
6.1.4.2	Coordination between 5GSM and ESM without N26 interface	371
6.1.4a	Coordination between 5GSM and SM.....	373
6.1.5	Coordination for interworking with ePDG connected to EPC.....	374
6.2	General on elementary 5GSM procedures.....	374
6.2.1	Principles of PTI handling for 5GSM procedures.....	374
6.2.2	PDU session types	376
6.2.3	PDU session management	376
6.2.4	IP address allocation	376
6.2.4.1	General	376
6.2.4.2	IP address allocation via NAS signalling	377
6.2.4.3	Additional RG related requirements for IP address allocation.....	378
6.2.5	Quality of service.....	378
6.2.5.1	General	378
6.2.5.1.1	QoS rules	378
6.2.5.1.1.1	General.....	378
6.2.5.1.1.2	Signalled QoS rules	379
6.2.5.1.1.3	Derived QoS rules.....	380
6.2.5.1.1.4	QoS flow descriptions.....	380
6.2.5.1.2	Session-AMBR.....	381

6.2.5.1.2A	Void.....	381
6.2.5.1.3	UL user data packet matching	381
6.2.5.1.4	Reflective QoS.....	382
6.2.5.1.4.1	General.....	382
6.2.5.1.4.2	Derivation of packet filter for UL direction from DL user data packet	382
6.2.5.1.4.3	Creating a derived QoS rule by reflective QoS in the UE.....	383
6.2.5.1.4.4	Updating a derived QoS rule by reflective QoS in the UE	384
6.2.5.1.4.5	Deleting a derived QoS rule in the UE	384
6.2.5.1.4.6	Ignoring RQI in the UE.....	384
6.2.5.2	QoS in MA PDU session.....	384
6.2.6	Local area data network (LADN)	385
6.2.7	Handling of DNN based congestion control	386
6.2.8	Handling of S-NSSAI based congestion control.....	386
6.2.9	Interaction with upper layers	388
6.2.9.1	General	388
6.2.9.2	URSP.....	388
6.2.10	Handling of 3GPP PS data off	388
6.2.11	Multi-homed IPv6 PDU session	389
6.2.12	Handling of network rejection not due to congestion control	389
6.2.13	Handling of Small data rate control	390
6.2.14	Handling of Serving PLMN rate control.....	391
6.2.15	Handling of Reliable Data Service	392
6.2.16	Handling of header compression for control plane CIoT optimizations	392
6.3	Network-requested 5GSM procedures	392
6.3.1	PDU session authentication and authorization procedure.....	392
6.3.1.1	General	392
6.3.1.2	PDU EAP message reliable transport procedure	394
6.3.1.2.1	PDU EAP message reliable transport procedure initiation.....	394
6.3.1.2.2	PDU EAP message reliable transport procedure accepted by the UE	395
6.3.1.2.3	Abnormal cases on the network side	395
6.3.1.2.4	Abnormal cases in the UE	396
6.3.1.3	PDU EAP result message transport procedure	396
6.3.1.3.1	PDU EAP result message transport procedure initiation	396
6.3.2	Network-requested PDU session modification procedure	396
6.3.2.1	General	396
6.3.2.2	Network-requested PDU session modification procedure initiation	396
6.3.2.3	Network-requested PDU session modification procedure accepted by the UE.....	399
6.3.2.4	Network-requested PDU session modification procedure not accepted by the UE.....	405
6.3.2.5	Abnormal cases on the network side.....	409
6.3.2.6	Abnormal cases in the UE.....	410
6.3.3	Network-requested PDU session release procedure	410
6.3.3.1	General	410
6.3.3.2	Network-requested PDU session release procedure initiation	410
6.3.3.3	Network-requested PDU session release procedure accepted by the UE.....	412
6.3.3.4	N1 SM delivery skipped.....	419
6.3.3.5	Abnormal cases on the network side.....	419
6.3.3.6	Abnormal cases in the UE.....	420
6.4	UE-requested 5GSM procedures.....	420
6.4.1	UE-requested PDU session establishment procedure	420
6.4.1.1	General	420
6.4.1.2	UE-requested PDU session establishment procedure initiation	421
6.4.1.3	UE-requested PDU session establishment procedure accepted by the network	427
6.4.1.4	UE requested PDU session establishment procedure not accepted by the network	436
6.4.1.4.1	General	436
6.4.1.4.2	Handling of network rejection due to congestion control.....	439
6.4.1.4.3	Handling of network rejection not due to congestion control.....	445
6.4.1.5	Handling the maximum number of established PDU sessions.....	450
6.4.1.5A	Handling the maximum number of allowed active user-plane resources for PDU sessions of UEs in NB-N1 mode	450
6.4.1.6	Abnormal cases in the UE.....	451
6.4.1.7	Abnormal cases on the network side.....	452
6.4.2	UE-requested PDU session modification procedure.....	452

6.4.2.1	General	452
6.4.2.2	UE-requested PDU session modification procedure initiation	453
6.4.2.3	UE-requested PDU session modification procedure accepted by the network	456
6.4.2.4	UE-requested PDU session modification procedure not accepted by the network	457
6.4.2.4.1	General	457
6.4.2.4.2	Handling of network rejection due to congestion control.....	458
6.4.2.4.3	Handling of network rejection not due to congestion control.....	464
6.4.2.5	Abnormal cases in the UE.....	467
6.4.2.6	Abnormal cases on the network side.....	467
6.4.3	UE-requested PDU session release procedure	468
6.4.3.1	General	468
6.4.3.2	UE-requested PDU session release procedure initiation	468
6.4.3.3	UE-requested PDU session release procedure accepted by the network.....	469
6.4.3.4	UE-requested PDU session release procedure not accepted by the network.....	469
6.4.3.5	Abnormal cases in the UE.....	470
6.4.3.6	Abnormal cases on the network side.....	470
6.5	5GSM status procedure	471
6.5.1	General.....	471
6.5.2	5GSM status received in the UE.....	471
6.5.3	5GSM status received in the SMF	471
6.6	Miscellaneous procedures	472
6.6.1	Exchange of extended protocol configuration options.....	472
7	Handling of unknown, unforeseen, and erroneous protocol data	472
7.1	General	472
7.2	Message too short or too long	472
7.2.1	Message too short	472
7.2.2	Message too long	473
7.3	Unknown or unforeseen procedure transaction identity or PDU Session identity.....	473
7.3.1	Procedure transaction identity.....	473
7.3.2	PDU Session identity.....	474
7.4	Unknown or unforeseen message type	474
7.5	Non-semantic mandatory information element errors	475
7.5.1	Common procedures	475
7.5.2	5GS mobility management	475
7.5.3	5GS session management	475
7.6	Unknown and unforeseen IEs in the non-imperative message part.....	476
7.6.1	IEs unknown in the message	476
7.6.2	Out of sequence IEs	476
7.6.3	Repeated IEs	476
7.7	Non-imperative message part errors.....	476
7.7.1	Syntactically incorrect optional IEs.....	477
7.7.2	Conditional IE errors	477
7.8	Messages with semantically incorrect contents.....	477
8	Message functional definitions and contents.....	477
8.1	Overview	477
8.2	5GS mobility management messages	477
8.2.1	Authentication request	477
8.2.1.1	Message definition	477
8.2.1.2	Authentication parameter RAND.....	478
8.2.1.3	Authentication parameter AUTN	478
8.2.1.4	Void.....	478
8.2.1.5	EAP message.....	478
8.2.2	Authentication response.....	478
8.2.2.1	Message definition	478
8.2.2.2	Authentication response parameter	479
8.2.2.3	EAP message.....	479
8.2.3	Authentication result.....	479
8.2.3.1	Message definition	479
8.2.3.2	ABBA	479
8.2.4	Authentication failure	480

8.2.4.1	Message definition	480
8.2.4.2	Authentication failure parameter.....	480
8.2.5	Authentication reject.....	480
8.2.5.1	Message definition	480
8.2.5.2	EAP message.....	481
8.2.6	Registration request	481
8.2.6.1	Message definition	481
8.2.6.2	Non-current native NAS key set identifier.....	484
8.2.6.3	5GMM capability	484
8.2.6.4	UE security capability	484
8.2.6.5	Requested NSSAI	484
8.2.6.6	Last visited registered TAI.....	484
8.2.6.7	S1 UE network capability	484
8.2.6.8	Uplink data status.....	484
8.2.6.9	PDU session status	484
8.2.6.10	MICO indication	484
8.2.6.11	UE status	485
8.2.6.12	Additional GUTI.....	485
8.2.6.13	Allowed PDU session status	485
8.2.6.14	UE's usage setting	485
8.2.6.15	Requested DRX parameters	485
8.2.6.16	EPS NAS message container.....	485
8.2.6.17	LADN indication.....	485
8.2.6.17A	Payload container type	485
8.2.6.18	Payload container	485
8.2.6.19	Network slicing indication	486
8.2.6.20	5GS update type	486
8.2.6.21	NAS message container	486
8.2.6.22	Requested extended DRX parameters	486
8.2.6.23	EPS bearer context status	486
8.2.6.24	T3324 value.....	486
8.2.6.25	Mobile station classmark.....	486
8.2.6.26	Supported codecs.....	486
8.2.6.27	UE radio capability.....	486
8.2.6.28	Requested mapped NSSAI.....	486
8.2.6.29	Additional information requested.....	487
8.2.6.30	Requested WUS assistance information.....	487
8.2.6.31	Void.....	487
8.2.6.32	N5GC indication	487
8.2.6.33	Requested NB-N1 mode DRX parameters.....	487
8.2.7	Registration accept.....	487
8.2.7.1	Message definition	487
8.2.7.2	5G-GUTI.....	490
8.2.7.3	Equivalent PLMNs.....	490
8.2.7.4	TAI list	490
8.2.7.5	Allowed NSSAI	490
8.2.7.6	Rejected NSSAI	491
8.2.7.7	Configured NSSAI.....	491
8.2.7.8	5GS network feature support.....	491
8.2.7.9	PDU session status	491
8.2.7.10	PDU session reactivation result.....	491
8.2.7.11	PDU session reactivation result error cause	491
8.2.7.12	LADN information.....	491
8.2.7.13	MICO indication	491
8.2.7.14	Network slicing indication	491
8.2.7.15	Service area list	491
8.2.7.16	T3512 value.....	492
8.2.7.17	Non-3GPP de-registration timer value	492
8.2.7.18	T3502 value.....	492
8.2.7.19	Emergency number list	492
8.2.7.20	Extended emergency number list	492
8.2.7.21	SOR transparent container	492

8.2.7.22	EAP message.....	492
8.2.7.23	NSSAI inclusion mode.....	492
8.2.7.24	Operator-defined access category definitions	492
8.2.7.25	Negotiated DRX parameters	492
8.2.7.26	Non-3GPP NW provided policies	492
8.2.7.27	Negotiated extended DRX parameters	493
8.2.7.28	T3447 value.....	493
8.2.7.29	T3448 value.....	493
8.2.7.30	T3324 value.....	493
8.2.7.31	EPS bearer context status	493
8.2.7.32	UE radio capability ID	493
8.2.7.33	UE radio capability ID deletion indication.....	493
8.2.7.34	Pending NSSAI	493
8.2.7.35	Ciphering key data	493
8.2.7.36	CAG information list.....	493
8.2.7.37	Truncated 5G-S-TMSI configuration.....	494
8.2.7.38	Negotiated NB-N1 mode DRX parameters.....	494
8.2.7.39	Negotiated WUS assistance information.....	494
8.2.8	Registration complete	494
8.2.8.1	Message definition	494
8.2.8.2	SOR transparent container	494
8.2.9	Registration reject.....	495
8.2.9.1	Message definition	495
8.2.9.2	T3346 value.....	495
8.2.9.3	T3502 value.....	495
8.2.9.4	EAP message.....	495
8.2.9.5	Rejected NSSAI	495
8.2.9.6	CAG information list.....	495
8.2.10	UL NAS transport.....	496
8.2.10.1	Message definition	496
8.2.10.2	PDU session ID	496
8.2.10.3	Old PDU session ID	496
8.2.10.4	Request type	497
8.2.10.5	S-NSSAI	497
8.2.10.6	DNN.....	497
8.2.10.7	Additional information.....	497
8.2.10.8	MA PDU session information	497
8.2.10.9	Release assistance indication	497
8.2.11	DL NAS transport.....	497
8.2.11.1	Message definition	497
8.2.11.2	PDU session ID	498
8.2.11.3	Additional information.....	498
8.2.11.4	5GMM cause.....	498
8.2.11.5	Back-off timer value	498
8.2.12	De-registration request (UE originating de-registration)	498
8.2.12.1	Message definition	498
8.2.13	De-registration accept (UE originating de-registration).....	499
8.2.13.1	Message definition	499
8.2.14	De-registration request (UE terminated de-registration).....	499
8.2.14.1	Message definition	499
8.2.14.2	5GMM cause.....	500
8.2.14.3	T3346 value.....	500
8.2.14.4	Rejected NSSAI	500
8.2.14.5	CAG information list.....	500
8.2.15	De-registration accept (UE terminated de-registration).....	500
8.2.15.1	Message definition	500
8.2.16	Service request.....	501
8.2.16.1	Message definition	501
8.2.16.2	Uplink data status.....	501
8.2.16.3	PDU session status	501
8.2.16.4	Allowed PDU session status	502
8.2.16.5	NAS message container	502

8.2.17	Service accept	502
8.2.17.1	Message definition	502
8.2.17.2	PDU session status	502
8.2.17.3	PDU session reactivation result.....	502
8.2.17.4	PDU session reactivation result error cause	503
8.2.17.5	EAP message.....	503
8.2.17.6	T3448 value.....	503
8.2.18	Service reject	503
8.2.18.1	Message definition	503
8.2.18.2	PDU session status	503
8.2.18.3	T3346 value.....	504
8.2.18.4	EAP message.....	504
8.2.18.5	T3448 value.....	504
8.2.18.6	CAG information list.....	504
8.2.19	Configuration update command.....	504
8.2.19.1	Message definition	504
8.2.19.2	Configuration update indication.....	506
8.2.19.3	5G-GUTI.....	506
8.2.19.4	TAI list	506
8.2.19.5	Allowed NSSAI	506
8.2.19.6	Service area list	506
8.2.19.7	Full name for network	506
8.2.19.8	Short name for network.....	506
8.2.19.9	Local time zone	506
8.2.19.10	Universal time and local time zone	506
8.2.19.11	Network daylight saving time	506
8.2.19.12	LADN information.....	506
8.2.19.13	MICO indication	506
8.2.19.14	Network slicing indication	506
8.2.19.15	Configured NSSAI.....	506
8.2.19.16	Rejected NSSAI	507
8.2.19.17	Operator-defined access category definitions.....	507
8.2.19.18	SMS indication	507
8.2.19.19	T3447 value.....	507
8.2.19.20	CAG information list.....	507
8.2.19.21	UE radio capability ID	507
8.2.19.22	UE radio capability ID deletion indication.....	507
8.2.19.23	5GS registration result.....	507
8.2.19.24	Truncated 5G-S-TMSI configuration.....	507
8.2.19.25	Additional configuration indication	507
8.2.20	Configuration update complete.....	507
8.2.20.1	Message definition	507
8.2.20.2	Void.....	508
8.2.21	Identity request	508
8.2.21.1	Message definition	508
8.2.22	Identity response.....	508
8.2.22.1	Message definition	508
8.2.23	Notification	509
8.2.23.1	Message definition	509
8.2.24	Notification response	509
8.2.24.1	Message definition	509
8.2.24.2	PDU session status	510
8.2.25	Security mode command	510
8.2.25.1	Message definition	510
8.2.25.2	IMEISV request	511
8.2.25.3	Void.....	511
8.2.25.4	Selected EPS NAS security algorithms.....	511
8.2.25.5	Additional 5G security information	511
8.2.25.6	EAP message.....	511
8.2.25.7	ABBA	511
8.2.25.8	Replayed S1 UE security capabilities	512
8.2.26	Security mode complete.....	512