

SLOVENSKI STANDARD

SIST EN 15004-7:2018

01-februar-2018

Nadomešča:
SIST EN 15004-7:2008

Vgrajeni gasilni sistemi - Sistemi za gašenje s plinom - 7. del: Fizikalne lastnosti in načrtovanje sistema za gašenje s plinom za gasilo IG-01 (ISO 14520-12:2015, spremenjen)

Fixed firefighting systems - Gas extinguishing systems - Part 7: Physical properties and system design of gas extinguishing systems for IG-01 extinguishant (ISO 14520-12:2015, modified)

iTeh STANDARD PREVIEW

(standards.iteh.ai)

Ortsfeste Brandbekämpfungsanlagen - Löschanlagen mit gasförmigen Löschmitteln - Teil 7: Physikalische Eigenschaften und Anlagenauslegung für Löschmittel IG-01 (ISO 14520-12:2015, modifiziert)

[SIST EN 15004-7:2018](https://standards.iteh.ai/catalog/standards/sist/e7675ac1-6994-4d10-9c42-91deb29cc787/sist-en-15004-7-2018)

<https://standards.iteh.ai/catalog/standards/sist/e7675ac1-6994-4d10-9c42-91deb29cc787/sist-en-15004-7-2018>

Installations fixes de lutte contre l'incendie - Installations d'extinction à gaz - Partie 7 : Propriétés physiques et conception des systèmes pour agent extincteur IG-01 (ISO 14520-12:2015, modifiée)

Ta slovenski standard je istoveten z: EN 15004-7:2017

ICS:

13.220.10 Gašenje požara Fire-fighting

SIST EN 15004-7:2018

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 15004-7:2018

<https://standards.iteh.ai/catalog/standards/sist/e7675ac1-6994-4d10-9c42-91deb29cc787/sist-en-15004-7-2018>

EUROPEAN STANDARD

EN 15004-7

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 2017

ICS 13.220.20

Supersedes EN 15004-7:2008

English Version

Fixed firefighting systems - Gas extinguishing systems -
Part 7: Physical properties and system design of gas
extinguishing systems for IG-01 extinguishant (ISO 14520-
12:2015, modified)

Installations fixes de lutte contre l'incendie -
Installations d'extinction à gaz - Partie 7 : Propriétés
physiques et conception des systèmes pour agent
extincteur IG-01 (ISO 14520-12:2015, modifiée)

Ortsfeste Brandbekämpfungsanlagen - Löschanlagen
mit gasförmigen Löschmitteln - Teil 7: Physikalische
Eigenschaften und Anlagenauslegung für Löschmittel
IG-01 (ISO 14520-12:2015, modifiziert)

This European Standard was approved by CEN on 25 September 2017.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

| Contents | Page |
|---|-------------|
| European foreword | 3 |
| 1 Scope | 4 |
| 2 Normative references | 4 |
| 3 Terms and definitions | 4 |
| 4 Characteristics and uses | 4 |
| 4.1 General | 4 |
| 4.2 Use of IG-01 systems | 5 |
| 5 Safety of personnel | 9 |
| 6 System design | 9 |
| 6.1 Fill pressure | 9 |
| 6.2 Superpressurization | 10 |
| 6.3 Extinguishant quantity | 11 |
| 7 Environmental Properties | 11 |

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 15004-7:2018](https://standards.iteh.ai/catalog/standards/sist/e7675ac1-6994-4d10-9c42-91deb29cc787/sist-en-15004-7-2018)

<https://standards.iteh.ai/catalog/standards/sist/e7675ac1-6994-4d10-9c42-91deb29cc787/sist-en-15004-7-2018>

European foreword

This document (EN 15004-7:2017) has been prepared by Technical Committee CEN/TC 191 “Fixed firefighting systems”, the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2018, and conflicting national standards shall be withdrawn at the latest by June 2018.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 15004-7:2008.

The text of the International Standard ISO 14520-12:2015 from Technical Committee ISO/TC 21 “Equipment for fire protection and firefighting” of the International Organization for Standardization (ISO) has been taken over as a European Standard by Technical Committee CEN/TC 191 “Fixed firefighting systems”, the secretariat of which is held by BSI, with common modifications which are indicated by a straight line in the margin of the text.

This European Standard will consist of the following parts, under the general title *Fixed firefighting systems – Gas extinguishing systems*:

- Part 1: *Design, installation and maintenance*;
- Part 2: *Physical properties and system design of gas extinguishing systems for FK-5-1-12 extinguishant*;
- Part 3: *Physical properties and system design of gas extinguishing systems for HCFC Blend A extinguishant*;
- Part 4: *Physical properties and system design of gas extinguishing systems for HFC 125 extinguishant*;
- Part 5: *Physical properties and system design of gas extinguishing systems for HFC 227ea extinguishant*;
- Part 6: *Physical properties and system design of gas extinguishing systems for HFC 23 extinguishant*;
- Part 7: *Physical properties and system design of gas extinguishing systems for IG-01 extinguishant*;
- Part 8: *Physical properties and system design of gas extinguishing systems for IG-100 extinguishant*;
- Part 9: *Physical properties and system design of gas extinguishing systems for IG-55 extinguishant*;
- Part 10: *Physical properties and system design of gas extinguishing systems for IG-541 extinguishant*.

The International Standards ISO 14520-2 and ISO 14520-11, which dealt with CF₃I and HFC 236fa extinguishants, respectively, have not been implemented by CEN, as CF₃I is only valid for local application and HFC 236fa extinguishant is only applicable for portable fire extinguishers and local application, respectively, which is not covered by the scope.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

1.1 This document specifies requirements for gaseous fire-extinguishing systems, with respect to the IG-01 extinguishant. It includes details of physical properties, specification, usage and safety aspects.

1.2 This document is applicable for systems operating at nominal pressures of 160 bar, 200 bar and 300 bar at 15 °C. This does not preclude the use of other systems, although design data for other pressures are not available at this time.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 15004-1:2017, *Fixed firefighting systems - Gas extinguishing systems - Part 1: Design, installation and maintenance*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 15004-1 apply.

4 Characteristics and uses

4.1 General

Extinguishant IG-01 shall comply with the specification shown in Table 1.

IG-01 is a colourless, odourless, electrically non-conductive gas at ambient (20 °C) temperatures, with a density approximately 1,4 times that of air.

The physical properties are shown in Table 2.

IG-01 extinguishes fires mainly by a reduction of the oxygen concentration in the atmosphere of the hazard enclosure.

Table 1 — Specification for IG-01

| Property | Requirement |
|------------------------------|------------------------|
| Purity | 99,9 % by volume, min. |
| Moisture | 50 ppm by mass, max. |
| Suspended matter or sediment | None visible |

Table 2 — Physical properties of IG-01

| Property | Units | Value |
|--|----------------------|--------|
| Molecular mass | — | 39,9 |
| Boiling point at 1,013 bar (absolute) | °C | -185,9 |
| Freezing point | °C | -189,4 |
| Critical temperature | °C | -122,3 |
| Critical pressure | bar abs | 49,0 |
| Critical volume | cm ³ /mol | — |
| Critical density | kg/m ³ | 536 |
| Vapour pressure 20 °C | bar abs | — |
| Liquid density 20 °C | kg/m ³ | — |
| Saturated vapour density 20 °C | kg/m ³ | — |
| Specific volume of superheated vapour at 1,013 bar and 20 °C | m ³ /kg | 0,602 |
| Chemical formula | Ar | |
| Chemical name | Argon | |

4.2 Use of IG-01 systems

IG-01 total flooding systems may be used for extinguishing fires of all classes within the limits specified in EN 15004-1:2017, Clause 4.

The extinguishant requirements per volume of protected space are shown in Table 3 for various levels of concentration. These are based on methods shown in EN 15004-1:2017, 7.6.

The extinguishing concentrations and design concentrations for heptane and surface class A hazards are shown in Table 4.

Table 3 — IG-01 total flooding quantity

| Temperature T °C | Specific vapour volume S m ³ /kg | Amount of IG-01 per unit volume of protected space, V/V (m ³ /m ³) | | | | | | | |
|--------------------------|---|--|-------|-------|-------|-------|-------|-------|-------|
| | | Design concentration (by volume) | | | | | | | |
| | | 34 % | 38 % | 42 % | 46 % | 50 % | 54 % | 58 % | 62 % |
| -40 | 0,4790 | 0,522 | 0,601 | 0,685 | 0,775 | 0,872 | 0,976 | 1,091 | 1,217 |
| -35 | 0,4893 | 0,511 | 0,588 | 0,671 | 0,758 | 0,853 | 0,956 | 1,068 | 1,191 |
| -30 | 0,4996 | 0,501 | 0,576 | 0,657 | 0,743 | 0,836 | 0,936 | 1,046 | 1,167 |
| -25 | 0,5098 | 0,491 | 0,565 | 0,644 | 0,728 | 0,819 | 0,917 | 1,025 | 1,143 |
| -20 | 0,5201 | 0,481 | 0,554 | 0,631 | 0,714 | 0,803 | 0,899 | 1,005 | 1,120 |
| -15 | 0,5304 | 0,472 | 0,543 | 0,619 | 0,700 | 0,787 | 0,882 | 0,985 | 1,099 |
| -10 | 0,5406 | 0,463 | 0,533 | 0,607 | 0,686 | 0,772 | 0,865 | 0,966 | 1,078 |
| -5 | 0,5509 | 0,454 | 0,523 | 0,596 | 0,674 | 0,758 | 0,849 | 0,948 | 1,058 |
| 0 | 0,5612 | 0,446 | 0,513 | 0,585 | 0,661 | 0,744 | 0,833 | 0,931 | 1,038 |
| 5 | 0,5715 | 0,438 | 0,504 | 0,574 | 0,649 | 0,731 | 0,818 | 0,914 | 1,020 |
| 10 | 0,5817 | 0,430 | 0,495 | 0,564 | 0,638 | 0,718 | 0,804 | 0,898 | 1,002 |
| 15 | 0,5920 | 0,423 | 0,486 | 0,554 | 0,627 | 0,705 | 0,790 | 0,883 | 0,984 |
| 20 | 0,6023 | 0,416 | 0,478 | 0,545 | 0,616 | 0,693 | 0,777 | 0,868 | 0,968 |
| 25 | 0,6126 | 0,409 | 0,470 | 0,536 | 0,606 | 0,682 | 0,764 | 0,853 | 0,951 |
| 30 | 0,6228 | 0,402 | 0,462 | 0,527 | 0,596 | 0,670 | 0,751 | 0,839 | 0,936 |
| 35 | 0,6331 | 0,395 | 0,455 | 0,518 | 0,586 | 0,659 | 0,739 | 0,825 | 0,920 |
| 40 | 0,6434 | 0,389 | 0,448 | 0,510 | 0,577 | 0,649 | 0,727 | 0,812 | 0,906 |
| 45 | 0,6536 | 0,383 | 0,440 | 0,502 | 0,568 | 0,639 | 0,716 | 0,799 | 0,892 |
| 50 | 0,6639 | 0,377 | 0,434 | 0,494 | 0,559 | 0,629 | 0,704 | 0,787 | 0,878 |
| 55 | 0,6742 | 0,371 | 0,427 | 0,487 | 0,550 | 0,619 | 0,694 | 0,775 | 0,864 |
| 60 | 0,6845 | 0,366 | 0,421 | 0,479 | 0,542 | 0,610 | 0,683 | 0,763 | 0,851 |
| 65 | 0,6947 | 0,360 | 0,414 | 0,472 | 0,534 | 0,601 | 0,673 | 0,752 | 0,839 |
| 70 | 0,7050 | 0,355 | 0,408 | 0,465 | 0,526 | 0,592 | 0,663 | 0,741 | 0,827 |
| 75 | 0,7153 | 0,350 | 0,403 | 0,459 | 0,519 | 0,584 | 0,654 | 0,730 | 0,815 |
| 80 | 0,7256 | 0,345 | 0,397 | 0,452 | 0,511 | 0,575 | 0,645 | 0,720 | 0,803 |
| 85 | 0,7358 | 0,340 | 0,391 | 0,446 | 0,504 | 0,567 | 0,636 | 0,710 | 0,792 |

| Temperature T °C | Specific vapour volume S m ³ /kg | Amount of IG-01 per unit volume of protected space, V/V (m ³ /m ³) | | | | | | | |
|--------------------------|---|--|-------|-------|-------|-------|-------|-------|-------|
| | | Design concentration (by volume) | | | | | | | |
| | | 34 % | 38 % | 42 % | 46 % | 50 % | 54 % | 58 % | 62 % |
| 90 | 0,7461 | 0,335 | 0,386 | 0,440 | 0,497 | 0,560 | 0,627 | 0,700 | 0,781 |
| 95 | 0,7564 | 0,331 | 0,381 | 0,434 | 0,491 | 0,552 | 0,618 | 0,691 | 0,770 |
| 100 | 0,7666 | 0,326 | 0,376 | 0,428 | 0,484 | 0,545 | 0,610 | 0,682 | 0,760 |

NOTE This information refers only to the product IG-01, and does not represent any other products containing argon as a component.

Symbols:

V/V is the agent volume requirements (m³/m³); i.e. the quantity Q_R (m³) of agent required at a reference temperature of 20 °C and a pressure of 1,013 bar per cubic metre of protected volume to produce the indicated concentration at the temperature specified:

$$Q_R = m \cdot S_R;$$

where

S_R is the specific reference volume (m³/kg); i.e. the specific vapour volume at the filling reference temperature for superheated IG-01 vapour at a pressure of 1,013 bar which may be approximated by the formula:

$$S_R = k_1 + k_2 \cdot T_R$$

where

$$k_1 = 0,561 \text{ 19} \quad \text{https://standards.iteh.ai/catalog/standards/sist/e7675ac1-6994-4d10-9c42-91deb29cc787/sist-en-15004-7-2018}$$

$$k_2 = 0,002 \text{ 054 5}$$

T_R is the reference temperature (°C); i.e. filling temperature (20°C in the table)

$$m = \frac{V}{S} \cdot \ln \left(\frac{100}{100 - c} \right)$$

V is the net volume of hazard (m³); i.e. the enclosed volume minus the fixed structures impervious to extinguishant;

T is the temperature (°C); i.e. the design temperature of the protected area;

S is the specific volume (m³/kg); the specific volume of superheated IG-01 vapour at a pressure of 1,013 bar may be approximated by the formula:

$$S = k_1 + k_2 \cdot T$$

c is the concentration (%); i.e. the volumetric concentration of IG-01 in air at the temperature indicated, and a pressure of 1,013 bar absolute.