

ETSI TS 138 413 V16.4.0 (2021-01)



**5G;
NG-RAN;
NG Application Protocol (NGAP)
(3GPP TS 38.413 version 16.4.0 Release 16)**

<https://standards.iteh.ai/catalog/standards/sist/72c41d54-d685-4a88-93d0-6fdc3e66ed30/etsi-ts-138-413-v16-4-0-2021-01>



ReferenceRTS/TSGR-0338413vg40

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Important notice

ETSI TS 138 413 V16.4.0 (2021-01)
<https://standards.iteh.ai/catalog/standards/sist/72c41d54-d685-4a88-93d0-6ddc5c9d30/etsi-ts-138-413-v16-4-0-2021-01>
The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

<https://standards.iteh.ai/catalog/standards/sist/72c41d54-d685-4a88-93d0-6fd03e66cd30/etsi-ts-138-413-v16-4-0-2021-01>

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology	2
Foreword	16
1 Scope	17
2 References	17
3 Definitions and abbreviations	18
3.1 Definitions	18
3.2 Abbreviations	19
4 General	20
4.1 Procedure Specification Principles	20
4.2 Forwards and Backwards Compatibility	21
4.3 Specification Notations	21
5 NGAP Services	21
6 Services Expected from Signalling Transport	22
7 Functions of NGAP	22
8 NGAP Procedures	22
8.1 List of NGAP Elementary Procedures	22
8.2 PDU Session Management Procedures	24
8.2.1 PDU Session Resource Setup	24
8.2.1.1 General	24
8.2.1.2 Successful Operation	25
8.2.1.3 Unsuccessful Operation	28
8.2.1.4 Abnormal Conditions	28
8.2.2 PDU Session Resource Release	29
8.2.2.1 General	29
8.2.2.2 Successful Operation	29
8.2.2.3 Unsuccessful Operation	30
8.2.2.4 Abnormal Conditions	30
8.2.3 PDU Session Resource Modify	30
8.2.3.1 General	30
8.2.3.2 Successful Operation	30
8.2.3.3 Unsuccessful Operation	33
8.2.3.4 Abnormal Conditions	33
8.2.4 PDU Session Resource Notify	34
8.2.4.1 General	34
8.2.4.2 Successful Operation	34
8.2.4.3 Abnormal Conditions	35
8.2.5 PDU Session Resource Modify Indication	35
8.2.5.1 General	35
8.2.5.2 Successful Operation	35
8.2.5.3 Unsuccessful Operation	37
8.2.5.4 Abnormal Conditions	37
8.3 UE Context Management Procedures	37
8.3.1 Initial Context Setup	37
8.3.1.1 General	37
8.3.1.2 Successful Operation	37
8.3.1.3 Unsuccessful Operation	40
8.3.1.4 Abnormal Conditions	40
8.3.2 UE Context Release Request (NG-RAN node initiated)	41
8.3.2.1 General	41

8.3.2.2	Successful Operation.....	41
8.3.2.3	Abnormal Conditions	41
8.3.3	UE Context Release (AMF initiated).....	41
8.3.3.1	General	41
8.3.3.2	Successful Operation.....	42
8.3.3.3	Unsuccessful Operation	42
8.3.3.4	Abnormal Conditions	42
8.3.4	UE Context Modification.....	42
8.3.4.1	General	42
8.3.4.2	Successful Operation.....	43
8.3.4.3	Unsuccessful Operation	45
8.3.4.4	Abnormal Conditions	45
8.3.5	RRC Inactive Transition Report	45
8.3.5.1	General	45
8.3.5.2	Successful Operation.....	45
8.3.5.3	Abnormal Conditions	45
8.3.6	Connection Establishment Indication	46
8.3.6.1	General	46
8.3.6.2	Successful Operation.....	46
8.3.6.3	Abnormal Conditions	47
8.3.7	AMF CP Relocation Indication	47
8.3.7.1	General	47
8.3.7.2	Successful Operation.....	47
8.3.7.3	Abnormal Conditions	47
8.3.8	RAN CP Relocation Indication.....	47
8.3.8.1	General	47
8.3.8.2	Successful Operation.....	48
8.3.8.3	Abnormal Conditions	48
8.3.9	Retrieve UE Information	48
8.3.9.1	General	48
8.3.9.2	Successful Operation.....	49
8.3.9.3	Abnormal Conditions	49
8.3.10	UE Information Transfer	49
8.3.10.1	General	49
8.3.10.2	Successful Operation.....	49
8.3.10.3	Abnormal Conditions	50
8.3.11	UE Context Suspend	50
8.3.11.1	General	50
8.3.11.2	Successful Operation.....	50
8.3.11.3	Unsuccessful Operation	51
8.3.11.4	Abnormal Conditions	51
8.3.12	UE Context Resume.....	51
8.3.12.1	General	51
8.3.12.2	Successful Operation.....	51
8.3.12.3	Unsuccessful Operation	52
8.4	UE Mobility Management Procedures	52
8.4.1	Handover Preparation	52
8.4.1.1	General	52
8.4.1.2	Successful Operation.....	53
8.4.1.3	Unsuccessful Operation	55
8.4.1.4	Abnormal Conditions	55
8.4.2	Handover Resource Allocation	55
8.4.2.1	General	55
8.4.2.2	Successful Operation.....	56
8.4.2.3	Unsuccessful Operation	60
8.4.2.4	Abnormal Conditions	60
8.4.3	Handover Notification	61
8.4.3.1	General	61
8.4.3.2	Successful Operation.....	61
8.4.3.3	Abnormal Conditions	61
8.4.4	Path Switch Request	61
8.4.4.1	General	61

8.4.4.2	Successful Operation.....	62
8.4.4.3	Unsuccessful Operation	65
8.4.4.4	Abnormal Conditions	65
8.4.5	Handover Cancellation	65
8.4.5.1	General	65
8.4.5.2	Successful Operation.....	65
8.4.5.3	Unsuccessful Operation	66
8.4.5.4	Abnormal Conditions	66
8.4.6	Uplink RAN Status Transfer.....	66
8.4.6.1	General	66
8.4.6.2	Successful Operation.....	66
8.4.6.3	Abnormal Conditions	66
8.4.7	Downlink RAN Status Transfer.....	66
8.4.7.1	General	66
8.4.7.2	Successful Operation.....	67
8.4.7.3	Abnormal Conditions	67
8.4.8	Handover Success	67
8.4.8.1	General	67
8.4.8.2	Successful Operation.....	67
8.4.8.3	Abnormal Conditions	68
8.4.9	Uplink RAN Early Status Transfer	68
8.4.9.1	General	68
8.4.9.2	Successful Operation.....	68
8.4.9.3	Abnormal Conditions	68
8.4.10	Downlink RAN Early Status Transfer	68
8.4.10.1	General	68
8.4.10.2	Successful Operation.....	69
8.4.10.3	Abnormal Conditions	69
8.5	Paging Procedures	69
8.5.1	Paging	69
8.5.1.1	General	69
8.5.1.2	Successful Operation.....	69
8.5.1.3	Abnormal Conditions	70
8.6	Transport of NAS Messages Procedures	70
8.6.1	Initial UE Message.....	70
8.6.1.1	General	70
8.6.1.2	Successful Operation.....	71
8.6.1.3	Abnormal Conditions	71
8.6.2	Downlink NAS Transport.....	72
8.6.2.1	General	72
8.6.2.2	Successful Operation.....	72
8.6.2.3	Abnormal Conditions	73
8.6.3	Uplink NAS Transport.....	73
8.6.3.1	General	73
8.6.3.2	Successful Operation.....	74
8.6.3.3	Abnormal Conditions	74
8.6.4	NAS Non Delivery Indication	74
8.6.4.1	General	74
8.6.4.2	Successful Operation.....	74
8.6.4.3	Abnormal Conditions	74
8.6.5	Reroute NAS Request.....	75
8.6.5.1	General	75
8.6.5.2	Successful Operation.....	75
8.6.5.3	Abnormal Conditions	75
8.7	Interface Management Procedures	75
8.7.1	NG Setup	75
8.7.1.1	General	75
8.7.1.2	Successful Operation.....	76
8.7.1.3	Unsuccessful Operation	77
8.7.1.4	Abnormal Conditions	77
8.7.2	RAN Configuration Update	77
8.7.2.1	General	77

8.7.2.2	Successful Operation.....	77
8.7.2.3	Unsuccessful Operation	78
8.7.2.4	Abnormal Conditions	78
8.7.3	AMF Configuration Update.....	79
8.7.3.1	General	79
8.7.3.2	Successful Operation.....	79
8.7.3.3	Unsuccessful Operation	80
8.7.3.4	Abnormal Conditions	80
8.7.4	NG Reset.....	80
8.7.4.1	General	80
8.7.4.2	Successful Operation.....	81
8.7.4.2.1	NG Reset initiated by the AMF	81
8.7.4.2.2	NG Reset initiated by the NG-RAN node	82
8.7.4.3	Unsuccessful Operation	82
8.7.4.4	Abnormal Conditions	82
8.7.4.4.1	Abnormal Condition at the 5GC.....	82
8.7.4.4.2	Abnormal Condition at the NG-RAN.....	83
8.7.4.4.3	Crossing of NG RESET Messages	83
8.7.5	Error Indication.....	83
8.7.5.1	General	83
8.7.5.2	Successful Operation.....	83
8.7.5.3	Abnormal Conditions	84
8.7.6	AMF Status Indication.....	84
8.7.6.1	General	84
8.7.6.2	Successful Operation.....	84
8.7.6.3	Abnormal Conditions	85
8.7.7	Overload Start	85
8.7.7.1	General	85
8.7.7.2	Successful Operation.....	85
8.7.7.3	Abnormal Conditions	86
8.7.8	Overload Stop	86
8.7.8.1	General	86
8.7.8.2	Successful Operation.....	86
8.7.8.3	Abnormal Conditions	86
8.8	Configuration Transfer Procedures	86
8.8.1	Uplink RAN Configuration Transfer	86
8.8.1.1	General	86
8.8.1.2	Successful Operation.....	87
8.8.1.3	Abnormal Conditions	87
8.8.2	Downlink RAN Configuration Transfer	87
8.8.2.1	General	87
8.8.2.2	Successful Operation.....	87
8.8.2.3	Abnormal Conditions	88
8.9	Warning Message Transmission Procedures.....	88
8.9.1	Write-Replace Warning	88
8.9.1.1	General	88
8.9.1.2	Successful Operation.....	89
8.9.1.3	Unsuccessful Operation	90
8.9.1.4	Abnormal Conditions	90
8.9.2	PWS Cancel.....	90
8.9.2.1	General	90
8.9.2.2	Successful Operation.....	90
8.9.2.3	Unsuccessful Operation	91
8.9.2.4	Abnormal Conditions	91
8.9.3	PWS Restart Indication.....	91
8.9.3.1	General	91
8.9.3.2	Successful Operation.....	91
8.9.3.3	Abnormal Conditions	91
8.9.4	PWS Failure Indication.....	92
8.9.4.1	General	92
8.9.4.2	Successful Operation.....	92
8.9.4.3	Abnormal Conditions	92

8.10	NRPPa Transport Procedures.....	92
8.10.1	General.....	92
8.10.2	Successful Operations.....	92
8.10.2.1	DOWNLINK UE ASSOCIATED NRPPA TRANSPORT.....	92
8.10.2.2	UPLINK UE ASSOCIATED NRPPA TRANSPORT.....	93
8.10.2.3	DOWNLINK NON UE ASSOCIATED NRPPA TRANSPORT.....	93
8.10.2.4	UPLINK NON UE ASSOCIATED NRPPA TRANSPORT.....	93
8.10.3	Unsuccessful Operations.....	94
8.10.4	Abnormal Conditions.....	94
8.11	Trace Procedures.....	94
8.11.1	Trace Start.....	94
8.11.1.1	General.....	94
8.11.1.2	Successful Operation.....	94
8.11.1.3	Abnormal Conditions.....	95
8.11.2	Trace Failure Indication.....	95
8.11.2.1	General.....	95
8.11.2.2	Successful Operation.....	95
8.11.2.3	Abnormal Conditions.....	95
8.11.3	Deactivate Trace.....	95
8.11.3.1	General.....	95
8.11.3.2	Successful Operation.....	96
8.11.3.3	Abnormal Conditions.....	96
8.11.4	Cell Traffic Trace.....	96
8.11.4.1	General.....	96
8.11.4.2	Successful Operation.....	96
8.11.4.3	Abnormal Conditions.....	96
8.12	Location Reporting Procedures.....	97
8.12.1	Location Reporting Control.....	97
8.12.1.1	General.....	97
8.12.1.2	Successful Operation.....	97
8.12.1.3	Abnormal Conditions.....	98
8.12.2	Location Reporting Failure Indication.....	98
8.12.2.1	General.....	98
8.12.2.2	Successful Operation.....	98
8.12.2.3	Abnormal Conditions.....	98
8.12.3	Location Report.....	98
8.12.3.1	General.....	98
8.12.3.2	Successful Operation.....	99
8.12.3.3	Abnormal Conditions.....	99
8.13	UE TNLA Binding Procedures.....	99
8.13.1	UE TNLA Binding Release.....	99
8.13.1.1	General.....	99
8.13.1.2	Successful Operation.....	99
8.13.1.3	Abnormal Conditions.....	100
8.14	UE Radio Capability Management Procedures.....	100
8.14.1	UE Radio Capability Info Indication.....	100
8.14.1.1	General.....	100
8.14.1.2	Successful Operation.....	100
8.14.1.3	Abnormal Conditions.....	100
8.14.2	UE Radio Capability Check.....	100
8.14.2.1	General.....	100
8.14.2.2	Successful Operation.....	101
8.14.2.3	Unsuccessful Operation.....	101
8.14.2.4	Abnormal Conditions.....	101
8.14.3	UE Radio Capability ID Mapping.....	101
8.14.3.1	General.....	101
8.14.3.2	Successful Operation.....	102
8.14.3.3	Unsuccessful Operation.....	102
8.14.3.4	Abnormal Conditions.....	102
8.15	Data Usage Reporting Procedures.....	102
8.15.1	Secondary RAT Data Usage Report.....	102
8.15.1.1	General.....	102

8.15.1.2	Successful Operation.....	102
8.15.1.3	Abnormal Conditions	103
8.16	RIM Information Transfer Procedures	103
8.16.1	Uplink RIM Information Transfer	103
8.16.1.1	General	103
8.16.1.2	Successful Operation.....	103
8.16.1.3	Abnormal Conditions	103
8.16.2	Downlink RIM Information Transfer	103
8.16.2.1	General	103
8.16.2.2	Successful Operation.....	104
8.16.2.3	Abnormal Conditions	104
9	Elements for NGAP Communication.....	104
9.0	General	104
9.1	Tabular Format Contents.....	104
9.1.1	Presence	104
9.1.2	Criticality	105
9.1.3	Range	105
9.1.4	Assigned Criticality	105
9.2	Message Functional Definition and Content	105
9.2.1	PDU Session Management Messages	105
9.2.1.1	PDU SESSION RESOURCE SETUP REQUEST.....	105
9.2.1.2	PDU SESSION RESOURCE SETUP RESPONSE.....	106
9.2.1.3	PDU SESSION RESOURCE RELEASE COMMAND	107
9.2.1.4	PDU SESSION RESOURCE RELEASE RESPONSE	108
9.2.1.5	PDU SESSION RESOURCE MODIFY REQUEST	108
9.2.1.6	PDU SESSION RESOURCE MODIFY RESPONSE	110
9.2.1.7	PDU SESSION RESOURCE NOTIFY	110
9.2.1.8	PDU SESSION RESOURCE MODIFY INDICATION.....	111
9.2.1.9	PDU SESSION RESOURCE MODIFY CONFIRM	112
9.2.2	UE Context Management Messages	113
9.2.2.1	INITIAL CONTEXT SETUP REQUEST	113
9.2.2.2	INITIAL CONTEXT SETUP RESPONSE	115
9.2.2.3	INITIAL CONTEXT SETUP FAILURE	116
9.2.2.4	UE CONTEXT RELEASE REQUEST	117
9.2.2.5	UE CONTEXT RELEASE COMMAND	117
9.2.2.6	UE CONTEXT RELEASE COMPLETE	118
9.2.2.7	UE CONTEXT MODIFICATION REQUEST	118
9.2.2.8	UE CONTEXT MODIFICATION RESPONSE.....	119
9.2.2.9	UE CONTEXT MODIFICATION FAILURE	120
9.2.2.10	RRC INACTIVE TRANSITION REPORT.....	120
9.2.2.11	CONNECTION ESTABLISHMENT INDICATION.....	120
9.2.2.12	AMF CP RELOCATION INDICATION	121
9.2.2.13	RAN CP RELOCATION INDICATION.....	121
9.2.2.14	RETRIEVE UE INFORMATION	121
9.2.2.15	UE INFORMATION TRANSFER	122
9.2.2.16	UE CONTEXT SUSPEND REQUEST	122
9.2.2.17	UE CONTEXT SUSPEND RESPONSE	123
9.2.2.18	UE CONTEXT SUSPEND FAILURE	123
9.2.2.19	UE CONTEXT RESUME REQUEST	123
9.2.2.20	UE CONTEXT RESUME RESPONSE.....	124
9.2.2.21	UE CONTEXT RESUME FAILURE	125
9.2.3	UE Mobility Management Messages	125
9.2.3.1	HANDOVER REQUIRED	125
9.2.3.2	HANDOVER COMMAND	126
9.2.3.3	HANDOVER PREPARATION FAILURE	127
9.2.3.4	HANDOVER REQUEST	128
9.2.3.5	HANDOVER REQUEST ACKNOWLEDGE.....	130
9.2.3.6	HANDOVER FAILURE	131
9.2.3.7	HANDOVER NOTIFY	131
9.2.3.8	PATH SWITCH REQUEST	132
9.2.3.9	PATH SWITCH REQUEST ACKNOWLEDGE	134

9.2.3.10	PATH SWITCH REQUEST FAILURE	136
9.2.3.11	HANDOVER CANCEL	136
9.2.3.12	HANDOVER CANCEL ACKNOWLEDGE	137
9.2.3.13	UPLINK RAN STATUS TRANSFER	137
9.2.3.14	DOWNLINK RAN STATUS TRANSFER	137
9.2.3.15	HANDOVER SUCCESS	137
9.2.3.16	UPLINK RAN EARLY STATUS TRANSFER	138
9.2.3.17	DOWNLINK RAN EARLY STATUS TRANSFER	138
9.2.4	Paging Messages	138
9.2.4.1	PAGING	138
9.2.5	NAS Transport Messages	140
9.2.5.1	INITIAL UE MESSAGE	140
9.2.5.2	DOWNLINK NAS TRANSPORT	141
9.2.5.3	UPLINK NAS TRANSPORT	141
9.2.5.4	NAS NON DELIVERY INDICATION	142
9.2.5.5	REROUTE NAS REQUEST	142
9.2.6	Interface Management Messages	142
9.2.6.1	NG SETUP REQUEST	142
9.2.6.2	NG SETUP RESPONSE	143
9.2.6.3	NG SETUP FAILURE	144
9.2.6.4	RAN CONFIGURATION UPDATE	144
9.2.6.5	RAN CONFIGURATION UPDATE ACKNOWLEDGE	146
9.2.6.6	RAN CONFIGURATION UPDATE FAILURE	146
9.2.6.7	AMF CONFIGURATION UPDATE	146
9.2.6.8	AMF CONFIGURATION UPDATE ACKNOWLEDGE	148
9.2.6.9	AMF CONFIGURATION UPDATE FAILURE	148
9.2.6.10	AMF STATUS INDICATION	148
9.2.6.11	NG RESET	149
9.2.6.12	NG RESET ACKNOWLEDGE	149
9.2.6.13	ERROR INDICATION	149
9.2.6.14	OVERLOAD START	150
9.2.6.15	OVERLOAD STOP	150
9.2.7	Configuration Transfer Messages	150
9.2.7.1	UPLINK RAN CONFIGURATION TRANSFER	150
9.2.7.2	DOWNLINK RAN CONFIGURATION TRANSFER	151
9.2.8	Warning Message Transmission Messages	151
9.2.8.1	WRITE-REPLACE WARNING REQUEST	151
9.2.8.2	WRITE-REPLACE WARNING RESPONSE	152
9.2.8.3	PWS CANCEL REQUEST	152
9.2.8.4	PWS CANCEL RESPONSE	152
9.2.8.5	PWS RESTART INDICATION	153
9.2.8.6	PWS FAILURE INDICATION	153
9.2.9	NRPPa Transport Messages	154
9.2.9.1	DOWNLINK UE ASSOCIATED NRPPA TRANSPORT	154
9.2.9.2	UPLINK UE ASSOCIATED NRPPA TRANSPORT	154
9.2.9.3	DOWNLINK NON UE ASSOCIATED NRPPA TRANSPORT	155
9.2.9.4	UPLINK NON UE ASSOCIATED NRPPA TRANSPORT	155
9.2.10	Trace Messages	155
9.2.10.1	TRACE START	155
9.2.10.2	TRACE FAILURE INDICATION	155
9.2.10.3	DEACTIVATE TRACE	155
9.2.10.4	CELL TRAFFIC TRACE	156
9.2.11	Location Reporting Messages	156
9.2.11.1	LOCATION REPORTING CONTROL	156
9.2.11.2	LOCATION REPORTING FAILURE INDICATION	157
9.2.11.3	LOCATION REPORT	157
9.2.12	UE TNLA Binding Messages	157
9.2.12.1	UE TNLA BINDING RELEASE REQUEST	157
9.2.13	UE Radio Capability Management Messages	158
9.2.13.1	UE RADIO CAPABILITY INFO INDICATION	158
9.2.13.2	UE RADIO CAPABILITY CHECK REQUEST	158
9.2.13.3	UE RADIO CAPABILITY CHECK RESPONSE	158

9.2.13.4	UE RADIO CAPABILITY ID MAPPING REQUEST	158
9.2.13.5	UE RADIO CAPABILITY ID MAPPING RESPONSE	159
9.2.14	Data Usage Reporting Messages	159
9.2.14.1	SECONDARY RAT DATA USAGE REPORT	159
9.2.15	RIM Information Transfer Messages	159
9.2.15.1	UPLINK RIM INFORMATION TRANSFER	159
9.2.15.2	DOWNLINK RIM INFORMATION TRANSFER	160
9.3	Information Element Definitions	160
9.3.1	Radio Network Layer Related IEs	160
9.3.1.1	Message Type	160
9.3.1.2	Cause	160
9.3.1.3	Criticality Diagnostics	166
9.3.1.4	Bit Rate	166
9.3.1.5	Global RAN Node ID	167
9.3.1.6	Global gNB ID	167
9.3.1.7	NR CGI	167
9.3.1.8	Global ng-eNB ID	168
9.3.1.9	E-UTRA CGI	168
9.3.1.10	GBR QoS Flow Information	168
9.3.1.11	Void	169
9.3.1.12	QoS Flow Level QoS Parameters	169
9.3.1.13	QoS Flow List with Cause	170
9.3.1.14	Trace Activation	171
9.3.1.15	Core Network Assistance Information for RRC INACTIVE	171
9.3.1.16	User Location Information	172
9.3.1.17	Slice Support List	174
9.3.1.18	Dynamic 5QI Descriptor	174
9.3.1.19	Allocation and Retention Priority	176
9.3.1.20	Source to Target Transparent Container	176
9.3.1.21	Target to Source Transparent Container	177
9.3.1.22	Handover Type	177
9.3.1.23	MICO Mode Indication	178
9.3.1.24	S-NSSAI	178
9.3.1.25	Target ID	178
9.3.1.26	Emergency Fallback Indicator	178
9.3.1.27	Security Indication	179
9.3.1.28	Non Dynamic 5QI Descriptor	179
9.3.1.29	Source NG-RAN Node to Target NG-RAN Node Transparent Container	180
9.3.1.30	Target NG-RAN Node to Source NG-RAN Node Transparent Container	181
9.3.1.31	Allowed NSSAI	182
9.3.1.32	Relative AMF Capacity	182
9.3.1.33	DL Forwarding	182
9.3.1.34	DRBs to QoS Flows Mapping List	183
9.3.1.35	Message Identifier	183
9.3.1.36	Serial Number	183
9.3.1.37	Warning Area List	183
9.3.1.38	Number of Broadcasts Requested	184
9.3.1.39	Warning Type	184
9.3.1.40	Void	184
9.3.1.41	Data Coding Scheme	184
9.3.1.42	Warning Message Contents	185
9.3.1.43	Broadcast Completed Area List	185
9.3.1.44	Broadcast Cancelled Area List	186
9.3.1.45	Number of Broadcasts	188
9.3.1.46	Concurrent Warning Message Indicator	188
9.3.1.47	Cancel-All Warning Messages Indicator	188
9.3.1.48	Emergency Area ID	188
9.3.1.49	Repetition Period	188
9.3.1.50	PDU Session ID	189
9.3.1.51	QoS Flow Identifier	189
9.3.1.52	PDU Session Type	189
9.3.1.53	DRB ID	189

9.3.1.54	Masked IMEISV	189
9.3.1.55	New Security Context Indicator	190
9.3.1.56	Time to Wait	190
9.3.1.57	Global N3IWF ID	190
9.3.1.58	UE Aggregate Maximum Bit Rate	190
9.3.1.59	Security Result	191
9.3.1.60	User Plane Security Information	191
9.3.1.61	Index to RAT/Frequency Selection Priority	191
9.3.1.62	Data Forwarding Accepted	191
9.3.1.63	Data Forwarding Not Possible	191
9.3.1.64	Direct Forwarding Path Availability	192
9.3.1.65	Location Reporting Request Type	192
9.3.1.66	Area of Interest	193
9.3.1.67	UE Presence in Area of Interest List	193
9.3.1.68	UE Radio Capability for Paging	193
9.3.1.69	Assistance Data for Paging	194
9.3.1.70	Assistance Data for Recommended Cells	194
9.3.1.71	Recommended Cells for Paging	194
9.3.1.72	Paging Attempt Information	194
9.3.1.73	NG-RAN CGI	195
9.3.1.74	UE Radio Capability	195
9.3.1.74a	UE Radio Capability – E-UTRA Format	195
9.3.1.75	Time Stamp	195
9.3.1.76	Location Reporting Reference ID	196
9.3.1.77	Data Forwarding Response DRB List	196
9.3.1.78	Paging Priority	196
9.3.1.79	Packet Loss Rate	196
9.3.1.80	Packet Delay Budget	196
9.3.1.81	Packet Error Rate	197
9.3.1.82	Averaging Window	197
9.3.1.83	Maximum Data Burst Volume	197
9.3.1.84	Priority Level	197
9.3.1.85	Mobility Restriction List	197
9.3.1.86	UE Security Capabilities	199
9.3.1.87	Security Key	200
9.3.1.88	Security Context	201
9.3.1.89	IMS Voice Support Indicator	201
9.3.1.90	Paging DRX	201
9.3.1.91	RRC Inactive Transition Report Request	201
9.3.1.92	RRC State	201
9.3.1.93	Expected UE Behaviour	202
9.3.1.94	Expected UE Activity Behaviour	202
9.3.1.95	UE History Information	203
9.3.1.96	Last Visited Cell Information	203
9.3.1.97	Last Visited NG-RAN Cell Information	204
9.3.1.98	Cell Type	204
9.3.1.99	Associated QoS Flow List	204
9.3.1.100	Information on Recommended Cells and RAN Nodes for Paging	204
9.3.1.101	Recommended RAN Nodes for Paging	205
9.3.1.102	PDU Session Aggregate Maximum Bit Rate	205
9.3.1.103	Maximum Integrity Protected Data Rate	205
9.3.1.104	Overload Response	206
9.3.1.105	Overload Action	206
9.3.1.106	Traffic Load Reduction Indication	206
9.3.1.107	Slice Overload List	206
9.3.1.108	RAN Status Transfer Transparent Container	207
9.3.1.109	COUNT Value for PDCP SN Length 12	210
9.3.1.110	COUNT Value for PDCP SN Length 18	210
9.3.1.111	RRC Establishment Cause	210
9.3.1.112	Warning Area Coordinates	210
9.3.1.113	Network Instance	210
9.3.1.114	Secondary RAT Usage Information	211

9.3.1.115	Volume Timed Report List	211
9.3.1.116	Redirection for Voice EPS Fallback	212
9.3.1.117	UE Retention Information	212
9.3.1.118	UL Forwarding	212
9.3.1.119	CN Assisted RAN Parameters Tuning	212
9.3.1.120	Common Network Instance	212
9.3.1.121	Data Forwarding Response E-RAB List	213
9.3.1.122	gNB Set ID	213
9.3.1.123	RNC-ID	213
9.3.1.124	Extended RNC-ID	213
9.3.1.125	RAT Information	213
9.3.1.126	Extended RAT Restriction Information	213
9.3.1.127	SgNB UE X2AP ID	214
9.3.1.128	SRVCC Operation Possible	214
9.3.1.129	IAB Authorized	214
9.3.1.130	TSC Traffic Characteristics	214
9.3.1.131	TSC Assistance Information	215
9.3.1.132	Periodicity	215
9.3.1.133	Burst Arrival Time	215
9.3.1.134	Redundant QoS Flow Indicator	215
9.3.1.135	Extended Packet Delay Budget	215
9.3.1.136	Redundant PDU Session Information	216
9.3.1.137	NB-IoT Default Paging DRX	216
9.3.1.138	NB-IoT Paging eDRX Information	216
9.3.1.139	NB-IoT Paging DRX	216
9.3.1.140	Enhanced Coverage Restriction	216
9.3.1.141	Paging Assistance Data for CE Capable UE	217
9.3.1.142	UE Radio Capability ID	217
9.3.1.143	WUS Assistance Information	217
9.3.1.144	UE Differentiation Information	217
9.3.1.145	NB-IoT UE Priority	219
9.3.1.146	NR V2X Services Authorized	219
9.3.1.147	LTE V2X Services Authorized	219
9.3.1.148	NR UE Sidelink Aggregate Maximum Bit Rate	219
9.3.1.149	LTE UE Sidelink Aggregate Maximum Bit Rate	219
9.3.1.150	PC5 QoS Parameters	220
9.3.1.151	Alternative QoS Parameters Set List	220
9.3.1.152	Alternative QoS Parameters Set Index	221
9.3.1.153	Alternative QoS Parameters Set Notify Index	221
9.3.1.154	Paging eDRX Information	221
9.3.1.155	CE-mode-B Restricted	221
9.3.1.156	CE-mode-B Support Indicator	222
9.3.1.157	LTE-M Indication	222
9.3.1.158	Suspend Request Indication	222
9.3.1.159	Suspend Response Indication	222
9.3.1.160	UE User Plane CIoT Support Indicator	222
9.3.1.161	Global TNGF ID	223
9.3.1.162	Global W-AGF ID	223
9.3.1.163	Global TWIF ID	223
9.3.1.164	W-AGF User Location Information	224
9.3.1.165	Global eNB ID	224
9.3.1.166	UE History Information from UE	224
9.3.1.167	MDT Configuration	225
9.3.1.168	MDT PLMN List	225
9.3.1.169	MDT Configuration-NR	225
9.3.1.170	MDT Configuration-EUTRA	227
9.3.1.171	M1 Configuration	228
9.3.1.172	M4 Configuration	228
9.3.1.173	M5 Configuration	229
9.3.1.174	M6 Configuration	229
9.3.1.175	M7 Configuration	229
9.3.1.176	MDT Location Information	229

9.3.1.177	Bluetooth Measurement Configuration	230
9.3.1.178	WLAN Measurement Configuration	230
9.3.1.179	Sensor Measurement Configuration	231
9.3.1.180	Event Trigger Logged MDT Configuration	231
9.3.1.181	NR Frequency Info	232
9.3.1.182	Area Scope of Neighbour Cells	232
9.3.1.183	NPN Paging Assistance Information	232
9.3.1.184	NPN Mobility Information	233
9.3.1.185	Cell CAG Information	233
9.3.1.186	Target to Source Failure Transparent Container	233
9.3.1.187	Target NG-RAN Node to Source NG-RAN Node Failure Transparent Container	233
9.3.1.188	DAPS Request Information	234
9.3.1.189	DAPS Response Information	234
9.3.1.190	Early Status Transfer Transparent Container	234
9.3.1.191	Extended Slice Support List	235
9.3.1.192	UE Capability Info Request	235
9.3.1.193	Extended RAN Node Name	235
9.3.2	Transport Network Layer Related IEs	235
9.3.2.1	QoS Flow per TNL Information List	235
9.3.2.2	UP Transport Layer Information	236
9.3.2.3	E-RAB ID	236
9.3.2.4	Transport Layer Address	236
9.3.2.5	GTP-TEID	236
9.3.2.6	CP Transport Layer Information	237
9.3.2.7	TNL Association List	237
9.3.2.8	QoS Flow per TNL Information	237
9.3.2.9	TNL Association Usage	237
9.3.2.10	TNL Address Weight Factor	238
9.3.2.11	UP Transport Layer Information Pair List	238
9.3.2.12	UP Transport Layer Information List	238
9.3.2.13	QoS Flow List with Data Forwarding	238
9.3.2.14	URI	239
9.3.3	NAS Related IEs	239
9.3.3.1	AMF UE NGAP ID	239
9.3.3.2	RAN UE NGAP ID	239
9.3.3.3	GUAMI	239
9.3.3.4	NAS-PDU	240
9.3.3.5	PLMN Identity	240
9.3.3.6	SON Configuration Transfer	240
9.3.3.7	SON Information	240
9.3.3.8	SON Information Reply	241
9.3.3.9	Xn TNL Configuration Info	241
9.3.3.10	TAC	242
9.3.3.11	TAI	242
9.3.3.12	AMF Set ID	242
9.3.3.13	Routing ID	242
9.3.3.14	NRPPa-PDU	242
9.3.3.15	RAN Paging Priority	243
9.3.3.16	EPS TAC	243
9.3.3.17	EPS TAI	243
9.3.3.18	UE Paging Identity	243
9.3.3.19	AMF Pointer	243
9.3.3.20	5G-S-TMSI	243
9.3.3.21	AMF Name	244
9.3.3.22	Paging Origin	244
9.3.3.23	UE Identity Index Value	244
9.3.3.24	Periodic Registration Update Timer	245
9.3.3.25	UE-associated Logical NG-connection List	245
9.3.3.26	NAS Security Parameters from NG-RAN	245
9.3.3.27	Source to Target AMF Information Reroute	246
9.3.3.28	RIM Information Transfer	246
9.3.3.29	RIM Information	246

9.3.3.30	LAI	247
9.3.3.31	Extended Connected Time	247
9.3.3.32	End Indication	247
9.3.3.33	Inter-system SON Configuration Transfer	247
9.3.3.34	Inter-system SON Information	248
9.3.3.35	SON Information Report	248
9.3.3.36	Inter-system SON Information Report	248
9.3.3.37	Failure Indication	249
9.3.3.38	Inter-system Failure Indication	249
9.3.3.39	HO Report	249
9.3.3.40	Inter-system HO Report	250
9.3.3.41	UE RLF Report Container	251
9.3.3.42	NID	252
9.3.3.43	CAG ID	252
9.3.3.44	NPN Support	252
9.3.3.45	Allowed PNI-NPN List	252
9.3.3.46	NPN Access Information	253
9.3.3.47	Cell CAG List	253
9.3.3.48	UL CP Security Information	253
9.3.3.49	DL CP Security Information	254
9.3.3.50	Configured TAC Indication	254
9.3.3.51	Extended AMF Name	254
9.3.4	SMF Related IEs	254
9.3.4.1	PDU Session Resource Setup Request Transfer	254
9.3.4.2	PDU Session Resource Setup Response Transfer	256
9.3.4.3	PDU Session Resource Modify Request Transfer	258
9.3.4.4	PDU Session Resource Modify Response Transfer	260
9.3.4.5	PDU Session Resource Notify Transfer	262
9.3.4.6	PDU Session Resource Modify Indication Transfer	262
9.3.4.7	PDU Session Resource Modify Confirm Transfer	263
9.3.4.8	Path Switch Request Transfer	264
9.3.4.9	Path Switch Request Acknowledge Transfer	266
9.3.4.10	Handover Command Transfer	266
9.3.4.11	Handover Request Acknowledge Transfer	267
9.3.4.12	PDU Session Resource Release Command Transfer	269
9.3.4.13	PDU Session Resource Notify Released Transfer	269
9.3.4.14	Handover Required Transfer	269
9.3.4.15	Path Switch Request Setup Failed Transfer	269
9.3.4.16	PDU Session Resource Setup Unsuccessful Transfer	270
9.3.4.17	PDU Session Resource Modify Unsuccessful Transfer	270
9.3.4.18	Handover Preparation Unsuccessful Transfer	270
9.3.4.19	Handover Resource Allocation Unsuccessful Transfer	270
9.3.4.20	Path Switch Request Unsuccessful Transfer	270
9.3.4.21	PDU Session Resource Release Response Transfer	270
9.3.4.22	PDU Session Resource Modify Indication Unsuccessful Transfer	270
9.3.4.23	Secondary RAT Data Usage Report Transfer	271
9.3.4.24	UE Context Resume Request Transfer	271
9.3.4.25	UE Context Resume Response Transfer	271
9.3.4.26	UE Context Suspend Request Transfer	271
9.4	Message and Information Element Abstract Syntax (with ASN.1)	271
9.4.1	General	271
9.4.2	Usage of private message mechanism for non-standard use	272
9.4.3	Elementary Procedure Definitions	273
9.4.4	PDU Definitions	287
9.4.5	Information Element Definitions	338
9.4.6	Common Definitions	438
9.4.7	Constant Definitions	439
9.4.8	Container Definitions	448
9.5	Message Transfer Syntax	452
9.6	Timers	452
10	Handling of Unknown, Unforeseen and Erroneous Protocol Data	453