
Geometrical product specifications (GPS) — Population specification

Spécification géométrique des produits (GPS) — Spécification de population

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[ISO 18391:2016](https://standards.iteh.ai/catalog/standards/sist/3306f836-0dd5-43ef-a102-4d04bd7faea8/iso-18391-2016)

<https://standards.iteh.ai/catalog/standards/sist/3306f836-0dd5-43ef-a102-4d04bd7faea8/iso-18391-2016>



iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 18391:2016

<https://standards.iteh.ai/catalog/standards/sist/3306f836-0dd5-43ef-a102-4d04bd7faea8/iso-18391-2016>



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Rules for establishing a population specification	3
4.1 General.....	3
4.2 Rules.....	3
4.2.1 Rule 1: Description of a population specification.....	3
4.2.2 Rule 2: Description of type of individual GPS specification (univariate or multivariate).....	5
4.2.3 Rule 3.....	7
5 Symbol used to specify a population specification	8
6 Rules for indicating a population specification	11
Annex A (informative) Relation in the GPS matrix model	15
Bibliography	16

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 18391:2016](https://standards.iteh.ai/catalog/standards/sist/3306f836-0dd5-43ef-a102-4d04bd7faea8/iso-18391-2016)

<https://standards.iteh.ai/catalog/standards/sist/3306f836-0dd5-43ef-a102-4d04bd7faea8/iso-18391-2016>

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 213, *Dimensional and geometrical product specifications and verification*.

ISO 18391:2016

<https://standards.iteh.ai/catalog/standards/sist/3306f836-0dd5-43ef-a102-4d04bd7faea8/iso-18391-2016>

Introduction

This International Standard is a Geometrical Product Specification (GPS) standard and is to be regarded as a global GPS standard (see ISO 14638). It influences all chain links of all chains of standards.

The ISO/GPS Masterplan given in ISO 14638 gives an overview of the ISO/GPS system of which this document is a part. The fundamental rules of ISO/GPS given in ISO 8015 apply to this document and the default decision rules given in ISO 14253-1 apply to specifications made in accordance with this document, unless otherwise indicated. For more detailed information on the relationship of this International standard to other standards and to the GPS matrix model, see [Annex A](#).

In order to define the permissible interval for a geometrical characteristic, the designer only defines a condition (a unilateral tolerance limit or a bilateral pair of tolerance limits) for each workpiece, by considering the worst case impact in an assembly.

But when the tolerancing is based on a set of hypotheses about the population of the workpieces, one or more additional requirements should be added to verify these hypotheses.

NOTE The intent of this International Standard is not to define calculation methods to determine tolerances, but to give the means to express the hypotheses to verify.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ISO 18391:2016](#)

<https://standards.iteh.ai/catalog/standards/sist/3306f836-0dd5-43ef-a102-4d04bd7faea8/iso-18391-2016>

iTeh STANDARD PREVIEW
(standards.iteh.ai)

ISO 18391:2016

<https://standards.iteh.ai/catalog/standards/sist/3306f836-0dd5-43ef-a102-4d04bd7faea8/iso-18391-2016>

Geometrical product specifications (GPS) — Population specification

1 Scope

This International Standard defines rules to establish and to indicate population specifications, which are used to specify conditions on population characteristics, which are established from a set of characteristic values obtained one on each workpiece of a population of workpieces.

A population specification (as applied to a population of workpieces considered as a collection and not as individual items) can be seen as a complementary requirement to the individual specification (as applied to each workpiece considered as individual items). Population specifications express the statistical hypotheses used on the population of workpieces.

NOTE 1 A population specification is a complement to an individual GPS specification.

NOTE 2 This International Standard is not intended to mandate a given tolerancing method or how to calculate tolerance values. Its intent is to specify tools to allow the expression of population specifications.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1101, *Geometrical product specifications (GPS) — Geometrical tolerancing — Tolerances of form, orientation, location and run-out*

ISO 14405-1, *Geometrical product specifications (GPS) — Dimensional tolerancing — Part 1: Linear sizes*

ISO 17450-1, *Geometrical product specifications (GPS) — General concepts — Part 1: Model for geometrical specification and verification*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 17450-1 and the following apply.

3.1

population characteristic

statistic defined from the characteristic values, obtained on the population of workpieces or the population of assemblies

Note 1 to entry: Population characteristics are used to consider the population of workpieces.

Note 2 to entry: Population characteristics are only statistically meaningful when the values are based upon global individual characteristics, see Example 2.

EXAMPLE 1 The arithmetic mean and the standard deviation of a global individual characteristic on the population of workpieces, are population characteristics.

EXAMPLE 2 The minimum circumscribed diameter has one unique value for a given cylindrical feature. Therefore a population characteristic based on this individual characteristic value will be statistically meaningful. The two-point diameter for a given cylindrical feature will vary within a range, dependent upon the form deviations of the feature. In this case, one population characteristic for two-point diameter cannot be defined from the population of values. However, it is possible to establish a population characteristic from the maximum two point diameter along the geometric feature, which is a global individual characteristic, together with a population characteristic from the minimum two-point diameter along the geometric feature which is another global individual characteristic.

3.2 population condition

limit that applies to the population characteristic value

Note 1 to entry: Population conditions can be used for statistical process control (SPC).

EXAMPLE The mean value, μ , of the minimum circumscribed diameter of a population of workpieces can be considered as a population characteristic, and required to be less than or equal to 10,1, which is a population condition (see [Clause 6](#)).

3.3 statistic

completely specified function of random variables

[SOURCE: ISO 3534-1:2006, definition 1.8, modified — Notes have not been reproduced.]

Note 1 to entry: In GPS, the random variables, which are used are in most of cases one-dimensional (scalar). Multi-dimensional (vector) variables also exist.

Note 2 to entry: For a population or a sample of individual characteristic values, at least one statistic can be applied. In GPS, a statistic can be used on a population of local individual characteristic values taken on one workpiece or, on a population of global individual characteristic values taken on a population of workpieces.

EXAMPLE See [Table 1](#). More information can be found in ISO 3534- series.
<https://standards.iteh.ai/catalog/standards/sist/3306f836-0dd5-43ef-a102-4d04bd7faea8/iso-18391-2016>

Table 1 — Non exhaustive list of population statistics^a

	Description of the statistic	Mathematical description according to ISO 3534-1 ^b
A)	Minimum	minimum (X)
B)	Maximum	maximum (X)
C)	Mean: expected value	$\mu = E(X) = \frac{1}{n} \sum_{i=1}^n X_i ,$ or $\mu = E [g(X)] = \int g(X) dp = \int g(x) dF(x)$
D)	Mean deviation: difference between the mean and the target value (τ)	$\delta = \mu - \tau$
E)	Standard deviation	$\sigma = \sqrt{V(X)}$
F)	Variance	$V(X) = E \left\{ [X - E(X)]^2 \right\}$
G)	y % distribution quantile of the variable X	$X_{y \%} : P [X \leq X_{y \%}] = y \%$

Table 1 (continued)

	Description of the statistic	Mathematical description according to ISO 3534-1 ^b
H)	Median, i.e 50 % distribution quantile	$X_{50\%}$
I)	Median absolute deviation from median ^c	$\Delta_{50\%}$ with $\Delta = x - X_{50\%} $
a	The symbols used in this table are defined in Table 2	
b	Where X is the global characteristic value on one workpiece.	
c	See Reference [6] .	

4 Rules for establishing a population specification

4.1 General

A population characteristic is a characteristic, which is calculated from a set of values, each of which is an global individual characteristic value obtained on one workpiece of the population.

In some applications it is necessary to specify that one or more relations between the workpieces of the population shall be satisfied. The following rules describe the implication on the individual specification, and how to indicate a population specification.

A population characteristic can be used to manage statistical tolerancing requirements or the implementation of statistical process control indexes.

4.2 Rules

ISO 18391:2016

[https://standards.iteh.ai/catalog/standards/sist/3306f836-0dd5-43ef-a102-](https://standards.iteh.ai/catalog/standards/sist/3306f836-0dd5-43ef-a102-4401b475a8/iso-18391-2016)

4.2.1 Rule 1: Description of a population specification

4.2.1.1 Rule # 1a (indicating a population specification)

By default, a GPS specification is an individual specification. When a population specification is required to complement an individual specification then the tolerance value of the individual GPS specification shall be followed by the modifier \diamond ST.

4.2.1.2 Rule # 1b (individual characteristic)

To define a population characteristic, an individual specification shall be used to define an individual signed global characteristic on each workpiece. In cases where the characteristic captures material deviation, the positive direction is out of the material.

4.2.1.3 Rule # 1c (deriving a global characteristic from a local characteristic)

By default, if the GPS characteristic is a local characteristic, it shall be transformed in one or two global characteristics by applying a rank order operator as defined in ISO 14405-1 (\textcircled{SA} , \textcircled{SX} , \textcircled{SN} , \textcircled{SR} , \textcircled{SD} , etc.). If no rank order operator is indicated, two separate global characteristics apply, one for the minimum and one for the maximum of the local characteristic.

ISO 18391:2016(E)

EXAMPLE 1 Defined transformation:

specification of local characteristic

$$10 \pm 0,1 \text{ (LP)}$$

specification of global characteristics

$$0,2 \text{ (LP) (SR)}$$

$$9,9 \text{ min. (LP) (SN)}$$

EXAMPLE 2 Implicit transformation:

specification of local characteristic

$$10 \pm 0,1 \text{ (LP)}$$

implicit global characteristics

$$+0,1 \text{ (LP) (SX)}$$

$$10 -0,1 \text{ (LP) (SN)}$$

4.2.1.4 Rule # 1d (population specification / individual specification)

By default a population specification is a complementary requirement to an individual specification. The individual specification and each population specification shall be satisfied independently. Conformance of the population of workpieces is subject to the conformance of all specified (individual and population) specifications.

When a population specification is not a complementary requirement to an individual specification then no individual specification shall be specified, but the individual characteristic, used to define the population characteristic, shall be specified explicitly.

For the purpose of general specifications, see ISO 2768-1, a dimension with a population specification is considered as having an individual tolerance indication. Therefore general specifications do not apply to this dimension.

The following examples illustrate the rule # 1d to show requirements combining or not combining individual specification and population specification.

	Indications of requirements	Individual specification	Population specification
a)	$\varnothing 8 \pm 0,1$	Yes	No
b)	$\varnothing 8 \pm 0,1 \text{ (ST)}_{LP_{pk} 1,33}$	Yes	Yes
c)	$\varnothing 8 \text{ (SN) (ST)}_{\sigma 0,02}$	No	Yes
d)	$\text{[} \square \text{] } 0,002$	Yes	No
e)	$\text{[} \square \text{] } 0,002 \text{ (ST)}_{LP_{pk} 1,33}$	Yes	Yes
f)	$\text{[} \square \text{] (F) (ST)}_{\sigma 0,02}$	No	Yes

4.2.1.5 Rule # 1e (target value)

By default, the target value is equal to:

- the mid-value of the tolerance limits for a dimensional bilateral specification,
- zero for form, orientation, run-out, and location specifications;
- zero for surface texture parameters when the condition is defined only as an upper tolerance limit;

- the mid-value of the tolerance limits for a surface texture bilateral specification,

When no default target value is defined, the target value shall be defined.

NOTE The TEDs used in a geometrical specification of form, orientation, location or run-out are not target values; they allow the construction of reference feature from which the geometrical characteristic is established.

EXAMPLE Implicit target value defined for population specification from an individual characteristic with or without associated condition:

Individual characteristic	Target value for the population specification
$10 \pm 0,1$ (SA) <ST>	10
0,1 (SR) <ST>	0
(SR) <ST>	0
— 0,1 <ST>	0
— <ST>	0

4.2.2 Rule 2: Description of type of individual GPS specification (univariate or multivariate)

4.2.2.1 Rule # 2a (default type of the individual GPS characteristic)

An individual global characteristic is by default a univariate characteristic unless it defines a population characteristic. Surface texture characteristics, dimensional characteristics, and form characteristics by default define univariate population characteristics and orientation and location characteristics by default define multivariate population characteristics.

<https://standards.iteh.ai/catalog/standards/sist/3306f836-0dd5-43ef-a102-4d0487facab5/iso-18391-2016>

NOTE The range of values of a population characteristic considered univariate is larger than the range of the statistical combination of the components of the same characteristic considered multivariate, especially for the characteristics of orientation or location. Of course, if the population characteristic is acceptable without taking into account rule # 2a, it will also be acceptable when taking into account rule # 2a.

4.2.2.2 Rule # 2b (multivariate individual GPS characteristic)

If an individual global characteristic shall be decomposed into a multivariate characteristic, this shall be explicitly indicated. In this case, the population characteristic is established from the population of

- global characteristics of the variation curves on each workpiece, or
- the collection of transformed characteristics resulting from the parameterization of the individual global characteristic on each workpiece.

EXAMPLE 1 The minimum circumscribed diameter is a univariate characteristic.

EXAMPLE 2 The location of the axis of a feature of size (as in the example of [Figure 1](#)) is by default a univariate global characteristic. It can be defined as a multivariate characteristic by considering the variation curve along the specified axis.