

ETSI TS 136 331 V13.17.0 (2021-01)



LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
Radio Resource Control (RRC);
Protocol specification
(3GPP TS 36.331 version 13.17.0 Release 13)



Reference

RTS/TSGR-0236331vdh0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Important notice

ETSI TS 136 331 V13.17.0 (2021-01)
<https://standards.iteh.ai/catalog/standards/sist/6ef2bb19-0a24-4027-9bb8-815874d13d49/etsi-ts-136-331-v13-17-0-2021-01>
The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

<https://standards.iteh.ai/catalog/standards/sist/6ef2bb19-0a24-4027-9bb8-8f589ad15d44/etsi-ts-136-331-v13-17-0-2021-01>

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	19
1 Scope	20
2 References	20
3 Definitions, symbols and abbreviations	23
3.1 Definitions	23
3.2 Abbreviations	25
4 General	28
4.1 Introduction	28
4.2 Architecture	29
4.2.1 UE states and state transitions including inter RAT	29
4.2.2 Signalling radio bearers	30
4.3 Services	31
4.3.1 Services provided to upper layers	31
4.3.2 Services expected from lower layers	31
4.4 Functions	31
4.5 Data available for transmission for NB-IoT	33
5 Procedures	33
5.1 General	33
5.1.1 Introduction.....	33
5.1.2 General requirements.....	33
5.2 System information	34
5.2.1 Introduction.....	34
5.2.1.1 General	34
5.2.1.2 Scheduling.....	35
5.2.1.2a Scheduling for NB-IoT	36
5.2.1.3 System information validity and notification of changes	36
5.2.1.4 Indication of ETWS notification	38
5.2.1.5 Indication of CMAS notification.....	38
5.2.1.6 Notification of EAB parameters change	38
5.2.1.7 Access Barring parameters change in NB-IoT	39
5.2.2 System information acquisition	39
5.2.2.1 General	39
5.2.2.2 Initiation.....	39
5.2.2.3 System information required by the UE.....	40
5.2.2.4 System information acquisition by the UE.....	40
5.2.2.5 Essential system information missing	43
5.2.2.6 Actions upon reception of the <i>MasterInformationBlock</i> message.....	44
5.2.2.7 Actions upon reception of the <i>SystemInformationBlockType1</i> message	44
5.2.2.8 Actions upon reception of <i>SystemInformation</i> messages	45
5.2.2.9 Actions upon reception of <i>SystemInformationBlockType2</i>	46
5.2.2.10 Actions upon reception of <i>SystemInformationBlockType3</i>	47
5.2.2.11 Actions upon reception of <i>SystemInformationBlockType4</i>	47
5.2.2.12 Actions upon reception of <i>SystemInformationBlockType5</i>	47
5.2.2.13 Actions upon reception of <i>SystemInformationBlockType6</i>	48
5.2.2.14 Actions upon reception of <i>SystemInformationBlockType7</i>	48
5.2.2.15 Actions upon reception of <i>SystemInformationBlockType8</i>	49
5.2.2.16 Actions upon reception of <i>SystemInformationBlockType9</i>	49
5.2.2.17 Actions upon reception of <i>SystemInformationBlockType10</i>	50
5.2.2.18 Actions upon reception of <i>SystemInformationBlockType11</i>	50
5.2.2.19 Actions upon reception of <i>SystemInformationBlockType12</i>	50

5.2.2.20	Actions upon reception of <i>SystemInformationBlockType13</i>	51
5.2.2.21	Actions upon reception of <i>SystemInformationBlockType14</i>	51
5.2.2.22	Actions upon reception of <i>SystemInformationBlockType15</i>	51
5.2.2.23	Actions upon reception of <i>SystemInformationBlockType16</i>	51
5.2.2.24	Actions upon reception of <i>SystemInformationBlockType17</i>	52
5.2.2.25	Actions upon reception of <i>SystemInformationBlockType18</i>	52
5.2.2.26	Actions upon reception of <i>SystemInformationBlockType19</i>	52
5.2.2.27	Actions upon reception of <i>SystemInformationBlockType20</i>	52
5.2.3	Acquisition of an SI message.....	53
5.2.3a	Acquisition of an SI message by BL UE or UE in CE or a NB-IoT UE.....	53
5.3	Connection control	54
5.3.1	Introduction.....	54
5.3.1.1	RRC connection control.....	54
5.3.1.2	Security	55
5.3.1.2a	RN security	56
5.3.1.3	Connected mode mobility	56
5.3.1.4	Connection control in NB-IoT	57
5.3.2	Paging	58
5.3.2.1	General	58
5.3.2.2	Initiation.....	58
5.3.2.3	Reception of the <i>Paging</i> message by the UE	59
5.3.3	RRC connection establishment.....	60
5.3.3.1	General	60
5.3.3.1a	Conditions for establishing RRC Connection for sidelink communication/ discovery.....	61
5.3.3.2	Initiation.....	62
5.3.3.3	Actions related to transmission of <i>RRCConnectionRequest</i> message	67
5.3.3.3a	Actions related to transmission of <i>RRCConnectionResumeRequest</i> message.....	67
5.3.3.4	Reception of the <i>RRCConnectionSetup</i> by the UE.....	68
5.3.3.4a	Reception of the <i>RRCConnectionResume</i> by the UE.....	70
5.3.3.5	Cell re-selection while T300, T302, T303, T305, T306, or T308 is running.....	72
5.3.3.6	T300 expiry.....	72
5.3.3.7	T302, T303, T305, T306, or T308 expiry or stop.....	74
5.3.3.8	Reception of the <i>RRCConnectionReject</i> by the UE.....	74
5.3.3.9	Abortion of RRC connection establishment.....	75
5.3.3.10	Handling of SSAC related parameters	75
5.3.3.11	Access barring check.....	76
5.3.3.12	EAB check	77
5.3.3.13	Access barring check for ACDC.....	78
5.3.3.14	Access Barring check for NB-IoT.....	78
5.3.4	Initial security activation	80
5.3.4.1	General	80
5.3.4.2	Initiation.....	80
5.3.4.3	Reception of the <i>SecurityModeCommand</i> by the UE.....	80
5.3.5	RRC connection reconfiguration	81
5.3.5.1	General	81
5.3.5.2	Initiation.....	82
5.3.5.3	Reception of an <i>RRCConnectionReconfiguration</i> not including the <i>mobilityControlInfo</i> by the UE.....	82
5.3.5.4	Reception of an <i>RRCConnectionReconfiguration</i> including the <i>mobilityControlInfo</i> by the UE (handover).....	84
5.3.5.5	Reconfiguration failure	87
5.3.5.6	T304 expiry (handover failure)	88
5.3.5.7	Void.....	89
5.3.5.7a	T307 expiry (SCG change failure).....	89
5.3.5.8	Radio Configuration involving full configuration option.....	89
5.3.6	Counter check	90
5.3.6.1	General	90
5.3.6.2	Initiation.....	90
5.3.6.3	Reception of the <i>CounterCheck</i> message by the UE.....	91
5.3.7	RRC connection re-establishment.....	91
5.3.7.1	General	91
5.3.7.2	Initiation.....	92

5.3.7.3	Actions following cell selection while T311 is running.....	93
5.3.7.4	Actions related to transmission of <i>RRCConnectionReestablishmentRequest</i> message	93
5.3.7.5	Reception of the <i>RRCConnectionReestablishment</i> by the UE	94
5.3.7.6	T311 expiry	96
5.3.7.7	T301 expiry or selected cell no longer suitable.....	96
5.3.7.8	Reception of <i>RRCConnectionReestablishmentReject</i> by the UE	96
5.3.8	RRC connection release	96
5.3.8.1	General	96
5.3.8.2	Initiation.....	96
5.3.8.3	Reception of the <i>RRCConnectionRelease</i> by the UE	97
5.3.8.4	T320 expiry	97
5.3.9	RRC connection release requested by upper layers	98
5.3.9.1	General	98
5.3.9.2	Initiation.....	98
5.3.10	Radio resource configuration.....	98
5.3.10.0	General	98
5.3.10.1	SRB addition/ modification.....	99
5.3.10.2	DRB release	99
5.3.10.3	DRB addition/ modification	100
5.3.10.3a1	DC specific DRB addition or reconfiguration.....	101
5.3.10.3a2	LWA specific DRB addition or reconfiguration	102
5.3.10.3a3	LWIP specific DRB addition or reconfiguration.....	103
5.3.10.3a	SCell release.....	103
5.3.10.3b	SCell addition/ modification	103
5.3.10.3c	PSCell addition or modification.....	104
5.3.10.4	MAC main reconfiguration	104
5.3.10.5	Semi-persistent scheduling reconfiguration	105
5.3.10.6	Physical channel reconfiguration	105
5.3.10.7	Radio Link Failure Timers and Constants reconfiguration	106
5.3.10.8	Time domain measurement resource restriction for serving cell.....	106
5.3.10.9	Other configuration	106
5.3.10.10	SCG reconfiguration	107
5.3.10.11	SCG dedicated resource configuration	109
5.3.10.12	Reconfiguration SCG of split DRB by <i>drb-ToAddModList</i>	109
5.3.10.13	Neighbour cell information reconfiguration.....	109
5.3.10.14	Void.....	110
5.3.10.15	Sidelink dedicated configuration.....	110
5.3.10.16	T370 expiry	111
5.3.11	Radio link failure related actions	111
5.3.11.1	Detection of physical layer problems in RRC_CONNECTED.....	111
5.3.11.2	Recovery of physical layer problems	112
5.3.11.3	Detection of radio link failure	112
5.3.12	UE actions upon leaving RRC_CONNECTED	114
5.3.13	UE actions upon PUCCH/ SRS release request.....	115
5.3.14	Proximity indication	115
5.3.14.1	General	115
5.3.14.2	Initiation.....	115
5.3.14.3	Actions related to transmission of <i>ProximityIndication</i> message.....	116
5.3.15	Void	116
5.4	Inter-RAT mobility.....	116
5.4.1	Introduction.....	116
5.4.2	Handover to E-UTRA.....	117
5.4.2.1	General	117
5.4.2.2	Initiation.....	117
5.4.2.3	Reception of the <i>RRCConnectionReconfiguration</i> by the UE.....	117
5.4.2.4	Reconfiguration failure	119
5.4.2.5	T304 expiry (handover to E-UTRA failure).....	119
5.4.3	Mobility from E-UTRA	120
5.4.3.1	General	120
5.4.3.2	Initiation.....	120
5.4.3.3	Reception of the <i>MobilityFromEUTRACommand</i> by the UE	120
5.4.3.4	Successful completion of the mobility from E-UTRA.....	122

5.4.3.5	Mobility from E-UTRA failure	122
5.4.4	Handover from E-UTRA preparation request (CDMA2000)	123
5.4.4.1	General	123
5.4.4.2	Initiation	123
5.4.4.3	Reception of the <i>HandoverFromEUTRAPreparationRequest</i> by the UE	123
5.4.5	UL handover preparation transfer (CDMA2000)	124
5.4.5.1	General	124
5.4.5.2	Initiation	124
5.4.5.3	Actions related to transmission of the <i>ULHandoverPreparationTransfer</i> message	124
5.4.5.4	Failure to deliver the <i>ULHandoverPreparationTransfer</i> message	124
5.4.6	Inter-RAT cell change order to E-UTRAN	124
5.4.6.1	General	124
5.4.6.2	Initiation	125
5.4.6.3	UE fails to complete an inter-RAT cell change order	125
5.5	Measurements	125
5.5.1	Introduction	125
5.5.2	Measurement configuration	127
5.5.2.1	General	127
5.5.2.2	Measurement identity removal	128
5.5.2.2a	Measurement identity autonomous removal	128
5.5.2.3	Measurement identity addition/ modification	128
5.5.2.4	Measurement object removal	129
5.5.2.5	Measurement object addition/ modification	129
5.5.2.6	Reporting configuration removal	132
5.5.2.7	Reporting configuration addition/ modification	132
5.5.2.8	Quantity configuration	132
5.5.2.9	Measurement gap configuration	133
5.5.2.10	Discovery signals measurement timing configuration	133
5.5.2.11	RSSI measurement timing configuration	133
5.5.3	Performing measurements	134
5.5.3.1	General	134
5.5.3.2	Layer 3 filtering	136
5.5.4	Measurement report triggering	137
5.5.4.1	General	137
5.5.4.2	Event A1 (Serving becomes better than threshold)	141
5.5.4.3	Event A2 (Serving becomes worse than threshold)	141
5.5.4.4	Event A3 (Neighbour becomes offset better than PCell/ PSCell)	142
5.5.4.5	Event A4 (Neighbour becomes better than threshold)	143
5.5.4.6	Event A5 (PCell/ PSCell becomes worse than threshold1 and neighbour becomes better than threshold2)	143
5.5.4.6a	Event A6 (Neighbour becomes offset better than SCell)	144
5.5.4.7	Event B1 (Inter RAT neighbour becomes better than threshold)	145
5.5.4.8	Event B2 (PCell becomes worse than threshold1 and inter RAT neighbour becomes better than threshold2)	145
5.5.4.9	Event C1 (CSI-RS resource becomes better than threshold)	146
5.5.4.10	Event C2 (CSI-RS resource becomes offset better than reference CSI-RS resource)	147
5.5.4.11	Event W1 (WLAN becomes better than a threshold)	147
5.5.4.12	Event W2 (All WLAN inside WLAN mobility set becomes worse than threshold1 and a WLAN outside WLAN mobility set becomes better than threshold2)	148
5.5.4.13	Event W3 (All WLAN inside WLAN mobility set becomes worse than a threshold)	149
5.5.5	Measurement reporting	149
5.5.6	Measurement related actions	153
5.5.6.1	Actions upon handover and re-establishment	153
5.5.6.2	Speed dependant scaling of measurement related parameters	154
5.5.7	Inter-frequency RSTD measurement indication	155
5.5.7.1	General	155
5.5.7.2	Initiation	155
5.5.7.3	Actions related to transmission of <i>InterFreqRSTDMeasurementIndication</i> message	155
5.6	Other	156
5.6.0	General	156
5.6.1	DL information transfer	156
5.6.1.1	General	156

5.6.1.2	Initiation.....	156
5.6.1.3	Reception of the <i>DLInformationTransfer</i> by the UE	156
5.6.2	UL information transfer	157
5.6.2.1	General	157
5.6.2.2	Initiation.....	157
5.6.2.3	Actions related to transmission of <i>ULInformationTransfer</i> message	157
5.6.2.4	Failure to deliver <i>ULInformationTransfer</i> message	157
5.6.3	UE capability transfer	158
5.6.3.1	General	158
5.6.3.2	Initiation.....	158
5.6.3.3	Reception of the <i>UECapabilityEnquiry</i> by the UE	158
5.6.4	CSFB to 1x Parameter transfer	162
5.6.4.1	General	162
5.6.4.2	Initiation.....	162
5.6.4.3	Actions related to transmission of <i>CSFBParametersRequestCDMA2000</i> message.....	162
5.6.4.4	Reception of the <i>CSFBParametersResponseCDMA2000</i> message.....	162
5.6.5	UE Information	162
5.6.5.1	General	162
5.6.5.2	Initiation.....	163
5.6.5.3	Reception of the <i>UEInformationRequest</i> message	163
5.6.6	Logged Measurement Configuration	164
5.6.6.1	General	164
5.6.6.2	Initiation.....	164
5.6.6.3	Reception of the <i>LoggedMeasurementConfiguration</i> by the UE	164
5.6.6.4	T330 expiry	165
5.6.7	Release of Logged Measurement Configuration.....	165
5.6.7.1	General	165
5.6.7.2	Initiation.....	165
5.6.8	Measurements logging	165
5.6.8.1	General	165
5.6.8.2	Initiation	165
5.6.9	In-device coexistence indication	168
5.6.9.1	General	168
5.6.9.2	Initiation	168
5.6.9.3	Actions related to transmission of <i>InDeviceCoexIndication</i> message.....	169
5.6.10	UE Assistance Information	170
5.6.10.1	General	170
5.6.10.2	Initiation.....	170
5.6.10.3	Actions related to transmission of <i>UEAssistanceInformation</i> message	171
5.6.11	Mobility history information.....	171
5.6.11.1	General	171
5.6.11.2	Initiation.....	171
5.6.12	RAN-assisted WLAN interworking.....	171
5.6.12.1	General	171
5.6.12.2	Dedicated WLAN offload configuration.....	172
5.6.12.3	WLAN offload RAN evaluation	172
5.6.12.4	T350 expiry or stop	172
5.6.12.5	Cell selection/ re-selection while T350 is running	172
5.6.13	SCG failure information	173
5.6.13.1	General	173
5.6.13.2	Initiation.....	173
5.6.13.3	Actions related to transmission of <i>SCGFailureInformation</i> message	173
5.6.14	LTE-WLAN Aggregation.....	174
5.6.14.1	Introduction.....	174
5.6.14.2	Reception of LWA configuration.....	174
5.6.14.3	Release of LWA configuration	175
5.6.15	WLAN connection management.....	175
5.6.15.1	Introduction.....	175
5.6.15.2	WLAN connection status reporting.....	175
5.6.15.2.1	General	175
5.6.15.2.2	Initiation	176
5.6.15.2.3	Actions related to transmission of <i>WLANConnectionStatusReport</i> message	176

5.6.15.3	T351 Expiry (WLAN connection attempt timeout)	176
5.6.15.4	WLAN status monitoring	176
5.6.16	RAN controlled LTE-WLAN interworking	177
5.6.16.1	General	177
5.6.16.2	WLAN traffic steering command	177
5.6.17	LTE-WLAN aggregation with IPsec tunnel	177
5.6.17.1	General	177
5.6.17.2	LWIP reconfiguration	177
5.6.17.3	LWIP release	178
5.7	Generic error handling	178
5.7.1	General	178
5.7.2	ASN.1 violation or encoding error	179
5.7.3	Field set to a not comprehended value	179
5.7.4	Mandatory field missing	179
5.7.5	Not comprehended field	180
5.8	MBMS	181
5.8.1	Introduction	181
5.8.1.1	General	181
5.8.1.2	Scheduling	181
5.8.1.3	MCCH information validity and notification of changes	181
5.8.2	MCCH information acquisition	182
5.8.2.1	General	182
5.8.2.2	Initiation	183
5.8.2.3	MCCH information acquisition by the UE	183
5.8.2.4	Actions upon reception of the <i>MBSFNAreaConfiguration</i> message	183
5.8.2.5	Actions upon reception of the <i>MBMSCountingRequest</i> message	183
5.8.3	MBMS PTM radio bearer configuration	183
5.8.3.1	General	183
5.8.3.2	Initiation	184
5.8.3.3	MRB establishment	184
5.8.3.4	MRB release	184
5.8.4	MBMS Counting Procedure	184
5.8.4.1	General	184
5.8.4.2	Initiation	184
5.8.4.3	Reception of the <i>MBMSCountingRequest</i> message by the UE	185
5.8.5	MBMS interest indication	185
5.8.5.1	General	185
5.8.5.2	Initiation	186
5.8.5.3	Determine MBMS frequencies of interest	186
5.8.5.4	Actions related to transmission of <i>MBMSInterestIndication</i> message	187
5.8a	SC-PTM	188
5.8a.1	Introduction	188
5.8a.1.1	General	188
5.8a.1.2	SC-MCCH scheduling	188
5.8a.1.3	SC-MCCH information validity and notification of changes	188
5.8a.1.4	Procedures	188
5.8a.2	SC-MCCH information acquisition	189
5.8a.2.1	General	189
5.8a.2.2	Initiation	189
5.8a.2.3	SC-MCCH information acquisition by the UE	189
5.8a.2.4	Actions upon reception of the <i>SCPTMConfiguration</i> message	189
5.8a.3	SC-PTM radio bearer configuration	190
5.8a.3.1	General	190
5.8a.3.2	Initiation	190
5.8a.3.3	SC-MRB establishment	190
5.8a.3.4	SC-MRB release	190
5.9	RN procedures	191
5.9.1	RN reconfiguration	191
5.9.1.1	General	191
5.9.1.2	Initiation	191
5.9.1.3	Reception of the <i>RNReconfiguration</i> by the RN	191
5.10	Sidelink	191

5.10.1	Introduction.....	191
5.10.1a	Conditions for sidelink communication operation.....	192
5.10.2	Sidelink UE information.....	193
5.10.2.1	General.....	193
5.10.2.2	Initiation.....	194
5.10.2.3	Actions related to transmission of <i>SidelinkUEInformation</i> message.....	198
5.10.3	Sidelink communication monitoring.....	200
5.10.4	Sidelink communication transmission.....	201
5.10.5	Sidelink discovery monitoring.....	202
5.10.6	Sidelink discovery announcement.....	203
5.10.6a	Sidelink discovery announcement pool selection.....	206
5.10.6b	Sidelink discovery announcement reference carrier selection.....	206
5.10.7	Sidelink synchronisation information transmission.....	207
5.10.7.1	General.....	207
5.10.7.2	Initiation.....	208
5.10.7.3	Transmission of SLSS.....	209
5.10.7.4	Transmission of <i>MasterInformationBlock-SL</i> message.....	210
5.10.7.5	Void.....	211
5.10.8	Sidelink synchronisation reference.....	211
5.10.8.1	General.....	211
5.10.8.2	Selection and reselection of synchronisation reference UE (SyncRef UE).....	211
5.10.9	Sidelink common control information.....	212
5.10.9.1	General.....	212
5.10.9.2	Actions related to reception of <i>MasterInformationBlock-SL</i> message.....	212
5.10.10	Sidelink relay UE operation.....	212
5.10.10.1	General.....	212
5.10.10.2	AS-conditions for relay related sidelink communication transmission by sidelink relay UE.....	212
5.10.10.3	AS-conditions for relay PS related sidelink discovery transmission by sidelink relay UE.....	213
5.10.10.4	Sidelink relay UE threshold conditions.....	213
5.10.11	Sidelink remote UE operation.....	213
5.10.11.1	General.....	213
5.10.11.2	AS-conditions for relay related sidelink communication transmission by sidelink remote UE.....	213
5.10.11.3	AS-conditions for relay PS related sidelink discovery transmission by sidelink remote UE.....	214
5.10.11.4	Selection and reselection of sidelink relay UE.....	214
5.10.11.5	Sidelink remote UE threshold conditions.....	215
6	Protocol data units, formats and parameters (tabular & ASN.1).....	215
6.1	General.....	215
6.2	RRC messages.....	217
6.2.1	General message structure.....	217
–	<i>EUTRA-RRC-Definitions</i>	217
–	<i>BCCH-BCH-Message</i>	217
–	<i>BCCH-DL-SCH-Message</i>	217
–	<i>BCCH-DL-SCH-Message-BR</i>	218
–	<i>MCCH-Message</i>	218
–	<i>PCCH-Message</i>	218
–	<i>DL-CCCH-Message</i>	219
–	<i>DL-DCCH-Message</i>	219
–	<i>UL-CCCH-Message</i>	219
–	<i>UL-DCCH-Message</i>	220
–	<i>SC-MCCH-Message</i>	220
6.2.2	Message definitions.....	221
–	<i>CounterCheck</i>	221
–	<i>CounterCheckResponse</i>	222
–	<i>CSFBParametersRequestCDMA2000</i>	222
–	<i>CSFBParametersResponseCDMA2000</i>	223
–	<i>DLInformationTransfer</i>	223
–	<i>HandoverFromEUTRAPreparationRequest (CDMA2000)</i>	224
–	<i>InDeviceCoexIndication</i>	225
–	<i>InterFreqRSTDMeasurementIndication</i>	227
–	<i>LoggedMeasurementConfiguration</i>	229
–	<i>MasterInformationBlock</i>	230

- MBMSCountingRequest 231
- MBMSCountingResponse 231
- MBMSInterestIndication 232
- MBSFNAreaConfiguration 233
- MeasurementReport 234
- MobilityFromEUTRACommand 234
- Paging 237
- ProximityIndication 238
- RNRReconfiguration 239
- RNRReconfigurationComplete 239
- RRCConnectionReconfiguration 240
- RRCConnectionReconfigurationComplete 246
- RRCConnectionReestablishment 247
- RRCConnectionReestablishmentComplete 247
- RRCConnectionReestablishmentReject 248
- RRCConnectionReestablishmentRequest 249
- RRCConnectionReject 249
- RRCConnectionRelease 251
- RRCConnectionRequest 254
- RRCConnectionResume 255
- RRCConnectionResumeComplete 256
- RRCConnectionResumeRequest 256
- RRCConnectionSetup 257
- RRCConnectionSetupComplete 258
- SCGFailureInformation 259
- SCPTMConfiguration 260
- SecurityModeCommand 261
- SecurityModeComplete 262
- SecurityModeFailure 262
- SidelinkUEInformation 263
- SystemInformation 264
- SystemInformationBlockType1 265
- UEAssistanceInformation 272
- UECapabilityEnquiry 273
- UECapabilityInformation 274
- UEInformationRequest 275
- UEInformationResponse 275
- ULHandoverPreparationTransfer (CDMA2000) 281
- ULInformationTransfer 282
- WLANConnectionStatusReport 282
- 6.3 RRC information elements 283
- 6.3.1 System information blocks 283
- SystemInformationBlockType2 283
- SystemInformationBlockType3 287
- SystemInformationBlockType4 290
- SystemInformationBlockType5 291
- SystemInformationBlockType6 296
- SystemInformationBlockType7 299
- SystemInformationBlockType8 300
- SystemInformationBlockType9 304
- SystemInformationBlockType10 304
- SystemInformationBlockType11 305
- SystemInformationBlockType12 306
- SystemInformationBlockType13 306
- SystemInformationBlockType14 307
- SystemInformationBlockType15 307
- SystemInformationBlockType16 308
- SystemInformationBlockType17 309
- SystemInformationBlockType18 310
- SystemInformationBlockType19 310
- SystemInformationBlockType20 313
- 6.3.2 Radio resource control information elements 313

STANDARD PREVIEW
(standards.iteh.ai)
ETSI TS 136 331 V13.17.0 (2021-01)
<https://standards.iteh.ai/catalog/standards/sist/6ef2bb19-0a24-4027-9bb8-578f9ad15d4/etsi-ts-136-331-v13-17-0-2021-01>

-	<i>AntennaInfo</i>	313
-	<i>AntennaInfoUL</i>	315
-	<i>CQI-ReportConfig</i>	316
-	<i>CQI-ReportPeriodicProcExtId</i>	323
-	<i>CrossCarrierSchedulingConfig</i>	323
-	<i>CSI-IM-Config</i>	324
-	<i>CSI-IM-ConfigId</i>	324
-	<i>CSI-Process</i>	325
-	<i>CSI-ProcessId</i>	326
-	<i>CSI-RS-Config</i>	326
-	<i>CSI-RS-ConfigEMIMO</i>	328
-	<i>CSI-RS-ConfigNZIP</i>	329
-	<i>CSI-RS-ConfigNZPID</i>	330
-	<i>CSI-RS-ConfigZP</i>	330
-	<i>CSI-RS-ConfigZPID</i>	331
-	<i>DMRS-Config</i>	331
-	<i>DRB-Identity</i>	331
-	<i>EPDCCH-Config</i>	331
-	<i>EIMTA-MainConfig</i>	333
-	<i>LogicalChannelConfig</i>	334
-	<i>LWA-Configuration</i>	335
-	<i>LWIP-Configuration</i>	336
-	<i>MAC-MainConfig</i>	336
-	<i>P-C-AndCBSR</i>	340
-	<i>PDCCH-ConfigSCell</i>	341
-	<i>PDCP-Config</i>	342
-	<i>PDSCH-Config</i>	345
-	<i>PDSCH-RE-MappingQCL-ConfigId</i>	347
-	<i>PHICH-Config</i>	347
-	<i>PhysicalConfigDedicated</i>	347
-	<i>P-Max</i>	352
-	<i>PRACH-Config</i>	352
-	<i>PresenceAntennaPort1</i>	354
-	<i>PUCCH-Config</i>	355
-	<i>PUSCH-Config</i>	359
-	<i>RACH-ConfigCommon</i>	363
-	<i>RACH-ConfigDedicated</i>	365
-	<i>RadioResourceConfigCommon</i>	366
-	<i>RadioResourceConfigDedicated</i>	370
-	<i>RCLWI-Configuration</i>	375
-	<i>RLC-Config</i>	376
-	<i>RLF-TimersAndConstants</i>	378
-	<i>RN-SubframeConfig</i>	378
-	<i>SchedulingRequestConfig</i>	380
-	<i>SoundingRS-UL-Config</i>	381
-	<i>SPS-Config</i>	383
-	<i>TDD-Config</i>	385
-	<i>TimeAlignmentTimer</i>	386
-	<i>TPC-PDCCH-Config</i>	386
-	<i>TunnelConfigLWIP</i>	387
-	<i>UplinkPowerControl</i>	388
-	<i>WLAN-Id-List</i>	391
-	<i>WLAN-MobilityConfig</i>	391
6.3.3	Security control information elements.....	391
-	<i>NextHopChainingCount</i>	391
-	<i>SecurityAlgorithmConfig</i>	392
-	<i>ShortMAC-I</i>	392
6.3.4	Mobility control information elements.....	392
-	<i>AdditionalSpectrumEmission</i>	392
-	<i>ARFCN-ValueCDMA2000</i>	393
-	<i>ARFCN-ValueEUTRA</i>	393
-	<i>ARFCN-ValueGERAN</i>	393

STANDARD PREVIEW
(standards.iteh.ai)
ETSI TS 136 331 V13.17.0 (2021-01)
<https://standards.iteh.ai/catalog/standards/sist/6ef2bb19-0a24-4027-9bb8-8f58f9ad15d4/etsi-ts-136-331-v13-17-0-2021-01>

- ARFCN-ValueUTRA 393
- BandclassCDMA2000 394
- BandIndicatorGERAN 394
- CarrierFreqCDMA2000 394
- CarrierFreqGERAN 394
- CarrierFreqsGERAN 395
- CarrierFreqListMBMS 395
- CDMA2000-Type 396
- CellIdentity 396
- CellIndexList 396
- CellReselectionPriority 396
- CellSelectionInfoCE 396
- CellSelectionInfoCE1 397
- CellReselectionSubPriority 397
- CSFB-RegistrationParamIXRTT 397
- CellGlobalIdEUTRA 398
- CellGlobalIdUTRA 399
- CellGlobalIdGERAN 399
- CellGlobalIdCDMA2000 399
- CellSelectionInfoNFreq 400
- CSG-Identity 400
- FreqBandIndicator 400
- MobilityControlInfo 401
- MobilityParametersCDMA2000 (1xRTT) 402
- MobilityStateParameters 403
- MultiBandInfoList 403
- NS-PmaxList 403
- PhysCellId 404
- PhysCellIdRange 404
- PhysCellIdRangeUTRA-FDDList 405
- PhysCellIdCDMA2000 405
- PhysCellIdGERAN 405
- PhysCellIdUTRA-FDD 406
- PhysCellIdUTRA-TDD 406
- PLMN-Identity 406
- PLMN-IdentityList3 407
- PreRegistrationInfoHRPD 407
- Q-QualMin 407
- Q-RxLevMin 407
- Q-OffsetRange 408
- Q-OffsetRangeInterRAT 408
- ReselectionThreshold 408
- ReselectionThresholdQ 408
- SCellIndex 409
- ServCellIndex 409
- SpeedStateScaleFactors 409
- SystemInfoListGERAN 409
- SystemTimeInfoCDMA2000 410
- TrackingAreaCode 411
- T-Reselection 411
- T-ReselectionEUTRA-CE 411
- 6.3.5 Measurement information elements 411
 - AllowedMeasBandwidth 411
 - CSI-RSRP-Range 411
 - Hysteresis 412
 - LocationInfo 412
 - MBSFN-RSRQ-Range 413
 - MeasConfig 413
 - MeasDS-Config 415
 - MeasGapConfig 416
 - MeasId 416
 - MeasIdToAddModList 417

ITeH STANDARD PREVIEW
(standards.iteh.ai)

ETSI TS 136 331 V13.17.0 (2021-01)

[iteh.ai/catalog/standards/sist/6ef2bb19-0a24-4027-9bb8-](https://standards.iteh.ai/catalog/standards/sist/6ef2bb19-0a24-4027-9bb8-9ad15d4/etsi-ts-136-331-v13-17-0-2021-01)

[9ad15d4/etsi-ts-136-331-v13-17-0-2021-01](https://standards.iteh.ai/catalog/standards/sist/6ef2bb19-0a24-4027-9bb8-9ad15d4/etsi-ts-136-331-v13-17-0-2021-01)

-	<i>MeasObjectCDMA2000</i>	417
-	<i>MeasObjectEUTRA</i>	418
-	<i>MeasObjectGERAN</i>	421
-	<i>MeasObjectId</i>	421
-	<i>MeasObjectToAddModList</i>	421
-	<i>MeasObjectUTRA</i>	422
-	<i>MeasObjectWLAN</i>	423
-	<i>MeasResults</i>	424
-	<i>MeasScaleFactor</i>	430
-	<i>QuantityConfig</i>	430
-	<i>ReportConfigEUTRA</i>	431
-	<i>ReportConfigId</i>	435
-	<i>ReportConfigInterRAT</i>	435
-	<i>ReportConfigToAddModList</i>	438
-	<i>ReportInterval</i>	439
-	<i>RSRP-Range</i>	439
-	<i>RSRQ-Range</i>	440
-	<i>RSRQ-Type</i>	440
-	<i>RS-SINR-Range</i>	441
-	<i>RSSI-Range-r13</i>	441
-	<i>TimeToTrigger</i>	441
-	<i>UL-DelayConfig</i>	441
-	<i>WLAN-CarrierInfo</i>	442
-	<i>WLAN-RSSI-Range</i>	442
-	<i>WLAN-Status</i>	442
6.3.6	Other information elements	443
-	<i>AbsoluteTimeInfo</i>	443
-	<i>AreaConfiguration</i>	443
-	<i>C-RNTI</i>	443
-	<i>DedicatedInfoCDMA2000</i>	444
-	<i>DedicatedInfoNAS</i>	444
-	<i>FilterCoefficient</i>	444
-	<i>LoggingDuration</i>	444
-	<i>LoggingInterval</i>	445
-	<i>MeasSubframePattern</i>	445
-	<i>MMEC</i>	445
-	<i>NeighCellConfig</i>	445
-	<i>OtherConfig</i>	446
-	<i>RAND-CDMA2000 (1xRTT)</i>	447
-	<i>RAT-Type</i>	447
-	<i>ResumeIdentity</i>	448
-	<i>RRC-TransactionIdentifier</i>	448
-	<i>S-TMSI</i>	448
-	<i>TraceReference</i>	448
-	<i>UE-CapabilityRAT-ContainerList</i>	449
-	<i>UE-EUTRA-Capability</i>	449
-	<i>UE-RadioPagingInfo</i>	482
-	<i>UE-TimersAndConstants</i>	483
-	<i>VisitedCellInfoList</i>	484
-	<i>WLAN-OffloadConfig</i>	484
6.3.7	MBMS information elements	487
-	<i>MBMS-NotificationConfig</i>	487
-	<i>MBMS-ServiceList</i>	487
-	<i>MBSFN-AreaId</i>	487
-	<i>MBSFN-AreaInfoList</i>	488
-	<i>MBSFN-SubframeConfig</i>	488
-	<i>PMCH-InfoList</i>	489
6.3.7a	SC-PTM information elements	491
-	<i>SC-MTCH-InfoList</i>	491
-	<i>SCPTM-NeighbourCellList</i>	492
6.3.8	Sidelink information elements	492
-	<i>SL-CommConfig</i>	492

–	<i>SL-CommResourcePool</i>	494
–	<i>SL-CP-Len</i>	495
–	<i>SL-DiscConfig</i>	495
–	<i>SL-DiscResourcePool</i>	498
–	<i>SL-DiscTxPowerInfo</i>	499
–	<i>SL-GapConfig</i>	500
–	<i>SL-GapRequest</i>	500
–	<i>SL-HoppingConfig</i>	500
–	<i>SL-OffsetIndicator</i>	501
–	<i>SL-PeriodComm</i>	501
–	<i>SL-Priority</i>	502
–	<i>SLSSID</i>	502
–	<i>SL-SyncConfig</i>	502
–	<i>SL-DiscSysInfoReport</i>	504
–	<i>SL-TF-ResourceConfig</i>	505
–	<i>SL-TxParameters</i>	505
–	<i>SL-TxPoolIdentity</i>	506
–	<i>SL-TxPoolToReleaseList</i>	506
6.4	RRC multiplicity and type constraint values	506
–	Multiplicity and type constraint definitions	506
–	End of EUTRA-RRC-Definitions	509
6.5	PC5 RRC messages	509
6.5.1	General message structure	509
–	<i>PC5-RRC-Definitions</i>	509
–	<i>SBCCH-SL-BCH-Message</i>	509
6.5.2	Message definitions	509
–	<i>MasterInformationBlock-SL</i>	509
–	End of <i>PC5-RRC-Definitions</i>	510
6.6	Direct Indication Information	510
6.7	NB-IoT RRC messages	511
6.7.1	General NB-IoT message structure	511
–	<i>BCCH-BCH-Message-NB</i>	511
–	<i>BCCH-DL-SCH-Message-NB</i>	512
–	<i>PCCH-Message-NB</i>	512
–	<i>DL-CCCH-Message-NB</i>	512
–	<i>DL-DCCH-Message-NB</i>	513
–	<i>UL-CCCH-Message-NB</i>	513
–	<i>UL-DCCH-Message-NB</i>	513
6.7.2	NB-IoT Message definitions	514
–	<i>DLInformationTransfer-NB</i>	514
–	<i>MasterInformationBlock-NB</i>	514
–	<i>Paging-NB</i>	516
–	<i>RRCCConnectionReconfiguration-NB</i>	517
–	<i>RRCCConnectionReconfigurationComplete-NB</i>	518
–	<i>RRCCConnectionReestablishment-NB</i>	518
–	<i>RRCCConnectionReestablishmentComplete-NB</i>	519
–	<i>RRCCConnectionReestablishmentRequest-NB</i>	519
–	<i>RRCCConnectionReject-NB</i>	520
–	<i>RRCCConnectionRelease-NB</i>	520
–	<i>RRCCConnectionRequest-NB</i>	521
–	<i>RRCCConnectionResume-NB</i>	522
–	<i>RRCCConnectionResumeComplete-NB</i>	522
–	<i>RRCCConnectionResumeRequest-NB</i>	523
–	<i>RRCCConnectionSetup-NB</i>	524
–	<i>RRCCConnectionSetupComplete-NB</i>	524
–	<i>SystemInformation-NB</i>	525
–	<i>SystemInformationBlockType1-NB</i>	526
–	<i>UECapabilityEnquiry-NB</i>	529
–	<i>UECapabilityInformation-NB</i>	529
–	<i>ULInformationTransfer-NB</i>	530
6.7.3	NB-IoT information elements	531
6.7.3.1	NB-IoT System information blocks	531